

# Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Room101/301/401/102/202/302/402/502/602/702/802, No. 7-2, Caipin Road, Huangpu District, Guangzhou, Guangdong, China

Job No.: 240326030GZU

FCC ID: 2BF54-AXV3Y

## **RF Exposure Compliance Requirement**

Model no.: AXV3Y

### 1. Standard requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

### (a) Limits for Occupational / Controlled Exposure

| Frequency Range<br>(MHz) | Electric Field<br>Strength (E) (V/m) | Magnetic Field<br>Strength (H) (A/m) | Power Density<br>(S)(mW/cm²) | Averaging Times  E   2 , H  2 or S  (minutes) |  |
|--------------------------|--------------------------------------|--------------------------------------|------------------------------|---|--|
| 0.3-3.0                  | 614                                  | 1.63                                 | (100)*                       | 6   |  |
| 3.0-30                   | 1842/f                               | 4.89/f                               | (900/f)*                     | 6   |  |
| 30-300                   | 61.4                                 | 0.163                                | 1.0                          | 6   |  |
| 300-1500                 |                                      |                                      | F/300                        | 6   |  |
| 1500-100000              |                                      |                                      | 5                            | 6   |  |

## (b) Limits for General Population / Uncontrolled Exposure

| Frequency Range<br>(MHz) | Electric Field<br>Strength (E) (V/m) | Magnetic Field<br>Strength (H) (A/m) | Power Density (S)(mW/cm²) | Averaging Times  E   2 , H  2 or S  (minutes) |
|--------------------------|--------------------------------------|--------------------------------------|---------------------------|---|
| 0.3-1.34                 | 614                                  | 1.63                                 | (100)*                    | 30  |
| 1.34-30                  | 824/f                                | 2.19/f                               | (180/f)*                  | 30  |
| 30-300                   | 27.5                                 | 0.073                                | 0.2                       | 30  |
| 300-1500                 |                                      |                                      | F/1500                    | 30  |
| 1500-100000              |                                      |                                      | 1.0                       | 30  |

Note: f=frequency in MHz; \*Plane-wave equivalent power density



# Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Room101/301/401/102/202/302/402/502/602/702/802, No. 7-2, Caipin Road, Huangpu District, Guangzhou, Guangdong, China

Job No.: 240326030GZU

FCC ID: 2BF54-AXV3Y

#### 2. MPE Calculation Method

 $E(V/m)=(30*P*G)^{0.5}/d$  Power Density:  $Pd(W/m^2)=E^2/377$ 

E=Electric Field (V/m)

P= RF output Power (W)

G=EUT Antenna numeric gain (numeric)

d= Separation distance between radiator and human body (m)

The formula can be changed to

 $Pd= (30*P*G)/(377*d^2)$ 

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

#### 3. Calculated Result and Limit

| Frequency<br>(MHz) | Antenna<br>Gain<br>(Numeric) | Output Power<br>(dBm) | Peak Output<br>Power (mW) | Power Density<br>(S) (mW/cm <sup>2</sup> ) | Limit of<br>Power<br>Density (S)<br>(mW/cm <sup>2</sup> ) | Test<br>Result |
|--------------------|------------------------------|-----------------------|---------------------------|--|---|----------------|
| 2412-2462          | 2.38                         | 14                    | 25.12                     | 0.0119                                     | 1   | Complies       |

### Test Location:

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

All tests were performed at:

Room102/104, No 203, KeZhu Road, Science City, GETDD Guangzhou, China