

**Report No.:** DDT-R22072109-1E02

■ Issued Date: Aug. 16, 2022

# RF EXPOSURE REPORT

#### **FOR**

Applicant		Shenzhen Kunhong Electronics Co., LTD	
Address	•••	Suites 2108-2110, Tower C, Times Square Excellence, Baoan Center, Shenzhen, China	
Equipment under Test	••	Wireless Bluetooth earphones	
Model No.		KHBT013, 71242, 71452, 71453	
Trade Mark	••	N/A	
FCC ID	•	2ATNH-BT013	
Manufacturer	1	Shenzhen Kunhong Electronics Co., LTD	
Address	• •	Suites 2108-2110, Tower C, Times Square Excellence, Baoan Center, Shenzhen, China	

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

**Tel.:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, http://www.dgddt.com



# **Table of Contents**

	Test report declares	3
1.	General Information	5
1.1.	Description of equipment	5
1.2.	Assess laboratory	5
2	RF Exposure evaluation for ECC	

## **Test Report Declare**

Applicant	:	Shenzhen Kunhong Electronics Co., LTD		
Address	:	Suites 2108-2110, Tower C, Times Square Excellence, Baoan Center, Shenzhen, China		
Equipment under Test	:	Wireless Bluetooth earphones		
Model No.	:	KHBT013, 71242, 71452, 71453		
Trade mark	:	N/A ®		
Manufacturer		Shenzhen Kunhong Electronics Co., LTD		
Address	1	Suites 2108-2110, Tower C, Times Square Excellence, Baoan Center, Shenzhen, China		

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

#### We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R22072109-1E02		
Date of Receipt:	Jul. 29, 2022	Date of Test:	Jul. 29, 2022 ~ Aug. 15, 2022

Prepared By:

Johnny Wang/Engineer

Damon Hu/EMC Manager

Approved B

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

# **Revision History**

Rev.	Revisions	Issue Date	Revised By
	Initial issue	Aug. 16, 2022	8
	nD) nD)	nD	7

## 1. General Information

#### 1.1. Description of equipment

EUT* Name	:	Wireless Bluetooth earphones		
Model Number	:	KHBT013, 71242, 71452, 71453		
Difference of models	:	Above models are identical in schematic and structure, only the name and colour are different for all the models, therefore the test performed on the model KHBT013.		
EUT Function Description	:	Please reference user manual of this device		
Power Supply		CHARGING CASE: DC 5V from external AC Adapter EARBUDS: DC 5V from external charging case CHARGING CASE: DC 3.7V Polymer Li-ion built-in battery EARBUDS: DC 3.7V Polymer Li-ion built-in battery		
Radio Specification	:	Bluetooth V5.1		
Operation Frequency	:	2402 MHz - 2480 MHz		
Modulation	:	GFSK, π/4-DQPSK, 8DPSK		
Data Rate	:	1 Mbps, 2 Mbps, 3 Mbps		
Antenna Gain	:	Maximum PK gain: 1.24 dBi		
Sample Type	:	Series production		
Sample Number	:	S22072109-01 for conductive S22072109-02 for radiation		

#### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

## 2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

#### **Manufacturing Tolerance**

#### BT

	GFSK	(Peak)				
Channel	Channel 0	Channel 39	Channel 78			
Target (dBm)	5.06	6.52	6.41			
Tolerance ±(dB)	1	1	1			
π/4DQPSK (Peak)						
Channel	Channel 0	Channel 39	Channel 78			
Target (dBm)	5.55	6.75	6.70			
Tolerance ±(dB)	1	1	1			
	8DPSK	(Peak)				
Channel	Channel 0	Channel 39	Channel 78			
Target (dBm)	5.81	7.10	7.11			
Tolerance ±(dB)	1 🎉	1	¥ 1 1			

#### **Estimtion Result**

Worse case is as below: [2480 MHz, 8.11 dBm, (6.47 mW) output power]

 $(6.47/5) \cdot [\sqrt{2.480(GHz)}] = 2.04 < 3.0 \text{ for } 1-g \text{ SAR}$ 

Then SAR evaluation is not required.

**END OF REPORT**