



SAR EVALUATION REPORT

Applicant Name:

LG Electronics U.S.A., Inc.
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:

04/24/19 - 05/21/19

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

1M1904220062-01-R1.ZNF

FCC ID:

ZNFQ720QM

APPLICANT:

LG ELECTRONICS U.S.A., INC.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model:

LM-Q720QM

Additional Model(s):


LM-Q720QM5, LM-Q720QM6, LMQ720QM, LMQ720QM5,
LMQ720QM6, Q720QM, Q720QM5, Q720QM6

Equipment Class	Band & Mode	Tx Frequency	SAR			
			1g Head (W/kg)	1g Body-Worn (W/kg)	1g Hotspot (W/kg)	10g Phablet (W/kg)
PCE	CDMA/EVDO BC10 (900S)	817.90 - 823.10 MHz	0.18	0.51	0.52	N/A
PCE	CDMA/EVDO BC10 (224)	824.70 - 848.31 MHz	0.19	0.55	0.56	N/A
PCE	PCS CDMA/EVDO	1851.25 - 1908.75 MHz	0.14	0.46	1.15	N/A
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.19	0.67	0.67	N/A
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	< 0.1	0.37	0.88	N/A
PCE	UMTS 850	825.40 - 846.80 MHz	0.20	0.65	0.65	N/A
PCE	UMTS 1755	1712.4 - 1752.6 MHz	0.13	0.56	0.90	N/A
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.11	0.47	1.06	N/A
PCE	LTE Band 71	665.5 - 695.5 MHz	0.19	0.58	0.76	N/A
PCE	LTE Band 12	699.7 - 715.3 MHz	0.18	0.43	0.43	N/A
PCE	LTE Band 17	706.5 - 713.5 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 13	779.5 - 784.5 MHz	0.20	0.68	0.68	N/A
PCE	LTE Band 26 (Cell)	814.7 - 848.3 MHz	0.21	0.58	0.58	N/A
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 66 (AWS)	1710.7 - 1770.3 MHz	0.11	0.52	0.98	N/A
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.11	0.39	0.96	N/A
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 41	2496.5 - 2587.5 MHz	< 0.1	0.33	0.51	2.37
DTS	2.4 GHz WLAN	2412 - 2482 MHz	0.98	0.88	0.83	N/A
NI	U-NI-1	5180 - 5240 MHz	N/A	N/A	0.85	N/A
NI	U-NI-2A	5260 - 5320 MHz	0.90	0.84	N/A	2.17
NI	U-NI-2C	5500 - 5700 MHz	0.79	0.83	N/A	2.03
NI	U-NI-3	5745 - 5825 MHz	0.79	0.84	0.84	N/A
DSS/DTS	Bluetooth	2402 - 2480 MHz	0.10	< 0.1	< 0.1	N/A
Simultaneous SAR per KDB 690783 D01v01r03:			1.20	1.56	1.59	3.55

Note: This revised Test Report (S/N: 1M1904220062-01-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.



This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President





The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 1 of 99

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	12
3	INTRODUCTION	13
4	DOSIMETRIC ASSESSMENT	14
5	DEFINITION OF REFERENCE POINTS	15
6	TEST CONFIGURATION POSITIONS	16
7	RF EXPOSURE LIMITS	20
8	FCC MEASUREMENT PROCEDURES.....	21
9	RF CONDUCTED POWERS	28
10	SYSTEM VERIFICATION.....	60
11	SAR DATA SUMMARY	64
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	83
13	SAR MEASUREMENT VARIABILITY	93
14	EQUIPMENT LIST.....	95
15	MEASUREMENT UNCERTAINTIES.....	96
16	CONCLUSION.....	97
17	REFERENCES	98
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX G: POWER REDUCTION VERIFICATION		
APPENDIX H: DOWNLINK LTE CA RF CONDUCTED POWERS		

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 2 of 99

1 DEVICE UNDER TEST



1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
CDMA/EVDO BC10 (\$90S)	Voice/Data	817.90 - 823.10 MHz
CDMA/EVDO BC0 (\$22H)	Voice/Data	824.70 - 848.31 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 71	Voice/Data	665.5 - 695.5 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 17	Voice/Data	706.5 - 713.5 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 26 (Cell)	Voice/Data	814.7 - 848.3 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Voice/Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Voice/Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5700 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz

1.2 Power Reduction for SAR

This device uses a power reduction mechanism for SAR compliance. The power reduction mechanism is activated when the device is used in close proximity to the user's body. FCC KDB Publication 616217 D04v01r02 Section 6 was used as a guideline for selecting SAR test distances for this device. Detailed descriptions of the power reduction mechanism are included in the operational description.

This device uses an independent fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 3 of 99

1.3 Nominal and Maximum Output Power Specifications



This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum PCE Output Power



Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.2	33.2	32.2	30.7	29.2	27.7	27.7	27.2	27.2
	Nominal	32.7	32.7	31.7	30.2	28.7	27.2	27.2	26.7	26.7
GSM/GPRS/EDGE 1900	Maximum	30.7	30.7	29.2	27.2	25.7	26.2	26.2	25.7	25.7
	Nominal	30.2	30.2	28.7	26.7	25.2	25.7	25.7	25.2	25.2

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	25.5	25.5	25.5
	Nominal	25.0	25.0	25.0
UMTS Band 4 (1750 MHz)	Maximum	24.0	24.0	24.0
	Nominal	23.5	23.5	23.5
UMTS Band 2 (1900 MHz)	Maximum	24.0	24.0	24.0
	Nominal	23.5	23.5	23.5

Mode / Band		Modulated Average (dBm)
CDMA/EVDO BC10 (§90S)	Maximum	25.0
	Nominal	24.5
CDMA/EVDO BC0 (§22H)	Maximum	25.0
	Nominal	24.5
PCS CDMA/EVDO	Maximum	24.7
	Nominal	24.2

FCC ID: ZNFQ720QM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 4 of 99

Mode / Band		Modulated Average (dBm)
LTE Band 71	Maximum	25.5
	Nominal	25.0
LTE Band 12	Maximum	25.5
	Nominal	25.0
LTE Band 17	Maximum	25.5
	Nominal	25.0
LTE Band 13	Maximum	25.5
	Nominal	25.0
LTE Band 26 (Cell)	Maximum	25.5
	Nominal	25.0
LTE Band 5 (Cell)	Maximum	25.5
	Nominal	25.0
LTE Band 66 (AWS)	Maximum	24.0
	Nominal	23.5
LTE Band 4 (AWS)	Maximum	24.0
	Nominal	23.5
LTE Band 25 (PCS)	Maximum	24.0
	Nominal	23.5
LTE Band 2 (PCS)	Maximum	24.0
	Nominal	23.5
LTE Band 41	Maximum	25.0
	Nominal	24.5

FCC ID: ZNFQ720QM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 5 of 99

1.3.2 Reduced PCE Output Power



Mode / Band		Modulated Average (dBm)
LTE Band 41	Maximum	24.0
	Nominal	23.5

1.3.3 Maximum WLAN and Bluetooth Output Power

Mode / Band		Modulated Average - Single Tx Chain (dBm)				
Channel		1	2	3 - 9	10	11
IEEE 802.11b (2.4 GHz)	Maximum	23.0				
	Nominal	22.0				
IEEE 802.11g (2.4 GHz)	Maximum	19.0	20.0	22.0	20.0	18.5
	Nominal	18.0	19.0	21.0	19.0	17.5
IEEE 802.11n (2.4 GHz)	Maximum	18.0	19.0	21.0	19.0	17.5
	Nominal	17.0	18.0	20.0	18.0	16.5

Mode / Band		Modulated Average - Single Tx Chain (dBm)																						
		20 MHz Bandwidth							40 MHz Bandwidth							80 MHz Bandwidth								
	Channel	36	40-60	64-100	104-136	140-149	153-161	165	38	46-54	62-102	110	118-126	134	151-159	42	58	106	122-155					
IEEE 802.11a (5 GHz)	Maximum	16.0	19.5	16.0	19.5	18.0	20.0	18.0																
	Nominal	15.0	18.5	15.0	18.5	17.0	19.0	17.0																
IEEE 802.11n (5 GHz)	Maximum	15.0	18.5	15.0	18.5	17.0	19.0	17.0	13.0	15.0	13.0	15.0	15.0	15.0	15.0									
	Nominal	14.0	17.5	14.0	17.5	16.0	18.0	16.0	12.0	14.0	12.0	14.0	14.0	14.0	14.0									
IEEE 802.11ac (5 GHz)	Maximum	12.0	15.5	12.0	15.5	14.0	16.0	14.0	12.0	13.0	12.0	13.0	13.0	13.0	13.0	11.0	12.0	11.0	13.0					
	Nominal	11.0	14.5	11.0	14.5	13.0	15.0	13.0	11.0	12.0	11.0	12.0	12.0	12.0	12.0	10.0	11.0	10.0	12.0					

Mode/Band		Modulated Average (dBm)
Bluetooth	Maximum	11.0
	Nominal	10.0
Bluetooth LE	Maximum	2.0
	Nominal	1.0



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 6 of 99

1.3.4

Reduced WLAN Output Power

Mode / Band		Modulated Average (dBm)				
Channel		1	2	3 - 9	10	11
IEEE 802.11b (2.4 GHz)	Maximum	19.0				
	Nominal	18.0				
IEEE 802.11g (2.4 GHz)	Maximum	16.0	17.0	19.0	17.0	15.5
	Nominal	15.0	16.0	18.0	16.0	14.5
IEEE 802.11n (2.4 GHz)	Maximum	16.0	17.0	19.0	17.0	15.5
	Nominal	15.0	16.0	18.0	16.0	14.5

Mode / Band		Modulated Average - Single Tx Chain (dBm)																						
		20 MHz Bandwidth							40 MHz Bandwidth							80 MHz Bandwidth								
	Channel	36	40-60	64-100	104-136	140-149	153-161	165	38	46-54	62-102	110	118-126	134	151-159	42	58	106	122-155					
IEEE 802.11a (5 GHz)	Maximum	14.0	17.5	14.0	17.5	16.0	18.0	16.0																
	Nominal	13.0	16.5	13.0	16.5	15.0	17.0	15.0																
IEEE 802.11n (5 GHz)	Maximum	14.0	17.5	14.0	17.5	16.0	18.0	16.0	13.0	15.0	13.0	15.0	15.0	15.0	15.0									
	Nominal	13.0	16.5	13.0	16.5	15.0	17.0	15.0	12.0	14.0	12.0	14.0	14.0	14.0	14.0									
IEEE 802.11ac (5 GHz)	Maximum	12.0	15.5	12.0	15.5	14.0	16.0	14.0	12.0	13.0	12.0	13.0	13.0	13.0	13.0	11.0	12.0	11.0	13.0					
	Nominal	11.0	14.5	11.0	14.5	13.0	15.0	13.0	11.0	12.0	11.0	12.0	12.0	12.0	12.0	10.0	11.0	10.0	12.0					

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 7 of 99

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device antennas can be found in Appendix F. Since the diagonal dimension of this device is > 160 mm and <200 mm, it is considered a “phablet.”

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Front	Top	Bottom	Right	Left
EVDO BC10 (§90S)	Yes	Yes	No	Yes	Yes	Yes
EVDO BC0 (§22H)	Yes	Yes	No	Yes	Yes	Yes
PCS EVDO	Yes	Yes	No	Yes	Yes	No
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	No
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	Yes	No
UMTS 1900	Yes	Yes	No	Yes	Yes	No
LTE Band 71	Yes	Yes	No	Yes	Yes	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 13	Yes	Yes	No	Yes	Yes	Yes
LTE Band 26 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 66 (AWS)	Yes	Yes	No	Yes	Yes	No
LTE Band 25 (PCS)	Yes	Yes	No	Yes	Yes	No
LTE Band 41	Yes	Yes	No	Yes	Yes	No
2.4 GHz WLAN	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN	Yes	Yes	Yes	No	No	Yes
Bluetooth	Yes	Yes	Yes	No	No	Yes

Note: Particular DUT edges were not required to be evaluated for wireless router SAR or phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III and FCC KDB Publication 648474 D04v01r03. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-2A and U-NII-2C operations are disabled.

1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be operating simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 8 of 99

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Phablet	Notes
1	1x CDMA voice + 2.4 GHz W-Fi	Yes	Yes	N/A	Yes	
2	1x CDMA voice + 5 GHz W-Fi	Yes	Yes	N/A	Yes	
3	1x CDMA voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	Yes	^ Bluetooth Tethering is considered
4	1x CDMA voice + 2.4 GHz Bluetooth + 5 GHz W-Fi	Yes^	Yes	N/A	Yes	^ Bluetooth Tethering is considered
5	GSM voice + 2.4 GHz W-Fi	Yes	Yes	N/A	Yes	
6	GSM voice + 5 GHz W-Fi	Yes	Yes	N/A	Yes	
7	GSM voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	Yes	^ Bluetooth Tethering is considered
8	GSM voice + 2.4 GHz Bluetooth + 5 GHz W-Fi	Yes^	Yes	N/A	Yes	^ Bluetooth Tethering is considered
9	UMTS + 2.4 GHz W-Fi	Yes	Yes	Yes	Yes	
10	UMTS + 5 GHz W-Fi	Yes	Yes	Yes	Yes	
11	UMTS + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	Yes	^ Bluetooth Tethering is considered
12	UMTS + 2.4 GHz Bluetooth + 5 GHz W-Fi	Yes^	Yes	Yes^	Yes	^ Bluetooth Tethering is considered
13	LTE + 2.4 GHz W-Fi	Yes	Yes	Yes	Yes	
14	LTE + 5 GHz W-Fi	Yes	Yes	Yes	Yes	
15	LTE + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	Yes	^ Bluetooth Tethering is considered
16	LTE + 2.4 GHz Bluetooth + 5 GHz W-Fi	Yes^	Yes	Yes^	Yes	^ Bluetooth Tethering is considered
17	CDMA/EVDO data + 2.4 GHz W-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
18	CDMA/EVDO data + 5 GHz W-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
19	CDMA/EVDO data + 2.4 GHz Bluetooth	Yes*^	Yes*	Yes^	Yes	* Pre-installed VOIP applications are considered ^ Bluetooth Tethering is considered
20	CDMA/EVDO data + 2.4 GHz Bluetooth + 5 GHz W-Fi	Yes*^	Yes*	Yes^	Yes	* Pre-installed VOIP applications are considered ^ Bluetooth Tethering is considered
21	GPRS/EDGE + 2.4 GHz W-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
22	GPRS/EDGE + 5 GHz W-Fi	Yes*	Yes*	Yes	Yes	* Pre-installed VOIP applications are considered
23	GPRS/EDGE + 2.4 GHz Bluetooth	Yes*^	Yes*	Yes^	Yes	* Pre-installed VOIP applications are considered ^ Bluetooth Tethering is considered
24	GPRS/EDGE + 2.4 GHz Bluetooth + 5 GHz W-Fi	Yes*^	Yes*	Yes^	Yes	* Pre-installed VOIP applications are considered ^ Bluetooth Tethering is considered

- 2.4 GHz WLAN and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
- 5 GHz Wireless Router is only supported for U-NII-1 and U-NII-3 by S/W, therefore U-NII2A and U-NII2C were not evaluated for wireless router conditions.
- This device supports VOLTE.
- This device supports VoWIFI.
- This device supports Bluetooth Tethering.



1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-2A & U-NII-2C WIFI, only 2.4 GHz, U-NII-1, and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

This device supports IEEE 802.11ac with the following features:

- Up to 80 MHz Bandwidth only
- No aggregate channel configurations
- 256 QAM is supported
- TDWR channels are supported
- 1 Tx antenna output

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 9 of 99	

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Because wireless router operations are not supported for U-NII-2A & U-NII-2C WLAN, phablet SAR tests were performed. Phablet SAR was not evaluated for 2.4 GHz WLAN, U-NII-1 WLAN, U-NII-3 WLAN and 2.4 GHz Bluetooth operations since wireless router 1g SAR was < 1.2 W/kg.

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.



LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports 64QAM on the uplink for LTE Operations. Conducted powers for 64QAM configurations were measured per Section 5.1 of FCC KDB Publication 941225 D05v02r05. SAR was not required for 64QAM since the highest maximum output power for 64 QAM is $\leq \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg, per Section 5.2.4 of FCC KDB Publication 941225 D05v02r05.

This device supports LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive. The downlink carrier aggregation exclusion analysis can be found in Appendix H.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Additional SAR tests for phablet SAR were evaluated per KDB 616217 Section 6 (See Section 6.9 for more information).

This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 10 of 99

1.8 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D04v01r03 (Phablet Procedures)
- FCC KDB Publication 616217 D04v01r02 (Proximity Sensor)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)
- April 2018 TCB Workshop Notes (LTE Carrier Aggregation)

1.9 Device Serial Numbers



Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 11.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 11 of 99

2

LTE INFORMATION

LTE Information					
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 71 (665.5 - 695.5 MHz)				
	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 17 (706.5 - 713.5 MHz)				
	LTE Band 13 (779.5 - 784.5 MHz)				
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 66 (AWS) (1710.7 - 1779.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 41 (2498.5 - 2687.5 MHz)				
	LTE Band 71: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Bandwidths	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 17: 5 MHz, 10 MHz				
	LTE Band 13: 5 MHz, 10 MHz				
	LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 71: 5 MHz				
	LTE Band 71: 10 MHz				
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High	High
	665.5 (133147)	680.5 (133297)	695.5 (133447)		
LTE Band 71: 10 MHz	668 (133172)	680.5 (133297)	693 (133422)		
LTE Band 71: 15 MHz	670.5 (133197)	680.5 (133297)	690.5 (133397)		
LTE Band 71: 20 MHz	673 (133222)	680.5 (133297)	688 (133372)		
LTE Band 12: 1.4 MHz	699.7 (23017)	707.5 (23095)	715.3 (23173)		
LTE Band 12: 3 MHz	700.5 (23025)	707.5 (23095)	714.5 (23165)		
LTE Band 12: 5 MHz	701.5 (23035)	707.5 (23095)	713.5 (23155)		
LTE Band 12: 10 MHz	704 (23060)	707.5 (23095)	711 (23130)		
LTE Band 17: 5 MHz	706.5 (23755)	710 (23790)	713.5 (23825)		
LTE Band 17: 10 MHz	709 (23780)	710 (23790)	711 (23800)		
LTE Band 13: 5 MHz	779.5 (23205)	782 (23230)	784.5 (23255)		
LTE Band 13: 10 MHz	N/A	782 (23230)	N/A		
LTE Band 26 (Cell): 1.4 MHz	814.7 (26697)	831.5 (26865)	848.3 (27033)		
LTE Band 26 (Cell): 3 MHz	815.5 (26705)	831.5 (26865)	847.5 (27025)		
LTE Band 26 (Cell): 5 MHz	816.5 (26715)	831.5 (26865)	846.5 (27015)		
LTE Band 26 (Cell): 10 MHz	819 (26740)	831.5 (26865)	844 (26990)		
LTE Band 26 (Cell): 15 MHz	821.5 (26765)	831.5 (26865)	841.5 (26965)		
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)		
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)		
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)		
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)		
LTE Band 66 (AWS): 1.4 MHz	1710.7 (131979)	1745 (132322)	1779.3 (132665)		
LTE Band 66 (AWS): 3 MHz	1711.5 (131987)	1745 (132322)	1778.5 (132657)		
LTE Band 66 (AWS): 5 MHz	1712.5 (131997)	1745 (132322)	1777.5 (132647)		
LTE Band 66 (AWS): 10 MHz	1715 (132022)	1745 (132322)	1775 (132622)		
LTE Band 66 (AWS): 15 MHz	1717.5 (132047)	1745 (132322)	1772.5 (132597)		
LTE Band 66 (AWS): 20 MHz	1720 (132072)	1745 (132322)	1770 (132572)		
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)		
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)		
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)		
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)		
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)		
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)		
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)	1882.5 (26365)	1914.3 (26683)		
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)	1882.5 (26365)	1913.5 (26675)		
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)	1882.5 (26365)	1912.5 (26665)		
LTE Band 25 (PCS): 10 MHz	1855 (26090)	1882.5 (26365)	1910 (26640)		
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)	1882.5 (26365)	1907.5 (26615)		
LTE Band 25 (PCS): 20 MHz	1860 (26140)	1882.5 (26365)	1905 (26590)		
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)		
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)		
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)		
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)		
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)		
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)		
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
UE Category	DL UE Cat 6, UL UE Cat 5				
Modulations Supported in UL	QPSK, 16QAM, 64QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations				
LTE Additional Information	This device does not support full CA features on 3GPP Release 10. It supports carrier aggregation features as shown in Appendix H. All other uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eICIC, WiFi Offloading, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 12 of 99

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$



SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 13 of 99

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.






Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoomTV}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
				$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: ZNFQ720QM	 SAR EVALUATION REPORT 			Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 14 of 99

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.




Figure 5-2
Front, back and side view of SAM Twin Phantom






Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 15 of 99

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.






Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 16 of 99




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.






Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 17 of 99

contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations



Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1g body and 10g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 18 of 99

6.8 Phablet Configurations



For smart phones with a display diagonal dimension > 150 mm or an overall diagonal dimension > 160 mm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna ≤ 25 mm from that surface or edge, in direct contact with the phantom, for 10g SAR. The UMPC mini-tablet 1g SAR at 5 mm is not required. When hotspot mode applies, 10g SAR is required only for the surfaces and edges with hotspot mode 1g SAR > 1.2 W/kg.

6.9 Proximity Sensor Considerations

This device uses a power reduction mechanism to reduce output powers in certain use conditions when the device is used close the user's body.

When the device's antenna is within a certain distance of the user, the sensor activates and reduces the maximum allowed output power. However, the sensor is not active when the device is moved beyond the sensor triggering distance and the maximum output power is no longer limited. Therefore, additional evaluation is needed in the vicinity of the triggering distance to ensure SAR is compliant when the device is allowed to operate at a non-reduced output power level. FCC KDB Publication 616217 D04v01r02 Section 6 was used as a guideline for selecting SAR test distances for this device at these additional test positions. Sensor triggering distance summary data is included in Appendix G.

The sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the sensor entirely covers the antennas.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 19 of 99

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.



7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 20 of 99

8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”



The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

8.4.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.” Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 21 of 99

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH₀ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH₀ data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

Table 8-1
Parameters for Max. Power for RC1

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 8-2
Parameters for Max. Power for RC3

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at full rate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode; otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

Head SAR is additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.4.5 for EVDO Rev. A configuration parameters.

8.4.3 Body-worn SAR Measurements



SAR for body-worn exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH+SCH_n), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH_n), with FCH at full rate and SCH₀ enabled at 9600 bps, using the highest reported SAR configuration for FCH only. When multiple code channels are enabled, the transmitter output can shift by more than 0.5 dB and may lead to higher SAR drifts and SCH dropouts.

The 3G SAR test reduction procedure is applied to body-worn accessory SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

8.4.4 Body-worn SAR Measurements for EVDO Devices

For handsets with EVDO capabilities, the 3G SAR test reduction procedure is applied to EVDO Rev. 0 with 1x RTT RC3 as the primary mode to determine body-worn accessory test requirements. Otherwise, body-worn accessory SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

The 3G SAR test reduction procedure is applied to Rev. A, with Rev. 0 as the primary mode to determine body-worn accessory SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1x RTT RC3 as the primary mode.

FCC ID: ZNFQ720QM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 22 of 99

When SAR is required for EVDO Rev. A, SAR is measured with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations, using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0 or 1x RTT RC3, as appropriate.

8.4.5 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode; otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

For EVDO data devices that also support 1x RTT voice and/or data operations, the 3G SAR test reduction procedure is applied to 1x RTT RC3 and RC1 with EVDO Rev. 0 and Rev. A as the respective primary modes. Otherwise, the 'Body-Worn Accessory SAR' procedures in the '3GPP2 CDMA 2000 1x Handsets' section are applied.

8.5 SAR Measurement Conditions for UMTS

8.5.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCH_n and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.5.2 Head SAR Measurements



SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1s". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.5.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.5.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 23 of 99

12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.5.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.6 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.6.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.6.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.



8.6.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.6.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 24 of 99

- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to ½ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is <1.45 W/kg.

8.6.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

8.6.6 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. Additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for downlink only carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.



8.7 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.7.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 25 of 99

8.7.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.7.4 Initial Test Position Procedure



For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 26 of 99

8.7.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.



8.7.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.7.6). When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 27 of 99

9 RF CONDUCTED POWERS

9.1 CDMA Conducted Powers

Table 9-1
Maximum Conducted Power

Band	Channel	Rule Part	Frequency	SO55 [dBm]	SO55 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC		MHz	RC1	RC3	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	564	90S	820.1	24.80	24.78	24.85	24.87	24.90	24.82
Cellular	1013	22H	824.7	24.87	24.96	24.93	24.93	24.99	24.96
	384	22H	836.52	24.79	24.87	24.85	24.89	24.91	24.96
	777	22H	848.31	24.68	24.74	24.73	24.78	24.83	24.79
PCS	25	24E	1851.25	24.67	24.63	24.62	24.64	24.67	24.66
	600	24E	1880	24.66	24.62	24.58	24.60	24.63	24.62
	1175	24E	1908.75	24.62	24.67	24.66	24.68	24.61	24.61

Note: RC1 is only applicable for IS-95 compatibility. For FCC Rule Part 90S, Per FCC KDB Publication 447498 D01v06 4.1.g), only one channel is required since the device operates within the transmission range of 817.90 – 823.10 MHz.






Figure 9-1
Power Measurement Setup

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 28 of 99



9.2 GSM Conducted Powers

Table 9-2
Maximum Conducted Power

Maximum Burst-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	32.79	32.62	31.85	30.67	29.00	27.56	27.50	26.90	26.65
	190	32.92	32.78	31.91	30.69	28.73	27.63	27.49	26.83	26.72
	251	32.95	33.02	31.67	30.70	28.98	27.60	27.63	26.85	26.69
GSM 1900	512	29.89	29.79	28.84	27.14	25.63	25.25	24.60	25.20	25.20
	661	29.87	29.83	28.52	27.15	25.67	25.23	24.54	25.19	25.27
	810	29.85	29.86	28.54	27.17	25.70	25.13	24.62	25.15	25.23

Calculated Maximum Frame-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	23.76	23.59	25.83	26.41	25.99	18.53	21.48	22.64	23.64
	190	23.89	23.75	25.89	26.43	25.72	18.60	21.47	22.57	23.71
	251	23.92	23.99	25.65	26.44	25.97	18.57	21.61	22.59	23.68
GSM 1900	512	20.86	20.76	22.82	22.88	22.62	16.22	18.58	20.94	22.19
	661	20.84	20.80	22.50	22.89	22.66	16.20	18.52	20.93	22.26
	810	20.82	20.83	22.52	22.91	22.69	16.10	18.60	20.89	22.22

GSM 850	Frame Avg.Targets:	23.67	23.67	25.68	25.94	25.69	18.17	21.18	22.44	23.69
GSM 1900		21.17	21.17	22.68	22.44	22.19	16.67	19.68	20.94	22.19

FCC ID: ZNFQ720QM			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset			Page 29 of 99



Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 12 (Max 4 Tx uplink slots)
EDGE Multislot class: 12 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A



Figure 9-2
Power Measurement Setup

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 30 of 99

9.3 UMTS Conducted Powers



Table 9-3
Maximum Conducted Power

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	25.49	25.33	25.40	23.78	23.81	23.76	23.86	23.85	23.95	-
99		12.2 kbps AMR	25.50	25.35	25.37	23.85	23.83	23.77	23.84	23.81	23.95	-
6	HSDPA	Subtest 1	25.50	25.33	25.42	23.76	23.71	23.81	23.86	23.86	23.96	0
6		Subtest 2	25.49	25.31	25.36	23.72	23.75	23.90	23.82	23.83	23.93	0
6		Subtest 3	24.92	24.82	24.85	23.23	23.24	23.05	23.35	23.34	23.48	0.5
6		Subtest 4	24.96	24.80	24.81	23.20	23.29	23.10	23.40	23.26	23.49	0.5
6	HSUPA	Subtest 1	24.78	24.55	24.58	22.76	22.72	22.78	22.84	22.84	22.96	0
6		Subtest 2	23.45	23.32	23.34	21.73	21.68	21.73	21.80	21.84	21.82	2
6		Subtest 3	24.47	24.36	24.50	22.77	22.66	22.78	22.81	22.79	22.99	1
6		Subtest 4	23.47	23.34	23.41	21.72	21.65	21.75	21.86	21.89	21.82	2
6		Subtest 5	25.50	25.33	25.37	23.80	23.70	23.68	23.93	23.85	23.93	0

This device does not support DC-HSDPA.



Figure 9-3
Power Measurement Setup

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 31 of 99

9.4 LTE Conducted Powers

9.4.1

LTE Band 71

Table 9-4
LTE Band 71 Conducted Powers - 20 MHz Bandwidth

LTE Band 71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.36	0	0
	1	50	25.21		0
	1	99	25.11		0
	50	0	24.19	0-1	1
	50	25	24.02		1
	50	50	24.14		1
	100	0	24.00		1
16QAM	1	0	24.24	0-1	1
	1	50	24.20		1
	1	99	24.25		1
	50	0	23.13	0-2	2
	50	25	23.21		2
	50	50	23.10		2
	100	0	23.00		2
64QAM	1	0	23.24	0-2	2
	1	50	23.12		2
	1	99	23.15		2
	50	0	21.97	0-3	3
	50	25	21.86		3
	50	50	21.81		3
	100	0	21.82		3

Note: LTE Band 71 at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 32 of 99

Table 9-5
LTE Band 71 Conducted Powers - 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.42	0	0
	1	36	25.16		0
	1	74	25.31		0
	36	0	23.84	0-1	1
	36	18	23.75		1
	36	37	23.74		1
	75	0	23.73		1
16QAM	1	0	24.04	0-1	1
	1	36	23.80		1
	1	74	23.92		1
	36	0	22.91	0-2	2
	36	18	22.84		2
	36	37	22.79		2
	75	0	22.71		2
64QAM	1	0	23.24	0-2	2
	1	36	23.03		2
	1	74	23.21		2
	36	0	21.77	0-3	3
	36	18	21.78		3
	36	37	21.64		3
	75	0	21.79		3

Note: LTE Band 71 at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.





FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 33 of 99

Table 9-6
LTE Band 71 Conducted Powers - 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.22	25.16	25.22	0	0
	1	25	25.07	25.14	25.36		0
	1	49	25.32	25.28	25.36		0
	25	0	23.80	23.89	23.80	0-1	1
	25	12	23.89	23.79	23.74		1
	25	25	23.84	23.84	23.80		1
	50	0	23.87	23.84	23.85		1
16QAM	1	0	23.89	24.11	24.03	0-1	1
	1	25	23.82	23.89	24.00		1
	1	49	24.00	24.02	24.23		1
	25	0	22.92	22.88	22.85	0-2	2
	25	12	22.92	22.83	22.82		2
	25	25	22.91	22.85	22.85		2
	50	0	22.80	22.84	22.84		2
64QAM	1	0	22.85	22.90	23.31	0-2	2
	1	25	22.78	22.85	23.33		2
	1	49	22.92	22.87	23.50		2
	25	0	21.91	21.98	21.80	0-3	3
	25	12	21.93	21.97	21.80		3
	25	25	21.92	22.05	21.86		3
	50	0	22.00	21.88	21.83		3

Table 9-7
LTE Band 71 Conducted Powers - 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.23	25.44	25.14	0	0
	1	12	25.13	25.35	25.18		0
	1	24	25.25	25.37	25.22		0
	12	0	23.83	23.80	23.97	0-1	1
	12	6	23.89	23.81	23.94		1
	12	13	23.82	23.77	23.84		1
16QAM	25	0	23.84	23.79	23.90		1
	1	0	24.07	24.10	24.04	0-1	1
	1	12	24.01	24.04	24.08		1
	1	24	24.02	24.06	24.01		
	12	0	22.84	22.85	23.01	0-2	2
	12	6	22.96	22.88	22.94		2
	12	13	22.74	22.89	22.91		2
64QAM	25	0	22.83	22.91	22.94		2
	1	0	23.04	23.37	22.98	0-2	2
	1	12	23.01	23.11	23.00		2
	1	24	22.94	23.27	23.00		
	12	0	21.86	21.78	21.94	0-3	3
	12	6	21.86	21.83	21.93		3
	12	13	21.82	21.80	21.87		3
	25	0	21.97	21.92	21.89		3

FCC ID: ZNFQ720QM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 34 of 99	

9.4.2

LTE Band 12

Table 9-8
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.24	0	0
	1	25	25.38		0
	1	49	25.50		0
	25	0	23.67	0-1	1
	25	12	23.68		1
	25	25	23.79		1
	50	0	23.67		1
16QAM	1	0	23.96	0-1	1
	1	25	24.07		1
	1	49	24.27		1
	25	0	22.76	0-2	2
	25	12	22.66		2
	25	25	22.82		2
	50	0	22.67		2
64QAM	1	0	22.78	0-2	2
	1	25	22.90		2
	1	49	22.94		2
	25	0	21.68	0-3	3
	25	12	21.66		3
	25	25	21.76		3
	50	0	21.71		3

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 35 of 99	

Table 9-9
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.03	25.11	25.32	0	0
	1	12	25.01	25.15	25.42		0
	1	24	25.13	25.16	25.38		0
	12	0	23.75	23.61	23.70	0-1	1
	12	6	23.70	23.68	23.61		1
	12	13	23.66	23.67	23.66		1
	25	0	23.67	23.73	23.61		1
16QAM	1	0	24.15	23.95	24.26	0-1	1
	1	12	24.13	23.81	24.42		1
	1	24	24.21	24.07	24.31		1
	12	0	22.58	22.57	22.67	0-2	2
	12	6	22.58	22.66	22.67		2
	12	13	22.60	22.65	22.61		2
	25	0	22.63	22.68	22.65		2
64QAM	1	0	23.05	22.91	22.99	0-2	2
	1	12	22.80	22.81	22.65		2
	1	24	22.99	22.85	22.97		2
	12	0	21.91	21.91	21.90	0-3	3
	12	6	21.90	21.95	21.94		3
	12	13	21.91	21.99	21.95		3
	25	0	21.95	21.98	21.89		3

Table 9-10
LTE Band 12 Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.89	25.02	24.96	0	0
	1	7	24.88	24.98	25.02		0
	1	14	25.08	25.02	25.02		0
	8	0	23.72	23.68	23.56	0-1	1
	8	4	23.65	23.75	23.64		1
	8	7	23.62	23.75	23.60		1
	15	0	23.66	23.73	23.64		1
16QAM	1	0	24.20	24.21	24.02	0-1	1
	1	7	24.48	24.50	24.27		1
	1	14	24.15	24.28	23.85		1
	8	0	22.73	22.69	22.85	0-2	2
	8	4	22.71	22.75	22.87		2
	8	7	22.69	22.81	22.77		2
	15	0	22.79	22.68	22.73		2
64QAM	1	0	23.12	23.02	23.16	0-2	2
	1	7	23.05	23.20	23.11		2
	1	14	23.10	23.05	23.08		2
	8	0	22.05	21.77	21.82	0-3	3
	8	4	21.93	21.81	21.85		3
	8	7	21.89	21.79	21.86		3
	15	0	21.90	21.80	21.82		3





FCC ID: ZNFQ720QM	 PCTEST <small>ENGINEERING LABORATORY, INC.</small>	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 36 of 99	

Table 9-11
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.92	25.03	25.06	0	0
	1	2	24.92	25.02	25.20		0
	1	5	25.06	25.07	25.19		0
	3	0	24.92	25.02	25.00		0
	3	2	25.04	25.06	25.21		0
	3	3	25.02	25.08	25.06		0
	6	0	23.63	23.69	23.68	0-1	1
16QAM	1	0	23.73	23.56	24.00	0-1	1
	1	2	23.75	23.63	24.20		1
	1	5	23.78	23.79	24.12		1
	3	0	23.65	23.73	23.60		1
	3	2	23.66	23.75	23.83		1
	3	3	23.61	23.81	23.70		1
	6	0	22.80	22.83	22.60	0-2	2
64QAM	1	0	23.23	23.16	22.99	0-2	2
	1	2	23.35	23.26	23.04		2
	1	5	23.27	23.33	22.98		2
	3	0	23.20	23.20	23.32		2
	3	2	23.24	23.29	23.34		2
	3	3	23.22	23.26	23.40		2
	6	0	21.50	21.45	21.55	0-3	3

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 37 of 99

9.4.3

LTE Band 13

Table 9-12
LTE Band 13 Conducted Powers - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.97	0	0
	1	25	24.88		0
	1	49	24.89		0
	25	0	23.69	0-1	1
	25	12	23.72		1
	25	25	23.78		1
	50	0	23.75		1
16QAM	1	0	23.92	0-1	1
	1	25	23.83		1
	1	49	23.87		1
	25	0	22.74	0-2	2
	25	12	22.80		2
	25	25	22.76		2
	50	0	22.80		2
64QAM	1	0	23.20	0-2	2
	1	25	22.92		2
	1	49	22.93		2
	25	0	21.62	0-3	3
	25	12	21.78		3
	25	25	21.76		3
	50	0	21.77		3





FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 38 of 99

Table 9-13
LTE Band 13 Conducted Powers - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.74	0	0
	1	12	24.83		0
	1	24	24.99		0
	12	0	23.83	0-1	1
	12	6	23.84		1
	12	13	23.72		1
	25	0	23.76		1
16QAM	1	0	24.30	0-1	1
	1	12	24.18		1
	1	24	24.02		1
	12	0	22.76	0-2	2
	12	6	22.80		2
	12	13	22.70		2
	25	0	22.74		2
64QAM	1	0	22.81	0-2	2
	1	12	22.63		2
	1	24	22.56		2
	12	0	21.64	0-3	3
	12	6	21.61		3
	12	13	21.62		3
	25	0	21.61		3

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 39 of 99	

9.4.4

LTE Band 26 (Cell)

Table 9-14
LTE Band 26 (Cell) Conducted Powers - 15 MHz Bandwidth

LTE Band 26 (Cell) 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26865 (831.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.50	0	0
	1	36	25.23		0
	1	74	25.21		0
	36	0	23.81	0-1	1
	36	18	23.75		1
	36	37	23.71		1
	75	0	23.76		1
16QAM	1	0	24.06	0-1	1
	1	36	23.87		1
	1	74	23.89		1
	36	0	22.89	0-2	2
	36	18	22.88		2
	36	37	22.78		2
	75	0	22.82		2
64QAM	1	0	23.15	0-2	2
	1	36	22.92		2
	1	74	22.95		2
	36	0	21.87	0-3	3
	36	18	21.81		3
	36	37	21.80		3
	75	0	21.79		3

Note: LTE Band 26 (Cell) at 15 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 40 of 99

Table 9-15
LTE Band 26 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.28	25.19	25.13	0	0
	1	25	24.94	25.07	25.02		0
	1	49	25.07	25.10	25.12		0
	25	0	23.50	23.54	23.44	0-1	1
	25	12	23.49	23.53	23.49		1
	25	25	23.41	23.54	23.50		1
	50	0	23.48	23.61	23.49		1
16QAM	1	0	23.87	23.94	23.93	0-1	1
	1	25	23.51	23.68	23.64		1
	1	49	23.69	23.78	23.78		1
	25	0	22.65	22.56	22.50	0-2	2
	25	12	22.64	22.55	22.52		2
	25	25	22.52	22.57	22.52		2
	50	0	22.61	22.54	22.56		2
64QAM	1	0	22.83	22.78	22.95	0-2	2
	1	25	22.56	22.56	22.93		2
	1	49	22.61	22.66	22.80		2
	25	0	21.66	21.71	21.55	0-3	3
	25	12	21.67	21.72	21.52		3
	25	25	21.58	21.77	21.47		3
	50	0	21.71	21.56	21.60		3

Table 9-16
LTE Band 26 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.29	25.21	25.10	0	0
	1	12	25.33	25.34	24.84		0
	1	24	25.09	25.16	24.92		0
	12	0	23.65	23.51	23.62	0-1	1
	12	6	23.59	23.51	23.56		1
	12	13	23.49	23.51	23.50		1
	25	0	23.52	23.51	23.56		1
16QAM	1	0	24.28	23.89	23.88	0-1	1
	1	12	24.07	23.83	23.66		1
	1	24	24.08	23.60	23.89		1
	12	0	22.81	22.65	22.62	0-2	2
	12	6	22.70	22.65	22.60		2
	12	13	22.57	22.64	22.47		2
	25	0	22.57	22.58	22.59		2
64QAM	1	0	22.96	23.10	22.85	0-2	2
	1	12	22.92	23.16	22.72		2
	1	24	22.77	22.88	22.66		2
	12	0	21.80	21.55	21.57	0-3	3
	12	6	21.69	21.51	21.57		3
	12	13	21.57	21.58	21.46		3
	25	0	21.64	21.45	21.58		3





FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 41 of 99	

Table 9-17
LTE Band 26 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.16	25.10	25.08	0	0
	1	7	25.20	25.07	24.90		0
	1	14	25.14	25.02	24.91		0
	8	0	23.55	23.45	23.43	0-1	1
	8	4	23.51	23.46	23.40		1
	8	7	23.45	23.43	23.40		1
	15	0	23.56	23.50	23.42		1
16QAM	1	0	23.60	23.80	23.78	0-1	1
	1	7	23.46	23.76	23.72		1
	1	14	23.41	23.76	23.46		1
	8	0	22.57	22.43	22.44	0-2	2
	8	4	22.52	22.52	22.41		2
	8	7	22.48	22.40	22.40		2
	15	0	22.56	22.52	22.44		2
64QAM	1	0	22.68	22.73	22.87	0-2	2
	1	7	22.42	22.60	22.80		2
	1	14	22.59	22.52	22.64		2
	8	0	21.65	21.53	21.52	0-3	3
	8	4	21.67	21.60	21.52		3
	8	7	21.54	21.49	21.47		3
	15	0	21.60	21.56	21.43		3

Table 9-18
LTE Band 26 (Cell) Conducted Powers - 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.04	25.02	25.01	0	0
	1	2	25.16	25.05	25.07		0
	1	5	25.11	25.02	25.09		0
	3	0	25.22	25.13	25.02		0
	3	2	25.19	25.24	24.99		0
	3	3	25.16	25.10	24.97		0
	6	0	23.61	23.45	23.33	0-1	1
16QAM	1	0	23.59	23.70	23.59	0-1	1
	1	2	23.56	23.71	23.45		1
	1	5	23.56	23.72	23.47		1
	3	0	23.67	23.38	23.27		1
	3	2	23.80	23.46	23.35		1
	3	3	23.76	23.40	23.34		1
	6	0	22.59	22.59	22.32	0-2	2
64QAM	1	0	22.65	22.68	22.69	0-2	2
	1	2	22.57	22.48	22.71		2
	1	5	22.50	22.50	22.62		2
	3	0	22.72	22.28	22.58		2
	3	2	22.96	22.37	22.56		2
	3	3	22.71	22.32	22.46		2
	6	0	21.40	21.51	21.34	0-3	3

FCC ID: ZNFQ720QM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 42 of 99	

9.4.5

LTE Band 66 (AWS)

Table 9-19
LTE Band 66 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.86	23.71	23.92	0	0
	1	50	23.81	23.87	23.96		0
	1	99	23.88	23.74	23.98		0
	50	0	22.72	22.53	22.63	0-1	1
	50	25	22.59	22.49	22.83		1
	50	50	22.62	22.33	22.70		1
	100	0	22.51	22.43	22.71		1
16QAM	1	0	22.63	22.54	22.61	0-1	1
	1	50	22.66	22.55	22.78		1
	1	99	22.90	22.88	22.84		1
	50	0	21.48	21.50	21.64	0-2	2
	50	25	21.63	21.56	21.69		2
	50	50	21.70	21.66	21.79		2
	100	0	21.52	21.58	21.71		2
64QAM	1	0	21.83	21.66	21.86	0-2	2
	1	50	21.59	21.55	21.82		2
	1	99	21.95	21.41	21.83		2
	50	0	20.48	20.88	20.64	0-3	3
	50	25	20.67	20.52	20.62		3
	50	50	20.75	20.54	20.75		3
	100	0	20.53	20.55	20.65		3



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 43 of 99

Table 9-20
LTE Band 66 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.81	23.85	23.86	0	0
	1	36	23.63	23.74	23.62		0
	1	74	23.73	23.84	23.68		0
	36	0	22.69	22.64	22.66	0-1	1
	36	18	22.66	22.58	22.64		1
	36	37	22.55	22.55	22.65		1
	75	0	22.59	22.48	22.60		1
16QAM	1	0	22.63	22.61	22.98	0-1	1
	1	36	22.34	22.43	22.75		1
	1	74	22.41	22.47	22.84		1
	36	0	21.56	21.78	21.67	0-2	2
	36	18	21.62	21.70	21.64		2
	36	37	21.62	21.62	21.64		2
	75	0	21.72	21.51	21.61		2
64QAM	1	0	21.78	21.99	22.00	0-2	2
	1	36	21.49	22.00	21.80		2
	1	74	21.54	21.91	21.91		2
	36	0	20.38	20.46	20.40	0-3	3
	36	18	20.30	20.27	20.33		3
	36	37	20.34	20.24	20.44		3
	75	0	20.31	20.26	20.34		3

Table 9-21
LTE Band 66 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132622 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.63	23.61	23.71	0	0
	1	25	23.46	23.43	23.60		0
	1	49	23.72	23.63	23.73		0
	25	0	22.49	22.38	22.38	0-1	1
	25	12	22.48	22.43	22.46		1
	25	25	22.50	22.40	22.51		1
	50	0	22.61	22.53	22.51		1
16QAM	1	0	22.25	22.88	22.81	0-1	1
	1	25	22.18	22.55	22.62		1
	1	49	22.48	22.78	22.87		1
	25	0	21.58	21.38	21.42	0-2	2
	25	12	21.59	21.44	21.54		2
	25	25	21.59	21.41	21.58		2
	50	0	21.53	21.45	21.50		2
64QAM	1	0	21.41	21.40	21.89	0-2	2
	1	25	21.22	21.22	21.68		2
	1	49	21.45	21.38	21.96		2
	25	0	20.28	20.42	20.17	0-3	3
	25	12	20.22	20.34	20.19		3
	25	25	20.28	20.27	20.26		3
	50	0	20.37	20.17	20.20		3



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 44 of 99

Table 9-22
LTE Band 66 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.66	23.76	23.79	0	0
	1	12	23.59	23.77	23.65		0
	1	24	23.67	23.71	23.74		0
	12	0	22.63	22.50	22.67	0-1	1
	12	6	22.56	22.46	22.72		1
	12	13	22.45	22.52	22.64		1
	25	0	22.57	22.45	22.69		1
16QAM	1	0	22.92	22.81	22.93	0-1	1
	1	12	22.75	22.63	22.90		1
	1	24	22.73	22.65	22.92		1
	12	0	21.64	21.49	21.69	0-2	2
	12	6	21.61	21.49	21.73		2
	12	13	21.56	21.50	21.66		2
	25	0	21.62	21.42	21.72		2
64QAM	1	0	21.89	21.96	21.86	0-2	2
	1	12	21.74	21.88	21.81		2
	1	24	21.70	21.82	21.79		2
	12	0	20.31	20.43	20.34	0-3	3
	12	6	20.29	20.09	20.31		3
	12	13	20.30	20.17	20.30		3
	25	0	20.34	20.07	20.38		3

Table 9-23
LTE Band 66 (AWS) Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.72	23.52	23.71	0	0
	1	7	23.81	23.47	23.53		0
	1	14	23.86	23.47	23.54		0
	8	0	22.48	22.40	22.44	0-1	1
	8	4	22.47	22.42	22.48		1
	8	7	22.48	22.31	22.40		1
	15	0	22.52	22.39	22.50		1
16QAM	1	0	22.28	22.77	22.63	0-1	1
	1	7	22.24	22.65	22.87		1
	1	14	22.45	22.63	22.50		1
	8	0	21.30	21.30	21.46	0-2	2
	8	4	21.34	21.28	21.45		2
	8	7	21.35	21.26	21.42		2
	15	0	21.49	21.45	21.55		2
64QAM	1	0	21.33	21.33	21.87	0-2	2
	1	7	21.36	21.26	21.79		2
	1	14	21.46	21.22	21.74		2
	8	0	20.20	20.44	20.17	0-3	3
	8	4	20.23	20.14	20.32		3
	8	7	20.34	20.04	20.31		3
	15	0	20.26	20.18	20.22		3





FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 45 of 99	

Table 9-24
LTE Band 66 (AWS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.64	23.41	23.80	0	0
	1	2	23.79	23.44	23.85		0
	1	5	23.72	23.43	23.77		0
	3	0	23.61	23.68	23.69		0
	3	2	23.68	23.73	23.69		0
	3	3	23.57	23.58	23.66		0
	6	0	22.37	22.32	22.40		0-1
16QAM	1	0	22.14	22.57	22.46	0-1	1
	1	2	22.16	22.54	22.59		1
	1	5	22.40	22.51	22.54		1
	3	0	22.46	22.45	22.39		1
	3	2	22.55	22.43	22.53		1
	3	3	22.51	22.36	22.50		1
	6	0	21.49	21.39	21.39		0-2
64QAM	1	0	21.39	21.21	21.79	0-2	2
	1	2	21.36	21.14	21.88		2
	1	5	21.48	21.18	21.77		2
	3	0	21.58	21.13	21.60		2
	3	2	21.66	21.19	21.65		2
	3	3	21.62	21.17	21.51		2
	6	0	20.10	20.06	20.22		0-3

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 46 of 99

9.4.6

LTE Band 25 (PCS)

Table 9-25
LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.80	23.66	23.87	0	0
	1	50	23.85	23.82	23.85		0
	1	99	23.78	23.86	23.78		0
	50	0	22.75	22.63	22.79	0-1	1
	50	25	22.69	22.66	22.65		1
	50	50	22.64	22.64	22.73		1
	100	0	22.50	22.50	22.63		1
16QAM	1	0	22.95	22.74	22.93	0-1	1
	1	50	22.98	22.87	22.99		1
	1	99	22.91	22.85	22.92		1
	50	0	21.76	21.59	21.83	0-2	2
	50	25	21.41	21.74	21.69		2
	50	50	21.45	21.63	21.69		2
	100	0	21.65	21.48	21.68		2
64QAM	1	0	21.91	21.89	21.72	0-2	2
	1	50	21.98	21.88	21.89		2
	1	99	21.97	21.64	21.73		2
	50	0	20.73	20.57	20.65	0-3	3
	50	25	20.80	20.69	20.63		3
	50	50	20.64	20.64	20.69		3
	100	0	20.71	20.50	20.56		3



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 47 of 99

Table 9-26
LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.79	23.69	23.72	0	0
	1	36	23.86	23.83	23.79		0
	1	74	23.70	23.62	23.65		0
	36	0	22.70	22.64	22.72	0-1	1
	36	18	22.96	22.93	22.81		1
	36	37	22.93	22.75	22.84		1
	75	0	22.78	22.63	22.98		1
16QAM	1	0	22.91	22.84	22.88	0-1	1
	1	36	23.00	22.94	22.92		1
	1	74	22.85	22.89	22.98		1
	36	0	21.77	21.70	21.97	0-2	2
	36	18	21.88	21.89	22.00		2
	36	37	21.90	21.78	22.00		2
	75	0	21.82	21.69	21.83		2
64QAM	1	0	21.84	21.76	21.85	0-2	2
	1	36	21.92	21.90	21.96		2
	1	74	21.88	21.70	21.79		2
	36	0	20.75	20.67	20.71	0-3	3
	36	18	21.00	20.90	20.96		3
	36	37	20.92	20.80	20.87		3
	75	0	20.79	20.73	20.81		3

Table 9-27
LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.82	23.81	23.74	0	0
	1	25	23.60	23.80	23.62		0
	1	49	23.67	23.77	23.64		0
	25	0	22.81	22.82	22.76	0-1	1
	25	12	22.66	22.82	22.78		1
	25	25	22.64	22.76	22.68		1
	50	0	22.74	22.75	22.71		1
16QAM	1	0	22.80	22.93	22.98	0-1	1
	1	25	22.62	22.80	22.91		1
	1	49	22.64	22.75	22.94		1
	25	0	21.83	21.82	21.77	0-2	2
	25	12	21.75	21.88	21.73		2
	25	25	21.74	21.85	21.73		2
	50	0	21.78	21.76	21.73		2
64QAM	1	0	21.91	21.95	21.76	0-2	2
	1	25	21.86	21.82	21.71		2
	1	49	21.97	21.86	21.53		2
	25	0	20.82	20.77	20.76	0-3	3
	25	12	20.68	20.76	20.85		3
	25	25	20.66	20.65	20.76		3
	50	0	20.75	20.73	20.79		3



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 48 of 99

Table 9-28
LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.92	23.99	23.80	0	0
	1	12	23.81	23.61	23.66		0
	1	24	23.66	23.91	23.66		0
	12	0	22.84	22.82	22.82	0-1	1
	12	6	22.79	22.76	22.72		1
	12	13	22.75	22.71	22.77		1
	25	0	22.80	22.73	22.76		1
16QAM	1	0	22.98	22.97	22.81	0-1	1
	1	12	22.88	22.97	22.75		1
	1	24	22.95	23.00	22.60		1
	12	0	21.95	21.83	21.83	0-2	2
	12	6	21.82	21.77	21.75		2
	12	13	21.86	21.72	21.77		2
	25	0	21.81	21.82	21.75		2
64QAM	1	0	21.98	21.97	21.89	0-2	2
	1	12	21.97	21.90	21.67		2
	1	24	22.00	21.96	21.78		2
	12	0	20.85	20.78	20.61	0-3	3
	12	6	20.83	20.73	20.60		3
	12	13	20.75	20.74	20.62		3
	25	0	20.82	20.70	20.79		3

Table 9-29
LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.64	23.61	23.72	0	0
	1	7	23.71	23.72	23.65		0
	1	14	23.62	23.55	23.60		0
	8	0	22.80	22.76	22.73	0-1	1
	8	4	22.82	22.67	22.69		1
	8	7	22.78	22.61	22.71		1
	15	0	22.80	22.68	22.72		1
16QAM	1	0	22.88	22.90	22.97	0-1	1
	1	7	22.96	22.98	22.88		1
	1	14	22.99	22.96	22.83		1
	8	0	21.90	21.86	21.76	0-2	2
	8	4	21.87	21.79	21.74		2
	8	7	21.85	21.77	21.75		2
	15	0	21.88	21.76	21.60		2
64QAM	1	0	21.95	21.85	21.97	0-2	2
	1	7	21.96	21.87	21.94		2
	1	14	21.92	21.83	21.96		2
	8	0	20.77	20.75	20.79	0-3	3
	8	4	20.78	20.68	20.75		3
	8	7	20.73	20.61	20.73		3
	15	0	20.79	20.74	20.79		3





FCC ID: ZNFQ720QM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 49 of 99	

Table 9-30
LTE Band 25 (PCS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.78	23.70	23.64	0	0
	1	2	24.00	23.67	23.66		0
	1	5	23.80	23.62	23.60		0
	3	0	23.70	23.69	23.60		0
	3	2	23.73	23.69	23.72		0
	3	3	23.66	23.62	23.57		0
	6	0	22.71	22.61	22.67	0-1	1
16QAM	1	0	23.00	22.87	22.81	0-1	1
	1	2	22.95	22.86	22.87		1
	1	5	22.92	22.82	22.82		1
	3	0	22.75	22.75	22.77		1
	3	2	22.78	22.81	22.83		1
	3	3	22.72	22.71	22.78		1
	6	0	21.81	21.74	21.70	0-2	2
64QAM	1	0	22.00	21.93	21.98	0-2	2
	1	2	22.00	22.00	21.96		2
	1	5	21.95	21.80	21.97		2
	3	0	21.74	21.61	21.74		2
	3	2	21.73	21.67	21.78		2
	3	3	21.76	21.56	21.75		2
	6	0	20.57	20.63	20.66	0-3	3

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 50 of 99

9.4.7

LTE Band 41

Table 9-31
LTE Band 41 Maximum Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.52	24.79	24.56	24.50	24.77	0	0
	1	50	24.57	24.74	24.61	24.62	24.70		0
	1	99	24.52	24.87	24.63	24.63	24.62		0
	50	0	23.62	23.85	23.73	23.81	23.68	0-1	1
	50	25	23.64	23.87	23.74	23.79	23.77		1
	50	50	23.70	23.90	23.86	23.80	23.72		1
	100	0	23.61	23.79	23.79	23.74	23.64		1
16QAM	1	0	23.60	23.98	23.62	23.68	23.74	0-1	1
	1	50	23.71	23.96	23.74	23.89	23.76		1
	1	99	23.80	23.95	23.87	23.46	23.79		1
	50	0	22.65	22.92	22.80	22.83	22.75	0-2	2
	50	25	22.67	22.98	22.78	22.82	22.70		2
	50	50	22.69	22.94	22.88	22.73	22.63		2
	100	0	22.68	22.88	22.88	22.80	22.67		2
64QAM	1	0	22.48	22.83	22.43	22.40	22.22	0-2	2
	1	50	22.60	22.78	22.57	22.65	22.33		2
	1	99	22.58	22.89	22.62	22.62	22.34		2
	50	0	21.66	21.93	21.81	21.88	21.81	0-3	3
	50	25	21.63	21.95	21.89	21.86	21.73		3
	50	50	21.77	21.96	21.90	21.82	21.69		3
	100	0	21.72	21.83	21.82	21.75	21.64		3

Table 9-32
LTE Band 41 Maximum Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.87	24.90	24.46	24.47	24.71	0	0
	1	36	24.86	24.78	24.77	24.68	24.61		0
	1	74	24.98	24.82	24.78	24.81	24.62		0
	36	0	23.92	23.92	23.68	23.70	23.80	0-1	1
	36	18	24.00	24.00	23.78	23.77	23.74		1
	36	37	23.97	23.91	23.82	23.74	23.65		1
	75	0	23.82	23.95	23.70	23.57	23.76		1
16QAM	1	0	23.67	23.84	23.37	23.34	23.51	0-1	1
	1	36	23.61	23.72	23.56	23.57	23.36		1
	1	74	23.77	23.75	23.65	23.70	23.40		1
	36	0	22.84	22.92	22.70	22.62	22.79	0-2	2
	36	18	22.86	22.95	22.75	22.76	22.78		2
	36	37	22.82	22.48	22.77	22.72	22.65		2
	75	0	22.85	22.98	22.71	22.73	22.82		2
64QAM	1	0	22.87	22.61	22.40	22.58	22.68	0-2	2
	1	36	22.88	22.50	22.66	22.81	22.77		2
	1	74	22.92	22.55	22.72	22.88	22.75		2
	36	0	21.89	21.91	21.75	21.73	21.80	0-3	3
	36	18	21.90	21.97	21.78	21.85	21.81		3
	36	37	21.84	21.94	21.88	21.76	21.75		3
	75	0	21.83	21.95	21.67	21.70	21.81		3



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 51 of 99	

Table 9-33
LTE Band 41 Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.78	24.84	24.87	24.88	24.78	0	0
	1	25	24.78	24.85	24.81	24.73	24.70		0
	1	49	24.95	24.96	24.94	24.95	25.00		0
	25	0	23.87	23.94	23.84	23.85	23.96	0-1	1
	25	12	23.97	23.91	23.85	23.88	23.97		1
	25	25	23.87	23.91	23.81	23.93	23.87		1
16QAM	50	0	23.95	23.89	23.87	23.86	23.94	0-1	1
	1	0	23.77	23.68	23.77	23.92	23.89		1
	1	25	23.81	23.77	23.71	23.81	23.73		1
	1	49	23.86	23.93	23.89	23.96	23.85	0-2	1
	25	0	22.89	22.93	22.98	22.90	23.00		2
	25	12	22.89	22.97	22.90	22.90	22.96		2
64QAM	25	25	22.83	22.98	22.83	22.93	22.95	0-2	2
	50	0	22.86	22.88	22.86	22.78	23.00		2
	1	0	22.79	22.80	22.64	22.85	22.68	0-2	2
	1	25	22.75	22.79	22.54	22.65	22.81		2
	1	49	22.94	22.92	22.71	23.00	22.76		2
	64QAM	25	0	21.78	21.90	21.84	21.86	21.83	0-3
25		12	21.86	21.90	21.79	21.87	21.93	3	
25		25	21.76	21.92	21.77	21.94	21.84	3	
50		0	21.74	21.86	21.78	21.76	21.93	3	

Table 9-34
LTE Band 41 Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.70	24.83	24.92	25.00	24.90	0	0
	1	12	24.62	24.96	24.88	24.85	24.83		0
	1	24	24.57	24.77	24.75	24.98	24.74		0
	12	0	23.79	23.79	23.93	23.90	23.91	0-1	1
	12	6	23.75	23.81	23.83	23.84	23.92		1
	12	13	23.66	23.76	23.80	23.93	23.87		1
16QAM	25	0	23.81	23.78	23.86	23.84	23.85	0-1	1
	1	0	23.62	23.96	23.98	23.79	23.90		1
	1	12	23.51	23.78	23.88	23.61	23.80		1
	1	24	23.49	23.83	23.88	23.67	23.79	0-2	1
	12	0	22.78	22.86	22.90	22.88	22.85		2
	12	6	22.74	22.78	22.89	22.81	22.95		2
64QAM	12	13	22.65	22.72	22.85	22.85	22.91	0-2	2
	25	0	22.86	22.70	22.74	22.88	22.88		2
	1	0	22.95	22.77	22.83	22.85	22.71	0-2	2
	1	12	22.87	22.73	22.75	22.82	22.79		2
	1	24	22.85	22.55	22.65	22.93	22.79	0-3	2
	12	0	21.87	21.81	21.98	21.98	21.82		3
12	6	21.82	21.72	21.87	21.91	21.92	3		
64QAM	12	13	21.76	21.71	21.84	21.97	21.85	0-3	3
	25	0	21.75	21.79	21.88	21.74	21.71		3



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 52 of 99	

Table 9-35
LTE Band 41 Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.50	23.70	23.51	23.42	23.57	0	0
	1	50	23.63	23.63	23.50	23.49	23.58		0
	1	99	23.52	23.69	23.55	23.47	23.66		0
	50	0	23.53	23.81	23.63	23.59	23.62	0-1	0
	50	25	23.62	23.75	23.68	23.62	23.56		0
	50	50	23.73	23.78	23.67	23.60	23.59		0
	100	0	23.67	23.67	23.61	23.53	23.58		0
16QAM	1	0	23.58	23.93	23.55	23.46	23.52	0-1	0
	1	50	23.75	23.88	23.73	23.47	23.62		0
	1	99	23.73	23.84	23.68	23.44	23.77		0
	50	0	22.58	22.79	22.55	22.65	22.55	0-2	1
	50	25	22.70	22.66	22.55	22.63	22.66		1
	50	50	22.71	22.78	22.67	22.60	22.67		1
	100	0	22.71	22.73	22.68	22.68	22.53		1
64QAM	1	0	22.34	22.61	22.43	22.29	22.33	0-2	1
	1	50	22.26	22.78	22.13	22.27	22.31		1
	1	99	22.41	22.63	22.12	22.26	22.37		1
	50	0	21.62	21.80	21.50	21.57	21.57	0-3	2
	50	25	21.67	21.85	21.49	21.56	21.63		2
	50	50	21.70	21.82	21.63	21.58	21.55		2
	100	0	21.62	21.70	21.66	21.67	21.54		2

Table 9-36
LTE Band 41 Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.77	24.00	24.00	23.34	23.42	0	0
	1	36	24.00	23.95	23.99	23.44	23.31		0
	1	74	23.95	23.96	23.98	23.32	23.46		0
	36	0	23.24	23.45	23.20	23.39	23.21	0-1	0
	36	18	23.35	23.46	23.25	23.28	23.23		0
	36	37	23.26	23.40	23.24	23.23	23.25		0
	75	0	23.32	23.41	23.24	23.13	23.14		0
16QAM	1	0	23.41	23.44	23.21	23.08	23.05	0-1	0
	1	36	23.31	23.47	23.30	23.08	23.15		0
	1	74	23.23	23.43	23.22	23.07	23.28		0
	36	0	22.21	22.40	22.27	22.15	22.28	0-2	1
	36	18	22.32	22.41	22.26	22.14	22.31		1
	36	37	22.22	22.44	22.30	22.23	22.36		1
	75	0	22.35	22.40	22.21	22.27	22.18		1
64QAM	1	0	22.21	22.71	22.22	21.91	22.56	0-2	1
	1	36	22.25	22.57	22.24	22.24	22.54		1
	1	74	22.20	22.69	22.26	22.25	22.47		1
	36	0	21.21	21.40	21.30	21.12	21.28	0-3	2
	36	18	21.28	21.40	21.21	21.07	21.27		2
	36	37	21.23	21.42	21.23	21.19	21.35		2
	75	0	21.21	21.43	21.24	21.22	21.16		2





FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 53 of 99	

Table 9-37
LTE Band 41 Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.89	23.86	23.80	23.88	23.95	0	0
	1	25	23.89	23.84	23.79	23.65	23.96		0
	1	49	23.85	23.83	23.82	23.85	23.95		0
	25	0	23.41	23.32	23.30	23.37	23.61	0-1	0
	25	12	23.53	23.35	23.35	23.35	23.51		0
	25	25	23.40	23.32	23.25	23.39	23.38		0
50	0	23.43	23.35	23.31	23.33	23.40	0		
16QAM	1	0	23.58	23.46	23.38	23.32	23.43	0-1	0
	1	25	23.57	23.46	23.35	23.29	23.44		0
	1	49	23.64	23.40	23.40	23.31	23.46		0
	25	0	22.40	22.41	22.35	22.40	22.51	0-2	1
	25	12	22.37	22.46	22.36	22.37	22.55		1
	25	25	22.38	22.48	22.34	22.30	22.40		1
50	0	22.35	22.33	22.28	22.32	22.40	1		
64QAM	1	0	22.59	22.34	22.30	22.38	22.40	0-2	1
	1	25	22.60	22.31	22.33	22.38	22.51		1
	1	49	22.70	22.61	22.33	22.40	22.42		1
	25	0	21.34	21.31	21.28	21.45	21.50	0-3	2
	25	12	21.37	21.35	21.36	21.35	21.45		2
	25	25	21.31	21.33	21.29	21.34	21.40		2
50	0	21.36	21.31	21.29	21.36	21.51	2		

Table 9-38
LTE Band 41 Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.83	23.80	23.82	23.74	23.73	0	0
	1	12	23.78	23.33	23.72	23.69	23.81		0
	1	24	23.79	23.81	23.77	23.59	23.79		0
	12	0	23.41	23.35	23.31	23.20	23.36	0-1	0
	12	6	23.42	23.25	23.22	23.23	23.36		0
	12	13	23.30	23.31	23.22	23.23	23.33		0
	25	0	23.33	23.27	23.24	23.29	23.32		0
16QAM	1	0	23.51	23.61	23.32	23.43	23.44	0-1	0
	1	12	23.43	23.45	23.35	23.15	23.91		0
	1	24	23.31	23.55	23.31	23.30	23.89		0
	12	0	22.39	22.61	22.25	22.25	22.50	0-2	1
	12	6	22.43	22.52	22.29	22.19	22.51		1
	12	13	22.35	22.48	22.32	22.25	22.43		1
	25	0	22.36	22.31	22.26	22.24	22.45		1
64QAM	1	0	22.46	22.44	22.61	22.14	22.61	0-2	1
	1	12	22.36	22.40	22.38	22.16	22.38		1
	1	24	22.28	22.31	22.44	22.15	22.33		1
	12	0	21.43	21.33	21.42	21.22	21.37	0-3	2
	12	6	21.49	21.41	21.40	21.21	21.35		2
	12	13	21.32	21.32	21.32	21.33	21.35		2
	25	0	21.38	21.31	21.22	21.27	21.32		2

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 54 of 99	

9.5 WLAN Conducted Powers

Table 9-39
2.4 GHz WLAN Maximum Average RF Power

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	22.24	18.19	17.20
2422	3	N/A	21.30	20.48
2437	6	22.19	21.27	20.38
2452	9	N/A	21.09	20.38
2462	11	22.32	17.56	16.53

Table 9-40
5 GHz WLAN Maximum Average RF Power

5GHz (20MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
		Average	Average	Average
5180	36	15.75	14.74	11.91
5200	40	19.12	18.23	15.35
5220	44	18.91	18.20	15.18
5240	48	18.77	17.91	15.08
5260	52	18.73	17.72	14.98
5280	56	18.70	17.76	15.18
5300	60	18.68	17.70	15.11
5320	64	15.50	14.51	11.95
5500	100	15.62	14.78	11.96
5520	104	18.74	17.94	15.23
5600	120	18.71	17.61	14.97
5680	136	18.65	17.92	15.02
5700	140	17.45	16.62	13.62
5745	149	17.78	16.60	13.93
5765	153	19.38	18.42	15.71
5785	157	19.52	18.42	15.67
5805	161	19.35	18.48	15.70
5825	165	17.59	16.59	13.57





FCC ID: ZNFQ720QM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 55 of 99

Table 9-41
2.4 GHz WLAN Reduced Average RF Power

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	18.34	15.07	15.03
2422	3	N/A	18.18	18.28
2437	6	18.30	18.13	18.14
2452	9	N/A	18.22	18.23
2462	11	18.22	14.54	14.63

Table 9-42
5 GHz WLAN Reduced Average RF Power

5GHz (20MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
		Average	Average	Average
5180	36	13.25	13.36	11.91
5200	40	16.94	17.01	15.35
5220	44	16.87	16.96	15.18
5240	48	16.96	16.93	15.08
5260	52	16.78	16.82	14.98
5280	56	16.77	16.86	15.18
5300	60	16.85	16.80	15.11
5320	64	13.54	13.46	11.95
5500	100	13.62	13.79	11.96
5520	104	16.84	16.84	15.23
5600	120	16.67	16.67	14.97
5680	136	16.91	17.05	15.02
5700	140	15.43	15.56	13.62
5745	149	15.54	15.51	13.93
5765	153	17.48	17.49	15.71
5785	157	17.44	17.50	15.67
5805	161	17.39	17.52	15.70
5825	165	15.69	15.61	13.57

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 56 of 99

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.






Figure 9-4
Power Measurement Setup

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 57 of 99

9.6 Bluetooth Conducted Powers

Table 9-43
Bluetooth Average RF Power

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	9.55	9.020
2441	1.0	39	10.99	12.560
2480	1.0	78	9.40	8.707
2402	2.0	0	8.88	7.727
2441	2.0	39	10.35	10.837
2480	2.0	78	8.78	7.548
2402	3.0	0	8.94	7.832
2441	3.0	39	10.33	10.778
2480	3.0	78	8.73	7.470




Figure 9-5
Bluetooth Transmission Plot

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 58 of 99

Equation 9-1
Bluetooth Duty Cycle Calculation

$$Duty\ Cycle = \frac{Pulse\ Width}{Period} * 100\% = \frac{2.89ms}{3.75ms} * 100\% = 77.1\%$$






Figure 9-6
Power Measurement Setup

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 59 of 99	

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Head Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
5/9/2019	750H	22.3	680	0.894	43.102	0.888	42.305	0.68%	1.88%
			695	0.899	43.046	0.889	42.227	1.12%	1.94%
			700	0.901	43.029	0.889	42.201	1.35%	1.96%
			710	0.904	42.997	0.890	42.149	1.57%	2.01%
			720	0.908	42.970	0.891	42.097	1.91%	2.07%
			725	0.909	42.958	0.891	42.071	2.02%	2.11%
			740	0.915	42.922	0.893	41.994	2.46%	2.21%
			755	0.920	42.881	0.894	41.916	2.91%	2.30%
			770	0.925	42.834	0.895	41.838	3.35%	2.38%
			785	0.930	42.781	0.896	41.760	3.79%	2.44%
4/24/2019	835H	22.7	820	0.931	41.940	0.899	41.578	3.56%	0.87%
			835	0.936	41.890	0.900	41.500	4.00%	0.94%
			850	0.942	41.857	0.916	41.500	2.84%	0.86%
5/6/2019	1750H	22.4	1710	1.367	41.745	1.348	40.142	1.41%	3.99%
			1750	1.392	41.682	1.371	40.079	1.53%	4.00%
			1790	1.417	41.611	1.394	40.016	1.65%	3.99%
5/8/2019	1900H	22.8	1850	1.381	39.570	1.400	40.000	-1.36%	-1.08%
			1880	1.411	39.433	1.400	40.000	0.79%	-1.42%
			1910	1.443	39.301	1.400	40.000	3.07%	-1.75%
5/12/2019	1900H	21.1	1850	1.405	38.795	1.400	40.000	0.36%	-3.01%
			1880	1.437	38.657	1.400	40.000	2.64%	-3.36%
			1910	1.468	38.521	1.400	40.000	4.86%	-3.70%
4/29/2019	2450H	19.9	2400	1.782	37.853	1.756	39.289	1.48%	-3.65%
			2450	1.820	37.749	1.800	39.200	1.11%	-3.70%
			2500	1.861	37.672	1.855	39.136	0.32%	-3.74%
5/2/2019	2450H	22.0	2500	1.852	37.910	1.855	39.136	-0.16%	-3.13%
			2550	1.891	37.823	1.909	39.073	-0.94%	-3.20%
			2600	1.927	37.745	1.964	39.009	-1.88%	-3.24%
			2650	1.966	37.657	2.018	38.945	-2.58%	-3.31%
			2700	2.005	37.589	2.073	38.882	-3.28%	-3.33%
5/20/2019	2450H	21.4	2400	1.778	38.867	1.756	39.289	1.25%	-1.07%
			2450	1.816	38.797	1.800	39.200	0.89%	-1.03%
			2500	1.855	38.723	1.855	39.136	0.00%	-1.06%
05/07/2019	5200H-5800H	23.3	5200	4.593	36.133	4.655	35.986	-1.33%	0.41%
			5220	4.616	36.087	4.676	35.963	-1.28%	0.34%
			5240	4.635	36.055	4.696	35.940	-1.30%	0.32%
			5260	4.655	36.023	4.717	35.917	-1.31%	0.30%
			5280	4.681	35.974	4.737	35.894	-1.18%	0.22%
			5300	4.707	35.941	4.758	35.871	-1.07%	0.20%
			5320	4.727	35.910	4.778	35.849	-1.07%	0.17%
			5500	4.928	35.586	4.963	35.643	-0.71%	-0.16%
			5520	4.952	35.552	4.983	35.620	-0.62%	-0.19%
			5540	4.982	35.512	5.004	35.597	-0.44%	-0.24%
			5560	5.007	35.485	5.024	35.574	-0.34%	-0.25%
			5580	5.028	35.454	5.045	35.551	-0.34%	-0.27%
			5600	5.048	35.409	5.065	35.529	-0.34%	-0.34%
			5620	5.074	35.367	5.086	35.506	-0.24%	-0.39%
			5640	5.100	35.324	5.106	35.483	-0.12%	-0.45%
			5660	5.124	35.284	5.127	35.460	-0.06%	-0.50%
			5680	5.147	35.269	5.147	35.437	0.00%	-0.47%
			5700	5.171	35.241	5.168	35.414	0.06%	-0.49%
			5745	5.225	35.143	5.214	35.363	0.21%	-0.62%
			5765	5.249	35.104	5.234	35.340	0.29%	-0.67%
			5785	5.273	35.079	5.255	35.317	0.34%	-0.67%
			5800	5.289	35.059	5.270	35.300	0.36%	-0.68%





FCC ID: ZNFQ720QM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 60 of 99

Table 10-2
Measured Body Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
5/9/2019	750B	22.5	680	0.950	54.359	0.958	55.804	-0.84%	-2.59%
			695	0.956	54.316	0.959	55.745	-0.31%	-2.56%
			700	0.958	54.301	0.959	55.726	-0.10%	-2.56%
			710	0.961	54.274	0.960	55.687	0.10%	-2.54%
			720	0.965	54.251	0.961	55.648	0.42%	-2.51%
			725	0.967	54.240	0.961	55.629	0.62%	-2.50%
			740	0.973	54.205	0.963	55.570	1.04%	-2.46%
			755	0.978	54.167	0.964	55.512	1.45%	-2.42%
			770	0.983	54.126	0.965	55.453	1.87%	-2.39%
5/6/2019	835B	19.9	785	0.989	54.085	0.966	55.395	2.38%	-2.36%
			820	0.995	53.293	0.969	55.258	2.68%	-3.56%
			835	1.001	53.243	0.970	55.200	3.20%	-3.55%
5/1/2019	1750B	21.9	850	1.005	53.225	0.988	55.154	1.72%	-3.50%
			1710	1.453	52.642	1.463	53.537	-0.68%	-1.67%
			1750	1.497	52.486	1.488	53.432	0.60%	-1.77%
5/6/2019	1750B	21.7	1790	1.540	52.312	1.514	53.326	1.72%	-1.90%
			1710	1.450	52.334	1.463	53.537	-0.89%	-2.25%
			1750	1.495	52.197	1.488	53.432	0.47%	-2.31%
5/1/2019	1900B	22.5	1790	1.539	52.024	1.514	53.326	1.65%	-2.44%
			1850	1.526	52.535	1.520	53.300	0.39%	-1.44%
			1880	1.557	52.423	1.520	53.300	2.43%	-1.65%
5/21/2019	1900B	22.0	1910	1.590	52.330	1.520	53.300	4.61%	-1.82%
			1850	1.529	51.835	1.520	53.300	0.59%	-2.75%
			1880	1.561	51.749	1.520	53.300	2.70%	-2.91%
5/6/2019	2450B	22.4	1910	1.594	51.667	1.520	53.300	4.87%	-3.06%
			2400	1.975	51.545	1.902	52.767	3.84%	-2.32%
			2450	2.034	51.400	1.950	52.700	4.31%	-2.47%
			2500	2.090	51.249	2.021	52.636	3.41%	-2.64%
			2550	2.151	51.099	2.092	52.573	2.82%	-2.80%
			2600	2.208	50.960	2.163	52.509	2.08%	-2.95%
			2650	2.270	50.811	2.234	52.445	1.61%	-3.12%
5/8/2019	2450B	21.1	2700	2.330	50.673	2.305	52.382	1.08%	-3.26%
			2400	1.988	52.395	1.902	52.767	4.52%	-0.70%
			2450	2.034	52.307	1.950	52.700	4.31%	-0.75%
04/30/2019	5200B-5800B	21.1	2500	2.079	52.249	2.021	52.636	2.87%	-0.74%
			5200	5.401	47.642	5.299	49.014	1.92%	-2.80%
			5220	5.428	47.586	5.323	48.987	1.97%	-2.86%
			5240	5.462	47.558	5.346	48.960	2.17%	-2.86%
			5260	5.488	47.514	5.369	48.933	2.22%	-2.90%
			5280	5.512	47.489	5.393	48.906	2.21%	-2.90%
			5300	5.537	47.454	5.416	48.879	2.23%	-2.92%
			5320	5.571	47.391	5.439	48.851	2.43%	-2.99%
			5500	5.826	47.067	5.650	48.607	3.12%	-3.17%
			5520	5.857	47.030	5.673	48.580	3.24%	-3.19%
			5540	5.892	46.980	5.696	48.553	3.44%	-3.24%
			5560	5.931	46.938	5.720	48.526	3.69%	-3.27%
			5580	5.959	46.911	5.743	48.499	3.76%	-3.27%
			5600	5.984	46.873	5.766	48.471	3.78%	-3.30%
			5620	6.009	46.827	5.790	48.444	3.78%	-3.34%
			5640	6.044	46.779	5.813	48.417	3.97%	-3.38%
			5660	6.078	46.735	5.837	48.390	4.13%	-3.42%
			5680	6.112	46.706	5.860	48.363	4.30%	-3.43%
			5700	6.141	46.673	5.883	48.336	4.39%	-3.44%
			5745	6.203	46.579	5.936	48.275	4.50%	-3.51%
			5765	6.238	46.542	5.959	48.248	4.68%	-3.54%
			5785	6.271	46.503	5.982	48.220	4.83%	-3.56%
			5800	6.293	46.477	6.000	48.200	4.88%	-3.57%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 61 of 99	

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-3
System Verification Results – 1g

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
D	750	HEAD	05/09/2019	23.1	22.3	0.200	1161	3914	1.730	8.030	8.650	7.72%
D	835	HEAD	04/24/2019	23.1	22.7	0.200	4d132	3914	1.970	9.590	9.850	2.71%
H	1750	HEAD	05/06/2019	21.9	22.4	0.100	1008	7409	3.640	36.200	36.400	0.55%
G	1900	HEAD	05/08/2019	23.8	22.8	0.100	5d149	7410	4.060	39.300	40.600	3.31%
G	1900	HEAD	05/12/2019	21.3	21.1	0.100	5d149	7410	4.240	39.300	42.400	7.89%
L	2450	HEAD	04/29/2019	20.1	19.9	0.100	719	7308	5.180	51.900	51.800	-0.19%
E	2450	HEAD	05/20/2019	23.1	21.4	0.100	797	3589	5.280	52.700	52.800	0.19%
E	2600	HEAD	05/02/2019	24.2	22.3	0.100	1064	3589	5.870	57.000	58.700	2.98%
H	5250	HEAD	05/07/2019	21.9	21.7	0.050	1237	7409	3.890	81.300	77.800	-4.31%
H	5750	HEAD	05/07/2019	21.9	21.7	0.050	1237	7409	3.840	80.600	76.800	-4.71%
E	750	BODY	05/09/2019	23.5	22.2	0.200	1161	3589	1.650	8.430	8.250	-2.14%
J	835	BODY	05/06/2019	20.0	19.5	0.200	4d132	7488	2.040	9.670	10.200	5.48%
D	1750	BODY	05/01/2019	22.3	21.9	0.100	1148	3914	3.820	37.000	38.200	3.24%
D	1750	BODY	05/06/2019	22.2	21.7	0.100	1008	3914	3.850	37.400	38.500	2.94%
G	1900	BODY	05/01/2019	23.2	21.7	0.100	5d149	7410	4.210	39.400	42.100	6.85%
G	1900	BODY	05/21/2019	23.2	21.7	0.100	5d149	7410	4.090	39.400	40.900	3.81%
L	2450	BODY	05/08/2019	21.6	21.1	0.100	719	7308	5.190	50.100	51.900	3.59%
K	2600	BODY	05/06/2019	22.2	21.6	0.100	1071	7417	5.330	54.200	53.300	-1.66%
L	5250	BODY	04/30/2019	22.0	21.1	0.050	1057	7308	3.670	75.900	73.400	-3.29%
L	5600	BODY	04/30/2019	22.0	21.1	0.050	1057	7308	3.890	79.900	77.800	-2.63%
L	5750	BODY	04/30/2019	22.0	21.1	0.050	1057	7308	3.570	76.700	71.400	-6.91%



FCC ID: ZNFQ720QM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 62 of 99

Table 10-4
System Verification Results – 10g

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{10g} (W/kg)	1 W Target SAR _{10g} (W/kg)	1 W Normalized SAR _{10g} (W/kg)	Deviation _{10g} (%)
K	2450	BODY	05/06/2019	22.2	21.6	0.100	797	7417	2.300	24.200	23.000	-4.96%
K	2600	BODY	05/06/2019	22.2	21.6	0.100	1071	7417	2.330	24.500	23.300	-4.90%
L	5250	BODY	04/30/2019	22.0	21.1	0.050	1057	7308	1.010	21.100	20.200	-4.27%
L	5600	BODY	04/30/2019	22.0	21.1	0.050	1057	7308	1.060	22.300	21.200	-4.93%
L	5750	BODY	04/30/2019	22.0	21.1	0.050	1057	7308	0.990	21.200	19.800	-6.60%






Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: ZNFQ720QM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 63 of 99	

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

Table 11-1
CDMA BC10 (\$90S) Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
820.10	564	CDMA BC10 (\$90S)	RC3 / SO55	25.0	24.78	0.01	Right	Cheek	01219	1:1	0.169	1.052	0.178	
820.10	564	CDMA BC10 (\$90S)	RC3 / SO55	25.0	24.78	-0.01	Right	Tilt	01219	1:1	0.107	1.052	0.113	
820.10	564	CDMA BC10 (\$90S)	RC3 / SO55	25.0	24.78	0.03	Left	Cheek	01219	1:1	0.174	1.052	0.183	A1
820.10	564	CDMA BC10 (\$90S)	RC3 / SO55	25.0	24.78	0.05	Left	Tilt	01219	1:1	0.138	1.052	0.145	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. A	25.0	24.82	0.02	Right	Cheek	01219	1:1	0.153	1.042	0.159	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. A	25.0	24.82	0.10	Right	Tilt	01219	1:1	0.076	1.042	0.079	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. A	25.0	24.82	0.05	Left	Cheek	01219	1:1	0.151	1.042	0.157	
820.10	564	CDMA BC10 (\$90S)	EVDO Rev. A	25.0	24.82	0.10	Left	Tilt	01219	1:1	0.100	1.042	0.104	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-2
CDMA BC0 (\$22H) Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.0	24.87	-0.02	Right	Cheek	01219	1:1	0.180	1.030	0.185	A2
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.0	24.87	0.10	Right	Tilt	01219	1:1	0.095	1.030	0.098	
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.0	24.87	-0.07	Left	Cheek	01219	1:1	0.171	1.030	0.176	
836.52	384	CDMA BC0 (\$22H)	RC3 / SO55	25.0	24.87	0.15	Left	Tilt	01219	1:1	0.114	1.030	0.117	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.0	24.96	0.02	Right	Cheek	01219	1:1	0.179	1.009	0.181	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.0	24.96	0.09	Right	Tilt	01219	1:1	0.097	1.009	0.098	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.0	24.96	-0.05	Left	Cheek	01219	1:1	0.166	1.009	0.167	
836.52	384	CDMA BC0 (\$22H)	EVDO Rev. A	25.0	24.96	0.12	Left	Tilt	01219	1:1	0.115	1.009	0.116	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							





FCC ID: ZNFQ720QM			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset			Page 64 of 99

Table 11-3
PCS CDMA Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.62	0.20	Right	Cheek	01219	1:1	0.136	1.019	0.139	A3
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.62	-0.12	Right	Tilt	01219	1:1	0.118	1.019	0.120	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.62	0.04	Left	Cheek	01219	1:1	0.108	1.019	0.110	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.62	0.14	Left	Tilt	01219	1:1	0.058	1.019	0.059	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.62	0.21	Right	Cheek	01219	1:1	0.131	1.019	0.133	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.62	-0.20	Right	Tilt	01219	1:1	0.090	1.019	0.092	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.62	0.20	Left	Cheek	01219	1:1	0.113	1.019	0.115	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.62	0.06	Left	Tilt	01219	1:1	0.057	1.019	0.058	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-4
GSM 850 Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.2	32.92	-0.02	Right	Cheek	01219	1	1:8.3	0.118	1.067	0.126	
836.60	190	GSM 850	GSM	33.2	32.92	0.11	Right	Tilt	01219	1	1:8.3	0.064	1.067	0.068	
836.60	190	GSM 850	GSM	33.2	32.92	-0.06	Left	Cheek	01219	1	1:8.3	0.117	1.067	0.125	
836.60	190	GSM 850	GSM	33.2	32.92	0.05	Left	Tilt	01219	1	1:8.3	0.074	1.067	0.079	
836.60	190	GSM 850	GPRS	30.7	30.69	-0.10	Right	Cheek	01219	3	1:2.76	0.194	1.002	0.194	A4
836.60	190	GSM 850	GPRS	30.7	30.69	0.06	Right	Tilt	01219	3	1:2.76	0.106	1.002	0.106	
836.60	190	GSM 850	GPRS	30.7	30.69	0.02	Left	Cheek	01219	3	1:2.76	0.191	1.002	0.191	
836.60	190	GSM 850	GPRS	30.7	30.69	0.05	Left	Tilt	01219	3	1:2.76	0.126	1.002	0.126	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 65 of 99

**Table 11-5
GSM 1900 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.7	29.87	-0.02	Right	Cheek	01219	1	1:8.3	0.062	1.211	0.075	
1880.00	661	GSM 1900	GSM	30.7	29.87	0.00	Right	Tilt	01219	1	1:8.3	0.054	1.211	0.065	
1880.00	661	GSM 1900	GSM	30.7	29.87	0.15	Left	Cheek	01219	1	1:8.3	0.062	1.211	0.075	
1880.00	661	GSM 1900	GSM	30.7	29.87	-0.20	Left	Tilt	01219	1	1:8.3	0.032	1.211	0.039	
1880.00	661	GSM 1900	GPRS	27.2	27.15	-0.18	Right	Cheek	01219	3	1:2.76	0.088	1.012	0.089	A5
1880.00	661	GSM 1900	GPRS	27.2	27.15	-0.04	Right	Tilt	01219	3	1:2.76	0.075	1.012	0.076	
1880.00	661	GSM 1900	GPRS	27.2	27.15	-0.03	Left	Cheek	01219	3	1:2.76	0.074	1.012	0.075	
1880.00	661	GSM 1900	GPRS	27.2	27.15	0.13	Left	Tilt	01219	3	1:2.76	0.040	1.012	0.040	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-6
UMTS 850 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	25.5	25.33	-0.01	Right	Cheek	01219	1:1	0.195	1.040	0.203	A6
836.60	4183	UMTS 850	RMC	25.5	25.33	0.14	Right	Tilt	01219	1:1	0.106	1.040	0.110	
836.60	4183	UMTS 850	RMC	25.5	25.33	0.16	Left	Cheek	01219	1:1	0.184	1.040	0.191	
836.60	4183	UMTS 850	RMC	25.5	25.33	0.00	Left	Tilt	01219	1:1	0.126	1.040	0.131	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-7
UMTS 1750 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	24.0	23.81	0.02	Right	Cheek	01219	1:1	0.125	1.045	0.131	A7
1732.40	1412	UMTS 1750	RMC	24.0	23.81	0.16	Right	Tilt	01219	1:1	0.094	1.045	0.098	
1732.40	1412	UMTS 1750	RMC	24.0	23.81	0.11	Left	Cheek	01219	1:1	0.109	1.045	0.114	
1732.40	1412	UMTS 1750	RMC	24.0	23.81	-0.01	Left	Tilt	01219	1:1	0.061	1.045	0.064	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 66 of 99

Table 11-8
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	24.0	23.85	0.21	Right	Cheek	01219	1:1	0.103	1.035	0.107	A8
1880.00	9400	UMTS 1900	RMC	24.0	23.85	0.03	Right	Tilt	01219	1:1	0.085	1.035	0.088	
1880.00	9400	UMTS 1900	RMC	24.0	23.85	0.04	Left	Cheek	01219	1:1	0.094	1.035	0.097	
1880.00	9400	UMTS 1900	RMC	24.0	23.85	-0.02	Left	Tilt	01219	1:1	0.050	1.035	0.052	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-9
LTE Band 71 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.5	25.36	-0.02	0	Right	Cheek	QPSK	1	0	01243	1:1	0.143	1.033	0.148	
680.50	133297	Mid	LTE Band 71	20	24.5	24.19	0.01	1	Right	Cheek	QPSK	50	0	01243	1:1	0.098	1.074	0.105	
680.50	133297	Mid	LTE Band 71	20	25.5	25.36	0.12	0	Right	Tilt	QPSK	1	0	01243	1:1	0.073	1.033	0.075	
680.50	133297	Mid	LTE Band 71	20	24.5	24.19	0.10	1	Right	Tilt	QPSK	50	0	01243	1:1	0.046	1.074	0.049	
680.50	133297	Mid	LTE Band 71	20	25.5	25.36	0.03	0	Left	Cheek	QPSK	1	0	01243	1:1	0.188	1.033	0.194	A9
680.50	133297	Mid	LTE Band 71	20	24.5	24.19	0.05	1	Left	Cheek	QPSK	50	0	01243	1:1	0.120	1.074	0.129	
680.50	133297	Mid	LTE Band 71	20	25.5	25.36	0.09	0	Left	Tilt	QPSK	1	0	01243	1:1	0.104	1.033	0.107	
680.50	133297	Mid	LTE Band 71	20	24.5	24.19	0.05	1	Left	Tilt	QPSK	50	0	01243	1:1	0.067	1.074	0.072	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-10
LTE Band 12 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	-0.01	0	Right	Cheek	QPSK	1	49	01243	1:1	0.141	1.000	0.141	
707.50	23095	Mid	LTE Band 12	10	24.5	23.79	-0.11	1	Right	Cheek	QPSK	25	25	01243	1:1	0.099	1.178	0.117	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	-0.07	0	Right	Tilt	QPSK	1	49	01243	1:1	0.078	1.000	0.078	
707.50	23095	Mid	LTE Band 12	10	24.5	23.79	-0.09	1	Right	Tilt	QPSK	25	25	01243	1:1	0.053	1.178	0.062	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.16	0	Left	Cheek	QPSK	1	49	01243	1:1	0.179	1.000	0.179	A10
707.50	23095	Mid	LTE Band 12	10	24.5	23.79	0.06	1	Left	Cheek	QPSK	25	25	01243	1:1	0.113	1.178	0.133	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.09	0	Left	Tilt	QPSK	1	49	01243	1:1	0.102	1.000	0.102	
707.50	23095	Mid	LTE Band 12	10	24.5	23.79	0.15	1	Left	Tilt	QPSK	25	25	01243	1:1	0.064	1.178	0.075	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 67 of 99

Table 11-11
LTE Band 13 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
782.00	23230	Mid	LTE Band 13	10	25.5	24.97	-0.02	0	Right	Cheek	QPSK	1	0	01243	1:1	0.175	1.130	0.198	A11
782.00	23230	Mid	LTE Band 13	10	24.5	23.78	0.04	1	Right	Cheek	QPSK	25	25	01243	1:1	0.156	1.180	0.184	
782.00	23230	Mid	LTE Band 13	10	25.5	24.97	0.07	0	Right	Tilt	QPSK	1	0	01243	1:1	0.082	1.130	0.093	
782.00	23230	Mid	LTE Band 13	10	24.5	23.78	0.09	1	Right	Tilt	QPSK	25	25	01243	1:1	0.077	1.180	0.091	
782.00	23230	Mid	LTE Band 13	10	25.5	24.97	0.21	0	Left	Cheek	QPSK	1	0	01243	1:1	0.170	1.130	0.192	
782.00	23230	Mid	LTE Band 13	10	24.5	23.78	0.07	1	Left	Cheek	QPSK	25	25	01243	1:1	0.133	1.180	0.157	
782.00	23230	Mid	LTE Band 13	10	25.5	24.97	0.09	0	Left	Tilt	QPSK	1	0	01243	1:1	0.100	1.130	0.113	
782.00	23230	Mid	LTE Band 13	10	24.5	23.78	0.03	1	Left	Tilt	QPSK	25	25	01243	1:1	0.082	1.180	0.097	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-12
LTE Band 26 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	25.50	0.04	0	Right	Cheek	QPSK	1	0	01250	1:1	0.187	1.000	0.187	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	23.81	0.03	1	Right	Cheek	QPSK	36	0	01250	1:1	0.139	1.172	0.163	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	25.50	-0.03	0	Right	Tilt	QPSK	1	0	01250	1:1	0.134	1.000	0.134	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	23.81	0.07	1	Right	Tilt	QPSK	36	0	01250	1:1	0.100	1.172	0.117	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	25.50	0.12	0	Left	Cheek	QPSK	1	0	01250	1:1	0.208	1.000	0.208	A12
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	23.81	0.01	1	Left	Cheek	QPSK	36	0	01250	1:1	0.143	1.172	0.168	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	25.50	0.03	0	Left	Tilt	QPSK	1	0	01250	1:1	0.174	1.000	0.174	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	23.81	0.10	1	Left	Tilt	QPSK	36	0	01250	1:1	0.122	1.172	0.143	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-13
LTE Band 66 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.98	0.05	0	Right	Cheek	QPSK	1	99	01250	1:1	0.109	1.005	0.110	A13
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.83	0.21	1	Right	Cheek	QPSK	50	25	01250	1:1	0.087	1.040	0.090	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.98	-0.06	0	Right	Tilt	QPSK	1	99	01250	1:1	0.084	1.005	0.084	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.83	-0.12	1	Right	Tilt	QPSK	50	25	01250	1:1	0.070	1.040	0.073	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.98	-0.05	0	Left	Cheek	QPSK	1	99	01250	1:1	0.108	1.005	0.109	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.83	0.09	1	Left	Cheek	QPSK	50	25	01250	1:1	0.078	1.040	0.081	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.98	0.02	0	Left	Tilt	QPSK	1	99	01250	1:1	0.044	1.005	0.044	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.83	-0.01	1	Left	Tilt	QPSK	50	25	01250	1:1	0.035	1.040	0.036	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 68 of 99	

Table 11-14
LTE Band 25 (PCS) Head SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.																	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.87	0.15	0	Right	Cheek	QPSK	1	0	01243	1:1	0.111	1.030	0.114
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.79	0.10	1	Right	Cheek	QPSK	50	0	01243	1:1	0.083	1.050	0.087
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.87	0.16	0	Right	Tilt	QPSK	1	0	01243	1:1	0.061	1.030	0.063
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.79	0.20	1	Right	Tilt	QPSK	50	0	01243	1:1	0.043	1.050	0.045
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.87	0.13	0	Left	Cheek	QPSK	1	0	01243	1:1	0.087	1.030	0.090
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.79	0.12	1	Left	Cheek	QPSK	50	0	01243	1:1	0.060	1.050	0.063
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.87	-0.21	0	Left	Tilt	QPSK	1	0	01243	1:1	0.048	1.030	0.049
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.79	0.21	1	Left	Tilt	QPSK	50	0	01243	1:1	0.029	1.050	0.030
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram									



Table 11-15
LTE Band 41 Head SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g) (W/kg)	Scaling Factor	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.																	
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	-0.12	0	Right	Cheek	QPSK	1	99	01342	1:1.58	0.047	1.030	0.048
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	-0.05	1	Right	Cheek	QPSK	50	50	01342	1:1.58	0.036	1.023	0.037
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	0.18	0	Right	Tilt	QPSK	1	99	01342	1:1.58	0.052	1.030	0.054
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	0.14	1	Right	Tilt	QPSK	50	50	01342	1:1.58	0.040	1.023	0.041
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	0.12	0	Left	Cheek	QPSK	1	99	01342	1:1.58	0.044	1.030	0.045
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	-0.17	1	Left	Cheek	QPSK	50	50	01342	1:1.58	0.038	1.023	0.039
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	0.14	0	Left	Tilt	QPSK	1	99	01342	1:1.58	0.040	1.030	0.041
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	0.13	1	Left	Tilt	QPSK	50	50	01342	1:1.58	0.030	1.023	0.031
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-16
DTS Head SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan W/kg	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.																	
2412	1	802.11b	DSSS	22	19.0	18.34	-0.02	Right	Cheek	01342	1	99.9	1.119	0.790	1.164	1.001	0.920	
2437	6	802.11b	DSSS	22	19.0	18.30	0.07	Right	Cheek	01342	1	99.9	1.113	0.780	1.175	1.001	0.917	
2462	11	802.11b	DSSS	22	19.0	18.22	0.03	Right	Cheek	01342	1	99.9	1.125	0.819	1.197	1.001	0.981	A16
2412	1	802.11b	DSSS	22	19.0	18.34	0.00	Right	Tilt	01342	1	99.9	0.985	0.779	1.164	1.001	0.908	
2437	6	802.11b	DSSS	22	19.0	18.30	-0.08	Right	Tilt	01342	1	99.9	0.939	0.777	1.175	1.001	0.914	
2412	1	802.11b	DSSS	22	19.0	18.34	0.12	Left	Cheek	01342	1	99.9	0.311	-	1.164	1.001	-	
2412	1	802.11b	DSSS	22	19.0	18.34	-0.16	Left	Tilt	01342	1	99.9	0.459	0.292	1.164	1.001	0.340	
2462	11	802.11b	DSSS	22	19.0	18.22	-0.02	Right	Cheek	01342	1	99.9	1.132	0.818	1.197	1.001	0.980	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram									

Note: Blue entry represents variability measurement



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 69 of 99	

**Table 11-17
NII Head SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maxim um Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	17.5	16.78	0.12	Right	Cheek	01342	6	99.2	1.179	0.680	1.180	1.008	0.809	
5280	56	802.11a	OFDM	20	17.5	16.77	0.14	Right	Cheek	01342	6	99.2	1.148	0.643	1.183	1.008	0.767	
5300	60	802.11a	OFDM	20	17.5	16.85	0.12	Right	Cheek	01342	6	99.2	1.098	0.765	1.161	1.008	0.895	A17
5300	60	802.11a	OFDM	20	17.5	16.85	0.21	Right	Tilt	01342	6	99.2	0.770	0.306	1.161	1.008	0.358	
5300	60	802.11a	OFDM	20	17.5	16.85	-0.18	Left	Cheek	01342	6	99.2	0.396	-	1.161	1.008	-	
5300	60	802.11a	OFDM	20	17.5	16.85	0.13	Left	Tilt	01342	6	99.2	0.312	-	1.161	1.008	-	
5680	136	802.11a	OFDM	20	17.5	16.91	0.16	Right	Cheek	01342	6	99.2	1.502	0.685	1.146	1.008	0.791	
5680	136	802.11a	OFDM	20	17.5	16.91	0.19	Right	Tilt	01342	6	99.2	0.854	0.307	1.146	1.008	0.355	
5680	136	802.11a	OFDM	20	17.5	16.91	0.12	Left	Cheek	01342	6	99.2	0.404	-	1.146	1.008	-	
5680	136	802.11a	OFDM	20	17.5	16.91	-0.06	Left	Tilt	01342	6	99.2	0.320	-	1.146	1.008	-	
5765	153	802.11a	OFDM	20	18.0	17.48	0.14	Right	Cheek	01342	6	99.2	1.266	0.691	1.127	1.008	0.785	
5765	153	802.11a	OFDM	20	18.0	17.48	0.20	Right	Tilt	01342	6	99.2	0.802	0.282	1.127	1.008	0.320	
5765	153	802.11a	OFDM	20	18.0	17.48	0.20	Left	Cheek	01342	6	99.2	0.358	-	1.127	1.008	-	
5765	153	802.11a	OFDM	20	18.0	17.48	-0.14	Left	Tilt	01342	6	99.2	0.306	-	1.127	1.008	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-18
DSS Head SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.											(W/kg)				
2441.00	39	Bluetooth	FHSS	11.0	10.99	0.07	Right	Cheek	01342	1	77.1	0.076	1.002	1.297	0.099	
2441.00	39	Bluetooth	FHSS	11.0	10.99	-0.05	Right	Tilt	01342	1	77.1	0.077	1.002	1.297	0.100	A18
2441.00	39	Bluetooth	FHSS	11.0	10.99	-0.19	Left	Cheek	01342	1	77.1	0.025	1.002	1.297	0.032	
2441.00	39	Bluetooth	FHSS	11.0	10.99	0.13	Left	Tilt	01342	1	77.1	0.029	1.002	1.297	0.038	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 70 of 99



11.2 Standalone Body-Worn SAR Data

Table 11-19
GSM/UMTS/CDMA Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
820.10	564	CDMA BC10 (§90S)	TDSO / SO32	25.0	24.87	-0.01	10 mm	01219	N/A	1:1	back	0.495	1.030	0.510	A19
836.52	384	CDMA BC0 (§22H)	TDSO / SO32	25.0	24.89	-0.01	10 mm	01219	N/A	1:1	back	0.534	1.026	0.548	A21
1880.00	600	PCS CDMA	TDSO / SO32	24.7	24.60	-0.02	10 mm	01219	N/A	1:1	back	0.447	1.023	0.457	A23
836.60	190	GSM 850	GSM	33.2	32.92	-0.02	10 mm	01219	1	1:8.3	back	0.407	1.067	0.434	
824.20	128	GSM 850	GPRS	30.7	30.67	-0.03	10 mm	01219	3	1:2.76	back	0.494	1.007	0.497	
836.60	190	GSM 850	GPRS	30.7	30.69	-0.04	10 mm	01219	3	1:2.76	back	0.669	1.002	0.670	A25
848.80	251	GSM 850	GPRS	30.7	30.70	-0.02	10 mm	01219	3	1:2.76	back	0.558	1.000	0.558	
1880.00	661	GSM 1900	GSM	30.7	29.87	0.03	10 mm	01219	1	1:8.3	back	0.268	1.211	0.325	
1880.00	661	GSM 1900	GPRS	27.2	27.15	-0.07	10 mm	01219	3	1:2.76	back	0.361	1.012	0.365	A26
826.40	4132	UMTS 850	RMC	25.5	25.49	-0.03	10 mm	01219	N/A	1:1	back	0.632	1.002	0.633	
836.60	4183	UMTS 850	RMC	25.5	25.33	0.00	10 mm	01219	N/A	1:1	back	0.606	1.040	0.630	
846.60	4233	UMTS 850	RMC	25.5	25.40	-0.03	10 mm	01219	N/A	1:1	back	0.636	1.023	0.651	A28
1732.40	1412	UMTS 1750	RMC	24.0	23.81	-0.05	10 mm	01219	N/A	1:1	back	0.533	1.045	0.557	A29
1880.00	9400	UMTS 1900	RMC	24.0	23.85	-0.13	10 mm	01219	N/A	1:1	back	0.451	1.035	0.467	A31
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-20
LTE Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.5	25.36	0.17	0	01250	QPSK	1	0	10 mm	back	1:1	0.562	1.033	0.581	A33
680.50	133297	Mid	LTE Band 71	20	24.5	24.19	0.02	1	01250	QPSK	50	0	10 mm	back	1:1	0.368	1.074	0.395	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.00	0	01250	QPSK	1	49	10 mm	back	1:1	0.426	1.000	0.426	A35
707.50	23095	Mid	LTE Band 12	10	24.5	23.79	0.04	1	01250	QPSK	25	25	10 mm	back	1:1	0.304	1.178	0.358	
782.00	23230	Mid	LTE Band 13	10	25.5	24.97	-0.06	0	01250	QPSK	1	0	10 mm	back	1:1	0.597	1.130	0.675	A36
782.00	23230	Mid	LTE Band 13	10	24.5	23.78	-0.06	1	01250	QPSK	25	25	10 mm	back	1:1	0.388	1.180	0.458	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	25.50	-0.04	0	01250	QPSK	1	0	10 mm	back	1:1	0.576	1.000	0.576	A37
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	23.81	-0.01	1	01250	QPSK	36	0	10 mm	back	1:1	0.417	1.172	0.489	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.98	-0.07	0	01243	QPSK	1	99	10 mm	back	1:1	0.516	1.005	0.519	A38
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.83	-0.07	1	01243	QPSK	50	25	10 mm	back	1:1	0.365	1.040	0.380	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.87	-0.11	0	01243	QPSK	1	0	10 mm	back	1:1	0.378	1.030	0.389	A40
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.79	-0.07	1	01243	QPSK	50	0	10 mm	back	1:1	0.296	1.050	0.311	
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	-0.01	0	01243	QPSK	1	99	10 mm	back	1:1.58	0.323	1.030	0.333	A42
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	-0.01	1	01243	QPSK	50	50	10 mm	back	1:1.58	0.258	1.023	0.264	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body										
Spatial Peak									1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population									averaged over 1 gram										

FCC ID: ZNFQ720QM			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 71 of 99	

**Table 11-21
DTS Body-Worn SAR**



MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	23.0	22.24	0.03	10 mm	01342	1	back	99.9	1.073	0.660	1.191	1.001	0.787	
2437	6	802.11b	DSSS	22	23.0	22.19	-0.01	10 mm	01342	1	back	99.9	0.998	0.602	1.205	1.001	0.726	
2462	11	802.11b	DSSS	22	23.0	22.32	-0.05	10 mm	01342	1	back	99.9	1.059	0.710	1.169	1.001	0.831	A44
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-22
NII Body-Worn SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	19.5	18.73	-0.04	10 mm	01342	6	back	99.2	1.313	0.696	1.194	1.008	0.838	
5280	56	802.11a	OFDM	20	19.5	18.70	-0.04	10 mm	01342	6	back	99.2	1.205	0.620	1.202	1.008	0.751	
5300	60	802.11a	OFDM	20	19.5	18.68	-0.06	10 mm	01342	6	back	99.2	1.235	0.631	1.208	1.008	0.768	
5520	104	802.11a	OFDM	20	19.5	18.74	0.06	10 mm	01342	6	back	99.2	1.369	0.692	1.191	1.008	0.831	
5600	120	802.11a	OFDM	20	19.5	18.71	-0.05	10 mm	01342	6	back	99.2	1.275	0.636	1.199	1.008	0.769	
5765	153	802.11a	OFDM	20	20.0	19.38	0.11	10 mm	01342	6	back	99.2	1.484	0.719	1.153	1.008	0.836	
5785	157	802.11a	OFDM	20	20.0	19.52	0.05	10 mm	01342	6	back	99.2	1.462	0.731	1.117	1.008	0.823	A45
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body										
Spatial Peak								1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population								averaged over 1 gram										

**Table 11-23
DSS Body-Worn SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441	39	Bluetooth	FHSS	11.0	10.99	0.00	10 mm	01342	1	back	77.1	0.032	1.002	1.297	0.042	A47
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 72 of 99	

11.3 Standalone Hotspot SAR Data

Table 11-24
GPRS/UMTS/CDMA Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. 0	25.0	24.90	0.02	10 mm	01219	N/A	1:1	back	0.512	1.023	0.524	A20
820.10	564	CDMA BC10 (§90S)	EVDO Rev. 0	25.0	24.90	-0.11	10 mm	01219	N/A	1:1	front	0.439	1.023	0.449	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. 0	25.0	24.90	0.07	10 mm	01219	N/A	1:1	bottom	0.182	1.023	0.186	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. 0	25.0	24.90	-0.04	10 mm	01219	N/A	1:1	right	0.157	1.023	0.161	
820.10	564	CDMA BC10 (§90S)	EVDO Rev. 0	25.0	24.90	-0.01	10 mm	01219	N/A	1:1	left	0.087	1.023	0.089	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. 0	25.0	24.91	0.01	10 mm	01219	N/A	1:1	back	0.552	1.021	0.564	A22
836.52	384	CDMA BC0 (§22H)	EVDO Rev. 0	25.0	24.91	-0.09	10 mm	01219	N/A	1:1	front	0.442	1.021	0.451	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. 0	25.0	24.91	0.01	10 mm	01219	N/A	1:1	bottom	0.212	1.021	0.216	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. 0	25.0	24.91	0.05	10 mm	01219	N/A	1:1	right	0.150	1.021	0.153	
836.52	384	CDMA BC0 (§22H)	EVDO Rev. 0	25.0	24.91	0.07	10 mm	01219	N/A	1:1	left	0.097	1.021	0.099	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.63	-0.02	10 mm	01219	N/A	1:1	back	0.448	1.016	0.455	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.63	0.02	10 mm	01219	N/A	1:1	front	0.483	1.016	0.491	
1851.25	25	PCS CDMA	EVDO Rev. 0	24.7	24.67	-0.03	10 mm	01219	N/A	1:1	bottom	1.100	1.007	1.108	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.63	-0.03	10 mm	01219	N/A	1:1	bottom	1.130	1.016	1.148	A24
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.7	24.61	-0.09	10 mm	01219	N/A	1:1	bottom	1.100	1.021	1.123	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.63	-0.17	10 mm	01219	N/A	1:1	right	0.183	1.016	0.186	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.63	-0.04	10 mm	01219	N/A	1:1	bottom	1.110	1.016	1.128	
824.20	128	GSM 850	GPRS	30.7	30.67	-0.03	10 mm	01219	3	1:2.76	back	0.494	1.007	0.497	
836.60	190	GSM 850	GPRS	30.7	30.69	-0.04	10 mm	01219	3	1:2.76	back	0.669	1.002	0.670	A25
848.80	251	GSM 850	GPRS	30.7	30.70	-0.02	10 mm	01219	3	1:2.76	back	0.558	1.000	0.558	
836.60	190	GSM 850	GPRS	30.7	30.69	0.00	10 mm	01219	3	1:2.76	front	0.486	1.002	0.487	
836.60	190	GSM 850	GPRS	30.7	30.69	-0.02	10 mm	01219	3	1:2.76	bottom	0.212	1.002	0.212	
836.60	190	GSM 850	GPRS	30.7	30.69	0.05	10 mm	01219	3	1:2.76	right	0.165	1.002	0.165	
836.60	190	GSM 850	GPRS	30.7	30.69	0.12	10 mm	01219	3	1:2.76	left	0.105	1.002	0.105	
1880.00	661	GSM 1900	GPRS	27.2	27.15	-0.07	10 mm	01219	3	1:2.76	back	0.361	1.012	0.365	
1880.00	661	GSM 1900	GPRS	27.2	27.15	0.09	10 mm	01219	3	1:2.76	front	0.364	1.012	0.368	
1850.20	512	GSM 1900	GPRS	27.2	27.14	-0.09	10 mm	01219	3	1:2.76	bottom	0.829	1.014	0.841	
1880.00	661	GSM 1900	GPRS	27.2	27.15	-0.08	10 mm	01219	3	1:2.76	bottom	0.869	1.012	0.879	A27
1909.80	810	GSM 1900	GPRS	27.2	27.17	-0.07	10 mm	01219	3	1:2.76	bottom	0.847	1.007	0.853	
1880.00	661	GSM 1900	GPRS	27.2	27.15	0.04	10 mm	01219	3	1:2.76	right	0.150	1.012	0.152	
826.40	4132	UMTS 850	RMC	25.5	25.49	-0.03	10 mm	01219	N/A	1:1	back	0.632	1.002	0.633	
836.60	4183	UMTS 850	RMC	25.5	25.33	0.00	10 mm	01219	N/A	1:1	back	0.606	1.040	0.630	
846.60	4233	UMTS 850	RMC	25.5	25.40	-0.03	10 mm	01219	N/A	1:1	back	0.636	1.023	0.651	A28
836.60	4183	UMTS 850	RMC	25.5	25.33	-0.05	10 mm	01219	N/A	1:1	front	0.506	1.040	0.526	
836.60	4183	UMTS 850	RMC	25.5	25.33	-0.08	10 mm	01219	N/A	1:1	bottom	0.235	1.040	0.244	
836.60	4183	UMTS 850	RMC	25.5	25.33	-0.06	10 mm	01219	N/A	1:1	right	0.160	1.040	0.166	
836.60	4183	UMTS 850	RMC	25.5	25.33	-0.12	10 mm	01219	N/A	1:1	left	0.098	1.040	0.102	
1732.40	1412	UMTS 1750	RMC	24.0	23.81	-0.05	10 mm	01219	N/A	1:1	back	0.533	1.045	0.557	
1732.40	1412	UMTS 1750	RMC	24.0	23.81	0.00	10 mm	01219	N/A	1:1	front	0.522	1.045	0.545	
1712.40	1312	UMTS 1750	RMC	24.0	23.78	-0.03	10 mm	01219	N/A	1:1	bottom	0.777	1.052	0.817	
1732.40	1412	UMTS 1750	RMC	24.0	23.81	-0.05	10 mm	01219	N/A	1:1	bottom	0.829	1.045	0.866	
1752.60	1513	UMTS 1750	RMC	24.0	23.76	-0.02	10 mm	01219	N/A	1:1	bottom	0.853	1.057	0.902	A30
1732.40	1412	UMTS 1750	RMC	24.0	23.81	-0.01	10 mm	01219	N/A	1:1	right	0.217	1.045	0.227	
1880.00	9400	UMTS 1900	RMC	24.0	23.85	-0.13	10 mm	01219	N/A	1:1	back	0.451	1.035	0.467	
1880.00	9400	UMTS 1900	RMC	24.0	23.85	0.00	10 mm	01219	N/A	1:1	front	0.518	1.035	0.536	
1852.40	9262	UMTS 1900	RMC	24.0	23.86	-0.04	10 mm	01219	N/A	1:1	bottom	1.020	1.033	1.054	
1880.00	9400	UMTS 1900	RMC	24.0	23.85	-0.03	10 mm	01219	N/A	1:1	bottom	1.020	1.035	1.056	A32
1907.60	9538	UMTS 1900	RMC	24.0	23.95	-0.01	10 mm	01219	N/A	1:1	bottom	0.967	1.012	0.979	
1880.00	9400	UMTS 1900	RMC	24.0	23.85	0.06	10 mm	01219	N/A	1:1	right	0.165	1.035	0.171	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body								
Spatial Peak							1.6 W/kg (mW/g)								
Uncontrolled Exposure/General Population							averaged over 1 gram								

Note: Blue entry represents variability measurement



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 73 of 99

Table 11-25
LTE Band 71 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
680.50	133297	Mid	LTE Band 71	20	25.5	25.36	0.17	0	01250	QPSK	1	0	10 mm	back	1:1	0.562	1.033	0.581	
680.50	133297	Mid	LTE Band 71	20	24.5	24.19	0.02	1	01250	QPSK	50	0	10 mm	back	1:1	0.368	1.074	0.395	
680.50	133297	Mid	LTE Band 71	20	25.5	25.36	0.00	0	01250	QPSK	1	0	10 mm	front	1:1	0.437	1.033	0.451	
680.50	133297	Mid	LTE Band 71	20	24.5	24.19	-0.01	1	01250	QPSK	50	0	10 mm	front	1:1	0.285	1.074	0.306	
680.50	133297	Mid	LTE Band 71	20	25.5	25.36	0.07	0	01250	QPSK	1	0	10 mm	bottom	1:1	0.121	1.033	0.125	
680.50	133297	Mid	LTE Band 71	20	24.5	24.19	-0.02	1	01250	QPSK	50	0	10 mm	bottom	1:1	0.088	1.074	0.095	
680.50	133297	Mid	LTE Band 71	20	25.5	25.36	0.16	0	01250	QPSK	1	0	10 mm	right	1:1	0.311	1.033	0.321	
680.50	133297	Mid	LTE Band 71	20	24.5	24.19	0.06	1	01250	QPSK	50	0	10 mm	right	1:1	0.174	1.074	0.187	
680.50	133297	Mid	LTE Band 71	20	25.5	25.36	0.03	0	01250	QPSK	1	0	10 mm	left	1:1	0.733	1.033	0.757	A34
680.50	133297	Mid	LTE Band 71	20	24.5	24.19	0.00	1	01250	QPSK	50	0	10 mm	left	1:1	0.391	1.074	0.420	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-26
LTE Band 12 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.00	0	01250	QPSK	1	49	10 mm	back	1:1	0.426	1.000	0.426	A35
707.50	23095	Mid	LTE Band 12	10	24.5	23.79	0.04	1	01250	QPSK	25	25	10 mm	back	1:1	0.304	1.178	0.358	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.00	0	01250	QPSK	1	49	10 mm	front	1:1	0.338	1.000	0.338	
707.50	23095	Mid	LTE Band 12	10	24.5	23.79	0.07	1	01250	QPSK	25	25	10 mm	front	1:1	0.254	1.178	0.299	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	-0.12	0	01250	QPSK	1	49	10 mm	bottom	1:1	0.120	1.000	0.120	
707.50	23095	Mid	LTE Band 12	10	24.5	23.79	0.04	1	01250	QPSK	25	25	10 mm	bottom	1:1	0.088	1.178	0.104	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	-0.05	0	01250	QPSK	1	49	10 mm	right	1:1	0.253	1.000	0.253	
707.50	23095	Mid	LTE Band 12	10	24.5	23.79	0.02	1	01250	QPSK	25	25	10 mm	right	1:1	0.161	1.178	0.190	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.02	0	01250	QPSK	1	49	10 mm	left	1:1	0.420	1.000	0.420	
707.50	23095	Mid	LTE Band 12	10	24.5	23.79	0.05	1	01250	QPSK	25	25	10 mm	left	1:1	0.283	1.178	0.333	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 74 of 99

Table 11-27
LTE Band 13 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	25.5	24.97	-0.06	0	01250	QPSK	1	0	10 mm	back	1:1	0.597	1.130	0.675	A36
782.00	23230	Mid	LTE Band 13	10	24.5	23.78	-0.06	1	01250	QPSK	25	25	10 mm	back	1:1	0.388	1.180	0.458	
782.00	23230	Mid	LTE Band 13	10	25.5	24.97	0.03	0	01250	QPSK	1	0	10 mm	front	1:1	0.505	1.130	0.571	
782.00	23230	Mid	LTE Band 13	10	24.5	23.78	0.03	1	01250	QPSK	25	25	10 mm	front	1:1	0.328	1.180	0.387	
782.00	23230	Mid	LTE Band 13	10	25.5	24.97	0.01	0	01250	QPSK	1	0	10 mm	bottom	1:1	0.178	1.130	0.201	
782.00	23230	Mid	LTE Band 13	10	24.5	23.78	0.00	1	01250	QPSK	25	25	10 mm	bottom	1:1	0.142	1.180	0.168	
782.00	23230	Mid	LTE Band 13	10	25.5	24.97	0.06	0	01250	QPSK	1	0	10 mm	right	1:1	0.207	1.130	0.234	
782.00	23230	Mid	LTE Band 13	10	24.5	23.78	0.10	1	01250	QPSK	25	25	10 mm	right	1:1	0.153	1.180	0.181	
782.00	23230	Mid	LTE Band 13	10	25.5	24.97	-0.08	0	01250	QPSK	1	0	10 mm	left	1:1	0.231	1.130	0.261	
782.00	23230	Mid	LTE Band 13	10	24.5	23.78	0.10	1	01250	QPSK	25	25	10 mm	left	1:1	0.135	1.180	0.159	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-28
LTE Band 26 (Cell) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	25.50	-0.04	0	01250	QPSK	1	0	10 mm	back	1:1	0.576	1.000	0.576	A37
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	23.81	-0.01	1	01250	QPSK	36	0	10 mm	back	1:1	0.417	1.172	0.489	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	25.50	0.13	0	01250	QPSK	1	0	10 mm	front	1:1	0.490	1.000	0.490	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	23.81	0.02	1	01250	QPSK	36	0	10 mm	front	1:1	0.354	1.172	0.415	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	25.50	-0.05	0	01250	QPSK	1	0	10 mm	bottom	1:1	0.232	1.000	0.232	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	23.81	-0.07	1	01250	QPSK	36	0	10 mm	bottom	1:1	0.173	1.172	0.203	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	25.50	-0.03	0	01250	QPSK	1	0	10 mm	right	1:1	0.210	1.000	0.210	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	23.81	0.04	1	01250	QPSK	36	0	10 mm	right	1:1	0.145	1.172	0.170	
831.50	26865	Mid	LTE Band 26 (Cell)	15	25.5	25.50	0.01	0	01250	QPSK	1	0	10 mm	left	1:1	0.095	1.000	0.095	
831.50	26865	Mid	LTE Band 26 (Cell)	15	24.5	23.81	0.03	1	01250	QPSK	36	0	10 mm	left	1:1	0.072	1.172	0.084	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 75 of 99	

Table 11-29
LTE Band 66 (AWS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.98	-0.07	0	01243	QPSK	1	99	10 mm	back	1:1	0.516	1.005	0.519	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.83	-0.07	1	01243	QPSK	50	25	10 mm	back	1:1	0.365	1.040	0.380	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.98	0.05	0	01243	QPSK	1	99	10 mm	front	1:1	0.592	1.005	0.595	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.83	-0.07	1	01243	QPSK	50	25	10 mm	front	1:1	0.420	1.040	0.437	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.0	23.88	-0.03	0	01243	QPSK	1	99	10 mm	bottom	1:1	0.867	1.028	0.891	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.0	23.87	-0.04	0	01243	QPSK	1	50	10 mm	bottom	1:1	0.769	1.030	0.792	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.98	-0.01	0	01243	QPSK	1	99	10 mm	bottom	1:1	0.971	1.005	0.976	A39
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.83	0.00	1	01243	QPSK	50	25	10 mm	bottom	1:1	0.657	1.040	0.683	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.71	0.03	1	01243	QPSK	100	0	10 mm	bottom	1:1	0.667	1.069	0.713	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.98	0.00	0	01243	QPSK	1	99	10 mm	right	1:1	0.205	1.005	0.206	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.0	22.83	-0.04	1	01243	QPSK	50	25	10 mm	right	1:1	0.145	1.040	0.151	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.98	-0.13	0	01243	QPSK	1	99	10 mm	bottom	1:1	0.932	1.005	0.937	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue entry represents variability measurement

Table 11-30
LTE Band 25 (PCS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.87	-0.11	0	01243	QPSK	1	0	10 mm	back	1:1	0.378	1.030	0.389	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.79	-0.07	1	01243	QPSK	50	0	10 mm	back	1:1	0.296	1.050	0.311	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.87	0.04	0	01243	QPSK	1	0	10 mm	front	1:1	0.459	1.030	0.473	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.79	0.03	1	01243	QPSK	50	0	10 mm	front	1:1	0.363	1.050	0.381	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.0	23.85	-0.04	0	01243	QPSK	1	50	10 mm	bottom	1:1	0.868	1.035	0.898	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.0	23.86	0.00	0	01243	QPSK	1	99	10 mm	bottom	1:1	0.742	1.033	0.766	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.87	-0.14	0	01243	QPSK	1	0	10 mm	bottom	1:1	0.927	1.030	0.955	A41
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.79	-0.10	1	01243	QPSK	50	0	10 mm	bottom	1:1	0.716	1.050	0.752	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.63	-0.02	1	01243	QPSK	100	0	10 mm	bottom	1:1	0.689	1.089	0.750	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.87	0.10	0	01243	QPSK	1	0	10 mm	right	1:1	0.128	1.030	0.132	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.0	22.79	0.02	1	01243	QPSK	50	0	10 mm	right	1:1	0.098	1.050	0.103	
								Body 1.6 W/kg (mW/g) averaged over 1 gram											





FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 76 of 99	

Table 11-31
LTE Band 41 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	Low-Mid														(W/kg)		(W/kg)	
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	-0.01	0	01243	QPSK	1	99	10 mm	back	1:1.58	0.323	1.030	0.333	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	-0.01	1	01243	QPSK	50	50	10 mm	back	1:1.58	0.258	1.023	0.264	
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	0.08	0	01243	QPSK	1	99	10 mm	front	1:1.58	0.249	1.030	0.256	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	0.01	1	01243	QPSK	50	50	10 mm	front	1:1.58	0.193	1.023	0.197	
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	-0.04	0	01243	QPSK	1	99	10 mm	bottom	1:1.58	0.498	1.030	0.513	A43
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	0.07	1	01243	QPSK	50	50	10 mm	bottom	1:1.58	0.401	1.023	0.410	
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	0.15	0	01243	QPSK	1	99	10 mm	right	1:1.58	0.091	1.030	0.094	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	0.13	1	01243	QPSK	50	50	10 mm	right	1:1.58	0.071	1.023	0.073	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT									Body										
Spatial Peak									1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population									averaged over 1 gram										



Table 11-32
WLAN Hotspot SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	23.0	22.24	0.03	10 mm	01342	1	back	99.9	1.073	0.660	1.191	1.001	0.787	
2437	6	802.11b	DSSS	22	23.0	22.19	-0.01	10 mm	01342	1	back	99.9	0.998	0.602	1.205	1.001	0.726	
2462	11	802.11b	DSSS	22	23.0	22.32	-0.05	10 mm	01342	1	back	99.9	1.059	0.710	1.169	1.001	0.831	A44
2462	11	802.11b	DSSS	22	23.0	22.32	-0.07	10 mm	01342	1	front	99.9	0.684	-	1.169	1.001	-	
2462	11	802.11b	DSSS	22	23.0	22.32	-0.04	10 mm	01342	1	top	99.9	0.899	0.565	1.169	1.001	0.661	
2462	11	802.11b	DSSS	22	23.0	22.32	-0.05	10 mm	01342	1	left	99.9	0.875	-	1.169	1.001	-	
5200	40	802.11a	OFDM	20	19.5	19.12	-0.07	10 mm	01342	6	back	99.2	1.392	0.769	1.091	1.008	0.846	A46
5220	44	802.11a	OFDM	20	19.5	18.91	-0.01	10 mm	01342	6	back	99.2	1.308	0.727	1.146	1.008	0.840	
5240	48	802.11a	OFDM	20	19.5	18.77	-0.06	10 mm	01342	6	back	99.2	1.287	0.696	1.183	1.008	0.830	
5200	40	802.11a	OFDM	20	19.5	19.12	-0.01	10 mm	01342	6	front	99.2	0.233	-	1.091	1.008	-	
5200	40	802.11a	OFDM	20	19.5	19.12	-0.17	10 mm	01342	6	top	99.2	0.169	-	1.091	1.008	-	
5200	40	802.11a	OFDM	20	19.5	19.12	-0.21	10 mm	01342	6	left	99.2	0.998	0.445	1.091	1.008	0.489	
5765	153	802.11a	OFDM	20	20.0	19.38	0.11	10 mm	01342	6	back	99.2	1.484	0.719	1.153	1.008	0.836	
5785	157	802.11a	OFDM	20	20.0	19.52	0.05	10 mm	01342	6	back	99.2	1.462	0.731	1.117	1.008	0.823	
5785	157	802.11a	OFDM	20	20.0	19.52	0.03	10 mm	01342	6	front	99.2	0.371	-	1.117	1.008	-	
5785	157	802.11a	OFDM	20	20.0	19.52	-0.15	10 mm	01342	6	top	99.2	0.153	-	1.117	1.008	-	
5785	157	802.11a	OFDM	20	20.0	19.52	-0.20	10 mm	01342	6	left	99.2	0.958	0.417	1.117	1.008	0.470	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body										
Spatial Peak								1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population								averaged over 1 gram										

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 77 of 99

**Table 11-33
DSS Hotspot SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441	39	Bluetooth	FHSS	11.0	10.99	0.00	10 mm	01342	1	back	77.1	0.032	1.002	1.297	0.042	A47
2441	39	Bluetooth	FHSS	11.0	10.99	0.18	10 mm	01342	1	front	77.1	0.022	1.002	1.297	0.029	
2441	39	Bluetooth	FHSS	11.0	10.99	-0.12	10 mm	01342	1	top	77.1	0.026	1.002	1.297	0.034	
2441	39	Bluetooth	FHSS	11.0	10.99	-0.12	10 mm	01342	1	left	77.1	0.032	1.002	1.297	0.042	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 78 of 99

11.4 Standalone Phablet SAR Data



Table 11-34
LTE Band 41 Phablet SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maxmum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (10g)	Scaling Factor	Reported SAR (10g)	Plot #
MHz	Ch.															(W/kg)		(W/kg)	
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	0.06	0	01243	QPSK	1	99	1 mm	back	1:1.58	1.100	1.030	1.133	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	0.07	1	01243	QPSK	50	50	1 mm	back	1:1.58	0.852	1.023	0.872	
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	0.04	0	01243	QPSK	1	99	1 mm	front	1:1.58	1.070	1.030	1.102	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	-0.05	1	01243	QPSK	50	50	1 mm	front	1:1.58	0.839	1.023	0.858	
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	-0.12	0	01243	QPSK	1	99	3 mm	bottom	1:1.58	1.060	1.030	1.092	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	-0.17	1	01243	QPSK	50	50	3 mm	bottom	1:1.58	0.853	1.023	0.873	
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.87	-0.04	0	01243	QPSK	1	99	0 mm	right	1:1.58	0.287	1.030	0.296	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.90	-0.05	1	01243	QPSK	50	50	0 mm	right	1:1.58	0.222	1.023	0.227	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.70	0.08	0	01243	QPSK	1	0	0 mm	back	1:1.58	1.290	1.072	1.383	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.81	0.10	0	01243	QPSK	50	0	0 mm	back	1:1.58	1.300	1.045	1.359	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.70	-0.01	0	01243	QPSK	1	0	0 mm	front	1:1.58	1.280	1.072	1.372	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.81	0.00	0	01243	QPSK	50	0	0 mm	front	1:1.58	1.260	1.045	1.317	
2506.00	39750	Low	LTE Band 41	20	24.0	23.63	-0.16	0	01243	QPSK	1	50	0 mm	bottom	1:1.58	2.050	1.089	2.232	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.70	-0.19	0	01243	QPSK	1	0	0 mm	bottom	1:1.58	2.210	1.072	2.369	
2593.00	40620	Mid	LTE Band 41	20	24.0	23.55	-0.12	0	01243	QPSK	1	99	0 mm	bottom	1:1.58	2.000	1.109	2.218	
2636.50	41055	Mid-High	LTE Band 41	20	24.0	23.49	-0.19	0	01243	QPSK	1	50	0 mm	bottom	1:1.58	1.870	1.125	2.104	
2680.00	41490	High	LTE Band 41	20	24.0	23.66	-0.18	0	01243	QPSK	1	99	0 mm	bottom	1:1.58	2.020	1.081	2.184	
2506.00	39750	Low	LTE Band 41	20	24.0	23.73	-0.06	0	01243	QPSK	50	50	0 mm	bottom	1:1.58	2.230	1.064	2.373	A48
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.81	-0.19	0	01243	QPSK	50	0	0 mm	bottom	1:1.58	2.190	1.045	2.289	
2593.00	40620	Mid	LTE Band 41	20	24.0	23.68	-0.18	0	01243	QPSK	50	25	0 mm	bottom	1:1.58	2.000	1.076	2.152	
2636.50	41055	Mid-High	LTE Band 41	20	24.0	23.62	-0.21	0	01243	QPSK	50	25	0 mm	bottom	1:1.58	1.940	1.091	2.117	
2680.00	41490	High	LTE Band 41	20	24.0	23.62	-0.06	0	01243	QPSK	50	0	0 mm	bottom	1:1.58	2.000	1.091	2.182	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.67	-0.21	0	01243	QPSK	100	0	0 mm	bottom	1:1.58	2.190	1.079	2.363	
2506.00	39750	Low	LTE Band 41	20	24.0	23.73	-0.19	0	01243	QPSK	50	50	0 mm	bottom	1:1.58	2.210	1.064	2.351	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.70	-0.06	0	01243	QPSK	1	0	0 mm	bottom	1:1.58	2.150	1.072	2.305	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Phablet 4.0 W/kg (mW/g) averaged over 10 grams											

Note: Blue entries represent variability measurements

Table 11-35
WLAN Phablet SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g)	Plot #
MHz	Ch.												W/kg	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	19.5	18.73	-0.02	0 mm	01342	6	back	99.2	13.425	1.800	1.194	1.008	2.166	A49
5280	56	802.11a	OFDM	20	19.5	18.70	-0.03	0 mm	01342	6	back	99.2	12.760	1.760	1.202	1.008	2.132	
5300	60	802.11a	OFDM	20	19.5	18.68	-0.04	0 mm	01342	6	back	99.2	12.755	1.670	1.208	1.008	2.033	
5260	52	802.11a	OFDM	20	19.5	18.73	0.15	0 mm	01342	6	front	99.2	4.730	-	1.194	1.008	-	
5260	52	802.11a	OFDM	20	19.5	18.73	-0.05	0 mm	01342	6	top	99.2	5.227	0.378	1.194	1.008	0.455	
5260	52	802.11a	OFDM	20	19.5	18.73	-0.13	0 mm	01342	6	left	99.2	15.806	1.390	1.194	1.008	1.673	
5520	104	802.11a	OFDM	20	19.5	18.74	-0.01	0 mm	01342	6	back	99.2	11.926	1.670	1.191	1.008	2.005	
5600	120	802.11a	OFDM	20	19.5	18.71	-0.08	0 mm	01342	6	back	99.2	14.200	1.680	1.199	1.008	2.030	
5520	104	802.11a	OFDM	20	19.5	18.74	-0.13	0 mm	01342	6	front	99.2	5.858	-	1.191	1.008	-	
5520	104	802.11a	OFDM	20	19.5	18.74	-0.18	0 mm	01342	6	top	99.2	6.560	0.347	1.191	1.008	0.417	
5520	104	802.11a	OFDM	20	19.5	18.74	-0.03	0 mm	01342	6	left	99.2	19.205	1.590	1.191	1.008	1.909	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population												Phablet 4.0 W/kg (mW/g) averaged over 10 grams						

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 79 of 99



11.5 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
10. Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is > 160 mm and < 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.
11. This device utilizes power reduction for some wireless modes and technologies, as outlined in Section 1.3. The maximum output power allowed for each transmitter and exposure condition was evaluated for SAR compliance based on expected use conditions and simultaneous transmission scenarios.
12. Unless otherwise noted, when 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds below.
13. Additional SAR tests for phablet SAR were evaluated per KDB 616217 Section 6 (See Section 6.9 for more information).

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.
4. GPRS was additionally evaluated for head and body-worn exposure conditions to address possible VoIP scenarios.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 80 of 99

CDMA Notes:



1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v03r01.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO Rev0 and RevA and TDSO / SO32 FCH+SCH SAR tests were not required per the 3G SAR Test Reduction Procedure in FCC KDB Publication 941225 D01v03r01.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01v03r01 procedures for data devices. Wireless Router SAR tests for Subtype 2 of Rev.A and 1x RTT configurations were not required per the 3G SAR Test Reduction Policy in KDB Publication 941225 D01v03r01.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.
5. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.6.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 and MCC=001 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per FCC KDB Publication 447498 D01v06, when the reported LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg for 1g evaluations, testing at the other channels was required for such test configurations.
5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.
6. Per KDB Publication 941225 D05Av01r02, SAR for downlink only LTE CA operations was not needed since the maximum average output power in LTE CA mode was not > 0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 81 of 99

WLAN Notes:

1. For held-to-ear, and hotspot, and phablet operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg for 1g evaluations, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.7.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 8.7.6 for more information.
4. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 9.6 for the time domain plot and calculation for the duty factor of the device.
2. Head and hotspot Bluetooth SAR were evaluated for BT BR tethering applications.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 82 of 99

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-1
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	CDMA/EVDO BC10 (§90S)	0.183	0.981	1.164
	CDMA/EVDO BC0 (§22H)	0.185	0.981	1.166
	PCS CDMA/EVDO	0.139	0.981	1.120
	GSM/GPRS 850	0.194	0.981	1.175
	GSM/GPRS 1900	0.089	0.981	1.070
	UMTS 850	0.203	0.981	1.184
	UMTS 1750	0.131	0.981	1.112
	UMTS 1900	0.107	0.981	1.088
	LTE Band 71	0.194	0.981	1.175
	LTE Band 12	0.179	0.981	1.160
	LTE Band 13	0.198	0.981	1.179
	LTE Band 26 (Cell)	0.208	0.981	1.189
	LTE Band 66 (AWS)	0.110	0.981	1.091
	LTE Band 25 (PCS)	0.114	0.981	1.095
	LTE Band 41	0.054	0.981	1.035



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 83 of 99

Table 12-2
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	CDMA/EVDO BC10 (§90S)	0.183	0.895	1.078
	CDMA/EVDO BC0 (§22H)	0.185	0.895	1.080
	PCS CDMA/EVDO	0.139	0.895	1.034
	GSM/GPRS 850	0.194	0.895	1.089
	GSM/GPRS 1900	0.089	0.895	0.984
	UMTS 850	0.203	0.895	1.098
	UMTS 1750	0.131	0.895	1.026
	UMTS 1900	0.107	0.895	1.002
	LTE Band 71	0.194	0.895	1.089
	LTE Band 12	0.179	0.895	1.074
	LTE Band 13	0.198	0.895	1.093
	LTE Band 26 (Cell)	0.208	0.895	1.103
	LTE Band 66 (AWS)	0.110	0.895	1.005
	LTE Band 25 (PCS)	0.114	0.895	1.009
	LTE Band 41	0.054	0.895	0.949

Table 12-3
Simultaneous Transmission Scenario with Bluetooth (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	CDMA/EVDO BC10 (§90S)	0.183	0.100	0.283
	CDMA/EVDO BC0 (§22H)	0.185	0.100	0.285
	PCS CDMA/EVDO	0.139	0.100	0.239
	GSM/GPRS 850	0.194	0.100	0.294
	GSM/GPRS 1900	0.089	0.100	0.189
	UMTS 850	0.203	0.100	0.303
	UMTS 1750	0.131	0.100	0.231
	UMTS 1900	0.107	0.100	0.207
	LTE Band 71	0.194	0.100	0.294
	LTE Band 12	0.179	0.100	0.279
	LTE Band 13	0.198	0.100	0.298
	LTE Band 26 (Cell)	0.208	0.100	0.308
	LTE Band 66 (AWS)	0.110	0.100	0.210
	LTE Band 25 (PCS)	0.114	0.100	0.214
	LTE Band 41	0.054	0.100	0.154





FCC ID: ZNFQ720QM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 84 of 99	

Table 12-4
Simultaneous Transmission Scenario with 5GHz WLAN and Bluetooth (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Head SAR	CDMA/EVDO BC10 (§90S)	0.183	0.895	0.100	1.178
	CDMA/EVDO BC0 (§22H)	0.185	0.895	0.100	1.180
	PCS CDMA/EVDO	0.139	0.895	0.100	1.134
	GSM/GPRS 850	0.194	0.895	0.100	1.189
	GSM/GPRS 1900	0.089	0.895	0.100	1.084
	UMTS 850	0.203	0.895	0.100	1.198
	UMTS 1750	0.131	0.895	0.100	1.126
	UMTS 1900	0.107	0.895	0.100	1.102
	LTE Band 71	0.194	0.895	0.100	1.189
	LTE Band 12	0.179	0.895	0.100	1.174
	LTE Band 13	0.198	0.895	0.100	1.193
	LTE Band 26 (Cell)	0.208	0.895	0.100	1.203
	LTE Band 66 (AWS)	0.110	0.895	0.100	1.105
	LTE Band 25 (PCS)	0.114	0.895	0.100	1.109
	LTE Band 41	0.054	0.895	0.100	1.049

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 85 of 99	

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-5
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	CDMA BC10 (§90S)	0.510	0.831	1.341
	CDMA BC0 (§22H)	0.548	0.831	1.379
	PCS CDMA	0.457	0.831	1.288
	GSM/GPRS 850	0.670	0.831	1.501
	GSM/GPRS 1900	0.365	0.831	1.196
	UMTS 850	0.651	0.831	1.482
	UMTS 1750	0.557	0.831	1.388
	UMTS 1900	0.467	0.831	1.298
	LTE Band 71	0.581	0.831	1.412
	LTE Band 12	0.426	0.831	1.257
	LTE Band 13	0.675	0.831	1.506
	LTE Band 26 (Cell)	0.576	0.831	1.407
	LTE Band 66 (AWS)	0.519	0.831	1.350
	LTE Band 25 (PCS)	0.389	0.831	1.220
	LTE Band 41	0.333	0.831	1.164

Table 12-6
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	CDMA BC10 (§90S)	0.510	0.838	1.348
	CDMA BC0 (§22H)	0.548	0.838	1.386
	PCS CDMA	0.457	0.838	1.295
	GSM/GPRS 850	0.670	0.838	1.508
	GSM/GPRS 1900	0.365	0.838	1.203
	UMTS 850	0.651	0.838	1.489
	UMTS 1750	0.557	0.838	1.395
	UMTS 1900	0.467	0.838	1.305
	LTE Band 71	0.581	0.838	1.419
	LTE Band 12	0.426	0.838	1.264
	LTE Band 13	0.675	0.838	1.513
	LTE Band 26 (Cell)	0.576	0.838	1.414
	LTE Band 66 (AWS)	0.519	0.838	1.357
	LTE Band 25 (PCS)	0.389	0.838	1.227
	LTE Band 41	0.333	0.838	1.171





FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 86 of 99

Table 12-7
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	CDMA BC10 (§90S)	0.510	0.042	0.552
	CDMA BC0 (§22H)	0.548	0.042	0.590
	PCS CDMA	0.457	0.042	0.499
	GSM/GPRS 850	0.670	0.042	0.712
	GSM/GPRS 1900	0.365	0.042	0.407
	UMTS 850	0.651	0.042	0.693
	UMTS 1750	0.557	0.042	0.599
	UMTS 1900	0.467	0.042	0.509
	LTE Band 71	0.581	0.042	0.623
	LTE Band 12	0.426	0.042	0.468
	LTE Band 13	0.675	0.042	0.717
	LTE Band 26 (Cell)	0.576	0.042	0.618
	LTE Band 66 (AWS)	0.519	0.042	0.561
	LTE Band 25 (PCS)	0.389	0.042	0.431
	LTE Band 41	0.333	0.042	0.375

Table 12-8
Simultaneous Transmission Scenario with 5GHz WLAN and Bluetooth (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Body-Worn	CDMA BC10 (§90S)	0.510	0.838	0.042	1.390
	CDMA BC0 (§22H)	0.548	0.838	0.042	1.428
	PCS CDMA	0.457	0.838	0.042	1.337
	GSM/GPRS 850	0.670	0.838	0.042	1.550
	GSM/GPRS 1900	0.365	0.838	0.042	1.245
	UMTS 850	0.651	0.838	0.042	1.531
	UMTS 1750	0.557	0.838	0.042	1.437
	UMTS 1900	0.467	0.838	0.042	1.347
	LTE Band 71	0.581	0.838	0.042	1.461
	LTE Band 12	0.426	0.838	0.042	1.306
	LTE Band 13	0.675	0.838	0.042	1.555
	LTE Band 26 (Cell)	0.576	0.838	0.042	1.456
	LTE Band 66 (AWS)	0.519	0.838	0.042	1.399
	LTE Band 25 (PCS)	0.389	0.838	0.042	1.269
	LTE Band 41	0.333	0.838	0.042	1.213

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 87 of 99	

12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB publication 248227, the worst case WLAN SAR result for the applicable exposure conditions was used for simultaneous transmission analysis.

Table 12-9
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	EVDO BC10 (§90S)	0.524	0.831	1.355
	EVDO BC0 (§22H)	0.564	0.831	1.395
	PCS EVDO	1.148	0.831	See Table Below
	GPRS 850	0.670	0.831	1.501
	GPRS 1900	0.879	0.831	See Table Below
	UMTS 850	0.651	0.831	1.482
	UMTS 1750	0.902	0.831	See Table Below
	UMTS 1900	1.056	0.831	See Table Below
	LTE Band 71	0.757	0.831	1.588
	LTE Band 12	0.426	0.831	1.257
	LTE Band 13	0.675	0.831	1.506
	LTE Band 26 (Cell)	0.576	0.831	1.407
	LTE Band 66 (AWS)	0.976	0.831	See Table Below
	LTE Band 25 (PCS)	0.955	0.831	See Table Below
	LTE Band 41	0.513	0.831	1.344

Simult Tx	Configuration	PCS EVDO SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2			1	2	1+2
Hotspot SAR	Back	0.455	0.831	1.286	Hotspot SAR	Back	0.365	0.831	1.196
	Front	0.491	0.831*	1.322		Front	0.368	0.831*	1.199
	Top	-	0.661	0.661		Top	-	0.661	0.661
	Bottom	1.148	-	1.148		Bottom	0.879	-	0.879
	Right	0.186	-	0.186		Right	0.152	-	0.152
	Left	-	0.831*	0.831		Left	-	0.831*	0.831
Hotspot SAR	Back	0.557	0.831	1.388	Hotspot SAR	Back	0.467	0.831	1.298
	Front	0.545	0.831*	1.376		Front	0.536	0.831*	1.367
	Top	-	0.661	0.661		Top	-	0.661	0.661
	Bottom	0.902	-	0.902		Bottom	1.056	-	1.056
	Right	0.227	-	0.227		Right	0.171	-	0.171
	Left	-	0.831*	0.831		Left	-	0.831*	0.831
Hotspot SAR	Back	0.519	0.831	1.350	Hotspot SAR	Back	0.389	0.831	1.220
	Front	0.595	0.831*	1.426		Front	0.473	0.831*	1.304
	Top	-	0.661	0.661		Top	-	0.661	0.661
	Bottom	0.976	-	0.976		Bottom	0.955	-	0.955
	Right	0.206	-	0.206		Right	0.132	-	0.132
	Left	-	0.831*	0.831		Left	-	0.831*	0.831



FCC ID: ZNFQ720QM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 88 of 99

Table 12-10
Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	EVDO BC10 (§90S)	0.524	0.846	1.370
	EVDO BC0 (§22H)	0.564	0.846	1.410
	PCS EVDO	1.148	0.846	See Table Below
	GPRS 850	0.670	0.846	1.516
	GPRS 1900	0.879	0.846	See Table Below
	UMTS 850	0.651	0.846	1.497
	UMTS 1750	0.902	0.846	See Table Below
	UMTS 1900	1.056	0.846	See Table Below
	LTE Band 71	0.757	0.846	See Table Below
	LTE Band 12	0.426	0.846	1.272
	LTE Band 13	0.675	0.846	1.521
	LTE Band 26 (Cell)	0.576	0.846	1.422
	LTE Band 66 (AWS)	0.976	0.846	See Table Below
	LTE Band 25 (PCS)	0.955	0.846	See Table Below
	LTE Band 41	0.513	0.846	1.359

Simult Tx	Configuration	PCS EVDO SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2			1	2	1+2
Hotspot SAR	Back	0.455	0.846	1.301	Hotspot SAR	Back	0.365	0.846	1.211
	Front	0.491	0.846*	1.337		Front	0.368	0.846*	1.214
	Top	-	0.846*	0.846		Top	-	0.846*	0.846
	Bottom	1.148	-	1.148		Bottom	0.879	-	0.879
	Right	0.186	-	0.186		Right	0.152	-	0.152
	Left	-	0.489	0.489		Left	-	0.489	0.489
Simult Tx	Configuration	UMTS 1750 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2			1	2	1+2
	Back	0.557	0.846	1.403		Back	0.467	0.846	1.313
	Front	0.545	0.846*	1.391		Front	0.536	0.846*	1.382
	Top	-	0.846*	0.846		Top	-	0.846*	0.846
	Bottom	0.902	-	0.902		Bottom	1.056	-	1.056
Hotspot SAR	Right	0.227	-	0.227	Hotspot SAR	Right	0.171	-	0.171
	Left	-	0.489	0.489		Left	-	0.489	0.489
Simult Tx	Configuration	LTE Band 71 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2			1	2	1+2
	Back	0.581	0.846	1.427		Back	0.519	0.846	1.365
	Front	0.451	0.846*	1.297		Front	0.595	0.846*	1.441
	Top	-	0.846*	0.846		Top	-	0.846*	0.846
	Bottom	0.125	-	0.125		Bottom	0.976	-	0.976
Hotspot SAR	Right	0.321	-	0.321	Hotspot SAR	Right	0.206	-	0.206
	Left	0.757	0.489	1.246		Left	-	0.489	0.489

Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	Back	0.389	0.846	1.235
	Front	0.473	0.846*	1.319
	Top	-	0.846*	0.846
	Bottom	0.955	-	0.955
	Right	0.132	-	0.132
	Left	-	0.489	0.489



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 89 of 99	

Table 12-11
Simultaneous Transmission Scenario with Bluetooth (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	EVDO BC10 (\$90S)	0.524	0.042	0.566
	EVDO BC0 (\$22H)	0.564	0.042	0.606
	PCS EVDO	1.148	0.042	1.190
	GPRS 850	0.670	0.042	0.712
	GPRS 1900	0.879	0.042	0.921
	UMTS 850	0.651	0.042	0.693
	UMTS 1750	0.902	0.042	0.944
	UMTS 1900	1.056	0.042	1.098
	LTE Band 71	0.757	0.042	0.799
	LTE Band 12	0.426	0.042	0.468
	LTE Band 13	0.675	0.042	0.717
	LTE Band 26 (Cell)	0.576	0.042	0.618
	LTE Band 66 (AWS)	0.976	0.042	1.018
	LTE Band 25 (PCS)	0.955	0.042	0.997
	LTE Band 41	0.513	0.042	0.555





FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 90 of 99

Table 12-12
Simultaneous Transmission Scenario with 5 GHz WLAN and Bluetooth (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Hotspot SAR	EVDO BC10 (§90S)	0.524	0.846	0.042	1.412
	EVDO BC0 (§22H)	0.564	0.846	0.042	1.452
	PCS EVDO	1.148	0.846	0.042	See Table Below
	GPRS 850	0.670	0.846	0.042	1.558
	GPRS 1900	0.879	0.846	0.042	See Table Below
	UMTS 850	0.651	0.846	0.042	1.539
	UMTS 1750	0.902	0.846	0.042	See Table Below
	UMTS 1900	1.056	0.846	0.042	See Table Below
	LTE Band 71	0.757	0.846	0.042	See Table Below
	LTE Band 12	0.426	0.846	0.042	1.314
	LTE Band 13	0.675	0.846	0.042	1.563
	LTE Band 26 (Cell)	0.576	0.846	0.042	1.464
	LTE Band 66 (AWS)	0.976	0.846	0.042	See Table Below
	LTE Band 25 (PCS)	0.955	0.846	0.042	See Table Below
	LTE Band 41	0.513	0.846	0.042	1.401

Simult Tx	Configuration	PCS EVDO SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3			1	2	3	1+2+3
Hotspot SAR	Back	0.455	0.846	0.042	1.343	Hotspot SAR	Back	0.365	0.846	0.042	1.253
	Front	0.491	0.846*	0.029	1.366		Front	0.368	0.846*	0.029	1.243
	Top	-	0.846*	0.034	0.880		Top	-	0.846*	0.034	0.880
	Bottom	1.148	-	-	1.148		Bottom	0.879	-	-	0.879
	Right	0.186	-	-	0.186		Right	0.152	-	-	0.152
	Left	-	0.489	0.042	0.531		Left	-	0.489	0.042	0.531
Hotspot SAR	Back	0.557	0.846	0.042	1.445	Hotspot SAR	Back	0.467	0.846	0.042	1.355
	Front	0.545	0.846*	0.029	1.420		Front	0.536	0.846*	0.029	1.411
	Top	-	0.846*	0.034	0.880		Top	-	0.846*	0.034	0.880
	Bottom	0.902	-	-	0.902		Bottom	1.056	-	-	1.056
	Right	0.227	-	-	0.227		Right	0.171	-	-	0.171
	Left	-	0.489	0.042	0.531		Left	-	0.489	0.042	0.531
Hotspot SAR	Back	0.581	0.846	0.042	1.469	Hotspot SAR	Back	0.519	0.846	0.042	1.407
	Front	0.451	0.846*	0.029	1.326		Front	0.595	0.846*	0.029	1.470
	Top	-	0.846*	0.034	0.880		Top	-	0.846*	0.034	0.880
	Bottom	0.125	-	-	0.125		Bottom	0.976	-	-	0.976
	Right	0.321	-	-	0.321		Right	0.206	-	-	0.206
	Left	0.757	0.489	0.042	1.288		Left	-	0.489	0.042	0.531

Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Hotspot SAR	Back	0.389	0.846	0.042	1.277
	Front	0.473	0.846*	0.029	1.348
	Top	-	0.846*	0.034	0.880
	Bottom	0.955	-	-	0.955
	Right	0.132	-	-	0.132
	Left	-	0.489	0.042	0.531

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 91 of 99

12.6 Phablet Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB publication 248227, the worst case WLAN SAR result for the applicable exposure conditions was used for simultaneous transmission analysis.

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required if wireless router 1g SAR (scaled to the maximum output power, including tolerance) < 1.2 W/kg. Therefore, no further analysis beyond the tables included in this section was required to determine that possible simultaneous transmission scenarios would not exceed the SAR limit.



For SAR summation, the highest reported SAR across all test distances was used as the most conservative evaluation for simultaneous transmission analysis for each device edge.

Table 12-13
Simultaneous Transmission Scenario with 5 GHz WLAN (Phablet)

Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Phablet SAR	Back	1.383	2.166	3.549
	Front	1.372	2.166*	3.538
	Top	-	0.455	0.455
	Bottom	2.373	-	2.373
	Right	0.296	-	0.296
	Left	-	1.909	1.909

12.7 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 92 of 99	

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
- 5) When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

Table 13-1
Head SAR Measurement Variability Results



HEAD VARIABILITY RESULTS												
Band	FREQUENCY		Mode/Band	Service	Side	Test Position	Data Rate (Mbps)	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	3rd Repeated SAR (1g)
	MHz	Ch.						(W/kg)	(W/kg)		(W/kg)	(W/kg)
2450	2462.00	11	802.11b, 22 MHz Bandwidth	DSSS	Right	Cheek	1	0.819	0.818	1.00	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Head				
Spatial Peak								1.6 W/kg (mW/g)				
Uncontrolled Exposure/General Population								averaged over 1 gram				

Table 13-2
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS												
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)	(W/kg)	
1750	1770.00	132572	LTE Band 66 (AWS), 20 MHz Bandwidth	QPSK, 1 RB, 99 RB Offset	bottom	10 mm	0.971	0.932	1.04	N/A	N/A	N/A
1900	1880.00	600	PCS CDMA	EVDO Rev. 0	bottom	10 mm	1.130	1.110	1.02	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Body						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						



Table 13-3
Phablet SAR Measurement Variability Results

PHABLET VARIABILITY RESULTS												
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (10g)	1st Repeated SAR (10g)	Ratio	2nd Repeated SAR (10g)	3rd Repeated SAR (10g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)	(W/kg)	
2450	2506.00	39750	LTE Band 41, 20 MHz Bandwidth	QPSK, 50 RB, 50 RB Offset	bottom	0 mm	2.230	2.210	1.01	N/A	N/A	N/A
2600	2549.50	40185	LTE Band 41, 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	bottom	0 mm	2.210	2.150	1.03	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Phablet						
Spatial Peak						4.0 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 10 grams						

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 93 of 99

13.2 Measurement Uncertainty

The measured SAR was <1.5 W/kg for 1g and <3.75 W/kg for 10g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 94 of 99

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	7/30/2018	Annual	7/30/2019	MY40000670
Agilent	8753ES	S-Parameter Vector Network Analyzer	8/30/2018	Annual	8/30/2019	MY40003841
Agilent	E4438C	ESG Vector Signal Generator	3/11/2019	Biennial	3/11/2021	MY45090700
Agilent	E5515C	8960 Series 10 Wireless Communications Test Set	12/18/2018	Annual	12/18/2019	GB42230325
Agilent	E5515C	Wireless Communications Test Set	2/7/2018	Triennial	2/7/2021	GB43304447
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB44450273
Agilent	N5182A	MXG Vector Signal Generator	11/28/2018	Annual	11/28/2019	MY47420603
Agilent	N5182A-506	MXG Vector Signal Generator	6/19/2018	Annual	6/19/2019	MY48180366
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433972
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433978
Anritsu	MA24106A	USB Power Sensor	8/20/2018	Annual	8/20/2019	1520504
Anritsu	MA24106A	USB Power Sensor	7/16/2018	Annual	7/16/2019	1520505
Anritsu	MA2411B	Pulse Power Sensor	10/30/2018	Annual	10/30/2019	1126066
Anritsu	MA2411B	Pulse Power Sensor	11/20/2018	Annual	11/20/2019	1339008
Anritsu	ML2496A	Power Meter	6/19/2018	Annual	6/19/2019	1306009
Anritsu	ML2496A	Power Meter	5/21/2018	Annual	5/21/2019	1351001
Anritsu	MT8000A	Radio Communication Test Station	11/14/2018	Annual	11/14/2019	6261914237
Anritsu	MT8821C	Radio Communication Analyzer	7/24/2018	Annual	7/24/2019	6201664756
Anritsu	MT8821C	Radio Communication Analyzer	1/25/2019	Annual	1/25/2020	6261895213
Anritsu	MT8862A	Wireless Connectivity Test Set	7/3/2018	Annual	7/3/2019	6261782395
COMTECH	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M355A00-009
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
Control Company	4040	Therm./ Clock/ Humidity Monitor	10/9/2018	Biennial	10/9/2020	181647802
Control Company	4040	Therm./ Clock/ Humidity Monitor	10/9/2018	Biennial	10/9/2020	181647811
Control Company	4352	Ultra Long Stem Thermometer	11/29/2018	Biennial	11/29/2020	181766777
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/4/2018	Annual	6/4/2019	MY53401181
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mitutoyo	CD-6°CSX	Digital Caliper	4/18/2018	Biennial	4/18/2020	13264165
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-53W2	Attenuator (3dB)	CBT	N/A	CBT	120
Pasternack	NC-100	Torque Wrench	5/23/2018	Biennial	5/23/2020	N/A
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
Rohde & Schwarz	CMW500	Radio Communication tester	8/3/2018	Annual	8/3/2019	140144
Rohde & Schwarz	CMW500	Radio Communication Tester	11/5/2018	Annual	11/5/2019	140148
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	1/30/2019	Annual	1/30/2020	162125
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	10/30/2018	Annual	10/30/2019	164948
SPEAG	DAK-3.5	Dielectric Assessment Kit	9/11/2018	Annual	9/11/2019	1091
SPEAG	D750V3	750 MHz SAR Dipole	10/19/2018	Annual	10/19/2019	1161
SPEAG	D835V2	835 MHz SAR Dipole	1/22/2019	Annual	1/22/2020	44132
SPEAG	D1765V2	1765 MHz SAR Dipole	5/23/2018	Annual	5/23/2019	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	10/23/2018	Annual	10/23/2019	54149
SPEAG	D2450V2	2450 MHz SAR Dipole	8/17/2017	Biennial	8/17/2019	719
SPEAG	D2600V2	2600 MHz SAR Dipole	6/7/2017	Biennial	6/7/2019	1064
SPEAG	D5GHzV2	5 GHz SAR Dipole	8/10/2018	Annual	8/10/2019	1237
SPEAG	D1750V2	1750 MHz SAR Dipole	5/9/2017	Biennial	5/9/2019	1148
SPEAG	D2450V2	2450 MHz SAR Dipole	9/11/2017	Biennial	9/11/2019	797
SPEAG	D2600V2	2600 MHz SAR Dipole	9/13/2016	Triennial	9/13/2019	1071
SPEAG	D5GHzV2	5 GHz SAR Dipole	1/16/2018	Biennial	1/16/2020	1057
SPEAG	EX3DV4	SAR Probe	1/25/2019	Annual	1/25/2020	3589
SPEAG	EX3DV4	SAR Probe	2/19/2019	Annual	2/19/2020	3914
SPEAG	EX3DV4	SAR Probe	6/25/2018	Annual	6/25/2019	7409
SPEAG	EX3DV4	SAR Probe	7/20/2018	Annual	7/20/2019	7410
SPEAG	EX3DV4	SAR Probe	8/23/2018	Annual	8/23/2019	7308
SPEAG	EX3DV4	SAR Probe	1/24/2019	Annual	1/24/2020	7488
SPEAG	EX3DV4	SAR Probe	2/19/2019	Annual	2/19/2020	7417
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/22/2018	Annual	8/22/2019	1450
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/14/2019	Annual	2/14/2020	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/18/2018	Annual	6/18/2019	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/11/2018	Annual	7/11/2019	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/3/2018	Annual	10/3/2019	1558
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/15/2019	Annual	1/15/2020	1530
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/13/2019	Annual	2/13/2020	665



Notes:

- CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
- Each equipment was used solely within its calibration period.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 95 of 99

15 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	



FCC ID: ZNFQ720QM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 96 of 99

16 CONCLUSION

16.1 Measurement Conclusion



The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]



FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 97 of 99

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: ZNFQ720QM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset	Page 98 of 99

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: ZNFQ720QM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1904220062-01-R1.ZNF	Test Dates: 04/24/19 - 05/21/19	DUT Type: Portable Handset		Page 99 of 99

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, Cellular CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 820.1 \text{ MHz}$; $\sigma = 0.931 \text{ S/m}$; $\epsilon_r = 41.94$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 04-24-2019; Ambient Temp: 23.1°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3914; ConvF(9.5, 9.5, 9.5) @ 820.1 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Left For Head SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. CDMA, Rule Part 90S, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.12 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.215 W/kg

SAR(1 g) = 0.174 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.937 \text{ S/m}$; $\epsilon_r = 41.887$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 04-24-2019; Ambient Temp: 23.1°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3914; ConvF(9.5, 9.5, 9.5) @ 836.52 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Left For Head SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1687

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: Cell. CDMA, Rule Part 22H, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.20 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.240 W/kg

SAR(1 g) = 0.180 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.437 \text{ S/m}$; $\epsilon_r = 38.657$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 05-12-2019; Ambient Temp: 21.3°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7410; ConvF(8.16, 8.16, 8.16) @ 1880 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: PCS CDMA, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.871 V/m; Power Drift = 0.20 dB

Peak SAR (extrapolated) = 0.203 W/kg

SAR(1 g) = 0.136 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, GSM GPRS; 3 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.76

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.937 \text{ S/m}$; $\epsilon_r = 41.886$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 04-24-2019; Ambient Temp: 23.1°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3914; ConvF(9.5, 9.5, 9.5) @ 836.6 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Left For Head SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 850, Right Head, Cheek, Mid.ch, 3 Tx slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.87 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.252 W/kg

SAR(1 g) = 0.194 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, GSM GPRS; 3 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.76

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.411 \text{ S/m}$; $\epsilon_r = 39.433$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 05-08-2019; Ambient Temp: 23.8°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN7410; ConvF(8.16, 8.16, 8.16) @ 1880 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 1900, Right Head, Cheek, Mid.ch, 3 Tx slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.490 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.133 W/kg

SAR(1 g) = 0.088 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.937 \text{ S/m}$; $\epsilon_r = 41.886$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 04-24-2019; Ambient Temp: 23.1°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3914; ConvF(9.5, 9.5, 9.5) @ 836.6 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Left For Head SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.76 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.252 W/kg

SAR(1 g) = 0.195 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.381 \text{ S/m}$; $\epsilon_r = 41.71$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 05-06-2019; Ambient Temp: 21.9°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN7409; ConvF(8.43, 8.43, 8.43) @ 1732.4 MHz; Calibrated: 6/25/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/18/2018

Phantom: SAM with CRP v5.0 right; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1750, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.843 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.183 W/kg

SAR(1 g) = 0.125 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.411 \text{ S/m}$; $\epsilon_r = 39.433$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 05-08-2019; Ambient Temp: 23.8°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN7410; ConvF(8.16, 8.16, 8.16) @ 1880 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1900, Right Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.798 V/m; Power Drift = 0.21 dB

Peak SAR (extrapolated) = 0.159 W/kg

SAR(1 g) = 0.103 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01243

Communication System: UID 0, LTE Band 71; Frequency: 680.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 680.5 \text{ MHz}$; $\sigma = 0.894 \text{ S/m}$; $\epsilon_r = 43.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 05-09-2019; Ambient Temp: 23.1°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(10, 10, 10) @ 680.5 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Left For Head SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 71, Left Head, Cheek, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.06 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.234 W/kg

SAR(1 g) = 0.188 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01243

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5$ MHz; $\sigma = 0.903$ S/m; $\epsilon_r = 43.005$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Test Date: 05-09-2019; Ambient Temp: 23.1°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(10, 10, 10) @ 707.5 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Left For Head SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 12, Left Head, Cheek, Mid.ch, QPSK,
10 MHz Bandwidth, 1 RB, 49 RB Offset**


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.62 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.223 W/kg

SAR(1 g) = 0.179 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01243

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.929 \text{ S/m}$; $\epsilon_r = 42.792$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 05-09-2019; Ambient Temp: 23.1°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(10, 10, 10) @ 782 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Left For Head SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 13, Right Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.53 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.229 W/kg

SAR(1 g) = 0.175 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01250

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$; $\sigma = 0.935 \text{ S/m}$; $\epsilon_r = 41.902$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 04-24-2019; Ambient Temp: 23.1°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3914; ConvF(9.5, 9.5, 9.5) @ 831.5 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Left For Head SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 26 (Cell.), Left Head, Cheek, Mid.ch,
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.54 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.262 W/kg

SAR(1 g) = 0.208 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01250

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1770 \text{ MHz}$; $\sigma = 1.404 \text{ S/m}$; $\epsilon_r = 41.647$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 05-06-2019; Ambient Temp: 21.9°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN7409; ConvF(8.43, 8.43, 8.43) @ 1770 MHz; Calibrated: 6/25/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/18/2018

Phantom: SAM with CRP v5.0 right; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 66 (AWS), Right Head, Cheek, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.350 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.163 W/kg

SAR(1 g) = 0.109 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01243

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.438 \text{ S/m}$; $\epsilon_r = 39.323$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 05-08-2019; Ambient Temp: 23.8°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN7410; ConvF(8.16, 8.16, 8.16) @ 1905 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 25 (PCS), Right Head, Cheek, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.566 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.173 W/kg

SAR(1 g) = 0.111 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01342

Communication System: UID 0, _LTE Band 41; Frequency: 2549.5 MHz; Duty Cycle: 1:1.58

Medium: 2450 Head Medium parameters used:

$f = 2550$ MHz; $\sigma = 1.891$ S/m; $\epsilon_r = 37.823$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Test Date: 05-02-2019; Ambient Temp: 24.2°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3589; ConvF(6.25, 6.25, 6.25) @ 2549.5 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 41, Right Head, Tilt, Low-Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.071 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.114 W/kg

SAR(1 g) = 0.052 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01342

Communication System: UID 0, _IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.83 \text{ S/m}$; $\epsilon_r = 37.731$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 04-29-2019; Ambient Temp: 20.1°C; Tissue Temp: 19.9°C

Probe: EX3DV4 - SN7308; ConvF(7.45, 7.45, 7.45) @ 2462 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V8.0; Type: QD 000 P41 Ax; Serial: 1966

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Right Head, Cheek, Ch 11, 1 Mbps


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.02 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.91 W/kg

SAR(1 g) = 0.819 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01342

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5GHz Head Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 4.707 \text{ S/m}$; $\epsilon_r = 35.941$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 05-07-2019; Ambient Temp: 21.9°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7409; ConvF(5.2, 5.2, 5.2) @ 5300 MHz; Calibrated: 6/25/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/18/2018

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11a, U-NII-2A, 20 MHz Bandwidth, Right Head, Cheek, Ch 60, 6 Mbps


Area Scan (13x22x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 5.897 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 3.69 W/kg

SAR(1 g) = 0.765 W/kg



0 dB = 2.03 W/kg = 3.07 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01342

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.297

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2441$ MHz; $\sigma = 1.813$ S/m; $\epsilon_r = 37.768$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Test Date: 04-29-2019; Ambient Temp: 20.1°C; Tissue Temp: 19.9°C

Probe: EX3DV4 - SN7308; ConvF(7.45, 7.45, 7.45) @ 2441 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V8.0; Type: QD 000 P41 Ax; Serial: 1966

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Bluetooth, Right Head, Tilt, Ch 39, 1 Mbps


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.885 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.191 W/kg

SAR(1 g) = 0.077 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 820.1 \text{ MHz}$; $\sigma = 0.995 \text{ S/m}$; $\epsilon_r = 53.293$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 20.0°C; Tissue Temp: 19.5°C

Probe: EX3DV4 - SN7488; ConvF(11.03, 11.03, 11.03) @ 820.1 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. CDMA, Rule Part 90S, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.63 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.870 W/kg

SAR(1 g) = 0.495 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, CDMA; Frequency: 820.1 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 820.1 \text{ MHz}$; $\sigma = 0.995 \text{ S/m}$; $\epsilon_r = 53.293$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 20.0°C; Tissue Temp: 19.5°C

Probe: EX3DV4 - SN7488; ConvF(11.03, 11.03, 11.03) @ 820.1 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. EVDO, Rule Part 90S, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.26 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.894 W/kg

SAR(1 g) = 0.512 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 1.001 \text{ S/m}$; $\epsilon_r = 53.241$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 20.0°C; Tissue Temp: 19.5°C

Probe: EX3DV4 - SN7488; ConvF(11.03, 11.03, 11.03) @ 836.52 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. CDMA, Rule Part 22H, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.85 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.942 W/kg

SAR(1 g) = 0.534 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 1.001 \text{ S/m}$; $\epsilon_r = 53.241$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 20.0°C; Tissue Temp: 19.5°C

Probe: EX3DV4 - SN7488; ConvF(11.03, 11.03, 11.03) @ 836.52 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Cell. EVDO, Rule Part 22H, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.31 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.973 W/kg

SAR(1 g) = 0.552 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.557 \text{ S/m}$; $\epsilon_r = 52.423$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 23.2°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7410; ConvF(7.78, 7.78, 7.78) @ 1880 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: PCS CDMA, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.94 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.771 W/kg

SAR(1 g) = 0.447 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.557 \text{ S/m}$; $\epsilon_r = 52.423$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 23.2°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7410; ConvF(7.78, 7.78, 7.78) @ 1880 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

Mode: PCS EVDO, Body SAR, Bottom Edge, Mid.ch


Area Scan (10x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 28.41 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.00 W/kg

SAR(1 g) = 1.13 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, _GSM GPRS; 3 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:2.76

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.001 \text{ S/m}$; $\epsilon_r = 53.241$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 20.0°C; Tissue Temp: 19.5°C

Probe: EX3DV4 - SN7488; ConvF(11.03, 11.03, 11.03) @ 836.6 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 3 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.87 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.669 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, _GSM GPRS; 3 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.76

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.557 \text{ S/m}$; $\epsilon_r = 52.423$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 23.2°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7410; ConvF(7.78, 7.78, 7.78) @ 1880 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 1900, Body SAR, Back side, Mid.ch, 3 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.32 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.618 W/kg

SAR(1 g) = 0.361 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, _GSM GPRS; 3 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.76

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.557 \text{ S/m}$; $\epsilon_r = 52.423$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 23.2°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7410; ConvF(7.78, 7.78, 7.78) @ 1880 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: GPRS 1900, Body SAR, Bottom Edge, Mid.ch, 3 Tx Slots


Area Scan (10x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.98 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.869 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, UMTS; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 846.6 \text{ MHz}$; $\sigma = 1.004 \text{ S/m}$; $\epsilon_r = 53.229$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 20.0°C; Tissue Temp: 19.5°C

Probe: EX3DV4 - SN7488; ConvF(11.03, 11.03, 11.03) @ 846.6 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 850, Body SAR, Back side, High.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.14 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.12 W/kg

SAR(1 g) = 0.636 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.478 \text{ S/m}$; $\epsilon_r = 52.555$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 22.3°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN3914; ConvF(7.89, 7.89, 7.89) @ 1732.4 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1750, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.91 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.933 W/kg

SAR(1 g) = 0.533 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, UMTS , Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1752.6 \text{ MHz}$; $\sigma = 1.5 \text{ S/m}$; $\epsilon_r = 52.475$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 22.3°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN3914; ConvF(7.89, 7.89, 7.89) @ 1752.6 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1750, Body SAR, Bottom Edge, High.ch


Area Scan (10x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.05 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.51 W/kg

SAR(1 g) = 0.853 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.557 \text{ S/m}$; $\epsilon_r = 52.423$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 23.2°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7410; ConvF(7.78, 7.78, 7.78) @ 1880 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.86 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.789 W/kg

SAR(1 g) = 0.451 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01219

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.557 \text{ S/m}$; $\epsilon_r = 52.423$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 23.2°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7410; ConvF(7.78, 7.78, 7.78) @ 1880 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: UMTS 1900, Body SAR, Bottom Edge, Mid.ch


Area Scan (10x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.91 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.81 W/kg

SAR(1 g) = 1.02 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01250

Communication System: UID 0, LTE Band 71; Frequency: 680.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 680.5 \text{ MHz}$; $\sigma = 0.95 \text{ S/m}$; $\epsilon_r = 54.358$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-09-2019; Ambient Temp: 23.5°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN3589; ConvF(8.34, 8.34, 8.34) @ 680.5 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 71, Body SAR, Back side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.61 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.959 W/kg

SAR(1 g) = 0.562 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01250

Communication System: UID 0, LTE Band 71; Frequency: 680.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 680.5 \text{ MHz}$; $\sigma = 0.95 \text{ S/m}$; $\epsilon_r = 54.358$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-09-2019; Ambient Temp: 23.5°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN3589; ConvF(8.34, 8.34, 8.34) @ 680.5 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 71, Body SAR, Left Edge, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (10x13x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.05 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.14 W/kg

SAR(1 g) = 0.733 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01250

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.96 \text{ S/m}$; $\epsilon_r = 54.281$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-09-2019; Ambient Temp: 23.5°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN3589; ConvF(8.34, 8.34, 8.34) @ 707.5 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 12, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.50 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.740 W/kg

SAR(1 g) = 0.426 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01250

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.988 \text{ S/m}$; $\epsilon_r = 54.093$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-09-2019; Ambient Temp: 23.5°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN3589; ConvF(8.34, 8.34, 8.34) @ 782 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 13, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.36 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.597 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01250

Communication System: UID 0, LTE Band 26; Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 831.5 \text{ MHz}$; $\sigma = 1 \text{ S/m}$; $\epsilon_r = 53.255$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 20.0°C; Tissue Temp: 19.5°C

Probe: EX3DV4 - SN7488; ConvF(11.03, 11.03, 11.03) @ 831.5 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 26 (Cell.), Body SAR, Back side, Mid.ch,
15 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.98 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.993 W/kg

SAR(1 g) = 0.576 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01243

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1770 \text{ MHz}$; $\sigma = 1.519 \text{ S/m}$; $\epsilon_r = 52.399$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 22.3°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN3914; ConvF(7.89, 7.89, 7.89) @ 1770 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 66 (AWS), Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.93 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.899 W/kg

SAR(1 g) = 0.516 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01243

Communication System: UID 0, _LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1770 \text{ MHz}$; $\sigma = 1.519 \text{ S/m}$; $\epsilon_r = 52.399$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 22.3°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN3914; ConvF(7.89, 7.89, 7.89) @ 1770 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 66 (AWS), Body SAR, Bottom Edge, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (11x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.52 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.74 W/kg

SAR(1 g) = 0.971 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01243

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.584 \text{ S/m}$; $\epsilon_r = 52.346$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 23.2°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7410; ConvF(7.78, 7.78, 7.78) @ 1905 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 25 (PCS), Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.69 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.643 W/kg

SAR(1 g) = 0.378 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01243

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.584 \text{ S/m}$; $\epsilon_r = 52.346$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 23.2°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7410; ConvF(7.78, 7.78, 7.78) @ 1905 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 25 (PCS), Body SAR, Bottom Edge, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x9x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.74 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.62 W/kg

SAR(1 g) = 0.927 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01243

Communication System: UID 0, LTE Band 41; Frequency: 2549.5 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body Medium parameters used:

$f = 2550 \text{ MHz}$; $\sigma = 2.151 \text{ S/m}$; $\epsilon_r = 51.099$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7417; ConvF(7.37, 7.37, 7.37) @ 2549.5 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/13/2019

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 41, Body SAR, Back side, Low-Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.91 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.604 W/kg

SAR(1 g) = 0.323 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01243

Communication System: UID 0, _LTE Band 41; Frequency: 2549.5 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body Medium parameters used:

$f = 2550 \text{ MHz}$; $\sigma = 2.151 \text{ S/m}$; $\epsilon_r = 51.099$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7417; ConvF(7.37, 7.37, 7.37) @ 2549.5 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/13/2019

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 41, Body SAR, Bottom Edge, Low-Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset**


Area Scan (10x9x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.13 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.992 W/kg

SAR(1 g) = 0.498 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01342

Communication System: UID 0, _IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 2.047 \text{ S/m}$; $\epsilon_r = 51.364$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7417; ConvF(7.51, 7.51, 7.51) @ 2462 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/13/2019

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 11, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.44 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 0.710 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01342

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5785 \text{ MHz}$; $\sigma = 6.271 \text{ S/m}$; $\epsilon_r = 46.503$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-30-2019; Ambient Temp: 22.0°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7308; ConvF(4.18, 4.18, 4.18) @ 5785 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1630

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11a, UNII-3, 20 MHz Bandwidth, Body SAR, Ch 157, 6 Mbps, Back Side


Area Scan (11x21x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 10.94 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 3.13 W/kg

SAR(1 g) = 0.731 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01342

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5200 \text{ MHz}$; $\sigma = 5.401 \text{ S/m}$; $\epsilon_r = 47.642$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-30-2019; Ambient Temp: 22.0°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7308; ConvF(4.48, 4.48, 4.48) @ 5200 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1630

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11a, UNII-1, 20 MHz Bandwidth, Body SAR, Ch 40, 6 Mbps, Back Side


Area Scan (11x21x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 12.76 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 2.71 W/kg

SAR(1 g) = 0.769 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01342

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.297

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 2.026 \text{ S/m}$; $\epsilon_r = 52.323$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-08-2019; Ambient Temp: 21.6°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7308; ConvF(7.57, 7.57, 7.57) @ 2441 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1630

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: Bluetooth, Body SAR, Ch 39, 1 Mbps, Back Side


Area Scan (11x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.280 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.0720 W/kg

SAR(1 g) = 0.032 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01243

Communication System: UID 0, _LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 2.097 \text{ S/m}$; $\epsilon_r = 51.231$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 05-06-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7417; ConvF(7.51, 7.51, 7.51) @ 2506 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/13/2019

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

**Mode: LTE Band 41, Phablet SAR, Bottom Edge, Low.ch,
20 MHz Bandwidth, QPSK, 50 RB, 50 RB Offset**


Area Scan (10x9x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 59.21 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 21.4 W/kg

SAR(10 g) = 2.23 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFQ720QM; Type: Portable Handset; Serial: 01342

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5260 \text{ MHz}$; $\sigma = 5.488 \text{ S/m}$; $\epsilon_r = 47.514$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 04-30-2019; Ambient Temp: 22.0°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7308; ConvF(4.48, 4.48, 4.48) @ 5260 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1630

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

Mode: IEEE 802.11a, U-NII-2A, 20 MHz Bandwidth, Phablet SAR, Ch 52, 6 Mbps, Back Side


Area Scan (13x20x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (9x9x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 35.88 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 28.3 W/kg

SAR(10 g) = 1.8 W/kg



0 dB = 15.5 W/kg = 11.90 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1161

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.918 \text{ S/m}$; $\epsilon_r = 42.895$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 05-09-2019; Ambient Temp: 23.1°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(10, 10, 10) @ 750 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Left For Head SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.77 W/kg

SAR(1 g) = 1.73 W/kg

Deviation(1 g) = 7.72%



0 dB = 2.38 W/kg = 3.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.936 \text{ S/m}$; $\epsilon_r = 41.89$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 04-24-2019; Ambient Temp: 23.1°C; Tissue Temp: 22.7°C

Probe: EX3DV4 - SN3914; ConvF(9.5, 9.5, 9.5) @ 835 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: Left For Head SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1687

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 3.04 W/kg

SAR(1 g) = 1.97 W/kg

Deviation(1 g) = 2.71%



0 dB = 2.69 W/kg = 4.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head; Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.392 \text{ S/m}$; $\epsilon_r = 41.682$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 21.9°C; Tissue Temp: 22.4°C

Probe: EX3DV4 - SN7409; ConvF(8.43, 8.43, 8.43) @ 1750 MHz; Calibrated: 6/25/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/18/2018

Phantom: SAM 30 with CRP v5.0 right; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.73 W/kg

SAR(1 g) = 3.64 W/kg

Deviation(1 g) = 0.55%



0 dB = 5.60 W/kg = 7.48 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.432 \text{ S/m}$; $\epsilon_r = 39.345$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-08-2019; Ambient Temp: 23.8°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN7410; ConvF(8.16, 8.16, 8.16) @ 1900 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.34 W/kg

SAR(1 g) = 4.06 W/kg

Deviation(1 g) = 3.31%



0 dB = 6.26 W/kg = 7.97 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.458 \text{ S/m}$; $\epsilon_r = 38.566$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-12-2019; Ambient Temp: 21.3°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7410; ConvF(8.16, 8.16, 8.16) @ 1900 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.68 W/kg

SAR(1 g) = 4.24 W/kg

Deviation(1 g) = 7.89%



0 dB = 6.59 W/kg = 8.19 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.82 \text{ S/m}$; $\epsilon_r = 37.749$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-29-2019; Ambient Temp: 20.1°C; Tissue Temp: 19.9°C

Probe: EX3DV4 - SN7308; ConvF(7.45, 7.45, 7.45) @ 2450 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V8.0; Type: QD 000 P41 Ax; Serial: 1966

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.1 W/kg

SAR(1 g) = 5.18 W/kg

Deviation(1 g) = -0.19%



0 dB = 8.73 W/kg = 9.41 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.816 \text{ S/m}$; $\epsilon_r = 38.797$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-20-2019; Ambient Temp: 23.1°C; Tissue Temp: 21.4°C

Probe: EX3DV4 - SN3589; ConvF(6.46, 6.46, 6.46) @ 2450 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.4 W/kg

SAR(1 g) = 5.28 W/kg

Deviation(1 g) = 0.19%



0 dB = 8.94 W/kg = 9.51 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1064

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 1.927 \text{ S/m}$; $\epsilon_r = 37.745$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-02-2019; Ambient Temp: 24.2°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3589; ConvF(6.25, 6.25, 6.25) @ 2600 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: Twin-SAM V5.0 (30); Type: QD 000 P40 CD; Serial: 1647

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 13.3 W/kg

SAR(1 g) = 5.87 W/kg

Deviation(1 g) = 2.98%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5GHz Head; Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 4.645 \text{ S/m}$; $\epsilon_r = 36.039$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-07-2019; Ambient Temp: 21.9°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7409; ConvF(5.2, 5.2, 5.2) @ 5250 MHz; Calibrated: 6/25/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/18/2018

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.8 W/kg

SAR(1 g) = 3.89 W/kg

Deviation(1 g) = -4.31%



0 dB = 9.19 W/kg = 9.63 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5GHz Head; Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 5.231 \text{ S/m}$; $\epsilon_r = 35.133$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-07-2019; Ambient Temp: 21.9°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7409; ConvF(4.82, 4.82, 4.82) @ 5750 MHz; Calibrated: 6/25/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 6/18/2018

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.7 W/kg

SAR(1 g) = 3.84 W/kg

Deviation(1 g) = -4.71%



0 dB = 9.24 W/kg = 9.66 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1161

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.976 \text{ S/m}$; $\epsilon_r = 54.18$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 05-09-2019; Ambient Temp: 23.5°C; Tissue Temp: 22.2°C

Probe: EX3DV4 - SN3589; ConvF(8.34, 8.34, 8.34) @ 750 MHz; Calibrated: 1/25/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 8/22/2018

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: 1648

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.58 W/kg

SAR(1 g) = 1.65 W/kg

Deviation(1 g) = -2.14%



0 dB = 2.24 W/kg = 3.50 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1.001 \text{ S/m}$; $\epsilon_r = 53.243$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 05-06-2019; Ambient Temp: 20.0°C; Tissue Temp: 19.5°C

Probe: EX3DV4 - SN7488; ConvF(11.03, 11.03, 11.03) @ 835 MHz; Calibrated: 1/24/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1530; Calibrated: 1/15/2019

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 3.10 W/kg

SAR(1 g) = 2.04 W/kg

Deviation(1 g) = 5.48%



0 dB = 2.68 W/kg = 4.28 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.497 \text{ S/m}$; $\epsilon_r = 52.486$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 22.3°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN3914; ConvF(7.89, 7.89, 7.89) @ 1750 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.07 W/kg

SAR(1 g) = 3.82 W/kg

Deviation(1 g) = 3.24%



0 dB = 5.85 W/kg = 7.67 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.495 \text{ S/m}$; $\epsilon_r = 52.197$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3914; ConvF(7.89, 7.89, 7.89) @ 1750 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/14/2019

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.11 W/kg

SAR(1 g) = 3.85 W/kg

Deviation(1 g) = 2.94%



0 dB = 5.94 W/kg = 7.74 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.579 \text{ S/m}$; $\epsilon_r = 52.361$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-01-2019; Ambient Temp: 23.2°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7410; ConvF(7.78, 7.78, 7.78) @ 1900 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.87 W/kg

SAR(1 g) = 4.21 W/kg

Deviation(1 g) = 6.85%



0 dB = 6.59 W/kg = 8.19 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.583 \text{ S/m}$; $\epsilon_r = 51.694$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-21-2019; Ambient Temp: 23.2°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7410; ConvF(7.78, 7.78, 7.78) @ 1900 MHz; Calibrated: 7/20/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1322; Calibrated: 7/11/2018

Phantom: Front; Type: QD 000 P40 CD; Serial: 1686

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.62 W/kg

SAR(1 g) = 4.09 W/kg

Deviation(1 g) = 3.81%



0 dB = 6.42 W/kg = 8.08 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.034 \text{ S/m}$; $\epsilon_r = 51.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7417; ConvF(7.51, 7.51, 7.51) @ 2450 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/13/2019

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.6 W/kg

SAR(10 g) = 2.3 W/kg

Deviation(10 g) = -4.96%



0 dB = 8.43 W/kg = 9.26 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.034 \text{ S/m}$; $\epsilon_r = 52.307$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-08-2019; Ambient Temp: 21.6°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7308; ConvF(7.57, 7.57, 7.57) @ 2450 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1630

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.9 W/kg

SAR(1 g) = 5.19 W/kg

Deviation(1 g) = 3.59%



0 dB = 8.69 W/kg = 9.39 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1071

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 2.208 \text{ S/m}$; $\epsilon_r = 50.96$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 05-06-2019; Ambient Temp: 22.2°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7417; ConvF(7.37, 7.37, 7.37) @ 2600 MHz; Calibrated: 2/19/2019

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/13/2019

Phantom: Right Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1797

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.8 W/kg

SAR(1 g) = 5.33 W/kg; SAR(10 g) = 2.33 W/kg

Deviation(1 g) = -1.66%; Deviation(10 g) = -4.90%



0 dB = 9.23 W/kg = 9.65 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.475 \text{ S/m}$; $\epsilon_r = 47.536$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-30-2019; Ambient Temp: 22.0°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7308; ConvF(4.48, 4.48, 4.48) @ 5250 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1630

Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Peak SAR (extrapolated) = 14.7 W/kg

SAR(1 g) = 3.67 W/kg; SAR(10 g) = 1.01 W/kg

Deviation(1 g) = -3.29%; Deviation(10 g) = -4.27%



0 dB = 8.67 W/kg = 9.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.984 \text{ S/m}$; $\epsilon_r = 46.873$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-30-2019; Ambient Temp: 22.0°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7308; ConvF(4, 4, 4) @ 5600 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1630

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.2 W/kg

SAR(1 g) = 3.89 W/kg; SAR(10 g) = 1.06 W/kg

Deviation(1 g) = -2.63%; Deviation(10 g) = -4.93%



0 dB = 9.58 W/kg = 9.81 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 6.212 \text{ S/m}$; $\epsilon_r = 46.57$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 04-30-2019; Ambient Temp: 22.0°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7308; ConvF(4.18, 4.18, 4.18) @ 5750 MHz; Calibrated: 8/23/2018

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1558; Calibrated: 10/3/2018

Phantom: Twin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1630

Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7450)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.9 W/kg

SAR(1 g) = 3.57 W/kg; SAR(10 g) = 0.990 W/kg

Deviation(1 g) = -6.91%; Deviation(10 g) = -6.60%



0 dB = 8.62 W/kg = 9.36 dBW/kg

APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **D750V3-1161_Oct18**

CALIBRATION CERTIFICATE

Object **D750V3 - SN:1161**

Calibration procedure(s) **QA CAL-05.v10**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **October 19, 2018**

*BN ✓
10-30-2018*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-18 (No. 217-02682)	Apr-19
Type-N mismatch combination	SN: 5047.2 / 06327	04-Apr-18 (No. 217-02683)	Apr-19
Reference Probe EX3DV4	SN: 7349	30-Dec-17 (No. EX3-7349_Dec17)	Dec-18
DAE4	SN: 601	04-Oct-18 (No. DAE4-601_Oct18)	Oct-19

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-18)	In house check: Oct-20
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-18)	In house check: Oct-20
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-18)	In house check: Oct-20
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-18)	In house check: Oct-20
Network Analyzer Agilent E8358A	SN: US41080477	31-Mar-14 (in house check Oct-18)	In house check: Oct-19

Calibrated by: **Manu Seitz** **Manu Seitz** **Manu Seitz**
Name Function Laboratory Technician

Approved by: **Katja Pokovic** **Katja Pokovic** **Katja Pokovic**
Name Function Technical Manager

[Signature]
[Signature]

Issued: October 22, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.2
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	750 MHz \pm 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 \pm 0.2) °C	40.8 \pm 6 %	0.89 mho/m \pm 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.02 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	8.03 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.32 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	5.26 W/kg \pm 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 \pm 0.2) °C	55.1 \pm 6 %	0.96 mho/m \pm 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.11 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	8.43 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.39 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	5.55 W/kg \pm 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	55.6 Ω - 1.9 j Ω
Return Loss	- 25.0 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	50.6 Ω - 4.2 j Ω
Return Loss	- 27.6 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.032 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	November 19, 2015

DASY5 Validation Report for Head TSL

Date: 19.10.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1161

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.89 \text{ S/m}$; $\epsilon_r = 40.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.22, 10.22, 10.22) @ 750 MHz; Calibrated: 30.12.2017
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.10.2018
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 58.51 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.04 W/kg


SAR(1 g) = 2.02 W/kg; SAR(10 g) = 1.32 W/kg

Maximum value of SAR (measured) = 2.70 W/kg



0 dB = 2.70 W/kg = 4.31 dBW/kg

Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 19.10.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1161

Communication System: UID 0 - CW; Frequency: 750 MHz

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.96 \text{ S/m}$; $\epsilon_r = 55.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.19, 10.19, 10.19) @ 750 MHz; Calibrated: 30.12.2017
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.10.2018
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 57.57 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.18 W/kg

SAR(1 g) = 2.11 W/kg; SAR(10 g) = 1.39 W/kg

Maximum value of SAR (measured) = 2.83 W/kg



0 dB = 2.83 W/kg = 4.52 dBW/kg