

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL5815-1**

Date: 09-28-2006

Tested by: G. Barbato

Test Sample (model) I) 5815-1

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 315MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

$$[(\text{Meter reading} + \text{Cable/Amp factor} + \text{Antenna factor}) / 20]$$

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				604.0
315	H	68.39	1.1	13.62	14305.4	10.0%	1430.5	6042.0
630	H	52.59	1.6	18.36	4241.3	10.0%	424.1	604.2
945	H	39.09	1.8	21.62	1335.1	10.0%	133.5	604.2
1260	H	42.79	2.3	24.42	2988.8	10.0%	298.9	500.0
1575	H	35.39	2.7	26.40	1676.9	10.0%	167.7	500.0
1890	H	34.79	2.9	28.46	2030.0	10.0%	203.0	604.2
2205	H	35.19	3.1	30.33	2697.7	10.0%	269.8	500.0
2520	H	35.99	3.3	31.40	3423.7	10.0%	342.4	604.2
2835	H	35.69	3.6	31.60	3503.5	10.0%	350.3	500.0
3150	H	36.89	4.1	31.78	4350.1	10.0%	435.0	604.2
4000			CABLE "A"	BICONILOG				