

Groenlo, 26 Augustus 2015

Declaration on radiation safety standard conformance

Return address: PO Box 6, 7140 AA Groenlo, The Netherlands

American Certification Body
Certification Department
6731 Whittier Avenue, Suite C110
McLean, Virginia 22101
USA

We, N.V. Nederlandsche Apparatenfabriek "Nedap", declare that the following product:

Description : Long-range vehicle and driver identification reader operating on 2.45 GHz, 433 MHz and 120 kHz. This calculation is for the 433 MHz part.
FCC ID : CGDTRANSITULTI
Manufacturer : N.V. Nederlandsche Apparatenfabriek "Nedap"
Brand : Nedap
Model : TRANSIT ULTIMATE

The measured field strength at 433 MHz is 82.84 dBµV/m @ 3 m distance.

$$E_{lim} = 20 \times \log_{10}\left(\frac{\sqrt{30P_{lim}}}{d}\right) + 120$$

Where:

E_{lim} = electric field strength limit, in dB (µV/m)
 P_{lim} = EIRP limit, in watts
 d = measurement distance, in meters

$$82.84 = 20 \log_{10}\left(\frac{\sqrt{30P_{lim}}}{3}\right) + 120 \gggg - 37.16 = 20 \log_{10}\left(\frac{\sqrt{30P_{lim}}}{3}\right) \gggg - 1.858 = \log_{10}\left(\frac{\sqrt{30P_{lim}}}{3}\right)$$

$$0.014 = \frac{\sqrt{30P_{lim}}}{3} \gggg P_{lim} = 6 \mu W$$

has a rated RF power of 6 µW, which means that the worst case prediction of power density (100% reflection) at 20 cm distance (worst case) can be calculated as follows:

$$S = \frac{EIRP}{4 * \pi * R^2} \quad (\text{power density without reflection})$$

$$S = \frac{2^2 * EIRP}{4 * \pi * R^2} \quad (\text{power density with 100\% reflection})$$

$$S = \frac{2^2 * EIRP}{4 * \pi * R^2} = \frac{0.006mW}{\pi * (20cm)^2} = 0.005 \mu W/cm^2 \quad (\text{Limit} = 457 \mu W/cm^2)$$

Yours Sincerely
N.V. Nederlandsche Apparatenfabriek "Nedap"

Jacques A.M. Hulshof
Approval officer

N.V. Nederlandsche Apparatenfabriek "Nedap"
Parallelweg 2
NL-7141 DC Groenlo
P.O. Box 6
NL-7140 AC Groenlo

T +31 (0)544 471 111
F +31 (0) 544 463 475
E info@nedap.com
www.nedap.com

Traderegister 08013836
ABN-AMRO 59.16.32.330
IBAN NL83ABNA0591632330
BIC ABNANL2A
VAT NL006456285B01