

28 June 2019

Federal Communications Commission

Equipment Authorization Devision, Application Processing Branch 7 435 Oakland Mills Road Columbia, MD 21048

Certification and Engineering Bureau

Innovation, Science and Economic Development Canada Spectrum Engineering Branch 3701 Carling Avenue, Building 94 Ottawa, Ontario K2H 8S2 Robert Bosch Tool Corporation 1800 W. Central Rd. Mount Prospect, IL 60056 Telephone +1 224 232-2382 Fax +1 224 232-2984 Gerard.Pasciak@ us.bosch.com www.bosch.us

Subject: Modular Approval Statement

Date: 28.06.2019

FCC Certification Number: TXTGPS25-4

ISED Company Number: 909H UPN: GPS25-4

HVIN (Hardware Version R2802-A PMN: (Product Marketing Name) Bosch GPS25-4

Identification Number):

HMN: (Host Marketing Name) FVIN: (Firmware Version Identification Number)

TO WHOM IT MAY CONCERN

We are requesting Limited Modular approval and pursuant to Paragraphs RSP-100 Issue 11, Annex D -January 2016 and 47 CFR §15.212, we herewith declare for our module:

Modular approval requirement	Yes	No *			
(a) The radio elements must have the radio frequency circuitry be shielded. Physical/discrete and tuning capacitors may be located external to the shield, but must be on the module assembly.					
*Please provide a detailed explanation if the answer is "No.":					



28 June 2019 page 2 of 3

(b) The module shall have buffered modulation/data input(s) (if such			
inputs are provided) to ensure that the module will comply with the	X		
requirements set out in the applicable RSS standard under conditions of	^		
excessive data rates or over-modulation.			
*Please provide a detailed explanation if the answer is "No.":			
(c) The module shall have its own power supply regulation on the module.			
This is to ensure that the module will comply with the requirements set	V		
out in the applicable standard regardless of the design of the power	X		
supplying circuitry in the host device which houses the module.			
*Please provide a detailed explanation if the answer is "No.": As desinformation: The module described in this document is intended to be supsupply: Either directly with nominal 3V by a CR2032 coin cell via the correspondent or with nominal 3.3.V indirectly by a host device via the "ext_pwinformation for block diagram.	oplied by an extesponding "coir	ternal voltage n cell +/-"	
(d) The module shall comply with the provisions for external power			
amplifiers and antennas detailed in this standard. The equipment	X		
certification submission shall contain a detailed description of the	^		
configuration of all antennas that will be used with the module.			
*Please provide a detailed explanation if the answer is "No.": The mo	odule described	d in this	
document is intended to be used with the integrated printed/meander ant	enna only. No e	external	
antennas are to be used, i.e. no description for the configuration of any a	ntennas is give	n.	
(e) The module shall be tested for compliance with the applicable			
standard in a stand-alone configuration, i.e. the module must not be	X		
inside another device during testing.			
*Please provide a detailed explanation if the answer is "No.":			
(f) The module shall comply with the Category I equipment labeling	X		
requirements and CFR § 15.212(a)(1)(vi).	^		
*Please provide a detailed explanation if the answer is "No.":			
(g) The module shall comply with applicable RSS-102 exposure			
requirements and any applicable FCC RF exposure requirement which	X		
are based on the intended use/configurations.			



28 June 2019 page 3 of 3

Sincerely,

Gerard Pasciak

Approvals Engineer