Report No.: SH1210819-35399E-00B

## **Applicable Standard**

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34-30	824/f	2.19/f	$*(180/f^2)$	30					
30-300	27.5	0.073	0.2	30					
300-1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

f = frequency in MHz

\* = Plane-wave equivalent power density

## Result

## **Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

FCC Part 15.247 Page 11 of 40

Mode	Frequency	Antenna Gain		Tune up conducted power		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	$(mW/cm^2)$	(mW/cm <sup>2</sup> )
BDR/EDR	2402-2480	5.0	3.16	7.0	5.01	20	0.003	1
BLE	2402-2480	5.0	3.16	1.5	1.41	20	0.001	1
Wi-Fi	2412-2462	5.0	3.16	16.5	44.67	20	0.028	1
WCDMA Band 2	1850-1910	0	1.0	23.0	200	20	0.040	1
WCDMA Band 4	1710-1755	0	1.0	23.0	200	20	0.040	1
WCDMA Band 5	824-849	0	1.0	23.0	200	20	0.040	0.549
LTE Band 2	1850-1910	0	1.0	23.0	200	20	0.040	1
LTE Band 4	1710-1755	0	1.0	23.0	200	20	0.040	1
LTE Band 5	824-849	0	1.0	23.0	200	20	0.040	0.549
LTE Band 7	2500-2570	0	1.0	23.0	200	20	0.040	1
LTE Band 12	699-716	0	1.0	23.0	200	20	0.040	0.466
LTE Band 13	777-787	0	1.0	23.0	200	20	0.040	0.518
LTE Band 17	704-716	0	1.0	23.0	200	20	0.040	0.469

Note: 1. the tune up conducted power was declared by the applicant 2. the Wi-Fi, WCDMA/LTE can transmit at the same time.

So the worst simultaneous transmitting consideration: The ratio=MPEwi-Fi/limit + MPElte/limit = 0.028/1.0+0.040/0.466=0.114 < 1.0

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliant** 

FCC Part 15.247 Page 12 of 40