

Prüfbericht-Nr.: Test Report No.:	50096096 001	Auftrags-Nr.: Order No.:	164103261	Seite 1 von 74 Page 1 of 74
Kunden-Referenz-Nr.: Client Reference No.:	N/A	Auftragsdatum: Order date:	22.06.2017	
Auftraggeber: Client:	Edifier International Limited, Room 2207-9, Tower Two, Lippo Centre 89 Queensway, Hong Kong			
Prüfgegenstand: Test item:	Portable Speaker			
Bezeichnung / Typ-Nr.: Identification / Type No.:	BIGBUN, MP255 (Edifier)			
Auftrags-Inhalt: Order content:	FCC/IC Certification			
Prüfgrundlage: Test specification:	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.209 CFR47 FCC Part 15: Subpart B Section 15.109 RSS-247 Issue 2 February 2017 ICES-003 Issue 6 January 2016			
	CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart B Section 15.107 FCC KDB Publication 447498 D01 v06 RSS-Gen Issue 4 November 2014 RSS-102 Issue 5 March 2015			
Wareneingangsdatum: Date of receipt:	22.06.2017			
Prüfmuster-Nr.: Test sample No.:	A000605083-002, A000605083-003, A000605083-004			
Prüfzeitraum: Testing period:	23.06.2017 - 02.07.2017			
Ort der Prüfung: Place of testing:	Accurate Technology Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von / tested by:		kontrolliert von / reviewed by:		
03-07-2017 Andy Yan/Project Manager Datum Name / Stellung Unterschrift Date Name / Position Signature		03-07-2017 Owen Tian/Technical Certifier Datum Name / Stellung Unterschrift Date Name / Position Signature		
Sonstiges / Other:				
FCC ID: Z9G-EDF57 IC: 10004A-EDF57 HVIN: BIGBUN, MP255				
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:		Prüfmuster vollständig und unbeschädigt Test item complete and undamaged		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

V04

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT*RESULT: Pass***5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER***RESULT: Pass***5.1.3 20dB BANDWIDTH AND 99% BANDWIDTH***RESULT: Pass***5.1.4 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100KHz BANDWIDTH***RESULT: Pass***5.1.5 SPURIOUS EMISSION***RESULT: Pass***5.1.6 FREQUENCY SEPARATION***RESULT: Pass***5.1.7 NUMBER OF HOPPING FREQUENCY***RESULT: Pass***5.1.8 TIME OF OCCUPANCY***RESULT: Pass***5.1.9 CONDUCTED EMISSIONS***RESULT: Pass***5.1.10 RADIATED EMISSION***RESULT: Pass***6.1.1 ELECTROMAGNETIC FIELDS***RESULT: Pass*

Contents

1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2.	TEST SITES	5
2.1	TEST FACILITIES	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3.	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	9
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	9
3.5	SUBMITTED DOCUMENTS	9
4.	TEST SET-UP AND OPERATION MODES	10
4.1	PRINCIPLE OF CONFIGURATION SELECTION.....	10
4.2	TEST OPERATION AND TEST SOFTWARE	10
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	10
4.5	TEST SETUP DIAGRAM	11
5.	TEST RESULTS	13
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	13
5.1.1	<i>Antenna Requirement</i>	<i>13</i>
5.1.2	<i>Maximum Peak Conducted Output Power.....</i>	<i>14</i>
5.1.3	<i>20dB Bandwidth and 99% Bandwidth.....</i>	<i>15</i>
5.1.4	<i>Conducted Spurious Emissions measured in 100kHz Bandwidth.....</i>	<i>16</i>
5.1.5	<i>Spurious Emission</i>	<i>23</i>
5.1.6	<i>Frequency Separation.....</i>	<i>55</i>
5.1.7	<i>Number of hopping frequency.....</i>	<i>56</i>
5.1.8	<i>Time of Occupancy</i>	<i>57</i>
5.1.9	<i>Conducted emissions.....</i>	<i>58</i>
5.1.10	<i>Radiated Emission.....</i>	<i>61</i>
6.	SAFETY HUMAN EXPOSURE	70
6.1	RADIO FREQUENCY EXPOSURE COMPLIANCE.....	70
6.1.1	<i>Electromagnetic Fields.....</i>	<i>70</i>
7.	PHOTOGRAPHS OF THE TEST SET-UP	71

Prüfbericht - Nr.: 50096096 001
*Test Report No.***Seite 4 von 74**
Page 4 of 74

8.	LIST OF TABLES	74
9.	LIST OF PHOTOGRAPHS	74

Prüfbericht - Nr.: 50096096 001
*Test Report No.***Seite 5 von 74**
Page 5 of 74

1. General Remarks

1.1 Complementary Materials

None.

2. Test Sites

2.1 Test Facilities

Accurate Technology Co., Ltd.

(FCC Registration No.: 752051)

(Test site Industry Canada No.: 5077A-2)

F1, Bldg. A, Changyuan New Material Port
Keyuan Rd., Science & Industry Park, Nanshan
Shenzhen, P.R. China

The tests at the test site have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Type	S/N	Calibrated until
Transmitter spurious emissions				
Spectrum Analyzer	Rohde & Schwarz	FSV40	101495	2018-01-06
Test Receiver	Rohde & Schwarz	ESCS30	100307	2018-01-06
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	2018-01-09
Loop Antenna	Schwarzbeck	FMZB1516	1516131	2018-01-09
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	2018-01-09
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	2018-01-09
RF Switching Unit+PreAMP	Compliance Direction	RSU-M2	38322	2018-01-06
Pre-Amplifier	Rohde&Schwarz	CBLU11835 40-01	3791	2018-01-06
50 Coaxial Switch	Anritsu Corp	MP59B	620050647 4	2018-01-06
RF Coaxial Cable	SUHNER	N-3m	No.8	2018-01-06
RF Coaxial Cable	RESENBERGER	N-3.5m	No.9	2018-01-06
RF Coaxial Cable	SUHNER	N-6m	No.10	2018-01-06
RF Coaxial Cable	RESENBERGER	N-12m	No.11	2018-01-06
RF Coaxial Cable	RESENBERGER	N-0.5m	No.12	2018-01-06
Radio Spectrum Test				
Spectrum Analyzer	Rohde & Schwarz	FSV40	101495	2018-01-06
Vector Signal Generator	Rohde & Schwarz	SMBV100A	260434	2018-01-06
Signal Generator	Rohde & Schwarz	SMB100A	108362	2018-01-06
Open Switch and Control Unit	Rohde & Schwarz	OSP120 + OSP-B157	101244 + 100866	2018-01-06
Conducted Emission				
Test Receiver	Rohde & Schwarz	ESCS30	100307	2018-01-06
L.I.S.N.	Schwarzbeck	NLSK8126	8126431	2018-01-06
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100815	2018-01-06
50Ω Coaxial Switch	Anritsu Corp	MP59B	6200283933	2018-01-06
Voltage Probe	Schwarzbeck	TK9416	N/A	2018-01-06
RF Current Probe	Rohde & Schwarz	EZ-17	100048	2018-01-06
8-Wire Impedance Stabilisation Network	Schwarzbeck	CAT5 8158	8158-0035	2018-01-06
RF Coaxial Cable	Suhner	N-2m	No.2	2018-01-06
RF Coaxial Cable	Suhner	N-2m	No.3	2018-01-06
RF Coaxial Cable	Suhner	N-2m	No.14	2018-01-06

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

Table 2: Measurement Uncertainty

Parameter	Uncertainty
Radio Spectrum	$< \pm 0.60$ dB
Radiated emission of transmitter, valid up to 26.5 GHz	$< \pm 4.42$ dB
Conducted Emission	$< \pm 2.23$ dB
Radiated Emission	$< \pm 4.42$ dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

Accurate Technology Co., Ltd. test facility located at F1, Bldg. A, Changyuan New Material Port Keyuan Rd., Science & Industry Park, Nanshan, Shenzhen, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3. General Product Information

3.1 Product Function and Intended Use

The EUTs are portable speaker system with Bluetooth function used for audio entertainment in house or similar environment. It operates at 2.4GHz ISM frequency band.

Two models are identical except the model name.
 For details refer to the User Manual and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of Bluetooth (BDR & EDR mode)

Technical Specification	Value
Kind of Equipment	Portable Speaker
Type Designation	BIGBUN, MP255
FCC ID	Z9G-EDF57
IC	10004A-EDF57
HVIN	BIGBUN, MP255
Operating Frequency band	2402 – 2480MHz
Channel separation	1MHz
Extreme Temperature Range	0~+45°C
Operation Voltage	AC 100-240V, 50/60Hz
Modulation	FHSS, GFSK, 8DPSK, $\pi/4$ DQPSK
Bluetooth version	4.1, BDR & EDR
Antenna Gain	2.5dBi

Table 4: RF channel and frequency of Bluetooth (BDR & EDR mode)

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
0	2402.00	21	2423.00	42	2444.00	63	2465.00
1	2403.00	22	2424.00	43	2445.00	64	2466.00
2	2404.00	23	2425.00	44	2446.00	65	2467.00
3	2405.00	24	2426.00	45	2447.00	66	2468.00
4	2406.00	25	2427.00	46	2448.00	67	2469.00
5	2407.00	26	2428.00	47	2449.00	68	2470.00
6	2408.00	27	2429.00	48	2450.00	69	2471.00
7	2409.00	28	2430.00	49	2451.00	70	2472.00
8	2410.00	29	2431.00	50	2452.00	71	2473.00
9	2411.00	30	2432.00	51	2453.00	72	2474.00

10	2412.00	31	2433.00	52	2454.00	73	2475.00
11	2413.00	32	2434.00	53	2455.00	74	2476.00
12	2414.00	33	2435.00	54	2456.00	75	2477.00
13	2415.00	34	2436.00	55	2457.00	76	2478.00
14	2416.00	35	2437.00	56	2458.00	77	2479.00
15	2417.00	36	2438.00	57	2459.00	78	2480.00
16	2418.00	37	2439.00	58	2460.00		
17	2419.00	38	2440.00	59	2461.00		
18	2420.00	39	2441.00	60	2462.00		
19	2421.00	40	2442.00	61	2463.00		
20	2422.00	41	2443.00	62	2464.00		

3.3 Independent Operation Modes

The basic operation modes are:

- A. On
 - 1. Bluetooth mode (BDR & EDR mode)
 - a. Transmitting
 - i. Low Channel
 - ii. Middle Channel
 - iii. High Channel
 - b. Receiving
- B. USB playing
- C. SD card playing
- D. Charging
- E. Standby
- F. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Bill of Material
- PCB Layout
- Photo Document
- Circuit Diagram
- Instruction Manual
- Rating Label

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.4: 2014 & ANSI C63.10: 2013.

4.3 Special Accessories and Auxiliary Equipment

The EUT was tested together with the following accessories:

Description	Manufacturer	Part No.	S/N
Galaxy S6	SAMSUNG	SM-G9209	R28G91298WH
Notebook PC	Lenovo	ThinkPad X240	---
Printer	HP	HP laserjet 1015	CNFG030424

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test




Diagram of Measurement Equipment Configuration for Conduction Measurement





Diagram of Measurement Equipment Configuration for Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Pass**

Test standard	:	Part 15.203 RSS-Gen Clause 8.3
Limit		The use of antennas with directional gains that do not exceed 6dBi

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is 2.5dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

5.1.2 Maximum Peak Conducted Output Power

RESULT:
Pass

Test date : 2017-06-23
 Test standard : FCC Part 15.247(b)(1)
 RSS-247 clause 5.4(b)
 Basic standard : ANSI C63.10: 2013
 Clause 9.1 of KDB 558074 v03r05
 Limit : 125mW
 Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
 Operation Mode : A.1.a
 Ambient temperature : 21°C
 Relative humidity : 60%
 Atmospheric pressure : 101kPa

Table 5: Test result of Peak Output Power of Buletooth (BDR mode)

Channel	Channel Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	e.i.r.p. (dBm)	Limit(dBm)
Low Channel	2402	2.51	21	5.01	36
Middle Channel	2441	2.47	21	4.97	36
High Channel	2480	2.50	21	5.00	36

Table 6: Test result of Peak Output Power of Bluetooth (EDR mode)

Channel	Channel Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	e.i.r.p. (dBm)	Limit(dBm)
Low Channel	2402	0.58	21	3.08	36
Middle Channel	2441	0.19	21	2.69	36
High Channel	2480	0.19	21	2.69	36

5.1.3 20dB Bandwidth and 99% Bandwidth**RESULT:****Pass**

Date of testing : 2017-06-23
Test standard : FCC Part 15.247(a)(1)
RSS-247 clause 5.1(b)
RSS-Gen clause 6.6
Basic standard : ANSI C63.10: 2013
Clause 8 of KDB 558074 v03r05
Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
Operation Mode : A.1.a
Ambient temperature : 21°C
Relative humidity : 60%
Atmospheric pressure : 101kPa

Table 7: Test result of 20dB & 99% Bandwidth of BDR mode

Channel	Channel Frequency (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low Channel	2402	0.921	0.946
Mid Channel	2441	0.929	0.946
High Channel	2480	0.925	0.946

Table 8: Test result of 20dB & 99% Bandwidth of EDR mode

Channel	Channel Frequency (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low Channel	2402	1.211	1.198
Mid Channel	2441	1.207	1.194
High Channel	2480	1.207	1.194

Prüfbericht - Nr.: 50096096 001

Test Report No.

Seite 16 von 74

Page 16 of 74

5.1.4 Conducted Spurious Emissions measured in 100kHz Bandwidth**RESULT:****Pass**

Date of testing	:	2017-06-23
Test standard	:	FCC part 15.247(d) RSS-247 clause 5.5
Basic standard	:	ANSI C63.10: 2013
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power);
Kind of test site	:	Shield room


Test setup

Test Channel	:	Low/ Middle/ High
Operation mode	:	A.1.a
Ambient temperature	:	21°C
Relative humidity	:	60%
Atmospheric pressure	:	101kPa


For details refer to following test plot.


Test Plot of Conducted spurious emissions measured in 100kHz Bandwidth of BDR mode



Low Channel



Middle Channel




High Channel



Band Edge



Test Plot of Conducted spurious emissions measured in 100kHz Bandwidth of EDR mode



Low Channel



Middle Channel



High Channel


Band Edge


Prüfbericht - Nr.: 50096096 001

Test Report No.

Seite 23 von 74

Page 23 of 74

5.1.5 Spurious Emission

RESULT:**Pass**

Date of testing	:	2017-07-02
Test standard	:	FCC part 15.247(d) RSS-Gen
Basic standard	:	ANSI C63.10: 2013 Clause 11 of KDB 558074 v03r05
Limits	:	FCC part 15.209(a)
Kind of test site	:	3m Semi-Anechoic Chamber & Anechoic Chamber

Test setup

Test Channel	:	Low/ Middle/ High
Operation mode	:	A.1.a
Ambient temperature	:	23°C
Relative humidity	:	48%
Atmospheric pressure	:	101kPa

For details refer to following test plot.


ACCURATE TECHNOLOGY CO., LTD.

FCC Class B 3M Radiated

EUT: Multimedia Speaker M/N:BIGBUN
 Manufacturer: EDIFIER
 Operating Condition: TX 2402MHz
 Test Site: 2# Chamber
 Operator: PING
 Test Specification: DC 3.7V
 Comment: X
 Start of Test: 2017-07-02 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD.

FCC Class B 3M Radiated

EUT: Multimedia Speaker M/N:BIGBUN
 Manufacturer: EDIFIER
 Operating Condition: TX 2402MHz
 Test Site: 2# Chamber
 Operator: PING
 Test Specification: DC 3.7V
 Comment: Y
 Start of Test: 2017-07-02 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD.

FCC Class B 3M Radiated

EUT: Multimedia Speaker M/N:BIGBUN
 Manufacturer: EDIFIER
 Operating Condition: TX 2402MHz
 Test Site: 2# Chamber
 Operator: PING
 Test Specification: DC 3.7V
 Comment: Z
 Start of Test: 2017-07-02 /

SCAN TABLE: "LFRE Fin"

Short Description:				_SUB_STD_VTERM2 1.70		
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD.

FCC Class B 3M Radiated

EUT: Multimedia Speaker M/N:BIGBUN
 Manufacturer: EDIFIER
 Operating Condition: TX 2441MHz
 Test Site: 2# Chamber
 Operator: PING
 Test Specification: DC 3.7V
 Comment: X
 Start of Test: 2017-07-02 /

SCAN TABLE: "LFRE Fin"

Short Description:				_SUB STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer	
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M	
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M	




ACCURATE TECHNOLOGY CO., LTD.

FCC Class B 3M Radiated

EUT: Multimedia Speaker M/N:BIGBUN
 Manufacturer: EDIFIER
 Operating Condition: TX 2441MHz
 Test Site: 2# Chamber
 Operator: PING
 Test Specification: DC 3.7V
 Comment: Y
 Start of Test: 2017-07-02 /

SCAN TABLE: "LFRE Fin"

Short Description:			SUB STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD.

FCC Class B 3M Radiated

EUT: Multimedia Speaker M/N:BIGBUN
 Manufacturer: EDIFIER
 Operating Condition: TX 2441MHz
 Test Site: 2# Chamber
 Operator: PING
 Test Specification: DC 3.7V
 Comment: Z
 Start of Test: 2017-07-02 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD.

FCC Class B 3M Radiated

EUT: Multimedia Speaker M/N:BIGBUN
 Manufacturer: EDIFIER
 Operating Condition: TX 2480MHz
 Test Site: 2# Chamber
 Operator: PING
 Test Specification: DC 3.7V
 Comment: X
 Start of Test: 2017-07-02 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD.
FCC Class B 3M Radiated

EUT: Multimedia Speaker M/N:BIGBUN
 Manufacturer: EDIFIER
 Operating Condition: TX 2480MHz
 Test Site: 2# Chamber
 Operator: PING
 Test Specification: DC 3.7V
 Comment: Y
 Start of Test: 2017-07-02 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD.

FCC Class B 3M Radiated

EUT: Multimedia Speaker M/N:BIGBUN
 Manufacturer: EDIFIER
 Operating Condition: TX 2480MHz
 Test Site: 2# Chamber
 Operator: PING
 Test Specification: DC 3.7V
 Comment: Z
 Start of Test: 2017-07-02 /

SCAN TABLE: "LFRE Fin"

Short Description:			SUB STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4060

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2402MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.3750	29.03	-10.49	18.54	40.00	-21.46	QP			
2	97.4560	28.62	-13.91	14.71	43.50	-28.79	QP			
3	483.9094	28.86	-4.81	24.05	46.00	-21.95	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4061

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2402MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	43.2017	28.93	-12.23	16.70	40.00	-23.30	QP			
2	100.9339	27.33	-13.21	14.12	43.50	-29.38	QP			
3	429.5228	28.93	-5.64	23.29	46.00	-22.71	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4063

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2441MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	46.6664	28.04	-12.60	15.44	40.00	-24.56	QP			
2	111.3468	28.95	-13.62	15.33	43.50	-28.17	QP			
3	620.7096	29.69	-2.09	27.60	46.00	-18.40	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4062

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2441MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	49.7068	28.22	-12.59	15.63	40.00	-24.37	QP			
2	98.4865	27.89	-13.56	14.33	43.50	-29.17	QP			
3	446.4141	29.21	-5.41	23.80	46.00	-22.20	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4064

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2480MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	44.9004	29.38	-12.60	16.78	40.00	-23.22	QP			
2	121.1230	29.08	-13.19	15.89	43.50	-27.61	QP			
3	473.8346	30.14	-4.97	25.17	46.00	-20.83	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4065

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2480MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	43.2017	28.16	-12.23	15.93	40.00	-24.07	QP			
2	106.3850	28.92	-13.86	15.06	43.50	-28.44	QP			
3	271.3245	31.19	-9.88	21.31	46.00	-24.69	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4071

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2402MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	54.62	36.78	91.40	/	/	peak			
2	4804.026	6.71	41.81	48.52	74.00	-25.48	peak			
3	4804.026	-4.65	41.88	37.23	54.00	-16.77	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4070

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2402MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	55.15	36.78	91.93	/	/	peak			
2	4804.026	7.13	41.88	49.01	74.00	-24.99	peak			
3	4804.026	-2.25	41.88	39.63	54.00	-14.37	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4072

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2441MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.000	53.82	36.96	90.78	/	/	peak			
2	4882.025	-3.56	42.20	38.64	54.00	-15.36	AVG			
3	4882.025	7.15	42.29	49.44	74.00	-24.56	peak			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4073

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2441MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.000	54.77	36.96	91.73	/	/	peak			
2	4882.028	7.85	42.20	50.05	74.00	-23.95	peak			
3	4882.028	-3.54	42.20	38.66	54.00	-15.34	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4075

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2480MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	54.53	37.10	91.63	/	/	peak			
2	4960.030	7.56	42.54	50.10	74.00	-23.90	peak			
3	4960.030	-3.26	42.54	39.28	54.00	-14.72	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4074

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2480MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	54.38	37.10	91.48	/	/	peak			
2	4960.028	7.37	42.54	49.91	74.00	-24.09	peak			
3	4960.028	-3.65	42.54	38.89	54.00	-15.11	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4114

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2402MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26062.917	9.71	40.28	49.99	74.00	-24.01	peak			
2	26062.917	-2.03	40.28	38.25	54.00	-15.75	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4115

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2402MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26316.150	9.32	40.93	50.25	74.00	-23.75	peak			
2	26316.150	-1.26	40.93	39.67	54.00	-14.33	AVG			

Prüfbericht - Nr.: 50096096 001
Test Report No.
Seite 47 von 74
Page 47 of 74

ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4117

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2441MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26153.799	10.36	40.32	50.68	74.00	-23.32	peak			
2	26153.799	-0.50	40.32	39.82	54.00	-14.18	AVG			

Prüfbericht - Nr.: 50096096 001
Test Report No.
Seite 48 von 74
Page 48 of 74

ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4116

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2441MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26062.917	8.68	40.97	49.65	74.00	-24.35	peak			
2	26062.917	-2.15	40.97	38.82	54.00	-15.18	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4118

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2480MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26143.685	10.26	40.32	50.58	74.00	-23.42	peak			
2	26143.685	1.30	40.32	41.62	54.00	-12.38	AVG			

Prüfbericht - Nr.: 50096096 001
Test Report No.
Seite 50 von 74
Page 50 of 74

ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4119

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2480MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25832.095	8.77	41.00	49.77	74.00	-24.23	peak			
2	25832.095	-2.02	41.00	38.98	54.00	-15.02	AVG			

Prüfbericht - Nr.: 50096096 001
Test Report No.
Seite 51 von 74
Page 51 of 74

ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4121

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2402MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2338.480	-0.73	36.52	35.79	54.00	-18.21	peak			
2	2338.480	-10.52	36.52	26.00	54.00	-28.00	AVG			

Prüfbericht - Nr.: 50096096 001
Test Report No.
Seite 52 von 74
Page 52 of 74

ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4120

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2402MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2344.240	0.56	36.54	37.10	54.00	-16.90	peak			
2	2344.240	-10.23	36.54	26.31	54.00	-27.69	AVG			

Prüfbericht - Nr.: 50096096 001
Test Report No.
Seite 53 von 74
Page 53 of 74

ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4122

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2480MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2490.859	-0.56	37.17	36.61	54.00	-17.39	peak			
2	2490.859	-10.26	37.17	26.91	54.00	-27.09	AVG			

Prüfbericht - Nr.: 50096096 001
Test Report No.
Seite 54 von 74
Page 54 of 74

ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4123

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: TX 2480MHz

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2493.648	-0.75	37.17	36.42	54.00	-17.58	peak			
2	2493.648	-10.34	37.17	26.83	54.00	-27.17	AVG			

5.1.6 Frequency Separation

RESULT:

Pass

Date of testing	:	2017-06-23
Test standard	:	FCC part 15.247(a)(1) RSS-247 clause 5.1(b)
Basic standard	:	ANSI C63.10: 2013
Limit	:	≥ 25kHz or two-thirds of 20dB bandwidth, whichever is greater
Kind of test site	:	Shield room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A.1.a
Ambient temperature	:	21°C
Relative humidity	:	60%
Atmospheric pressure	:	101kPa

Table 9: Test result of Frequency Separation

Channel	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)	Result
Low Channel	2402	1.0029	≥ 25kHz or two-thirds of 20dB bandwidth	Pass
Adjacency Channel	2403			
Mid Channel	2441	1.0029	≥ 25kHz or two-thirds of 20dB bandwidth	Pass
Adjacency Channel	2442			
High Channel	2479	1.0029	≥ 25kHz or two-thirds of 20dB bandwidth	Pass
Adjacency Channel	2480			

Prüfbericht - Nr.: 50096096 001

Test Report No.

Seite 56 von 74

Page 56 of 74

5.1.7 Number of hopping frequency**RESULT:****Pass**

Date of testing : 2017-06-23
Test standard : FCC part 15.247(a)(1)(iii)
RSS-247 clause 5.1(d)
Basic standard : ANSI C63.10: 2013
Limits : ≥ 15 non-overlapping channels
Kind of test site : Shield room

Test setup

Test Channel : Low/ Middle/ High
Operation Mode : A.1.a
Ambient temperature : 21°C
Relative humidity : 60%
Atmospheric pressure : 101kPa

Table 10: Test result of Number of hopping frequency

Frequency Range	Measured Quantity of Hopping Channel	Limit	Result
2402 to 2480MHz	79	≥ 15	Pass

5.1.8 Time of Occupancy

RESULT:

Pass

Date of testing	:	2017-06-23
Test standard	:	FCC part 15.247(a)(1)(iii) RSS-247 clause 5.1(d)
Basic standard	:	ANSI C63.10: 2013
Limits	:	0.4s
Kind of test site	:	Shield room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A.1.a
Ambient temperature	:	21°C
Relative humidity	:	60%
Atmospheric pressure	:	101kPa

Table 11: Test result of Time of Occupancy

Mode	Packet Type	Channel Frequency (MHz)	Packet Duration [ms]	Number of Hops per Channel	Dwell Time (ms)	Limit [ms]
BDR	DH1	2402	0.449	322	144.578	400
		2441	0.449	322	144.578	400
		2480	0.449	322	144.578	400
	DH3	2402	1.746	165	288.090	400
		2441	1.746	165	288.090	400
		2480	1.746	165	288.090	400
	DH5	2402	2.986	112	334.432	400
		2441	2.986	112	334.432	400
		2480	2.986	112	334.432	400
EDR	DH1	2402	0.449	322	144.578	400
		2441	0.449	322	144.578	400
		2480	0.449	322	144.578	400
	DH3	2402	1.739	165	286.935	400
		2441	1.739	165	286.935	400
		2480	1.739	165	286.935	400
	DH5	2402	2.986	112	334.432	400
		2441	2.986	112	334.432	400
		2480	2.986	112	334.432	400

Prüfbericht - Nr.: 50096096 001

Test Report No.

Seite 58 von 74

Page 58 of 74

5.1.9 Conducted emissions**RESULT:****Pass**

Date of testing	:	2017-07-01
Test standard	:	FCC Part 15.107 (a) FCC Part 15.207 RSS-Gen Clause 8.8 ICES-003 Issue 6 January 2016
Basic standard	:	ANSI C63.4: 2014
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.207 Table 3 of RSS-Gen
Kind of test site	:	Shield room

Test setup

Input Voltage	:	AC 120V, 60Hz
Operation Mode	:	D
Earthing	:	Not Connected
Ambient temperature	:	21°C
Relative humidity	:	60%
Atmospheric pressure	:	101kPa


For details refer to following test plot.

ACCURATE TECHNOLOGY CO., LTD
CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Multimedia Speaker M/N:BIGBUN
 Manufacturer: Edifier
 Operating Condition: Charging
 Test Site: 1#Shielding Room
 Operator: PING
 Test Specification: L 120V/60Hz
 Comment:
 Start of Test: 7/01/2017 /

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 Average
 150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average


MEASUREMENT RESULT: "T-0701-21_fin"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.280000	47.00	10.6	61	13.8	QP	L1	GND
0.935000	38.50	10.8	56	17.5	QP	L1	GND
9.180000	29.00	11.3	60	31.0	QP	L1	GND

MEASUREMENT RESULT: "T-0701-21_fin2"


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.275000	43.00	10.6	51	8.0	AV	L1	GND
0.955000	31.30	10.8	46	14.7	AV	L1	GND
7.800000	24.60	11.2	50	25.4	AV	L1	GND

ACCURATE TECHNOLOGY CO.,LTD
CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Multimedia Speaker M/N:BIGBUN
 Manufacturer: Edifier
 Operating Condition: Charging
 Test Site: 1#Shielding Room
 Operator: PING
 Test Specification: N 120V/60Hz
 Comment:
 Start of Test: 7/01/2017 /

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 Average
 150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average


MEASUREMENT RESULT: "T-0701-20_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.270000	47.20	10.6	61	13.9	QP	N	GND
0.965000	39.80	10.8	56	16.2	QP	N	GND
6.660000	33.10	11.2	60	26.9	QP	N	GND

MEASUREMENT RESULT: "T-0701-20_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.275000	42.70	10.6	51	8.3	AV	N	GND
0.955000	34.20	10.8	46	11.8	AV	N	GND
7.930000	26.70	11.2	50	23.3	AV	N	GND

Prüfbericht - Nr.: 50096096 001

Test Report No.

Seite 61 von 74

Page 61 of 74

5.1.10 Radiated Emission**RESULT:****Pass**

Date of testing : 2017-07-02
Test standard : FCC Part 15.109 (a)
ICES-003 Issue 6 January 2016
Test procedure : ANSI C63.4: 2014
Frequency range : 30 - 6000MHz
Equipment Classification : Class B
Limits : FCC Part 15.109(a)
ICES-003 Issue 6 January 2016
Kind of test site : 3m Semi-Anechoic Chamber

Test setup

Input Voltage : AC 120V, 60Hz
Operation mode : B, C, D
Earthing : Not connected
Ambient temperature : 23°C
Relative humidity : 48%
Atmospheric pressure : 101kPa

For details refer to following test plot.


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4197

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: Charging+USB playing

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Horizontal

Power Source: DC 5V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	99.8777	41.00	-13.09	27.91	43.50	-15.59	QP			
2	167.8242	44.43	-13.88	30.55	43.50	-12.95	QP			
3	340.7817	40.65	-7.73	32.92	46.00	-13.08	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4196
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Multimedia Speaker
Mode: Charging+USB playing
Model: BIGBUN
Manufacturer: EDIFIER

Polarization: Vertical
Power Source: DC 5V
Date: 17/07/02/
Time:
Engineer Signature: PING
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	97.7982	37.15	-13.80	23.35	43.50	-20.15	QP			
2	330.1949	38.56	-8.03	30.53	46.00	-15.47	QP			
3	392.0951	37.03	-6.77	30.26	46.00	-15.74	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: PING #4326
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Multimedia Speaker
Mode: Charging+USB playing
Model: BIGBUN
Manufacturer: EDIFIER

Polarization: Horizontal
Power Source: DC 5V
Date: 17/07/02/
Time:
Engineer Signature: PING
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	5525.306	37.27	7.48	44.75	74.00	-29.25	peak			
2	5525.306	29.09	7.48	36.57	54.00	-17.43	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4327

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: Charging+USB playing

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 5V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1269.095	52.13	-8.69	43.44	74.00	-30.56	peak			
2	1269.095	43.92	-8.69	35.23	54.00	-18.77	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4198
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Multimedia Speaker
Mode: MicroSD playing
Model: BIGBUN
Manufacturer: EDIFIER

Polarization: Horizontal
Power Source: DC 3.7V
Date: 17/07/02/
Time:
Engineer Signature: PING
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	51.3004	31.48	-12.68	18.80	40.00	-21.20	QP			
2	96.4361	31.88	-14.25	17.63	43.50	-25.87	QP			
3	428.0192	32.67	-5.68	26.99	46.00	-19.01	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4199

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: MicroSD playing

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	39.9941	30.55	-11.53	19.02	40.00	-20.98	QP			
2	101.2883	29.86	-13.26	16.60	43.50	-26.90	QP			
3	588.9050	31.92	-2.47	29.45	46.00	-16.55	QP			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4329
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Multimedia Speaker
Mode: MicroSD playing
Model: BIGBUN
Manufacturer: EDIFIER

Polarization: Horizontal
Power Source: DC 3.7V
Date: 17/07/02/
Time:
Engineer Signature: PING
Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	5696.195	37.58	7.51	45.09	74.00	-28.91	peak			
2	5696.195	28.73	7.51	36.24	54.00	-17.76	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: PING #4328

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Multimedia Speaker

Mode: MicroSD playing

Model: BIGBUN

Manufacturer: EDIFIER

Polarization: Vertical

Power Source: DC 3.7V


Date: 17/07/02/

Time:

Engineer Signature: PING

Distance: 3m

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	5525.306	36.94	7.48	44.42	74.00	-29.58	peak			
2	5525.306	28.76	7.48	36.24	54.00	-17.76	AVG			

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:**Pass**

Test standard : RSS-102 Issue 5 March 2015
FCC KDB Publication 447498 D01 v06

The maximum radiated power of the transmitter is 1.782mW (2.51dBm) only, which less than 4mW. Hence the EUT is exempted from routine evaluation limits (SAR Evaluation) according to clause 2.5.1 of RSS-102 Issue 5.

Since maximum radiated power of the transmitter is 1.782mW<10mW, and the distance from EUT to human is ≥ 5 mm, hence the EUT is excluded from SAR evaluation according to FCC KDB publication 447498 D01 General RF Exposure Guidance v06.

8. List of Tables

Table 1: List of Test and Measurement Equipment	6
Table 2: Measurement Uncertainty	7
Table 3: Technical Specification of Bluetooth (BDR & EDR mode)	8
Table 4: RF channel and frequency of Bluetooth (BDR & EDR mode)	8
Table 5: Test result of Peak Output Power of Bluetooth (BDR mode)	14
Table 6: Test result of Peak Output Power of Bluetooth (EDR mode)	14
Table 7: Test result of 20dB & 99% Bandwidth of BDR mode	15
Table 8: Test result of 20dB & 99% Bandwidth of EDR mode	15
Table 9: Test result of Frequency Separation	55
Table 10: Test result of Number of hopping frequency	56
Table 11: Test result of Time of Occupancy	57

9. List of Photographs

Photograph 1: Set-up for Spurious Emissions for below 30MHz	71
Photograph 2: Set-up for Spurious Emissions for 30 - 1000MHz	71
Photograph 3: Set-up for Spurious Emissions for 1 - 18GHz	72
Photograph 4: Set-up for Spurious Emissions for 18 - 26.5GHz	72
Photograph 5: Set-up for Conducted Emissions	73
Photograph 6: Set-up for Radiated Emissions	73