

MEASUREMENT REPORT

FCC PART 15C / WLAN 802.11b/g/n

FCC ID: HD5-CT40PL0N

Applicant: Honeywell International Inc
Honeywell Safety and Productivity Solutions

Application Type: Certification

Product: Mobile Computer

Model No.: CT40P-L0N

Brand Name: Honeywell


FCC Classification: Digital Transmission System (DTS)

FCC Rule Part(s): Part 15 Subpart C (Section 15.247)

Test Procedure(s): ANSI C63.10-2013


Test Date: July 02 ~ 27, 2020

Reviewed By:



(Jame Yuan)

Approved By:



(Robin Wu)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2006RSU069-U1	Rev. 01	Initial Report	07-27-2020	Valid

CONTENTS

Description	Page
General Information.....	5
1. INTRODUCTION.....	6
1.1. Scope.....	6
1.2. MRT Test Location.....	6
2. PRODUCT INFORMATION.....	7
2.1. Equipment Description.....	7
2.2. Product Specification Subjective to this Report.....	8
2.3. Working Frequencies for this report.....	9
2.4. Description of Available Antennas.....	9
2.5. Test Mode.....	9
2.6. Description of Test Software.....	9
2.7. Duty Cycle.....	10
2.8. EMI Suppression Device(s)/Modifications.....	11
2.9. Labeling Requirements.....	11
2.10. Test Environment Condition.....	11
3. DESCRIPTION of TEST.....	12
3.1. Evaluation Procedure.....	12
3.2. AC Line Conducted Emissions.....	12
3.3. Radiated Emissions.....	13
4. ANTENNA REQUIREMENTS.....	14
5. TEST EQUIPMENT CALIBRATION DATE.....	15
6. MEASUREMENT UNCERTAINTY.....	17
7. TEST RESULT.....	18
7.1. Summary.....	18
7.2. 6dB Bandwidth Measurement.....	19
7.2.1. Test Limit.....	19
7.2.2. Test Procedure used.....	19
7.2.3. Test Setting.....	19
7.2.4. Test Setup.....	19
7.2.5. Test Result.....	20
7.3. Output Power Measurement.....	25
7.3.1. Test Limit.....	25
7.3.2. Test Procedure Used.....	25

7.3.3.	Test Setting.....	25
7.3.4.	Test Setup	25
7.3.5.	Test Result.....	26
7.4.	Power Spectral Density Measurement.....	29
7.4.1.	Test Limit	29
7.4.2.	Test Procedure Used	29
7.4.3.	Test Setting.....	29
7.4.4.	Test Setup	29
7.4.5.	Test Result.....	30
7.5.	Conducted Band Edge and Out-of-Band Emissions	40
7.5.1.	Test Limit	40
7.5.2.	Test Procedure Used	40
7.5.3.	Test Setting.....	40
7.5.4.	Test Setup	41
7.5.5.	Test Result.....	42
7.6.	Radiated Spurious Emission Measurement	55
7.6.1.	Test Limit	55
7.6.2.	Test Procedure Used	55
7.6.3.	Test Setting.....	55
7.6.4.	Test Setup	57
7.6.5.	Test Result.....	58
7.7.	Radiated Restricted Band Edge Measurement.....	78
7.7.1.	Test Limit	78
7.7.2.	Test Procedure Used	79
7.7.3.	Test Setting.....	79
7.7.4.	Test Setup	80
7.7.5.	Test Result.....	81
7.8.	AC Conducted Emissions Measurement	128
7.8.1.	Test Limit	128
7.8.2.	Test Setup	128
7.8.3.	Test Result.....	129
8.	CONCLUSION	131
	Appendix A - Test Setup Photograph	132
	Appendix B - EUT Photograph.....	133

General Information

Applicant:	Honeywell International Inc Honeywell Safety and Productivity Solutions
Applicant Address:	9680 Old Bailes Road, Fort Mill, SC 29707 United States
Manufacturer:	Honeywell International Inc Honeywell Safety and Productivity Solutions
Manufacturer Address:	9680 Old Bailes Road, Fort Mill, SC 29707 United States
Test Site:	MRT Technology (Suzhou) Co., Ltd
Test Site Address:	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is an FCC registered (MRT Designation No. CN1166) test facility with the site description report on file and has met all the requirements specified in ANSI C63.4-2014.
- MRT facility is an IC registered (MRT Reg. No.11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-20025, G-20034, C-20020, T-20020) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LACert. No.3628.01) in EMC, Telecommunications, Radio and SAR testing.



1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada and Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The measurement facility compliant with the test site requirements specified in ANSI C63.4-2014.



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	Mobile Computer
Model No.	CT40P-L0N
Serial No.	19252B5D57 (Conducted Sample) 20010B217B (Radiated Sample)
Hardware Version	V2.0
Software Version	OS.03.001
Qualcomm Chipset	
Wi-Fi Specification	802.11a/b/g/n/ac
Bluetooth Version	v5.0 dual mode
Antenna Delivery	2*TX + 2*RX
Nordic Chipset	
Bluetooth Version	v5.1 single mode, LE only
NXP Chipset	
NFC Working Frequency	13.56MHz
Accessories	
USB Adapter	Model No.: ADS-12B-06 05010E Input Power: 100 - 240V ~ 50/60Hz, Max. 0.3A Output Power: 5VDC 2.0A
Rechargeable Li-ion Battery	Model No.: CT50-BTSC Capacitance: 4020mAh/15.5Wh Rated Voltage: 3.85V

2.2. Product Specification Subjective to this Report

Frequency Range	802.11b/g/n-HT20: 2412 ~ 2462 MHz 802.11n-HT40: 2422 ~ 2452 MHz
Channel Number	802.11b/g/n-HT20: 11 802.11b/g/n-HT20: 7
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM
Data Rate	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 300Mbps
Maximum Output Power	802.11b: 17.89dBm 802.11g: 14.87dBm 802.11n: 17.22dBm

Note: For other features of this EUT, test report will be issued separately.

2.3. Working Frequencies for this report

802.11b/g/n-HT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

2.4. Description of Available Antennas

Antenna Type	Frequency Band (GHz)	Antenna Gain (dBi)		Directional Gain (dBi)	
		Ant 0	Ant 1	For Power	For PSD
FPC Antenna	2.4~2.5	0.60	2.20	2.20	5.21
	5.1~5.725	1.30	1.80	1.80	4.81
	5.725~5.85	3.35	2.48	3.35	6.36

Note 1: SISO mode is only for Ant 0 port.

Note 2: The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.

2.5. Test Mode

Test Mode	Mode 1: Transmit by 802.11b (1Mbps)
	Mode 2: Transmit by 802.11g (6Mbps)
	Mode 3: Transmit by 802.11n-HT20 (MCS0)
	Mode 4: Transmit by 802.11n-HT40 (MCS0)

2.6. Description of Test Software


The test utility software used during testing was "QRCT", and the version was 3.0.268.0.

Power parameter value refers to operation description.

2.7. Duty Cycle

2.4GHz WLAN (DTS) operation is possible in 20MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Test Mode	Duty Cycle
802.11b	98.78%
802.11g	95.06%
802.11n-HT20	95.19%
802.11n-HT40	91.46%



2.8. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.9. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

2.10. Test Environment Condition

Ambient Temperature	15°C~35°C
Relative Humidity	20%RH ~75%RH

3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedure described in the document titled “American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices” (ANSI C63.10-2013) was used in the measurement.

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50 Ω /50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment which determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, which produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions - SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTSUE06185	1 year	2021/01/18
Two-Line V-Network	R&S	ENV 216	MRTSUE06002	1 year	2021/06/11
Two-Line V-Network	R&S	ENV 216	MRTSUE06003	1 year	2021/06/11
Thermohygrometer	Testo	608-H1	MRTSUE06404	1 year	2020/08/08
Shielding Room	MIX-BEP	Chamber-SR2	MRTSUE06215	N/A	N/A

Radiated Emissions - AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2020/08/01
PXA Signal Analyzer	Keysight	9030B	MRTSUE06395	1 year	2020/09/03
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2020/11/13
Bilog Period Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2021/04/03
Broad Band Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06023	1 year	2020/10/13
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06024	1 year	2020/12/29
Microwave System Amplifier	Agilent	83017A	MRTSUE06076	1 year	2020/11/15
Preamplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2021/06/11
Thermohygrometer	Testo	608-H1	MRTSUE06403	1 year	2020/08/08
Anechoic Chamber	TDK	Chamber-AC1	MRTSUE06212	1 year	2021/04/30

Radiated Emission - AC2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Keysight	N9038A	MRTSUE06125	1 year	2020/08/01
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2020/11/13
Bilog Period Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2020/10/13
Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06171	1 year	2020/10/27
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06024	1 year	2020/12/29
Broadband Coaxial Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2020/11/15
Preamplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2021/06/11
Temperature/Humidity Meter	Minggao	ETH529	MRTSUE06170	1 year	2020/12/15
Anechoic Chamber	RIKEN	Chamber-AC2	MRTSUE06213	1 year	2021/04/30

Conducted Test Equipment - TR3

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2021/04/14
EXA Signal Analyzer	Keysight	N9010B	MRTSUE06452	1 year	2020/07/11
Signal Analyzer	R&S	FSV40	MRTSUE06218	1 year	2021/04/14
Power Meter	Agilent	U2021XA	MRTSUE06030	1 year	2020/11/17
USB wideband power sensor	Keysight	U2021XA	MRTSUE06446	1 year	2021/06/11
USB wideband power sensor	Keysight	U2021XA	MRTSUE06447	1 year	2021/06/11
Bluetooth Test Set	Anritsu	MT8852B-042	MRTSUE06389	1 year	2021/06/11
Audio Analyzer	Agilent	U8903B	MRTSUE06143	1 year	2021/06/11
Modulation Analyzer	HP	8901A	MRTSUE06098	1 year	2020/10/10
Wideband Radio Communication Tester	R&S	CMW 500	MRTSUE06243	1 year	2020/11/07
DC Power Supply	GWINSTEK	DPS-3303C	MRTSUE06064	N/A	N/A
Attenuator	MVE	6dB	MRTSUE06534	1 year	2020/12/12
Attenuator	MVE	10dB	MRTSUE06543	1 year	2020/12/12
Temperature & Humidity Chamber	BAOYT	BYH-150CL	MRTSUE06051	1 year	2020/11/07
Thermohygrometer	testo	608-H1	MRTSUE06401	1 year	2020/08/08

Software	Version	Function
EMI Software	V3	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measurement Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz~150kHz: 3.74dB 150kHz~30MHz: 3.44dB
Radiated Disturbance
Measurement Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): Horizontal: 30MHz~300MHz: 5.04dB 300MHz~1GHz: 4.95dB 1GHz~40GHz: 6.40dB Vertical: 30MHz~300MHz: 5.24dB 300MHz~1GHz: 6.03dB 1GHz~40GHz: 6.40dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 0.78dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 1.13dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 1.15dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 0.28%

7. TEST RESULT

7.1. Summary

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	6dB Bandwidth	$\geq 500\text{kHz}$	Conducted	Pass	Section 7.2
15.247(b)(3)	Output Power	$\leq 1\text{Watt}$		Pass	Section 7.3
15.247(e)	Power Spectral Density	$\leq 8\text{dBm} / 3\text{kHz}$		Pass	Section 7.4
15.247(d)	Band Edge / Out-of-Band Emissions	$\geq 20\text{dBc (Peak)}$		Pass	Section 7.5
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	Pass	Section 7.6 & 7.7
15.207	AC Conducted Emissions 150kHz - 30MHz	$< \text{FCC 15.207 limits}$	Line Conducted	Pass	Section 7.8

Notes:

- 1) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 2) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.

7.2. 6dB Bandwidth Measurement

7.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


7.2.2. Test Procedure used

ANSI C63.10-2013 - Section 11.8

7.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace was allowed to stabilize

7.2.4. Test Setup



7.2.5. Test Result

Product	Mobile Computer	Test Engineer	Gordon Qi
Test Site	TR3	Test Date	2020/07/02
Test Mode	SISO Mode - ANT 0		


Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
802.11b	1Mbps	01	2412	7.59	≥ 0.5	Pass
802.11b	1Mbps	06	2437	8.07	≥ 0.5	Pass
802.11b	1Mbps	11	2462	8.05	≥ 0.5	Pass
802.11g	6Mbps	01	2412	16.35	≥ 0.5	Pass
802.11g	6Mbps	06	2437	16.38	≥ 0.5	Pass
802.11g	6Mbps	11	2462	16.41	≥ 0.5	Pass
802.11n-HT20	MCS0	01	2412	17.58	≥ 0.5	Pass
802.11n-HT20	MCS0	06	2437	17.59	≥ 0.5	Pass
802.11n-HT20	MCS0	11	2462	17.61	≥ 0.5	Pass
802.11n-HT40	MCS0	03	2422	36.34	≥ 0.5	Pass
802.11n-HT40	MCS0	06	2437	36.08	≥ 0.5	Pass
802.11n-HT40	MCS0	09	2452	35.91	≥ 0.5	Pass

802.11b 6dB Bandwidth


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g 6dB Bandwidth


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT20 6dB Bandwidth


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 6dB Bandwidth


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



7.3. Output Power Measurement

7.3.1. Test Limit

The maximum conducted output power shall not exceed 1 Watt (30dBm).

7.3.2. Test Procedure Used


ANSI C63.10-2013 - Section 11.9.2.3.2

7.3.3. Test Setting

Method AVGPM-G (Measurement using a gated RF average-reading power meter)

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

7.3.4. Test Setup



7.3.5.Test Result

Power output test was verified over all data rates of each mode shown as below, and then choose the maximum power output (gray marker) for final test of each channel.

Test Mode	Bandwidth (MHz)	Channel No.	Frequency (MHz)	Data Rate / MCS	Average Power (dBm)
802.11b	20	6	2437	1Mbps	17.73
				5.5Mbps	17.68
				11Mbps	17.62
802.11g	20	6	2437	6Mbps	14.67
				24Mbps	14.58
				54Mbps	14.51
802.11n	20	6	2437	MCS0	17.22
				MCS3	17.14
				MCS7	17.02
802.11n	40	6	2437	MCS0	16.61
				MCS3	16.52
				MCS7	16.44

Product	Mobile Computer	Test Engineer	Gordon Qi
Test Site	TR3	Test Date	2020/07/02
Test Mode	SISO Mode - ANT 0		

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	Average Power (dBm)	Limit (dBm)	Result
11b	1Mbps	01	2412	17.77	≤ 30.00	Pass
11b	1Mbps	06	2437	17.73	≤ 30.00	Pass
11b	1Mbps	11	2462	17.89	≤ 30.00	Pass
11g	6Mbps	01	2412	14.72	≤ 30.00	Pass
11g	6Mbps	06	2437	14.67	≤ 30.00	Pass
11g	6Mbps	11	2462	14.87	≤ 30.00	Pass
11n-HT20	MCS0	01	2412	14.92	≤ 30.00	Pass
11n-HT20	MCS0	06	2437	17.22	≤ 30.00	Pass
11n-HT20	MCS0	11	2462	16.78	≤ 30.00	Pass
11n-HT40	MCS0	03	2422	15.02	≤ 30.00	Pass
11n-HT40	MCS0	06	2437	16.61	≤ 30.00	Pass
11n-HT40	MCS0	09	2452	13.97	≤ 30.00	Pass

Product	Mobile Computer	Test Engineer	Gordon Qi
Test Site	TR3	Test Date	2020/07/02
Test Mode	MIMO Mode		

Test Result of Average Output Power

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	ANT 0 Average Power (dBm)	ANT 1 Average Power (dBm)	Total Average Power (dBm)	Limit (dBm)	Result
11n-HT20	MCS0	01	2412	13.71	14.83	17.32	≤ 30.00	Pass
11n-HT20	MCS0	06	2437	13.76	14.67	17.25	≤ 30.00	Pass
11n-HT20	MCS0	11	2462	13.83	14.64	17.26	≤ 30.00	Pass
11n-HT40	MCS0	03	2422	13.77	14.65	17.24	≤ 30.00	Pass
11n-HT40	MCS0	06	2437	13.87	14.81	17.38	≤ 30.00	Pass
11n-HT40	MCS0	09	2452	13.82	14.44	17.15	≤ 30.00	Pass

Note: Total Average Power (dBm) = $10 \cdot \log\{10^{(\text{ANT 0 Average Power} / 10)} + 10^{(\text{ANT 1 Average Power} / 10)}\}$ (dBm).

7.4. Power Spectral Density Measurement

7.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.


7.4.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.10.3 & 11.10.5

7.4.3. Test Setting

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the OBW
3. RBW = 3kHz
4. VBW = 10kHz
5. Detector = RMS
6. Employ trace averaging (rms) mode over a minimum of 100 traces.
7. Sweep time = auto couple
8. Trace mode = max hold
9. Trace was allowed to stabilize

7.4.4. Test Setup



7.4.5. Test Result

Product	Mobile Computer	Test Engineer	Gordon Qi
Test Site	TR3	Test Date	2020/07/02~2020/07/27
Test Mode	SISO Mode - ANT 0		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	AVG PSD (dBm/10kHz)	Duty Cycle (%)	AVG PSD (dBm/10kHz)	Limit (dBm / 3kHz)	Result
11b	1Mbps	01	2412	-8.67	98.78	-8.67	≤ 8.00	Pass
11b	1Mbps	06	2437	-8.21	98.78	-8.21	≤ 8.00	Pass
11b	1Mbps	11	2462	-8.58	98.78	-8.58	≤ 8.00	Pass
11g	6Mbps	01	2412	-14.31	95.06	-14.09	≤ 8.00	Pass
11g	6Mbps	06	2437	-14.36	95.06	-14.14	≤ 8.00	Pass
11g	6Mbps	11	2462	-13.85	95.06	-13.63	≤ 8.00	Pass
11n-HT20	MCS0	01	2412	-14.10	95.19	-13.88	≤ 8.00	Pass
11n-HT20	MCS0	06	2437	-11.96	95.19	-11.75	≤ 8.00	Pass
11n-HT20	MCS0	11	2462	-12.35	95.19	-12.14	≤ 8.00	Pass
11n-HT40	MCS0	03	2422	-16.75	91.46	-16.36	≤ 8.00	Pass
11n-HT40	MCS0	06	2437	-15.20	91.46	-14.81	≤ 8.00	Pass
11n-HT40	MCS0	09	2452	-16.68	91.46	-16.29	≤ 8.00	Pass

Note:

When EUT duty cycle > 98%, Final AVG PSD (dBm / 10kHz) = AVG PSD (dBm / 10kHz).

When EUT duty cycle < 98%, Final AVG PSD (dBm / 10kHz) = AVG PSD (dBm / 10kHz) + 10*log(1/Duty cycle).

Product	Mobile Computer	Test Engineer	Gordon Qi
Test Site	TR3	Test Date	2020/07/02
Test Mode	MIMO Mode		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	AVG PSD (dBm / 10kHz)		Duty Cycle (%)	Total AVG PSD (dBm / 10kHz)	Limit (dBm / 3kHz)	Result
				ANT 0	ANT 1				
11n-HT20	MCS0	01	2412	-15.67	-21.88	95.19	-14.51	≤ 8.00	Pass
11n-HT20	MCS0	06	2437	-15.77	-22.20	95.19	-14.66	≤ 8.00	Pass
11n-HT20	MCS0	11	2462	-15.12	-22.19	95.19	-14.11	≤ 8.00	Pass
11n-HT40	MCS0	03	2422	-18.91	-19.24	91.46	-15.63	≤ 8.00	Pass
11n-HT40	MCS0	06	2437	-17.30	-24.78	91.46	-16.15	≤ 8.00	Pass
11n-HT40	MCS0	09	2452	-17.42	-17.68	91.46	-14.10	≤ 8.00	Pass


Note:

When EUT duty cycle > 98%, Final AVG PSD (dBm / 10kHz) = $10 \cdot \log\{10^{(Ant\ 0\ AVG\ PSD/10)} + 10^{(Ant\ 1\ AVG\ PSD/10)}\}$.


When EUT duty cycle < 98%, Final AVG PSD (dBm / 10kHz) = $10 \cdot \log\{10^{(Ant\ 0\ AVG\ PSD/10)} + 10^{(Ant\ 1\ AVG\ PSD/10)}\} + 10 \cdot \log(1/Duty\ cycle)$.

SISO Mode - 802.11b AVGPSPD

Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




SISO Mode - 802.11g - AVGPSPD


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




SISO Mode - 802.11n-HT20 - AVGPSD


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




SISO Mode - 802.11n-HT40 - AVGPSD


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)




MIMO Mode Ant 0 - 802.11n-HT20 - AVGPSPD


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




MIMO Mode Ant 0 - 802.11n-HT40 - AVGPSPD


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)




MIMO Mode Ant 1 - 802.11n-HT20 - AVGPSPD


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




MIMO Mode Ant 1 - 802.11n-HT40 - AVGPDS


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



7.5. Conducted Band Edge and Out-of-Band Emissions

7.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

7.5.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.11

7.5.3. Test Setting


Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≥ 1.5 times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW $\geq 3 \times$ RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

7.5.4.Test Setup



7.5.5.Test Result


Product	Mobile Computer	Test Engineer	Gordon Qi
Test Site	TR3	Test Date	2020/07/03 ~ 2020/07/27
Test Mode	SISO Mode		

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	Limit	Result
802.11b	1Mbps	01	2412	30dBc	Pass
802.11b	1Mbps	06	2437	30dBc	Pass
802.11b	1Mbps	11	2462	30dBc	Pass
802.11g	6Mbps	01	2412	30dBc	Pass
802.11g	6Mbps	06	2437	30dBc	Pass
802.11g	6Mbps	11	2462	30dBc	Pass
802.11n-HT20	MCS0	01	2412	30dBc	Pass
802.11n-HT20	MCS0	06	2437	30dBc	Pass
802.11n-HT20	MCS0	11	2462	30dBc	Pass
802.11n-HT40	MCS0	03	2422	30dBc	Pass
802.11n-HT40	MCS0	06	2437	30dBc	Pass
802.11n-HT40	MCS0	09	2452	30dBc	Pass


SISO Mode - 802.11b Out-of-Band Emissions

Channel 01 (2412MHz)


100kHz PSD Reference Level



Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

100kHz PSD Reference Level



Spurious Emission




SISO Mode - 802.11b Out-of-Band Emissions

Channel 11 (2462MHz)

100kHz PSD Reference Level



High Band Edge



Spurious Emission

