Model: POWER16

Huizhou Qitai Electronic Technology Co., LTD



SPECIFICATIONS SHEET

CUSTOMER	: 	mof	hie	
DESCRIPTIO	N :	Y. 017. 0	005	
CUSTOMER	P/N :	1.017.0	000	
PART NUMB	ER :			
DATE OF AP	PLICATION :	Oct. 19	2024	
New applic			("√")	
New applic			("√")	
New applice New part is Revision of	eation added to accepted specifica accepted specification		("√")	
New applic	eation added to accepted specifica accepted specification		PREPARE BY	

ADDRESS: 3rd Floor, No. 181, Mingyue 2nd Road, Shiwan Town, Boluo County, Huizhou city

TELPHONE: 0752-6668681

E-MAIL: 839689578@qq.com

Manufacturer: Huizhou Qitai Electronic Technology Co., LTD ADD: 3rd Floor, No. 181, Mingyue 2nd Road, Shiwan Town,


Boluo County, Huizhou city

History For Davisod Cresting				CUSTOMER P/N :			mofhie		
History For Revised Specification			on	PART NUMBER :		R :	Y. 017. 0005		
Item	DESCRIPTION	(Content Or Reason For	Changed)	Rev.	Cust	Rev.	Г	ate	Revisor
1	In	itial Release		A0			Oct. 3	19, 2024	Chen jun
								1	
APF	PROVED BY	CHECKED BY	PREPARE	ED BY		DATE			PAGE
Cha	aulziqi		Chen	jun	Oct.	19,	2024	1	of 3

Huizhou Qitai Electronic Technology Co., LTD

Specification	CUSTOMER P/N:	mofhie
	PART NUMBER :	Y. 017. 0005

1. DIMENSIONS 外形尺寸: (Unit: mm)



А	В	С	D	Е	F	G	
24.5±0.3	14.5±0.5	7.6±0.5	10±1	2±1	2.5ref	2.6Max	

- 1. The back adhesive is white, ϕ 18.0.
- 2. Magnet specification: ϕ 7.5*2.5, magnetic field 3600GS \pm 150GS.
- 3. Slot the hard magnetic outlet.

APPROVED BY	CHECKED BY	PREPARED BY	DATE	PAGE
Chaulziqi		Chen jun	Oct. 19, 2024	2 of 3

Huizhou Qitai Electronic Technology Co., LTD

Specification	CUSTOMER P/N :	mofhie
	PART NUMBER :	Y. 017. 0005

2. WINDING DETAILS Coil1

Turns	Wire Dia	Wdg. Type Spred/Close	Wdg.Direction	Intersect Yes/Not
10TS	0.08*24P Hot air self-adhesive wir	close winding (Close)	backwind	Yes

3. (ELECTRICAL CHARACTERISTICS):

TEMPERATURE:25±10 , ℃ RELATIVE HUMIDITY:65±10%

NO.	ITEM	TERMINAL	SPECIFICATION	TEST FREQUENCY	TEST EQUIPMENTS			
	Coil 1							
1.	IND	S-F	4.1h±10%	100kHz/V	UC2906A			
2.	Q	S-F	20Min	100kHz/V	UC2906A			
3.	DCR	S-F	120m Ω Max	100kHz/V	UC2906A			

			T	
APPROVED BY	CHECKED BY	PREPARED BY	DATE	PAGE
,	0	1112.711125 51	5,112	.,.0=
			0.4 10 2024	0.10
Chaulziqi		Chen jun	Oct. 19, 2024	3 of 3