


Prüfbericht-Nr.: <i>Test report no.:</i>	IN2524D1 001	Auftrags-Nr.: <i>Order no.:</i>	146966291 010	Seite 1 von 42 Page 1 of 42
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	2390953	Auftragsdatum: <i>Order date:</i>	2024-09-24	
Auftraggeber: <i>Client:</i>	Proxim Wireless Corporation 2114 Ringwood Avenue, San Jose, CA 95131			
Prüfgegenstand: <i>Test item:</i>	Stratum™ X1 & Stratum™ X3			
Bezeichnung <i>Identification</i>	SX3-1020A-US & SX3-1021A-US & SX1-1023C-US SX3-1020A-WD & SX3-1021A-WD & SX1-1023C-WD			
Auftrags-Inhalt: <i>Order content:</i>	Testing and issue of Test Report with Grant Certificate			
Prüfgrundlage: <i>Test specification:</i>	FCC Part 15 Subpart C 15.247,15.205, 15.207 & 15.209 RSS 247 Issue 3 & RSS Gen Issue 5			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2024-07-02			
Prüfmuster-Nr.: Serien -Nr.: <i>Test sample no:</i> <i>Serial no.:</i>	A003759215-012 & A003759215-05 Engineering Sample			
Prüfzeitraum: <i>Testing period:</i>	2024-10-05 - 2025-01-02			
Ort der Prüfung: <i>Place of testing:</i>	Wireless laboratory, Bangalore			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (India) Pvt. Ltd. 27/B,2nd cross road, Electronic city Phase1, Bangalore-560100, India FCC Test Site Registration No: 496599 IC Test Site Registration No: 27711			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i> 2025-02-18	Ausstellatum: <i>Issue date:</i> 2025-02-18			
Stellung / Position:	M.V.Naveen Kumar Senior Engineer	Stellung / Position:	Madhu K.N Assistant Manager	
Sonstiges / Other:	FCC ID: HZB-MEGA2 IC: 1856A-MEGA2 Contains FCC ID: HZB-MEGA5 Contains IC: 1856A-MEGA5 HVIN: Megabit 5 single & Megabit 5 multi			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende:	1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet			
* Legend:	1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested			
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht - Nr.:

Test Report No.:

IN2524D1 001

Seite 2 von 42

Page 2 of 42

- | | |
|----------|---|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</p> <p>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.</p> <p>Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird.</p> <p><i>The decision rule for statements of conformity in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report.</i></p> |

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001

Seite 3 von 42
Page 3 of 42

TEST SUMMARY

Test Item	FCC	ISED	Result
Maximum conducted (Peak) output power	15.247 (b)(3)	RSS 247 Issue 3 Section 5.4(d)	N/T
Maximum Power Spectral Density	FCC 15.247(e)	RSS 247 Issue 3 Section 5.2(b)	N/T
DTS Bandwidth & 99% Bandwidth	FCC 15.247(a)(2)	RSS 247 Issue 3 Section 5.2(a) RSS Gen Issue 5 Section 6.7	N/T
Emissions in non-restricted frequency bands	15.247 (d)	RSS 247 Issue 3 Section 5.5	N/T
Spurious Radiated Emissions and Restricted Bands of Operation	15.247 (d) / FCC 15.209 / FCC 15.205	RSS-Gen Issue 5, Section 8.9 /8.10	Pass
AC Power lines Conducted emission	FCC 15.207	RSS Gen Issue 5 Section 8.8	Pass
Antenna Requirement	FCC 15.203	RSS Gen Issue 5 Section 6.8	Pass

***Note:**

N/T → Not tested, Since the device is certified, and you can find the test results with respect to test report no:
IN240QFC 001

Product Category: Electronics Testing

Test Discipline: EMC Test Facility

Prüfbericht - Nr.:

Test Report No.:

IN2524D1 001

Seite 4 von 42

Page 4 of 42

REVISION HISTORY OF THIS REPORT

Report Number	Version	Description	Issue date
IN2524D1 001	01	Initial issue of report	2025-02-18

Table of Contents

1	GENERAL REMARKS	6
1.1	Attachments	6
2	TEST SITES	7
2.1	Testing Facilities	7
2.2	List of Test and Measurement Instruments.....	7
3	GENERAL PRODUCT INFORMATION.....	8
3.1	Product Function and Intended Use	8
3.2	Ratings and System Details of Equipment under Test	8
3.3	Measurement Uncertainty:	9
4	TEST SET-UP AND OPERATION MODE.....	10
4.1	Principle of Configuration Selection	10
4.2	Test Operation and Test Software	10
4.3	Special Accessories and Auxiliary Equipment	10
4.4	Countermeasures to achieve EMC Compliance	10
4.5	List of frequencies	10
4.6	TUV Sample Identification.....	11
5	Operational Description	12
6	TEST METHODOLOGY	13
6.1	AC Power lines Conducted emission.....	13
6.1.1	Test Setup Configuration.....	13
6.2	Radiated Emission Test	14
6.2.1	Test Setup Configuration.....	14
7	TEST RESULTS	16
7.1	Spurious Radiated Emissions & Restricted Bands of Operation	16
7.2	AC Power lines Conducted Emission	37
8	LIST OF TABLES.....	42
9	List of Figures	42

Prüfbericht - Nr.:

Test Report No.:

IN2524D1 001

Seite 6 von 42

Page 6 of 42

1 GENERAL REMARKS

1.1 Attachments

All attachments are part of this test report and are issued in separate document

1. Test Setup photos
2. EUT External Photos
3. EUT Internal Photos
4. FCC Label and Label Location
5. Block Diagram
6. Specification of EUT
7. Schematic Diagrams
8. Bill of Material
9. User Manual
10. Maximum Permissible Exposure Information

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001

Seite 7 von 42
Page 7 of 42

2 TEST SITES

2.1 Testing Facilities

1. TÜV Rheinland (India) Pvt.Ltd.,
27/B, 2nd Cross,
ElectronicCityPhase1
Bangalore – 560 100,
India
2. TUV Rheinland (India) Pvt.Ltd.,
108, Beside ISBR Business School,
Electronic city Phase I
Bangalore - 560 100,
India

2.2 List of Test and Measurement Instruments

Table 1: List of test and measurement instruments

Equipment	Manufacturer	Model Name	Serial Number	Firmware Versions	Calibration Due Date	Periodicity	Test Facility
EMI Receiver	Rohde & Schwarz	ESW 44	101732	4.73 SP5	17.09.2025	Yearly	Radiated Spurious Emission
Active loop antenna	Frankonia	LAX-10	LAX-10-800	-	23.03.2025	Yearly	
Balun & Biconical Antenna	Schwarzbeck mess-elektronik	VHBB-9124 / BBA-9106	01028	-	08.02.2025	Yearly	
Log-Periodic Antenna	Schwarzbeck mess-elektronik	VUSLP 9111B	9111B-111	-	08.02.2025	Yearly	
Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-01944	-	12.11.2025	Yearly	
EMI Test Receiver	Rohde & Schwarz	ESW44	101773	1.72.SP1	26.01.2025	Yearly	
Semi Anechoic Chamber	Frankonia	-	-	-	-	-	
Fully Anechoic Chamber	Albatross	-	-	-	-	-	Conducted Test Parameters
Spectrum Analyzer	Agilent	E4407B	US411927 72	A.14.07	16.01.2026	Yearly	
10dB Attenuator	H+S Electronics Pvt. Ltd	6810.17. A	770041	-	08.03.2025	Yearly	Conducted AC Power line Test
EMI Receiver	Rohde & Schwarz	ESR7	101133	3.48 SP3	16.09.2025	Yearly	
Two Line V-Network (LISN)	Rohde & Schwarz	ENV 216	100022	-	15.04.2025	Yearly	
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100811	-	08.07.2025	Yearly	

Table 2: Instrument application Software versions

SL. No.	Test Type	Application software	Version
1	Radiated spurious emission measurement in FAC	EMC 32	10.60.20
2	Radiated spurious emission measurement in 10mtr SAC	BAT EMC	3.20.0.17

3 GENERAL PRODUCT INFORMATION

3.1 Product Function and Intended Use

The Stratum™ X3 and X1 are highly efficient radio endpoints that deliver up to one gigabit throughput in both point-to-point and multipoint wide area network configurations. Able to operate in MIMO 2x2, with either integrated or external antenna (software switchable on some variant), the Stratum™ X3 and X1 are ideally suited to backhaul, video surveillance, or multipoint deployments.

Powered by Proxim WOPR® (Wireless Outdoor Router Protocol), managed via web GUI, CLI, Bluetooth-enabled Proxim BlueConnect™ and SNMP for ProximVision® Advanced, these platforms offer advanced Quality of Service, granular service level management, and very secure networking.

3.2 Ratings and System Details of Equipment under Test

Table 3: Ratings and System Details as declared by Client*

Radio Protocol		Bluetooth Low Energy
Operating Frequency Range		2402MHz to 2480MHz
No. of Channels		40
Channel Spacing		2MHz
Transmitter Power level(dBm)		7dBm
Measured Peak power (dBm)		4.30dBm@2440MHz
Modulation		GFSK
Data Rates		1Mbps,2Mbps
Number of antennas		1
Antenna Gain		1.5dBi
Antenna Type		Chip Antenna
Supply Voltage to Product		36-57V DC to EUT & 110-230V AC to PoE
Environmental conditions	Storage(°C)	-50°C to 70°C
	Operating(°C)	-40°C to 60°C
EUT Dimension(L x W x H) in mm		SX3-1020A: 250 x 220 x 62 mm SX3-1021A: 305 x 305 x 85 mm SX1-1023C: 170 x 217 x 56 mm

***Disclaimer:** The information/data is supplied by the client and the same is considered to arrive at the final value. Any changes made apart from the specified specification, can directly impact on the tests results. Refer the products user manual for more details.

Prüfbericht - Nr.:

Test Report No.:

IN2524D1 001

Seite 9 von 42

Page 9 of 42

3.3 Measurement Uncertainty:

Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of $k = 2$

Table 4: Measurement Uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 5 \%$
RF output power, conducted	$\pm 1.5 \text{ dB}$
Power Spectral Density, conducted	$\pm 3 \text{ dB}$
Unwanted Emissions, conducted	$\pm 3 \text{ dB}$
All emissions, radiated	$\pm 6 \text{ dB}$
Temperature	$\pm 3 \text{ }^{\circ}\text{C}$
Supply Voltages	$\pm 3 \%$
Time	$\pm 5 \%$

4 TEST SET-UP AND OPERATION MODE

4.1 Principle of Configuration Selection

Transmission was enabled with highest possible duty cycle transmission on low, mid and high channel.

4.2 Test Operation and Test Software

Hardware Name & Version: Edge AX MB PCB & 1.0

Software Version: 15.05.1

Software Name: Openwrt Chaos Calmer

4.3 Special Accessories and Auxiliary Equipment

Model Name & Model Number	Power Adapter Ratings
Gigabit PoE Injector RP026-5601100YG/Proxim 400-00031	Input: 100-240V~50/60Hz 1.5A Max Output: 56.0VDC 1.1A 61.6W +(3,4,5,6) pins, -(1,2,7,8) pins
Gigabit PoE Injector RP025-5600536YG/Proxim 400-00021	Input: 100-240V~50/60Hz 0.7A Max Output: 56.0VDC 0.536A 30W +(3,4,5,6) pins, -(1,2,7,8) pins

4.4 Countermeasures to achieve EMC Compliance

- None

4.5 List of frequencies

Frequency Band (MHz)	Channel No.	Channel Frequency (MHz)
2402 – 2483.5 BLE	0	2402
	1	2404
	2	2406
	3	2408
	:	:
	11	2424
	12	2426
	:	:
	19	2440
	20	2442
	:	:
	:	:
	:	:
	:	:
	36	2474
	37	2476
	38	2478
	39	2480

Table 5: List of BLE Centre frequencies

Prüfbericht - Nr.:

Test Report No.:

IN2524D1 001

Seite 11 von 42

Page 11 of 42

Channel used for BLE testing.

Channel low: 2402MHz

Channel mid: 2440MHz

Channel high : 2480MHz

4.6 TUV Sample Identification

1. TUV Sample Identification number: A003759215-012 & A003759215-005 – Radiated & Conducted test Sample.

5 Operational Description

Proxim Stratum™ X1 and Stratum™ X3 products are based on Qualcomm IPQ5018 Dual Core ARM Cortex 64-bit A53 1.0GHz processor Maple Series. IPQ5018 is an SoC for 11ax Wi-Fi Access Points, Retail Routers and Carrier Gateways. The chip consists of a networking subsystem, and a CPU subsystem.

Differences between Stratum™ X1 and Stratum™ X3 products are based on the Ethernet controller and number of Ethernet ports available as below:

- Stratum X1 uses Qualcomm IPQ5018 built in ethernet controller and provides one 1Gbps port.
- Stratum X3 uses Qualcomm QCA8337N ethernet controller and provides three 1Gbps ports.

The Stratum™ X1 and Stratum™ X3 are highly efficient radio endpoints that deliver up to one gigabit throughput in both point-to-point and multipoint wide area network configurations. Able to operate in MIMO 2x2, with either integrated or external antenna (software switchable on some variant), the Stratum™ X1 and Stratum™ X3 are ideally suited to backhaul, video surveillance, or multipoint deployments.

Powered by Proxim WORP® (Wireless Outdoor Router Protocol), managed via web GUI, CLI, Bluetooth- enabled Proxim BlueConnect™ and SNMP for ProximVision® Advanced, these platform offer advanced Quality of Service, granular service level management, and very secure networking.


6 TEST METHODOLOGY

6.1 AC Power lines Conducted emission

Measured levels of ac powerline conducted emission across the 50Ω LISN port (to which the EUT is connected). All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer.

The device is placed on the test table, raised 80cm above the reference ground plane. The vertical conducting plane is located 40cm to the rear of the device. AC Conducted emission measurement is made over frequency range from 150 kHz to 30MHz, this measurement was performed an AC adaptor 110V AC 60Hz supply

6.1.1 Test Setup Configuration



6.2 Radiated Emission Test

The radiated emission measurement was performed according to the procedures in ANSI C63.10-2013. The equipment under test (EUT) was placed at the middle of the 80 cm high turntable for below 1 GHz & 1.5 m height for above 1 GHz measurement, and the EUT is 3 meters far from the measuring antenna. The turntable was rotated 360° for obtaining the maximum emission. The height of the measuring antennas was scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained. The measurement above 1000 MHz was performed by horn antenna, the measurement below 30 MHz was performed by loop antenna, Measurement from 30 MHz to 200 MHz was performed by Balloon and Biconical Antenna, and measurement from 200 MHz to 1 GHz was performed by Log-Periodic Antenna.

The EUT was rotated around the X-, Y-, and Z-Axis and the results from worst case axis are recorded

6.2.1 Test Setup Configuration




Figure 1: Frequency Range 9 kHz- 30 MHz




Figure 2: Frequency Range 30 MHz – 200 MHz




Figure 3: Frequency Range 200 MHz - 1GHz




Figure 4: Frequency Range above 1 GHz

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001

Seite 16 von 42
Page 16 of 42

7 TEST RESULTS

7.1 Spurious Radiated Emissions & Restricted Bands of Operation

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (d) / (15.209 & 15.205)/ RSS-Gen Issue 5, Section 8.9 /8.10
Test Method	ANSI C63.10
Measurement Location	Semi Anechoic Chamber 9kHz - 1 GHz Fully Anechoic Chamber 1 GHz - 26GHz
Measurement Bandwidth	100 kHz for frequency range < 1GHz 1 MHz for Frequency range >1GHz
Detector	Refer remarks below
Measuring Distance	3 m
Requirement	As per the limits mentioned in the below table
Test setup	Refer TEST METHODOLOGY

Table 6: Transmitter limits for Radiated emission

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Distance of Measurement (m)
0.009 – 0.490	2400/F(kHz)	48.50 – 13.80	300*
0.490 – 1.705	24000/F(kHz)	33.80 – 23.00	30*
1.705 -30	30	29.54	30*
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Remark: * The limit shows in the table above of frequency range 0.009 – 0.490, 0.490 – 1.705 MHz and 1.705-30MHz is at 300 meter, 30 meter and 30 meter range respectively, which corresponds to 128.51 – 93.80, 73.80 – 62.96 and 69.54 dBμV/m at 3m range by extrapolation calculation and the measurement of loop antenna.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Conditions:

Temperature (Norm) = +21.5 °C

Voltage = 56VDC through POE Injector

Relative humidity: 63%

Prüfbericht - Nr.:

Test Report No.:

IN2524D1 001

Seite 17 von 42

Page 17 of 42

Test results:

Note: All the losses are included during measurement and final values are mentioned in the test report. Refer TEST METHODOLOGY for more details


Test results for frequency range 9kHz – 30MHz

No emissions found in frequency range 9 kHz to 30 MHz, and measured levels are below 20dB from the limit line, hence not reported.

Table 7: Test results for frequency range 30MHz – 1GHz

Antenna Polarization	Measured Frequency (MHz)	Measured emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Vertical	31.13(QP)	33.91	40.00	-6.09
	36.12(PK)	26.10	40.00	-13.90
	60.27(PK)	29.70	40.00	-10.30
	86.67(QP)	39.09	40.00	-0.91
	412.97(PK)	42.90	46.00	-3.10
	544.02(QP)	42.81	46.00	-3.19
	622.34(QP)	38.61	46.00	-7.39
	636.86(QP)	41.51	46.00	-4.49
Horizontal	31.44(PK)	25.90	40.00	-14.10
	72.24(PK)	24.60	40.00	-15.40
	86.70(QP)	37.13	40.00	-2.87
	181.62(PK)	35.80	43.50	-7.70
	412.30(QP)	44.44	46.00	-1.56
	545.95(QP)	41.18	46.00	-4.82
	569.66(QP)	37.40	46.00	-8.60
	687.53(QP)	43.94	46.00	-2.06

Test Plots:




Channel Frequency 30MHz – 200MHz

Polarization Vertical

Prüfbericht - Nr.:
Test Report No.:


IN2524D1 001

Seite 18 von 42
Page 18 of 42



Channel Frequency 30MHz – 200MHz

Polarization Horizontal




Channel Frequency 200MHz – 1GHz

Polarization Vertical

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001

Seite 19 von 42
Page 19 of 42



Channel Frequency 200MHz – 1GHz

Polarization Horizontal

Prüfbericht - Nr.:

Test Report No.:

IN2524D1 001

Seite 20 von 42

Page 20 of 42

Table 8: Test results for the frequencies above 1GHz:

Data Rate: 1Mbps

Channel Frequency (MHz)	Measured Frequency (MHz)	Antenna Polarization	Emission level (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2402	2402(Pk)	Vertical	97.24	-	-
	2402(Av)		96.33	-	-
	2390(Pk)		43.53	74.00*	-30.47
	2390(Av)		25.65	54.00*	-28.35
	4804(Pk)		55.60	74.00	-18.40
	4804(Av)		50.86	54.00	-3.14
	7206(Pk)		50.08	74.00	-23.92
	7206(Av)		40.02	54.00	-13.98
	2402(Pk)	Horizontal	97.47	-	-
	2402(Av)		96.53	-	-
	2390(Pk)		38.26	74.00*	-35.74
	2390(Av)		25.68	54.00*	-28.32
	4804(Pk)		52.37	74.00	-21.63
	4804(Av)		46.63	54.00	-7.37
	7206(Pk)		51.97	74.00	-22.03
	7206(Av)		43.08	54.00	-10.92
2440	2440(Pk)	Vertical	99.43	-	-
	2440(Av)		98.50	-	-
	4880(Pk)		56.61	74.00	-17.39
	4880(Av)		52.02	54.00	-1.98
	7320(Pk)		50.16	74.00	-23.84
	7320(Av)		39.33	54.00	-14.67
	2440(Pk)	Horizontal	99.81	-	-
	2440(Av)		98.87	-	-
	4880(Pk)		54.65	74.00	-19.35
	4880(Av)		49.67	54.00	-4.33
	7320(Pk)		51.52	74.00	-22.48
	7320(Av)		40.94	54.00	-13.06
2480	2480(Pk)	Vertical	99.77	-	-
	2480(Av)		98.88	-	-
	2483.5(Pk)		50.23	74.00*	-23.77
	2483.5(Av)		31.56	54.00*	-22.44
	4960(Pk)		53.62	74.00	-20.38
	4960(Av)		48.71	54.00	-5.29
	7440(Pk)		50.16	74.00	-23.84
	7440(Av)		38.52	54.00	-15.48
	2480(Pk)	Horizontal	98.70	-	-
	2480(Av)		97.81	-	-
	2483.5(Pk)		41.97	74.00*	-32.03
	2483.5(Av)		30.73	54.00*	-23.27
	4960(Pk)		53.23	74.00	-20.77
	4960(Av)		48.45	54.00	-5.55
	7440(Pk)		56.38	74.00	-17.62
	7440(Av)		48.61	54.00	-5.39

_ → Fundamental Frequency

*→ Restricted Band edges

Pk: Peak Detector;

Av: Average Detector

Prüfbericht - Nr.:

Test Report No.:

IN2524D1 001

Seite 21 von 42

Page 21 of 42

Data Rate: 2Mbps

Channel Frequency (MHz)	Measured Frequency (MHz)	Antenna Polarization	Emission level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2402	2402(Pk)	Vertical	96.21	-	-
	2402(Av)		95.24	-	-
	2390(Pk)		43.51	74.00*	-30.49
	2390(Av)		25.22	54.00*	-28.78
	4804(Pk)		55.51	74.00	-18.49
	4804(Av)		50.86	54.00	-3.14
	7206(Pk)		52.75	74.00	-21.25
	7206(Av)		44.18	54.00	-9.82
	2402(Pk)	Horizontal	94.93	-	-
	2402(Av)		94.00	-	-
	2390(Pk)		37.88	74.00*	-36.12
	2390(Av)		25.28	54.00*	-28.72
	4804(Pk)		50.49	74.00	-23.51
	4804(Av)		44.82	54.00	-9.18
	7206(Pk)		51.05	74.00	-22.95
	7206(Av)		42.02	54.00	-11.98
2440	2440(Pk)	Vertical	99.42	-	-
	2440(Av)		98.48	-	-
	4880(Pk)		55.82	74.00	-18.18
	4880(Av)		51.09	54.00	-2.91
	7320(Pk)		49.03	74.00	-24.97
	7320(Av)		38.31	54.00	-15.69
	2440(Pk)	Horizontal	99.65	-	-
	2440(Av)		98.71	-	-
	4880(Pk)		54.46	74.00	-19.54
	4880(Av)		49.63	54.00	-4.37
	7320(Pk)		52.06	74.00	-21.94
	7320(Av)		42.72	54.00	-11.28
2480	2480(Pk)	Vertical	99.70	-	-
	2480(Av)		98.81	-	-
	2483.5(Pk)		50.55	74.00*	-23.45
	2483.5(Av)		31.40	54.00*	-22.60
	4960(Pk)		53.78	74.00	-20.22
	4960(Av)		48.66	54.00	-5.34
	7440(Pk)		51.64	74.00	-22.36
	7440(Av)		40.99	54.00	-13.01
	2480(Pk)	Horizontal	98.70	-	-
	2480(Av)		97.78	-	-
	2483.5(Pk)		42.29	74.00*	-31.71
	2483.5(Av)		30.63	54.00*	-23.37
	4960(Pk)		53.48	74.00	-20.52
	4960(Av)		48.41	54.00	-5.59
	7440(Pk)		53.06	74.00	-20.94
	7440(Av)		43.71	54.00	-10.29

_ → Fundamental Frequency

*→ Restricted Band edges

Pk: Peak Detector;

Av: Average Detector

Prüfbericht - Nr.:

Test Report No.:


IN2524D1 001

Seite 22 von 42

Page 22 of 42


Test Plots:

Data Rate: 1Mbps




Channel Frequency: 2402MHz

Polarization: Vertical




Channel Frequency: 2402MHz

Polarization: Horizontal




Channel Frequency: 2440MHz

Polarization: Vertical




Channel Frequency: 2440MHz

Polarization: Horizontal



Channel Frequency: 2480MHz

Polarization: Vertical



Channel Frequency: 2480MHz


Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001


Seite 25 von 42
Page 25 of 42

Channel frequency: 2402MHz



Polarization: Vertical

Frequency range: 1GHz to 18GHz



Polarization: Horizontal


Frequency range: 1GHz to 18GHz

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001


Seite 26 von 42
Page 26 of 42

Channel frequency: 2440MHz



Polarization: Vertical

Frequency range: 1GHz to 18GHz



Polarization: Horizontal

Frequency range: 1GHz to 18GHz

Prüfbericht - Nr.:


Test Report No.:

IN2524D1 001

Seite 27 von 42


Page 27 of 42

Channel frequency: 2480MHz



Polarization: Vertical

Frequency range: 1GHz to 18GHz



Polarization: Horizontal


Frequency range: 1GHz to 18GHz

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001


Seite 28 von 42
Page 28 of 42

Data Rate: 2Mbps




Channel frequency: 2402MHz

Polarization: Vertical




Channel frequency: 2402MHz

Polarization: Horizontal




Channel frequency: 2440MHz

Polarization: Vertical




Channel frequency: 2440MHz

Polarization: Horizontal



Channel frequency: 2480MHz

Polarization: Vertical



Channel frequency: 2480MHz


Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001


Seite 31 von 42
Page 31 of 42

Channel frequency: 2402MHz



Frequency range: 1GHz to 18GHz

Polarization: Vertical



Frequency range: 1GHz to 18GHz


Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001


Seite 32 von 42
Page 32 of 42

Channel frequency: 2440MHz



Frequency range: 1GHz to 18GHz

Polarization: Vertical



Frequency range: 1GHz to 18GHz


Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001


Seite 33 von 42
Page 33 of 42

Channel Frequency: 2480MHz



Frequency range: 1GHz to 18GHz

Polarization: Vertical



Frequency range: 1GHz to 18GHz

Polarization: Horizontal

Prüfbericht - Nr.:

Test Report No.:

IN2524D1 001

Seite 34 von 42


Page 34 of 42

Simultaneous Operation: BLE (2402MHz) & Wi-Fi 5GHz of (UNII-2a)


Channel Frequency (MHz)	Antenna Polarization	Measured Frequency (MHz)	Measured emission (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2402 & 5260	Vertical	2402(Pk)	86.49	-	-
		2402(Av)	85.51	-	-
		2390(Pk)	46.47	74.00	-27.53
		2390(Av)	28.77	54.00	-25.23
		4804(Pk)	42.49	74.00	-31.51
		4804(Av)	29.67	54.00	-24.33
		7206(Pk)	53.25	74.00	-20.75
		7206(Av)	45.70	54.00	-8.30
		5260 (Pk)	111.84	-	-
		5260 (Av)	102.53	-	-
		5350 (Pk)	48.33	74.00	-25.67
		5350 (Av)	35.37	54.00	-18.63
		10520 (Pk)	52.75	68.23	-15.48
		10520 (Av)	40.94	54.00	-13.06
		15780 (Pk)	53.67	68.23	-14.56
		15780 (Av)	41.24	54.00	-12.76
2402 & 5260	Horizontal	2402(Pk)	80.21	-	-
		2402(Av)	79.18	-	-
		2390(Pk)	44.10	74.00	-29.90
		2390(Av)	25.87	54.00	-28.13
		4804(Pk)	41.62	74.00	-32.38
		4804(Av)	29.14	54.00	-24.86
		7206(Pk)	50.16	74.00	-23.84
		7206(Av)	39.99	54.00	-14.01
		5260 (Pk)	112.81	-	-
		5260 (Av)	103.55	-	-
		5350 (Pk)	48.75	74.00	-25.25
		5350 (Av)	37.10	54.00	-16.90
		10520 (Pk)	53.53	68.23	-14.70
		10520 (Av)	40.65	54.00	-13.35
		15780 (Pk)	53.09	68.23	-15.14
		15780 (Av)	41.24	54.00	-12.76

Test Plots:

Restricted Bands of Operation:



Vertical Polarization



Horizontal Polarization

Prüfbericht - Nr.:


Test Report No.:

IN2524D1 001

Seite 36 von 42


Page 36 of 42

Spurious Radiated Emission:



Frequency range: 1GHz to 18GHz

Polarization: Vertical



Frequency range: 1GHz to 18GHz

Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001

Seite 37 von 42
Page 37 of 42

7.2 AC Power lines Conducted Emission

Result

Pass

Test Specification : FCC Part 15 Section 15.207/RSS Gen Issue 5 Section 8.8
Test Method : ANSI C 63.10-2013
Testing Location : Screened room
Measurement Bandwidth : 9kHz
Frequency Range : 150kHz – 30MHz
Supply Voltage : 110VAC,60Hz
Test Method : Refer TEST METHODOLOGY

Table 9: Limits for Conducted power line emission

Frequency of emission (MHz)	QP Limit (dBμV)	AV Limit (dBμV)
0.15 – 0.5	66 – 56*	56 – 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency

Prüfbericht - Nr.:

Test Report No.:

IN2524D1 001

Seite 38 von 42

Page 38 of 42

Test Conditions:

Temperature (Norm) = +24 °C


Voltage = 110V AC (Through POE Adapter)

Relative humidity: 64%

Test results:

Model No: RP026-5601100YG/Proxim 400-00031

110VAC-60Hz-Line



Quasi Peak:

Frequency (MHz)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Comments
0.4486	48.49	56.88	-8.39	Pass
0.42715	46.01	57.33	-11.33	Pass
0.1545	48.83	65.78	-16.95	Pass
28.2385	40.9	60.00	-19.1	Pass
29.16825	39.67	60.00	-20.33	Pass
11.17225	38.39	60.00	-21.61	Pass
0.8544	30.76	56.00	-25.24	Pass

Average:

Frequency (MHz)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Comments
0.42715	43.41	47.33	-3.92	Pass
0.4486	40.76	46.88	-6.11	Pass
28.2385	39.57	50.00	-10.43	Pass
29.16825	38.14	50.00	-11.86	Pass
11.17225	33.83	50.00	-16.17	Pass
0.8544	24.99	46.00	-21.01	Pass
0.1545	34.5	55.78	-21.28	Pass

Prüfbericht - Nr.:


Test Report No.:

IN2524D1 001

Seite 39 von 42

Page 39 of 42

110VAC-60Hz-Neutral:



Quasipeak:

Frequency (MHz)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Comments
0.4507	48.73	56.88	-8.15	Pass
0.2962	45.13	60.3	-15.17	Pass
0.40425	42.27	57.73	-15.46	Pass
0.1545	48.04	65.78	-17.74	Pass
28.5496	41.21	60.00	-18.79	Pass
27.92915	40.72	60.00	-19.28	Pass
11.17315	40.1	60.00	-19.9	Pass
1.2167	34.03	56.00	-21.97	Pass

Average:

Frequency (MHz)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Comments
0.4507	43.37	46.88	-3.51	Pass
0.40425	40.48	47.73	-7.24	Pass
28.5496	39.97	50.00	-10.03	Pass
27.92915	39.47	50.00	-10.53	Pass
11.17315	35.39	50.00	-14.61	Pass
0.2962	34.91	50.30	-15.39	Pass
0.1545	33.72	55.78	-22.06	Pass
1.2167	22.03	46.00	-23.97	Pass


Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001

Seite 40 von 42
Page 40 of 42

PoE Injector Model: RP026-5601100YG/Proxim 400-00021

110VAC-60Hz-Line



Quasipeak:

Frequency (MHz)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Comments
0.4469	51.24	56.95	-5.71	Pass
0.46395	49.68	56.66	-6.98	Pass
0.4239	48.13	57.41	-9.27	Pass
0.1509	53.92	66.00	-12.08	Pass
0.29665	46.25	60.30	-14.05	Pass
0.3331	43.59	59.35	-15.76	Pass
0.8834	37.93	56.00	-18.07	Pass
11.88205	35.67	60.00	-24.33	Pass

Average:


Frequency (MHz)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Comments
0.4469	44.15	46.95	-2.8	Pass
0.46395	36.56	46.66	-10.1	Pass
0.4239	36.49	47.41	-10.92	Pass
0.29665	37.56	50.30	-12.74	Pass
0.3331	36.58	49.35	-12.77	Pass
0.1509	37.26	56.00	-18.74	Pass
11.88205	28.85	50.00	-21.15	Pass
0.8834	23.1	46.00	-22.9	Pass

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001

Seite 41 von 42
Page 41 of 42

Neutral:



Quasipeak:-

Frequency (MHz)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Comments
0.4505	50.65	56.88	-6.22	Pass
0.46575	46.83	56.58	-9.76	Pass
0.42385	47.07	57.41	-10.34	Pass
0.15135	52.20	66.00	-13.8	Pass
0.298	45.29	60.30	-15.01	Pass
1.2468	38.15	56.00	-17.85	Pass
0.8879	35.89	56.00	-20.11	Pass
12.06095	36.94	60.00	-23.06	Pass

Average:

Frequency (MHz)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Comments
0.4505	45.85	46.88	-1.02	Pass
0.42385	34.92	47.41	-12.49	Pass
0.298	36.87	50.30	-13.43	Pass
0.46575	31.66	46.58	-14.92	Pass
1.2468	29.39	46.00	-16.61	Pass
12.06095	30.38	50.00	-19.62	Pass
0.15135	36.13	56.00	-19.87	Pass
0.8879	19.85	46.00	-26.15	Pass

Prüfbericht - Nr.:
Test Report No.:

IN2524D1 001

Seite 42 von 42
Page 42 of 42

8 LIST OF TABLES

Table 1: List of test and measurement instruments	7
Table 2: Instrument application Software versions	7
Table 3: Ratings and System Details as declared by Client*	8
Table 4: Measurement Uncertainty	9
Table 5: List of BLE Centre frequencies	10
Table 6: Transmitter limits for Radiated emission	16
Table 7: Test results for frequency range 30MHz – 1GHz	17
Table 8: Test results for the frequencies above 1GHz:	20
Table 9: Limits for Conducted power line emission	37

9 List of Figures

Figure 1: Frequency Range 9 kHz- 30 MHz	14
Figure 2: Frequency Range 30 MHz – 200 MHz	14
Figure 3: Frequency Range 200 MHz - 1GHz	15
Figure 4: Frequency Range above 1 GHz	15

*****End of test report*****