

TEST REPORT

LOFLICK 68 Triple Mode Connection **Product Name**

Mechanical Keyboard

Brand Mark : LOFREE

: OE902 Model No.

FCC ID : 2AC59-OE902

Report Number : BLA-EMC-202204-A5303

Date of Sample Receipt : 2022/4/19

Date of Test : 2022/4/19 to 2022/4/29

Date of Issue : 2022/4/29

47 CFR Part 1.1307, Part 2.1093, KDB Test Standard

447498

Test Result : Pass

Josu Blue Zhong

Prepared for:

SHENZHEN LOFREE CULTURE CO.,LTD F8 Building, F518 IDEA LAND, Baoyuan Road, Xixiang, Baoan District, Shenzhen, China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd. Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China

TEL: +86-755-23059481

Compiled by:

Review by:

Approved by:







Page 2 of 7

REPORT REVISE RECORD

Version No.	Date	Description	
00	00 2022/4/29 Original		





TABLE OF CONTENTS

1	Т	EST SUMMARY	.4
•	-		-
2	G	ENERAL INFORMATION	.5
3	G	ENERAL DESCRIPTION OF E.U.T	.5
4	L	ABORATORY LOCATION	.6
5	R	F EXPOSURE COMPLIANCE REQUIREMENT	.7
	5.1	STANDARD REQUIREMENT	
	5.2	LIMITS	. 7
	E 2	FLIT RE EXPOSURE	_



Page 4 of 7

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	PASS





2 GENERAL INFORMATION

Applicant	SHENZHEN LOFREE CULTURE CO.,LTD		
Address	F8 Building,F518 IDEA LAND,Baoyuan Road,Xixiang,Baoan District,Shenzhen,China		
Manufacturer	SHENZHEN LOFREE CULTURE CO.,LTD		
F8 Building, F518 IDEA LAND, Baoyuan Road, Xixiang, Baoan Distri Shenzhen, China			
Factory	HUHAI HENGCANG ELECTRONIC TECHNOLOGY CO., LTD.		
Address	Floor3, Plant Building A, No.7 Pingxi Road III, Nanping Technology Industrial Park,Zhuhai City, Guangdong Province, China		
Product Name	OFLICK 68 Triple Mode Connection Mechanical Keyboard		
Test Model No.	OE902		

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	OE902_V2_210927
Software Version	F.Nor52832.LFSZBD021-68KH-v01.01
Battery power supply	DC4.5V
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	PCB Antenna
Antenna Gain:	1.87dBi(Provided by the applicant)



Page 6 of 7

4 LABORATORY LOCATION

All tests were performed at:

BlueAsia of Technical Services(Shenzhen) Co., Ltd.

Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China

Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

No tests were sub-contracted.





Page 7 of 7

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 STANDARD REQUIREMENT

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.2 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation 17

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.3 EUT RF EXPOSURE

Operational Mode: BLE						
Channel	Maximum Peak Conducted	Tune up tolerance	Maximum tune-up Power		Calculated value	Exclusion threshold
Chamer	Output Power (dBm)	utput Power (dB)		(mW)		
2402 MHz	-0.211	±1	0.789	1.20	0.37	3.0
2442 MHz	-0.482	±1	0.518	1.13	0.35	3.0
2480 MHz	-0.802	±1	0.198	1.05	0.33	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.