

RF Exposure evaluation

FCC ID: 2AW9S-L350

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

The device can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain (dBi)
Antenna 0	WIFI antenna	FPC antenna	2.4GHz – 2.5 GHz 5.1GHz – 5.8 GHz	2.4G: 2.98 U-NII 1: 2.71 U-NII 3: 3.47
Antenna 1	BT Antenna	FPC antenna	2.4GHz – 2.5 GHz	2.70

5. Manufacturing Tolerance

2.4GWIFI (Conducted)

Frequency (MHz)	11b(Peak)		
	2412	2437	2462
Target (dBm)	15.0	15.0	15.0
Tolerance ± (dB)	1.0	1.0	1.0
Frequency (MHz)	11g(Peak)		
	2412	2437	2462
Target (dBm)	20.0	19.0	19.0
Tolerance ± (dB)	1.0	1.0	1.0
Frequency (MHz)	11n(HT20) (Peak)		
	2412	2437	2462
Target (dBm)	20.0	19.0	19.0
Tolerance ± (dB)	1.0	1.0	1.0

5GHz WLAN Band 1

<i>IEEE 802.11a (Average)</i>			
Frequency (MHz)	5180	5200	5240
Target (dBm)	9.0	9.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT20 (Average)</i>			
Frequency (MHz)	5180	5200	5240
Target (dBm)	8.0	8.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT40 (Average)</i>			
Frequency (MHz)	5190	5230	
Target (dBm)	9.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
<i>IEEE 802.11ac VHT20 (Average)</i>			
Frequency (MHz)	5180	5200	5240
Target (dBm)	9.0	9.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<i>IEEE 802.11ac VHT40 (Average)</i>			
Frequency (MHz)	5190	5230	
Target (dBm)	9.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
<i>IEEE 802.11ac VHT80 (Average)</i>			
Frequency (MHz)	5210		
Target (dBm)	10.0		
Tolerance $\pm$ (dB)	1.0		

5GHz WLAN Band 3

IEEE 802.11a (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	9.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	9.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Frequency (MHz)	5755	5795	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
IEEE 802.11ac VHT20 (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	9.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Frequency (MHz)	5755	5795	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
IEEE 802.11ac VHT80 (Average)			
Frequency (MHz)	5775		
Target (dBm)	10.0		
Tolerance $\pm$ (dB)	1.0		

BT

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	3	3	3
Tolerance $\pm$ (dB)	1.0	1.0	1.0
π /4DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	4	5	4
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	4	5	4
Tolerance $\pm$ (dB)	1.0	1.0	1.0
BLE			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	1	1	1

Tolerance $\pm$ (dB)	1.0	1.0	1.0
----------------------	-----	-----	-----

6. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna, the RF power density can be obtained.

Mode	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	radio
	dBm	mW					
WIFI 2.4G	21	3.1623	2.98	1.9861	0.0012	1.0000	0.0012
WIFI 5G U-NII 1	11	12.5893	2.71	1.8664	0.0047	1.0000	0.0047
WIFI 5G U-NII 3	11	12.5893	3.47	2.2233	0.0056	1.0000	0.0056
BT	6	3.9811	2.7	1.8621	0.0015	1.0000	0.0015

7. Summary simultaneous transmission results

The EUT have WIFI and BT function and can transmit simultaneously, if the sum of the ratios of all individual transmitters is less than 1, the simultaneously transmit can be exempt.

$$\text{SUM}_{\text{ratios}} = \text{MPE radio}_{(\text{WIFI})} + \text{MPE radio}_{(\text{BT})} = 0.0056 + 0.0015 = 0.0071 < 1$$

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----