

System / software:	SARA2 / 2.3 VPM	Input Power Drift:	
Date / Time:	2/18/2005 11:53:35 AM	DUT Battery Model/No:	
Filename:	Byst5mm5260_3d.txt	Probe Serial Number:	0123
Ambient Temperature:	22.0°C	Liquid Simulant:	5200
Device Under Test:	Broadcom PPT	Relative Permittivity:	47.67
Relative Humidity:	50%	Conductivity:	5.461
Phantom S/No:	HeadBox_spout.csv	Liquid Temperature:	22.0°C
Phantom Rotation:	0°	Max SAR Y-axis Location:	27.00 mm
DUT Position:	bystander 5mm	Max SAR Z-axis Location:	-157.00 mm
Antenna Configuration:	integral	Max E Field:	16.98 V/m
Test Frequency:	5260MHz	SAR 1g:	0.986 W/kg
Air Factors:	346 / 318 / 386	SAR 10g:	0.000 W/kg
Conversion Factors:	0.750 / 0.750 / 0.750	SAR Start:	1.012 W/kg
Type of Modulation:		SAR End:	1.012 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-0.01 dB
Diode Compression Factors (V*200):	19 / 19 / 19	Probe battery last changed:	2/3/05
Input Power Level:	max	Extrapolation:	poly4

