

RF EXPOSURE REPORT

Applicant	Shenzhen VanTop Technology & Innovation Co., Ltd.
Address	502, 5th Flr. BLDG 4, MinQi Technology Park, No. 65 Lishan Road, Taoyuan Street, Nanshan District, Shenzhen, China

Manufacturer or Supplier	Shenzhen VanTop Technology & Innovation Co., Ltd.
Address	502, 5th Flr. BLDG 4, MinQi Technology Park, No. 65 Lishan Road, Taoyuan Street, Nanshan District, Shenzhen, China
Product	Projector
Brand Name	VANKYO
Model	Leisure 470
Additional Models & Model Difference	Explore 2, Explore 2A, Explore 2W, Explore 4W, Explore 5A, Explore 5W, Explore 6A, Explore 6W, Explore 7A, Explore 7W, Explore 8A, Explore 8W, Explore 9A, Explore 9W, Leisure 410A, Leisure 410W, Leisure 430, Leisure 430A, Leisure 430W, Leisure 460A, , etc.; See section 2.1 note
Date of tests	Dec. 04, 2019 ~ Jun. 23, 2020

☒ FCC Part 2 (Section 2.1091)

☒ KDB 447498 D01

☒ IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Breeze Jiang Senior Project Engineer / EMC Department	Approved by Glyn He Assistant Manager/ EMC Department
	 Date: Jul. 13, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FM191204N055

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM191204N055	Original release	Jul. 13, 2020

1. CERTIFICATION

FCC ID:	2AQ3ALEISURE470
PRODUCT:	Projector
BRAND NAME:	VANKYO
MODEL NO.:	Leisure 470
ADDITIONAL NO.:	Explore 2, Explore 2A, Explore 2W, Explore 4W, Explore 5A, Explore 5W, Explore 6A, Explore 6W, Explore 7A, Explore 7W, Explore 8A, Explore 8W, Explore 9A, Explore 9W, Leisure 410A, Leisure 410W, Leisure 430, Leisure 430A, Leisure 430W, Leisure 460A, Leisure 460W, Leisure 470A, Leisure 470W, Leisure 490A, Leisure 490W, Leisure 510A, Leisure 510W, Leisure 520A, Leisure 520W, Leisure 530A, Leisure 530W, Leisure 540A, Leisure 540W, Leisure 550A, Leisure 550W, Cinemango 100A, Cinemango 100W, Cinemango 110A, Cinemango 110W, Cinemango 120A, Cinemango 120W
TEST SAMPLE:	Engineering Sample
APPLICANT:	Shenzhen VanTop Technology & Innovation Co., Ltd.
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1

Note: Additional models (see above table) are identical with the test model Leisure 470 except the model name for trading purpose.

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	2	Wire Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
802.11b	2412-2462	14	+2	12	16
802.11g	2412-2462	15	+2	13	17
802.11n(HT20)	2412-2462	14	+2	12	16
802.11n(HT40)	2422-2462	15	+2	13	17

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
802.11b	2462	14.88
802.11g	2462	15.69
802.11n(HT20)	2437	14.69
802.11n(HT40)	2437	15.56

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412-2462	17	2	20	0.015803	1.0

--- END ---