

TEST REPORT

Report No.:	8229EU010707W2
Applicant:	QUEST USA CORP
Address:	495 Flatbush Ave, Brooklyn, NY 11225, USA
Product Name:	2 in 1 Wireless Magnetic Charging Station
Model No.:	IJ1031-DG (refer to clause 2.4)
Trademark:	IJOY
FCC ID:	2AJQ7ELITE
Test Standard(s):	47 CFR Part 1 Subpart I Section 1.1310
Date of Receipt:	May 07, 2024
Test Date:	May 07, 2024 – Aug. 28, 2024
Date of Issue:	Aug. 28, 2024

ISSUED BY: SHENZHEN EU TESTING LABORATORY LUNTE

Prepared by:

Reviewed and Approved by:

TING LABOR

ROVED

Mikey zhu

Mikey Zhu/ Engineer

Sally zhang

Sally Zhang/ Manager

SHENZHEN EU TESTING LABORATORY LIMITED



Revision Record

Report Version	Issued Date	Description	Status
V0	Aug. 28, 2024	Original	Valid



SHENZHEN EU TESTING LABORATORY LIMITED



Table of Contents

1	COVER PAGE	1
2	GENERAL INFORMATION	4
	2.1 APPLICANT INFORMATION 2.2 MANUFACTURER INFORMATION 2.3 FACTORY INFORMATION 2.4 GENERAL DESCRIPTION OF E.U.T 2.5 TECHNICAL INFORMATION OF E.U.T	4 4 4 5
3	TEST SUMMARY	6
	3.1 TEST STANDARD 3.2 TEST VERDICT 3.3 TEST LABORATORY	6 6 6
4	TEST CONFIGURATION	7
	4.1 TEST ENVIRONMENT 4.2 TEST EQUIPMENT 4.3 TEST MODE	7 7 8
5	RF EXPOSURE EVALUATION	9
	5.1 TEST REQUIREMENT 5.2 TEST SETUP 5.1 EVALUATION RESULT	9 10 11
ANNE	X A TEST SETUP PHOTOS	12

SHENZHEN EU TESTING LABORATORY LIMITED



2 General Information

2.1 Applicant Information

Applicant	QUEST USA CORP
Address	495 Flatbush Ave, Brooklyn, NY 11225, USA

2.2 Manufacturer Information

Manufacturer	Shenzhen Willsoon Electronic Technology Co., Ltd	
Address	5/F Block A,No.10 East Area Shangxue Industrial Area,Bantian Town,Longgang District,Shenzhen,Guangdong,China	

2.3 Factory Information

Factory	Shenzhen Willsoon Electronic Technology Co., Ltd	
Address	5/F Block A,No.10 East Area Shangxue Industrial Area,Bantian Town,Longgang District,Shenzhen,Guangdong,China	

2.4 General Description of E.U.T.

Product Name	2 in 1 Wireless Magnetic Charging Station	
Model No. Under Test	IJ1031-DG	
List Model No.	IJPDQ363-DG, IJ10310-DG, IJ10226-FB, IJ10227-FB, IJAST203-FB, IJ10310-DG	
Depaription of Model	All models are same with electrical parameters and internal circuit structure, but	
differentiation	only differ in appearance color and model name.	
	(this information provided by the customer)	
	Input: 5V==3A; 9V==3A	
Rating(s)	Total Output: 15W(Max)	
(utilig(s)	Wireless output for Phone: 15W(Max)	
	Wireless output for Earbuds: 5W(Max)	
	⊠ Mobile	
Product Type	Portable	
	Fix Location	
Test Sample No.	-1/1(Normal Sample)	
Hardware Version	N/A	
Software Version	N/A	
Remark	For a more detailed features description, please refer to the manufacturer's	
Romany	specifications or the User's Manual.	

SHENZHEN EU TESTING LABORATORY LIMITED



2.5 Technical Information of E.U.T.

Technology Used	Wireless Power Transfer (WPT)		
The requirement for the following technical information of the EUT was tested in this report:			
Technology WPT			

Operating Frequency	110.1-205 kHz
Modulation Type	FSK
Antenna Type	Coil Antenna
Antenna Gain(Peak)	0 dBi



SHENZHEN EU TESTING LABORATORY LIMITED



3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

No.	Identity	Document Title
1	47 CFR Part 1 Subpart I Section 1.1310	Radio frequency radiation exposure limits.
2	KDB 680106 D01v04	RF exposure consideration for low power consumer wireless power transfer applications.

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

3.2 Test Verdict

No.	Description	FCC Part No.	Verdict	Remark
1	RF Exposure Evaluation	FCC 1.1310 KDB 680106 Section 5.2	Pass	

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Designation Number	CN1368
Test Firm Registration Number	952583

SHENZHEN EU TESTING LABORATORY LIMITED

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%				
Atmospheric Pressure	86 kPa to 106 kPa				
Temperature	NT (Normal Temperature)	+15℃ to +35℃			
Working Voltage of the EUT	NV (Normal Voltage)	AC 120V/60Hz			

4.2 Test Equipment

Conducted Emission at AC power line							
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date		
Electric and Magnetic Field Probe - Analyzer	Narda	EHP-200A	EE-405	2024/02/15	2025/02/14		



SHENZHEN EU TESTING LABORATORY LIMITED



4.3 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was prescanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned bellow was evaluated respectively.

No.	Description	Remark
TM1	Wireless Output (5W for Phone)	
TM2	Wireless Output (7.5W for Phone)	
TM3	Wireless Output (10W for Phone)	
TM4	Wireless Output (15W for Phone)	
TM5	Wireless Output (5W for Earbuds)	
TM6	Wireless Output (10W for Phone + 5W for Earbuds)	
Note:		

1. All the conditions have been tested. It is found that TM6 is the worst mode, and the data in the report only reflects the worst mode.



SHENZHEN EU TESTING LABORATORY LIMITED



5 RF Exposure Evaluation

5.1 Test Requirement

KDB 680106 D01 Wireless Power Transfer v04:

According to the item 5.2 of KDB 680106 D01v04:

Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

- Power transfer frequency is less than 1 MHz.
 YES. The device operates in the frequency range from 115-205kHz.
- b) The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts. YES. The maximum output power of the primary coil is 15W.
- c) A client device providing the maximum permitted load is placed in physical contact with the transmitter(i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)

YES. The transfer system includes only single primary and secondary coils.

- d) Client device is placed directly in contact with the transmitter.
 YES. Client device is placed directly in contact with the transmitter.
- e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion) YES. The EUT is a Wireless Charging mobile.
- f) The aggregate H-field strengths anywhere at or beyond 20 cm surrounding the device, and 20cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit. YES. The EUT field strength levels are less than 50% X MPE limit.

TABLE 1-LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
	(A) Limits for O	ccupational/Controlled Exp	osure	
0.3-3.0	614	1.63	*100	6
3.0-30	1842/1	f 4.89/i	f *900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
	(B) Limits for Gene	ral Population/Uncontrolled	Exposure	•
0.3-1.34	614	1.63	*100	30
1.34-30	824/1	f 2.19/i	f *180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

SHENZHEN EU TESTING LABORATORY LIMITED



5.2 Test Setup



- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at test distance (20cm) which is between the edge of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E, F) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 v04.

SHENZHEN EU TESTING LABORATORY LIMITED



5.1 Evaluation Result

					· · · · · · · · · · · · · · · · · · ·	
Lest Condition.	Lest Mode h or	erating with	Client device i	natter\	/ status of client d	evicei
					, status or onorit a	
				\		

	E-field (//m)			H-field (A/m)		
Test Position	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Тор	3.0910			0.1318		
Bottom	3.7608			0.1345		
Front	1.5793	614	0.940/	0.1026	1.62	14 100/
Rear	5.1471	014	0.04%	0.2299	1.03	14.10%
Left	2.4104			0.0597		
Right	3.8241			0.1490		

Test Condition: Test Mode 6 operating with client device (50% battery status of client device)

Test Desition	E-field (V/m)			H-field (A/m)			
Test Position	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)	
Тор	2.6974			0.0757			
Bottom	3.6061			0.1396			
Front	0.9176	614 0.804	614	0.90%	0.0044	1.62	12 940/
Rear	4.9065		0.00%	0.2256	1.05	13.04 %	
Left	2.5370			0.0859			
Right	3.1616			0.0796			

Test Condition: Test Mode 6 operating with client device (99% battery status of client device)

	E-field				H-field	
Tost Position		(V/m)		(A/m)		
Test Fosition	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Тор	2.4276			0.0428		
Bottom	3.4123			0.1812		
Front	1.4700	614	0.82%	0.1208	1.63	20 60%
Rear	5.0315	014	0.02 /0	0.3358	1.05	20.00 %
Left	2.2849			0.1243		
Right	3.4766			0.1226		

SHENZHEN EU TESTING LABORATORY LIMITED



ANNEX A TEST SETUP PHOTOS





SHENZHEN EU TESTING LABORATORY LIMITED



Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.

2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.

3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.

4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.

5. The test data and results are only valid for the tested samples provided by the customer.

6. This report shall not be partially reproduced without the written permission of the laboratory.

7. Any objection shall be raised to the laboratory within 30 days after receiving the report.



SHENZHEN EU TESTING LABORATORY LIMITED