



FCC LISTED, REGISTRATION
NUMBER: 2764.01

ISED LISTED REGISTRATION
NUMBER: 23595-1

Test report No:
3231ERM.011

Partial Test report

**USA FCC Part 15.247, 15.407 15.209, 15.207
CANADA RSS-247, RSS-Gen**

(*) Identification of item tested	In vehicle infotainment
(*) Trademark	Visteon
(*) Model and /or type reference tested	CRONY 2010
Other identification of the product	FCC ID: NT8-CRONY2010
(*) Features	AM/FM receiver, BT EDR, WiFi@5 GHz 802.11a/n20/n40/ac80, GNSS/GPS
Manufacturer	VISTEON CORPORATION One Village Center Drive, Van Buren Township, MI 48111, USA.
Test method requested, standard	USA FCC Part 15.247, 10-1-20 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz USA FCC Part 15.407 10-1-20 Edition : Unlicensed National Information Infrastructure Devices. General technical requirements. USA FCC Part 15.209 10-1-20 Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5 (April 2018). 558074 D01 15.247 Meas Guidance v05r02. Guidance for Compliance Measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under section §15.247 of the FCC Rules ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Domingo Galvez EMC&RF Lab Manager
Date of issue	02-15-2022
Report template No	FDT08_23 (*) "Data provided by the client"

Index

Competences and guarantees3

General conditions3

Uncertainty3

Data provided by the client.....4

Usage of samples.....4

Test sample description5

Identification of the client.....6

Testing period and place6

Document history6

Environmental conditions7

Remarks and comments7

Testing verdicts8

Summary8

List of equipment used during the test10

Appendix A: FCC Multi-transmitters Test Results11

Competences and guarantees

DEKRA Certification Inc. is a testing laboratory accredited by A2LA (The American Association for Laboratory Accreditation), to perform the tests indicated in the Certificate 2764.01

DEKRA Certification Inc. is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA Certification Inc. has a calibration and maintenance program for its measurement equipment.

DEKRA Certification Inc. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Certification at the time of performance of the test.

DEKRA Certification Inc. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Certification Inc.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Certification Inc.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Certification Inc. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Certification internal document PODT000.

Test case	Frequency (MHz)	U ($k=2$)	Units
Radiated Spurious Emission	30-180	4.27	dB
	180-1000	3.14	dB
	1000-18000	3.30	dB
	18000-40000	3.49	dB

Data provided by the client

An in-vehicle infotainment system that combines entertainment and information delivery for driver and passengers. This system consists of features like AM/FM Radio, GPS, RVC, USB & BT/WiFi interfaces with 10.25 Inch TFT & Touch screen interface.

This Infotainment can allow a driver to perform a number of tasks, such as standard radio and listen to music over a USB flash drive or Bluetooth, hands-free phone connections to make phone calls, vehicle voice commands, and other types of Interactive audio or video.

DEKRA declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Usage of samples

Samples used for test have been selected by: The client.

Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
3231/11	Radiated sample	VPNPLF-18C815-CB	-	12/17/2021
3231/35	Harness + Speaker board	PSSA-AEE2010	-	12/17/2021


Sample S/01 is composed of the following accessories:

Control N°	Description	Model	Serial N°	Date of reception
3231/16	Antenna	A0056I-01	-	12/17/2021
3231/21	USB type A (Male) to DB9 cable	-	-	12/17/2021
3231/30	Adapter USB 3.0 to Gigabit Ethernet	UE300	-	12/17/2021

1. Sample S/01 was used for the following test(s): All Radiated tests indicated in appendix A.

Test sample description

Ports..... :	Port name and description	Cable				
		Specified length [m]	Attached during test	Shielded	Coupled to patient	
	Main connector		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
	USB OTG		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
	GPS Antenna FAKRA connector		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
	AM/FM Antenna FAKRA connector		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Supplementary information to the ports..... :	No Data Provided					
Rated power supply	Voltage and Frequency	Reference poles				
		L1	L2	L3	N	PE
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input checked="" type="checkbox"/>	DC: 13.5 V vehicle battery				
	<input type="checkbox"/>	DC:				
Rated Power	Nominal current 3A					
Clock frequencies.....	DDR3 800 MHz, NAND Memory 100 MHz, TFT 298.5 kHz, LVDS 39.4 MHz, IMX8 1,2 GHz					
Other parameters	No Data Provided					
Software version	26381					
Hardware version	08.01.01					
Dimensions in cm (W x H x D)	(285.2 x 135.5 x 197.5) mm					
Mounting position	<input type="checkbox"/>	Table top equipment				
	<input type="checkbox"/>	Wall/Ceiling mounted equipment				
	<input type="checkbox"/>	Floor standing equipment				
	<input type="checkbox"/>	Hand-held equipment				
	<input checked="" type="checkbox"/>	Other: Installed in vehicle dashboard				
Modules/parts..... :	Module/parts of test item	Type		Manufacturer		
	Commercial samples					
	Radiated samples					
	Conducted samples					

Accessories (not part of the test item)	Description	Type	Manufacturer
	Harness		
	AM/FM Antenna		
	GPS antenna		
	Speakers		
	Test panel		
	USB convertors		
Documents as provided by the applicant.....	Description	File name	Issue date
	Declaration Equipment	FDT30_18 Declaration Equipment Data 12/17/2021	01/06/2022
	General description Crony 2010		01/06/2022
	FERMUSA201_0 test samples Quesionnaire		
Copy of marking plate:			
			

Identification of the client

VISTEON CORPORATION
One Village Center Drive
Van Buren Township, MI 48111, USA

Testing period and place

Test Location	DEKRA Certification, Inc.
Date (start)	01-19-2022
Date (finish)	01-25-2022

Document history

Report number	Date	Description
3231ERM.011	02-15-2022	First release

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the semi anechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 60 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

Remarks and comments

The tests have been performed by the technical personnel: Nasir Khan, Koji Nishimoto & Lourdes Maria Valverde

Testing verdicts

Not applicable :	N/A
Pass :	P
Fail :	F
Not measured :	N/M

Summary

FCC PART 15 PARAGRAPH / RSS-247 (Bluetooth EDR)					
Section	15.247 Spec Clause	RSS Spec Clause	Test Description	Verdict	Remark
-	§ 2.1049 & § 15.247 (a) (1)	RSS-247 5.1 (b)	20dB Emission Bandwidth, Occupied Bandwidth & Carrier Frequency Separation	N/M	Refer 1
-	§ 15.247 (a) (1) (iii)	RSS-247 5.1 (d)	Number of hopping channels	N/M	Refer 1
-	§ 15.247 (a) (1) (iii)	RSS-247 5.1 (d)	Time of Occupancy (Dwell Time)	N/M	Refer 1
-	§ 15.247 (b) (3)	RSS-247 5.4 (b)	Maximum peak conducted output power and antenna gain	N/M	Refer 1
-	§ 15.247 (d)	RSS-247 5.5	Band-edge conducted emissions compliance (Transmitter)	N/M	Refer 1
-	§ 15.247 (d)	RSS-247 5.5	Emission limitations Conducted (Transmitter)	N/M	Refer 1
A.1	§ 15.247 (d)	RSS-247 5.5	Emission limitations Radiated (Transmitter)	P	N/A
<u>Supplementary information and remarks:</u> 1) Only multi-transmitter radiated spurious emission test was requested.					

FCC PART 15 PARAGRAPH / RSS-247 (WIFI 5GHz) 5.725 GHz -5.825 GHz Band					
Report Section	15.407 Spec Clause	RSS Spec Clause	Test Description	Verdict	Remark
-	§ 15.403 KDB 789033 D02	RSS 247 6.2.4	26dB Emission Bandwidth & Occupied Bandwidth	N/M	Refer 1
-	§ 15.407 (e)	RSS 247 6.2.4.1	6dB Bandwidth	N/M	Refer 1
-	§ 15.407 (a)(3)	RSS 247 6.2.4.1	Power Limits. Maximum Output Power	N/M	Refer 1
-	§ 15.407 (a)(3)	RSS-247 6.2.4.1	Maximum Power Spectral Density	N/M	Refer 1
-	§ 15.407 (b)(4)	RSS-247 6.2.4.2	Band-edge conducted emissions compliance (Transmitter)	N/M	Refer 1
-	§ 15.407 (b)(6) § 15.207	RSS-Gen 8.8	Emission limitations Conducted (Transmitter)	N/M	Refer 1
A.1	§ 15.407 (b)(4),(7) § 15.209 § 15.205	RSS-247 6.2.4.2 RSS-Gen 8.9 & 8.10	Undesirable radiated emissions (Transmitter)	P	N/A
-	§ 15.407 (g)	RSS-Gen 6.11 & 8.11	Frequency Stability	N/M	Refer 1
Supplementary information and remarks:					
1) Only multi-transmitter radiated spurious emission test was requested.					

List of equipment used during the test

Radiated Measurements

CONTROL NUMBER	DESCRIPTION	MANUFACTURER	MODEL	LAST CALIBRATION	NEXT CALIBRATION
0981	RF pre-amplifier 1-18 GHz	Bonn Elektronik	BLMA 0118-2A	2020/11	2022/11
0982	RF pre-amplifier 18-40 GHz	Bonn Elektronik	BLMA 1840-1M	2020/11	2022/11
1010	ESR7 EMI Test Receiver	Rohde & Schwarz	ESR7	2020/10	2022/10
1014	FSV40 Signal Analyzer 40GHZ	Rohde & Schwarz	FSV40	2021/05	2023/05
1055	3116C DOUBLE-RIDGED WAVEGUIDE HORN ANTENNAS	ETS LINDGREN	3116C	2019-12-09	2022-12-09
1056	Double-ridge Waveguide Horn antenna 18-40 GHz	ETS LINDGREN	3116C	2020/01	2023/01
1057	Double-ridge Waveguide Horn antenna 1-18 GHz	ETS LINDGREN	3115	2020/06	2023/06
1065	Biconical Log antenna	ETS LINDGREN	3142E	2020/08	2023//08
1111	ETHERNET SNMP THERMOMETER	HW GROUP	HWg-STE Plain	2020/08	2022/08
1179	Semi anechoic Absorber Lined Chamber	Frankonia	SAC 3 plus "L"	N/A	N/A

Appendix A: FCC Multi-transmitters Test Results

Appendix A Content

PRODUCT INFORMATION 13

Description of Test Conditions 14

A.1: RADIATED EMISSIONS (Multi-Transmitters) 15

PRODUCT INFORMATION

Information	Description
Modulation	BR/EDR: GFSK, $\pi/4$ -DQPSK, 8DPSK Wi-Fi 5 GHz: OFDM
Operation mode 1: Single Antenna Equipment	
- Operating Frequency Range	BR/EDR: 2402 - 2480 MHz Wi-Fi 5 GHz: 5745 - 5825 MHz
- Nominal Channel Bandwidth	BR/EDR: 1 MHz Wi-Fi 5 GHz: 20/40/80 MHz
- RF Output Power	BR/EDR: 9.8 dBm Wi-Fi 5 GHz: 14 dBm
Extreme operating conditions	
- Temperature range	-
Antenna type	Automotive Chip Antenna 2,4/5 GHz
Antenna gain	BR/EDR: 3.2 dBi Wi-Fi 5 GHz: 3.5 dBi
Nominal Voltage	
- Supply Voltage	13.5 Vdc
- Type of power source	DC voltage
Equipment type	Bluetooth, and Wi-Fi 5 GHz
Geo-location capability	-

Description of Test Conditions

TEST CONDITIONS	DESCRIPTION												
TC#01 ⁽¹⁾	<u>Power supply (V):</u> 13.5 Vdc												
	<u>Test Frequencies for Radiated tests:</u>												
	<table><tr><th>Technology</th><th>Tested Frequency</th><th>BW</th><th>Modulation</th></tr><tr><td>BR/EDR</td><td>2402</td><td>1</td><td>GFSK</td></tr><tr><td>Wi-Fi 5 GHz</td><td>5745</td><td>20</td><td>OFDM</td></tr></table>	Technology	Tested Frequency	BW	Modulation	BR/EDR	2402	1	GFSK	Wi-Fi 5 GHz	5745	20	OFDM
	Technology	Tested Frequency	BW	Modulation									
	BR/EDR	2402	1	GFSK									
Wi-Fi 5 GHz	5745	20	OFDM										
The test was performed with the equipment transmitting with Bluetooth and Wi-Fi 5GHz radios simultaneously. These measurements have been performed in order to check the impact of the multi-transmitter of all radio interfaces that can be transmitting simultaneously.													

Note : Preliminary scan was performed to determine the worst case in Bluetooth and Wi-Fi 5 GHz. The following tables and plots show the results for the worst case in Bluetooth + Wi-Fi 5 GHz

A.1: RADIATED EMISSIONS (Multi-Transmitters)

LIMITS:	Product standard:	Part 15 Subpart C §15.247, Part 15 Subpart E §15.407 and RSS-247
	Test standard:	Part 15 Subpart C §15.247 (d), Part 15 Subpart E §15.407 (b) (1) & (4) and RSS-Gen 8.9 and 8.10

LIMITS

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength (µV/m)	Field strength (dBµV/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required

TEST SETUP

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at 3 m for the frequency range 30-1000 MHz (Bilog antenna) and 1-18 GHz (Double ridge horn antenna, and at 1m for the frequency range 18-40 GHz (Double ridge horn antenna).

For radiated emissions in the range 18-40 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.


The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

TEST SETUP (CONT.)


Radiated measurements Setup $f < 1$ GHz



Radiated measurements setup $1 \text{ GHz} < f < 18 \text{ GHz}$




Radiated measurements setup $f > 18 \text{ GHz}$



TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#01
TEST RESULTS:	PASS

Frequency range 30 MHz – 1000 MHz

RF_FCC_15.247_E Field_30MHz_1GHz




- PK+_MAXH
- PK+_CLRWR
- TX limits to Spurious Emission FCC15.247 (30MHz to 1GHz) Restricted Bands QPK Limit
- ▽ MaxPeak-PK+ (Single)
- × QuasiPeak-QPK (Single)

Frequency (MHz)	MaxPeak (dBμV/m)	QuasiPeak (dBμV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBμV/m)
163.035500	28.3	17.4	V	26.2	43.5
239.035000	44.8	32.1	H	---	---
330.021000	24.0	13.6	H	32.4	46.0
600.020500	42.4	39.4	V	---	---
797.997500	46.4	41.7	V	---	---
1000.000000	41.5	36.2	V	17.8	54.0

TEST RESULTS (Cont.):

FREQUENCY RANGE: 1-18 GHz




— AVG_MAXH
— PK+_MAXH
— TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
— TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBμV/m)	AVG_MAXH (dBμV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBμV/m)	Comment
2402.500000	96.1	92.0	H	---	---	Fundamental BT
5748.000000	95.9	87.2	H	---	---	Fundamental WiFi
18000.000000	52.2	42.5	H	11.5	54.0	

TEST RESULTS (Cont.):

FREQUENCY RANGE: 18-40 GHz




- AVG_MAXH
- PK+_MAXH
- TX limits to Spurious Emission FCC15.407 (1GHz to 40 GHz) Restricted Bands PK Limit
- TX limits to Spurious Emission FCC15.407 (1GHz to 40 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBμV/m)	AVG_MAXH (dBμV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBμV/m)
39988.312500	51.6	40.6	H	13.4	54.0

EST RESULTS (Cont.):

Restricted bands (2.31 GHz – 2.5 GHz)



- AVG_MAXH
- PK+_MAXH
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit