

Xiamen Joint Tech. Co., Ltd

MPE ASSESSMENT REPORT

Report Type:

FCC Part §2.1091, §2.1093 and §1.1307(b) assessment report

Model:

JNT-EVCXX/XXAC/XXC/XX/XX

REPORT NUMBER:

220302432SHA-005

ISSUE DATE:

January 6, 2023

DOCUMENT CONTROL NUMBER:

TTRFFCCMPE-01_V1 © 2018 Intertek



Applicant: Xiamen Joint Tech. Co., Ltd
Building #1, No. 268 HouXiang Rd,Xinyang Industrial Park, Haicang District, XIAMEN Fujian

Manufacturer: Xiamen Joint Tech. Co., Ltd
Building #1, No. 268 HouXiang Rd,Xinyang Industrial Park, Haicang District, XIAMEN Fujian

Manufacturing Site: Xiamen Joint Tech. Co., Ltd
Building #1, No. 268 HouXiang Rd,Xinyang Industrial Park, Haicang District, XIAMEN Fujian

Product Name: Electric Vehicle AC Charger

Type/Model: JNT-EVCxx/xxAC/xxC/xx/xx

FCC ID: 2A2RN-ACEVCN22P3

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:

Project Engineer

Dylan Tang

REVIEWED BY:

Reviewer

Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
220302432SHA-005	Rev. 01	Initial issue of report	January 6, 2023

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Electric Vehicle AC Charger
Type/Model:	JNT-EVCXX/XXAC/XXC/XX/XX "XX"denotes Wattage,can be 16=16A, 32=32A, 40=40A,48=48A. "XX"denotes Outlet type,can be 01=type 1 "XX"denotes Colour, can be SR=Silver, RD=Red, BK=Black, BU=Blue or other colour. "XX"denotes Function, can be RF/WF=RFID+WiFi.
Description of EUT:	The EUT is Electric Vehicle AC Charger with RFID Function, it supports WIFI function, the wireless modular FCC ID is 2AC7Z-ESPWROOM32. There are some series models and they are same except the appearance. So choose JNT-EVC15/XXAC/XXC/XX/XX to test as representative.
Rating:	200-240V ~ 60Hz
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	N2P3_H_1.0.0
Hardware Version:	N2-2P3
Serial numbers:	0230106-43-001(for radiation sample)
Sample received date:	November 1, 2022
Date of test:	November 1, 2022 ~ December 28, 2022

1.2 Technical Specification

Frequency Range:	13.56 MHz ~ 13.56 MHz
Modulation:	ASK
Antenna gain:	3dBi

TEST REPORT

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 MPE Assessment

Test result: Pass

2.1 MPE Assessment Limit

Mobile device exposure for standalone operations:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: Limit for 13.56MHz is 60.77 V/m

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0**

TEST REPORT

2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm²

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report 220801138SHA-001:

$$59.20\text{dBuV/m}@3\text{m}, @20\text{cm}=@3\text{m}+40\log(3/0.2)=99.84\text{dBuV/m}=0.205\text{V/m}<60.77.$$

The power for WIFI modular refer certificate of FCC ID: 2AC7Z- ESPWROOM32

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Frequency band	Power		Antenna Gain	R	S	Limits
(MHz)	dBm	mW	dBi	(cm)	(mW/cm ²)	(mW/cm ²)
2412 - 2462	16.62	45.92	2	20	0.018	1

Note: 1 mW/cm² from 1.310 Table 1.

RFID and WIFI Module can simultaneous transmitting, so the maximum rate of MPE is,
 $0.205/60.77+0.018/1=0.0214\leq 1.0$.

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.

*****END*****