

## FCC RF EXPOSURE REPORT

For

**Robotic Vacuum Cleaner** 

### MODEL NUMBER: RRE0VIC

### SERIES MODEL NUMBER: RRE0VCM

PROJECT NUMBER: 4791489429

### **REPORT NUMBER: 4791489429-2**

FCC ID: 2AN2O-RRE0VIC01

### **ISSUE DATE: Nov. 28, 2024**

Prepared for

Beijing Roborock Technology Co., Ltd.

Prepared by

UL-CCIC COMPANY LIMITED No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China Tel: +86 512-6808 6400 Fax: +86 512-6808 4099 Website: www.ul.com



### **Revision History**

Rev.	Issue Date	Revisions	Revised By
V0	11/28/2024	Initial Issue	

Form-ULID-008536-13 V3.0



# TABLE OF CONTENTS

1.	APPLICANT INFORMATION	.4
2.	TEST METHODOLOGY	.5
3.	FACILITIES AND ACCREDITATION	.5
4.	MEASUREMENT UNCERTAINTY	.6
5.	REQUIREMENT	.7



## **1. APPLICANT INFORMATION**

#### **Applicant Information**

Company Name:	Beijing Roborock Technology Co., Ltd.
Address:	Room 1001, Floor 10, Building 3, Yard 17, Anju Road,
	Changping District, Beijing, P.R. China
Manufacturer Information	
Company Name:	Beijing Roborock Technology Co., Ltd.
Address:	Room 1001, Floor 10, Building 3, Yard 17, Anju Road,
	Changping District, Beijing, P.R. China
EUT Description	
Product Name:	Robotic Vacuum Cleaner
Model Name:	RREOVIC
Series Model Name:	RRE0VCM
Model Difference:	RREOVCM has the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction with RREOVIC. The difference lies model number for marketing purposes. All these changes do not degrade the unwanted emissions of the certified product. Difference models of Robotic Vacuum Cleaner will sale with difference dock.
Sample Number: Data of Receipt Sample: Test Date:	7802359-S001 Nov. 08, 2024 Nov. 08, 2024~ Nov. 27, 2024

#### APPLICABLE STANDARDS

STANDARD

**TEST RESULTS** 

FCC Guidelines for Human Exposure IEEE

C95.1

Complies

Prepared By:

Reviewed By:

Tom Tang

Tom Tang

Authorized By:

Kenn. Shen

Kevin Shen

itevieweu by.

Emily Waney

**Emily Wang** 



# 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 1 Subpart I, section 1.1307 and KDB 447498 D04 Interim General RF Exposure Guidance v01.

# 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 25056; CAB No.: CN0073) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.
------------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China.

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.



## 4. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty					
Output Power to Antenna	1.3 dB					
Note: This uncertainty represents an expanded uncertainty expressed at approximately the $95\%$ confidence level using a coverage factor of k=2.						



# 5. REQUIREMENT

#### LIMIT AND CALCULATION METHOD

According to 447498 D04 Interim General RF Exposure Guidance v01,

#### 2.1.4 MPE-Based Exemption

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.10 For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

#### B.4 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of  $\lambda/4$ .

As for devices with antennas of length greater than  $\lambda/4$  where the gain is not well defined, but always less than that of a half-wave dipole (length  $\lambda/2$ ), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known. The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula (B.2).



### **MPE-based Exemption**

$$P_{\rm th} (\rm mW) = ERP_{20 \,\rm cm} (\rm mW) = \begin{cases} 2040f & 0.3 \,\rm GHz \le f < 1.5 \,\rm GHz \\ 3060 & 1.5 \,\rm GHz \le f \le 6 \,\rm GHz \end{cases}$$
(B.1)

$$P_{\rm th} (\rm mW) = \begin{cases} ERP_{20 \,\rm cm} (d/20 \,\rm cm)^x & d \le 20 \,\rm cm \\ \\ ERP_{20 \,\rm cm} & 20 \,\rm cm < d \le 40 \,\rm cm \end{cases}$$
(B.2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\,\mathrm{cm}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP<sub>20cm</sub> is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

		Distance (mm)										
equency (MHz)		5	10	15	20	25	30	35	40	45	50	
	300	39	65	88	110	129	148	166	184	201	217	
	450	22	44	67	89	112	135	158	180	203	226	
	835	9	25	44	66	90	116	145	175	207	240	
	1900	3	12	26	44	66	92	122	157	195	236	
	2450	3	10	22	38	59	83	111	143	179	219	
Fr	3600	2	8	18	32	49	71	96	125	158	195	
	5800	1	6	14	25	40	58	80	106	136	169	

 Table B.2—Example Power Thresholds (mW)

#### Fixed RF sources operating in the same time-averaging period- § 1.1307(b)(3)(ii)(B)

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated term) shall be used to determine exemption for simultaneous transmission according to Formula (C.1) [repeated from § 1.1307(b)(3)(ii)(B)].

$$\sum_{i=1}^{a} \frac{P_i}{P_{\text{th},i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{\text{th},j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$
(C.1)

Form-ULID-008536-13 V3.0



### **CALCULATED RESULTS**

Operating	Max. Tune up Power	Max. Antenna Gain	EIRP	ERP	ERP	Distance	Limit Threshold
Mode	(dBm)	(dBi)	(dBm)	(dBm)	(mW)	(cm)	(mW)
WiFi 2.4GHz	17.5	2.11	19.61	17.46	55.72	20	3060

Note:

- 1. The output power is from operation description.
- 2. The minimum separation distance of the device is greater than 20 cm.
- 3. All the channels had been tested, but only the worst data was recorded in the report.
- 4. The calculated result for the sample received is < Pass > according to < 47 CFR FCC Part 2 Subpart J, section 2.1091 > when < Simple Acceptance > decision rule is applied.

# END OF REPORT

Form-ULID-008536-13 V3.0