

Spot Check Evaluation

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : POCO
MODEL NAME : 25028PC03G
FCC ID : 2AFZZPC03G
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(L), 27(M), 90(S)
47 CFR Part 15 Subpart C §15.247
47 CFR Part 15 Subpart E §15.407
TEST DATE(S) : Jan. 03, 2025 ~ Jan. 13, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY	3
1 GENERAL DESCRIPTION	4
1.1 Applicant	4
1.2 Manufacturer	4
1.3 Product Feature of Equipment Under Test	4
1.4 Modification of EUT	4
1.5 Testing Site	5
1.6 Test Software	5
1.7 Applicable Standards	5
2 RE-USE OF MEASURED DATA	6
2.1 Introduction Section	6
2.2 Model Difference Information	6
2.3 Reference detail Section:	7
2.4 Spot Check Verification Data Section	8
3 LIST OF MEASURING EQUIPMENT	12
4 MEASUREMENT UNCERTAINTY	14
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
4D0203-02	Rev. 01	Initial issue of report	Jan. 20, 2025

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	POCO
Model Name	25028PC03G
FCC ID	2AFZZPC03G
IMEI Code	Conducted: 866361070007280/866361070007298 Radiation: 866361070009765/866361070009773
HW Version	135100C3Z
SW Version	Android 15
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH04-KS 03CH05-KS TH01-KS	CN1257	314309

1.6 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH04-KS	AUDIX	E3	210616
3.	03CH05-KS	AUDIX	E3	210616
4.	DFS01-KS	Sporton	Test Tools	1.0
5.	CO01-KS	AUDIX	E3	6.2009-8-24

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB 484596 D01 Referencing Test Data v02r03
- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L), 27(M), 90(S)
- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ 47 CFR Part 15 Subpart E §15.407
- ♦ ANSI C63.10-2013
- ♦ ANSI C63.26-2015

2 Re-use of Measured Data

2.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: 25028PC03G, FCC ID: 2AFZZPC03G) is electrically identical to the reference device (Model: 25028RN03L, FCC ID: 2AFZZRN03L) for the portions of the circuitry corresponding to the data being re-used, following the FCC KDB 484596 D01 Referencing Test Data v02r03.

ECR Data Referencing Inquiry has been approved by FCC, and the data referencing and spot check test plan includes RF/EMC, the details are presented in section 2.3 of this report, and for SAR Reference detail, please refer to FCC SAR report FA4D0203-02.

The criteria set in section 3 of KDB 484596 D01 v02r03 is followed to determine whether the data referencing is justified. For SAR, the higher between the referenced value and the spot check value is used to determine compliance in both standalone and simultaneous transmission conditions

The applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID: 2AFZZPC03G .

2.2 Model Difference Information

The **main** difference between FCC ID: 2AFZZRN03L and FCC ID: 2AFZZPC03G is as below:

- Remove LTE B13.
- Add LTE B20.

Other differences and all the details of similarity and difference can be found in the confidential documents (2AFZZPC03G Operational Description of Product Equality Declaration).



2.3 Reference detail Section:

Rule Part	Equipment Class	Frequency Band (MHz)	Reference FCC ID (Parent)	Reference on test	Reference Title	FCC ID Filling (Variant)	Test on the variant	Data Referencing (Y/N)
15C	DSS (BR/EDR)	2400~2483.5	2AFZZRN03L	Full test	FR4D0203A	2AFZZPC03G	Spot check	Y, All test items
	DTS (BLE)	2400~2483.5	2AFZZRN03L	Full test	FR4D0203B	2AFZZPC03G	Spot check	Y, All test items
	DTS (WLAN)	2400~2483.5	2AFZZRN03L	Full test	FR4D0203C	2AFZZPC03G	Spot check	Y, All test items
15E	U-NII	5180~5240	2AFZZRN03L	Full test	FR4D0203D	2AFZZPC03G	Spot check	Y, All test items
		5260~5320	2AFZZRN03L	Full test	FR4D0203D	2AFZZPC03G	Spot check	Y, All test items
		5500~5700	2AFZZRN03L	Full test	FR4D0203D	2AFZZPC03G	Spot check	Y, All test items
		5745~5825	2AFZZRN03L	Full test	FR4D0203D	2AFZZPC03G	Spot check	Y, All test items
		5260~5320 5500~5700	2AFZZRN03L	Full test	FZ4D0203	2AFZZPC03G	Spot check	Y, All test items
22, 24, 27, 90,	PCE (GSM)	GSM 850/1900	2AFZZRN03L	Full test	FG4D0203A	2AFZZPC03G	Spot check	Y, All test items
	PCE (WCDMA)	Band II, IV, V	2AFZZRN03L	Full test	FG4D0203A	2AFZZPC03G	Spot check	Y, All test items
	PCE (LTE)	B2/4/5/7/26/38/41/66	2AFZZRN03L	Full test	FG4D0203B	2AFZZPC03G	Spot check	Y, All test items
	PCE (LTE)	B26 (90S)	2AFZZRN03L	Full test	FG4D0203C	2AFZZPC03G	Spot check	Y, All test items

Y: Pointer to spot-check exhibit; N: Pointer to full test exhibit

2.4 Spot Check Verification Data Section

All test items test against the variant model based on the worst-case condition from the original model was performed in this filing to demonstrate the test data from original model remains representative for the variant model.

All test procedures follow the related section of parent report.

Spot-check measurements, while being always compliant with the applicable rule part(s) for the test under consideration, show a deviation d_{dB} from the reference data no larger than 3 dB:

$$d_{dB} = |V_{dB} - R_{dB}| \leq 3 \text{ dB} \quad (1)$$

V_{dB} , the variant spot-check level

R_{dB} , the corresponding measurement level for the reference model

An alternative to the limit of eq. (1) is available, and is based on considering how far the reference data R_{dB} is from the compliance threshold C_{dB} (also expressed in dB), for the particular test under consideration. In this case, if $M_{dB} = |C_{dB} - R_{dB}|$ is the margin in dB from the compliance limit, a spot check may be considered acceptable when the deviation d_{dB} from the reference data satisfies the following condition:

$$d_{dB} = |V_{dB} - R_{dB}| \leq (3 + M_{dB} / 20) \text{ dB}, \text{ for } 0 \leq M_{dB} \leq 60 \text{ dB} \quad (2)$$

$$d_{dB} = |V_{dB} - R_{dB}| = 6 \text{ dB}, \text{ for } M_{dB} > 60 \text{ dB}$$

where “| |” is the absolute value of the measured quantity.

When using the option in eq. (2), d_{dB} increases linearly from 3 dB to 6 dB.

Summary for spot check for each rule entry and technology is listed as below:

Mode	Test Item	2AFZZRN03L Parent Worst mode Test Result	2AFZZPC03G Variant Check Test Result	Deviation (dB)	Deviation Limit (dB)
BT 1Mbps (CH78)	Number of Channels	79	79	0	3
	Hopping Channel Separation	1.000	1.000	0	3
	Dwell Time of Each Channel	0.31	0.31	0	3
	20dB Bandwidth	0.91	0.95	0.04	3
	99% Bandwidth	0.872	0.869	0.03	3
	Conducted Band Edges	-47.92	-46.68	1.24	3
	Conducted Spurious Emission	-44.04	-45.77	1.63	3
BT 1Mbps (CH78)	Radiated Band Edges and Radiated Spurious Emission	59.22	58.49	0.73	3
BT	AC Conducted Emission	59.72	59.36	-0.36	3
BLE 1Mbps (CH39)	6dB Bandwidth	0.67	0.67	0	3
	99% Bandwidth	1.015	1.015	0	3
	Power Spectral Density	-7.89	-7.62	0.27	3
	Conducted Band Edges	-47.91	-45.94	2.03	3
	Conducted Spurious Emission	-43.66	-42.43	1.23	3
	Radiated Band Edges and Spurious Emission	42	42.21	-0.21	3
BLE	AC Conducted Emission	59.72	59.36	-0.36	3
WIFI 2.4G	6dB Bandwidth	9.55	9.52	0.03	3



(802.11b CH11)	99% Bandwidth	12.343	12.348	0.005	3
	Power Spectral Density	-0.83	-1.06	0.23	3
	Conducted Band Edges	-27	-26.69	0.31	3
	Conducted Spurious Emission	-44.25	-45.58	1.33	3
WIFI 2.4G	Radiated Band Edges and Spurious Emission	49.33	46.81	2.52	3
WIFI 2.4G	AC Conducted Emission	59.72	59.36	-0.36	3
WIFI 5G (802.11a CH165)	26dB Bandwidth	32.30	30.16	2.14	3
WIFI 5G (802.11a CH165)	99% Bandwidth	17.657	17.752	0.105	3
WIFI 5G (802.11a CH165)	Power Spectral Density	3.11	3.06	0.05	3
WIFI 5G (11ac 80 Ch42)	Radiated Band Edges and Spurious Emission	50.84	48.79	2.05	3
WIFI 5G (802.11ax HE80 CH106)	DFS	0.88763	0.972032	0.084402	3
WIFI 5G	AC Conducted Emission	55.78	57.76	1.98	3
90S_B26L	26dB	3.06	3.08	0.02	3
	Occupied Bandwidth	2.72	2.75	0.03	3
	Conducted Band Edge	-14.31	-14.31	0	3
	Conducted Spurious Emission	-20.68	-19.7	0.98	3
	Frequency Stability	0.0044	0.0038	0.0006	3
Part 22H GSM 850	Radiated Spurious Emission	-39.12	-41.19	-2.07	3
Part 27L WCDMA1700	Radiated Spurious Emission	-41.57	-44.32	2.75	3
Part 27M LTE Band 41	Radiated Spurious Emission	-40.43	-41.79	1.36	3



Test Item	Mode	2AFZZRN03L Parent Worst mode Test Result	2AFZZPC03G Variant Check Test Result	Deviation (dB)	Deviation Limit (dB)
Conducted Power (dBm)	BT2.0-CH 78-DH5	10.47	10.23	0.24	3
	BT2.0-CH 78-2DH1	7.93	7.88	0.05	3
	BT2.0-CH 78-3DH1	7.91	7.84	0.07	3
	BLE 1Mbps	7.56	7.16	0.40	3
	BLE 2Mbps	7.54	7.02	0.52	3
	11b, 2.4GHz	19.42	19.39	0.03	3
	11g, 2.4GHz	11.68	11.59	0.09	3
	11n HT20, 2.4GHz	11.75	11.54	0.21	3
	11a, 5.2GHz	17.98	17.87	0.11	3
	11a, 5.3GHz	17.88	17.55	0.33	3
	11a, 5.5GHz	18.07	17.92	0.15	3
	11a, 5.8GHz	17.67	17.56	0.11	3
	11n HT20, 5.2GHz	17.06	17.01	0.05	3
	11n HT20, 5.3GHz	16.96	16.64	0.32	3
	11n HT20, 5.5GHz	17.26	17.12	0.14	3
	11n HT20, 5.8GHz	16.92	16.8	0.12	3
	11ac VHT20, 5.2GHz	17.19	17.12	0.07	3
	11ac VHT20, 5.3GHz	17.11	16.8	0.31	3
	11ac VHT20, 5.5GHz	17.38	17.25	0.13	3
	11ac VHT20, 5.8GHz	17.06	16.95	0.11	3
	11n HT40, 5.2GHz	15.07	14.69	0.38	3
	11n HT40, 5.3GHz	14.94	14.71	0.23	3
	11n HT40, 5.5GHz	15.85	15.11	0.74	3
	11n HT40, 5.8GHz	14.59	14.47	0.12	3
	11ac VHT40, 5.2GHz	15.10	14.77	0.33	3
	11ac VHT40, 5.3GHz	14.99	14.79	0.2	3
	11ac VHT40, 5.5GHz	15.90	15.87	0.03	3
	11ac VHT40, 5.8GHz	14.62	14.55	0.07	3
	11ac VHT80, 5.2GHz	13.97	13.6	0.37	3
	11ac VHT80, 5.3GHz	13.24	13.13	0.11	3
	11ac VHT80, 5.5GHz	14.29	14.13	0.16	3
	11ac VHT80, 5.8GHz	12.96	12.9	0.06	3
	GSM 850	32.07	30.77	1.3	3
	GSM 1900	28.8	27.47	1.33	3
	WCDMA II	23.43	23.41	0.02	3
	WCDMA IV	23.62	23.22	0.4	3
	WCDMA V	23.92	23.84	0.08	3
	LTE B2	24.2	24.12	0.08	3
	LTE B4	24.25	23.89	0.36	3
	LTE B5	24.31	23.95	0.36	3
	LTE B7	23.84	23.6	0.24	3
	LTE B26L	24.5	23.95	0.55	3
	LTE B26H	24.11	24.03	0.08	3
	LTE B66	24.37	24.13	0.24	3
	LTE B38	24.27	24.12	0.15	3
	LTE B41	24.29	24.2	0.09	3

**Conclusion:**

All test items test against the variant model based on the worst-case condition from the original model was performed in this filing to demonstrate the test data from original model remains representative for the variant model.

Based on the spot check test result, the test data from the original model is representative for the variant model. All spot check test data are shown within expected level compliant to limit line.

We are using power and ERP/EIRP measurements from the original parent model reports to list on the grant.

We confirm that the test data referencing policy of FCC KDB 484596 D01 Referencing Test Data v02r03 has been followed and the test data as referenced from the parent model report represents compliance with new FCC ID.



3 List of Measuring Equipment

For BT/WIFI:

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024	Jan. 09, 2025~ Jan. 10, 2025	Oct. 09, 2025	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 03, 2025	Jan. 09, 2025~ Jan. 10, 2025	Jan. 02, 2026	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 03, 2025	Jan. 09, 2025~ Jan. 10, 2025	Jan. 02, 2026	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY57290151	3Hz~8.5GHz; Max 30dBm	Jul. 04, 2024	Jan. 13, 2025	Jul. 03, 2025	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz~44GHz, MAX 30dB	Oct. 10, 2024	Jan. 13, 2025	Oct. 09, 2025	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Jan. 13, 2025	Sep. 07, 2025	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz~1GHz	Apr. 18, 2024	Jan. 13, 2025	Apr. 17, 2025	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 11, 2024	Jan. 13, 2025	Apr. 10, 2025	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101116	18GHz~40GHz	Oct. 22, 2024	Jan. 13, 2025	Oct. 21, 2025	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380826	9KHz~1GHz	Jul. 03, 2024	Jan. 13, 2025	Jul. 02, 2025	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060851	18~40GHz	Jan. 02, 2025	Jan. 13, 2025	Jan. 01, 2026	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060843	1Ghz~18Ghz	Jan. 02, 2025	Jan. 13, 2025	Jan. 01, 2026	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz~18Ghz	Jan. 02, 2025	Jan. 13, 2025	Jan. 01, 2026	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 13, 2025	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 13, 2025	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 13, 2025	NCR	Radiation (03CH05-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 18, 2024	Jan. 03, 2025	Apr. 17, 2025	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Aug. 20, 2024	Jan. 03, 2025	Aug. 19, 2025	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Apr. 18, 2024	Jan. 03, 2025	Apr. 17, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 09, 2024	Jan. 03, 2025	Oct. 08, 2025	Conduction (CO01-KS)
Signal Analyzer	R&S	FSV7	101472	10Hz~7GHz	Jan. 02, 2025	Jan. 04, 2025	Jan. 01, 2026	Conducted (DFS01-KS)
Vector Signal Generator	R&S	SMJ100A	101908	100kHz~6GHz	Jan. 02, 2025	Jan. 04, 2025	Jan. 01, 2026	Conducted (DFS01-KS)
Combiner	MTJ Cooperation	MTJ7114-M	N/A	0.5GHz~18GHz	NCR	Jan. 04, 2025	NCR	Conducted (DFS01-KS)

NCR: No Calibration Required.



For WWAN Bands:

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024	Jan. 09, 2025~ Jan. 10, 2025	Oct. 09, 2025	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Jan. 09, 2025~ Jan. 10, 2025	NCR	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 04, 2024	Jan. 09, 2025~ Jan. 10, 2025	Jul. 03, 2025	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz~44G,MAX 30dB	Oct. 11, 2024	Jan. 13, 2025	Oct. 10, 2025	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Jan. 13, 2025	Sep. 07, 2025	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Nov. 23, 2024	Jan. 13, 2025	Nov. 22, 2025	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00227860	1GHz~18GHz	Aug. 16, 2024	Jan. 13, 2025	Aug. 15, 2025	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101116	18GHz~40GHz	Oct. 22, 2024	Jan. 13, 2025	Oct. 21, 2025	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	380826	9KHz~1GHz	Jul. 03, 2024	Jan. 13, 2025	Jul. 02, 2025	Radiation (03CH04-KS)
Amplifier	EM	EM18G40G A	060852	18~40GHz	Jan. 03, 2025	Jan. 13, 2025	Jan. 02, 2026	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060840	1Ghz~18Ghz	Oct. 09, 2024	Jan. 13, 2025	Oct. 08, 2025	Radiation (03CH04-KS)
Amplifier	EM	EM01G18G A	060892	1Ghz~18Ghz	Oct. 09, 2024	Jan. 13, 2025	Oct. 08, 2025	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 13, 2025	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 13, 2025	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 13, 2025	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required.

4 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement (BT/WIFI2.4G/5G)

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±2.22 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.50 dB
Conducted Power Spectral Density	±0.90 dB
Frequency	±0.04ppm

Uncertainty of Conducted Measurement (DFS)

Test Item	Uncertainty
Conducted Generated signal Levels	±0.56 dB
Conducted Time	0.38%

Uncertainty of Conducted Measurement (WWAN)

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±2.22 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.50 dB
Peak to Average Ratio	±0.50 dB
Frequency Stability	±0.04ppm

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.84 dB
---	---------

03CH05-KS(BT/WIF):

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.02 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.22 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.34 dB
---	---------

03CH04-KS(WWAN):

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.82 dB
---	---------

-THE END-