

Report Number: F690501/RF-RTL014483 Page: 53 of

# **TEST REPORT**

of

FCC Part 15 Subpart C §15.209 IC RSS-210 Issue 9, RSS-Gen Issue 5

FCC ID: CQOFG08520 IC Certification: 1551E-EG08520

**Equipment Under Test** : DL3 WSMK IBU

Model Name : EG08520

**Applicant** : DENSO Korea Corporation

Manufacturer : DENSO Korea Corporation

Date of Receipt : 2019.10.11

Date of Test(s) : 2019.10.14 ~ 2019.10.29

Nancy Park

Jungmin Yang

Date of Issue : 2019.11.01

In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Date:

2019.11.01

**Technical** 

Manager:

Date:

2019.11.01

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 2 53 of

# **Table of Contents**

1. General Information	3
2. Field Strength of Fundamental and Spurious Emission	6
3. 20 dB Bandwidth	44
1 Occupied Bandwidth	10



Report Number: F690501/RF-RTL014483 Page: 3 of 53

## 1. General Information

## 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a>.

Phone No. : +82 31 688 0901 Fax No. : +82 31 688 0921

## 1.2. Details of Applicant

Applicant : DENSO Korea Corporation

Address : 3, Cheomdansaneop-ro, Masanhappo-gu, Changwon-si, Gyeongsangnam-do, Korea

51776

Contact Person : Ha, Chang-su Phone No. : +82 55 220 9321

#### 1.3. Details of Manufacturer

Applicant : Same as applicant Address : Same as applicant

## 1.4. Description of EUT

Kind of Product		DL3 WSMK IBU
Model Name		EG08520
Power Supply		DC 12.0 V
Frequency Range	•	Tx: 125.00 kHz, Rx: 433.92 MHz
Antonna Typo	Tx	External Type (Coil Antenna)
Antenna Type	Rx	Internal Type

## 1.5. Declaration of Manufacturer

- The EUT has 7 transmit antennas and one receive antenna.
- The transmit antennas can not operate at the same time.



Report Number: F690501/RF-RTL014483 Page: 4 of 53

# 1.6. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval	Cal. Due
Spectrum Analyzer	R&S	FSV30	100768	Mar. 08, 2019	Annual	Mar. 08, 2020
Signal Generator	R&S	SMBV100A	259067	Jun. 10, 2019	Annual	Jun. 10, 2020
DC Power Supply	Agilent	U8002A	MY50060028	Mar. 12, 2019	Annual	Mar. 12, 2020
Test Receiver	R&S	ESU26	100109	Jan. 31, 2019	Annual	Jan. 31, 2020
Loop Antenna	Schwarzbeck Mess-Elektronik	FMZB 1519	1519-039	Aug. 22, 2019	Biennial	Aug. 22, 2021
Bilog Antenna	Schwarzbeck Mess-Elektronik	VULB9163	396	Mar. 21, 2019	Biennial	Mar. 21, 2021
Turn Table	Innco systems GmbH	DS 1200 S	N/A	N. C. R.	N/A	N. C. R.
Controller	Innco systems GmbH	CONTROLLER CO3000-4P	CO3000/963/3 8330516/L	N. C. R.	N/A	N. C. R.
Antenna Mast	Innco systems GmbH	MA4640-XP-ET	MA4640/536/3 8330516/L	N. C. R.	N/A	N. C. R.
Anechoic Chamber	SY Corporation	L × W × H (9.6 m × 6.4 m × 6.6 m)	N/A	N. C. R.	N/A	N. C. R.
Coaxial Cable	SUCOFLEX	104 (3 m)	MY3258414	Jul. 20, 2019	Semi- annual	Jan. 20, 2020
Coaxial Cable	SUCOFLEX	104 (10 m)	MY3145814	Jul. 20, 2019	Semi- annual	Jan. 20, 2020
Coaxial Cable	Rosenberger	LA1-C006-1500	131014 09/20	Aug. 23, 2019	Semi- annual	Feb. 23, 2020

## 1.7. Sample Calculation

Where relevant, the following sample calculation is provided: Field strength level ( $dB\mu N/m$ ) = Measured level ( $dB\mu N/m$ ) + Antenna factor (dB) + Cable loss (dB)

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: of 53

# 1.8. Summary of Test Results

The EUT has been tested according to the following specifications:

Applied standard: FCC Part15 subpart C, IC RSS-210 Issue 9, RSS-Gen Issue 5								
Section in FCC	Section in IC	Test Item	Result					
15.209	RSS-210 Issue 9 4.4 RSS-Gen Issue 5 8.9	Radiated emission, Spurious Emission and Field Strength of Fundamental	Complied					
2.1049	-	20 dB Bandwidth	Complied					
-	RSS-Gen Issue 5 6.7	Occupied Bandwidth	Complied					

## 1.9. Test Report Revision

Revision	Report Number	Date of Issue	Description	
0	F690501/RF-RTL014483	2019.11.01	Initial	

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

A4(210 mm × 297 mm)




Page: Report Number: F690501/RF-RTL014483 of 53


# 2. Field Strength of Fundamental and Spurious Emission

## 2.1. Test Setup

The diagram below shows the test setup that is utilized to make the measurements for emission below 30



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 Mb to 1 GHz Emissions.



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: of 53

## 2.2. Limits

#### 2.2.1. FCC

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (飐)	Field Strength (microvolts/meter)	Measurement Distance (meter)
0.009-0.490	2 400/F(kHz)	300
0.490-1.705	24 000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

<sup>\*\*</sup> Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 Mz, 76-88 Mz, 174-216 Mz or 470-806 Mz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

According to §15.209(d), The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kllz, 110-490 kllz and above 1 000 Mb. Radiated emission limits in these three bands are based on measurements employing an average detector.



Report Number: F690501/RF-RTL014483 Page: of 53

#### 2.2.2. IC

#### 2.2.2.1. Transmitter emission limits

According to RSS-Gen Issue 5, 8.9.

Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Frequency (账)	Field Strength (µV/m at 3 m)
30-88	100
88-216	150
216-960	200
Above 960	500

Table 6 - General field strength limits at frequencies below 30 №

Frequency	Magnetic Field Strength (H-Field) (μA/m)	Measurement Distance (m)
9-490 kHz 1	6.37/F (F in kllz)	300
490-1 705 kHz	63.7/F (F in kllz)	30
1.705-30 Mz	0.08	30

Note 1: The emission limits for the ranges 9-90 kllz and 110-490 kllz are based on measurements employing a linear average detector.

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: of 53

#### 2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.10-2013.

#### 2.3.1. Test Procedures for emission from 9 km to 30 km

- 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
- 3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.
- 5. To get a maximum emission level from the EUT, the EUT is manipulated through three orthogonal planes (X, Y, Z). Worst orthogonal plan of EUT is **X** – **axis** during radiation test.

#### 2.3.2. Test Procedures for emission from above 30 Mb

- 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meters above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. During performing radiated emission below 1 @b, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
- 3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 10 53

## 2.4. Field Strength of Fundamental Test Result

Ambient temperature : (23 ± 1) °C Relative humidity % R.H. 47

All emissions tested both horizontal and vertical. The following table shows the highest levels of radiated emissions on the worst polarization.

Radia	Radiated Emissions		Ant.	Corre Fact		Total		Limit	
Frequency (畑)	Reading (dBμV)	Detect Mode	Pol.	Ant. (dB/m)	Cable (dB)	Actual (dBμV/m) at 3 m	Actual (dBμV/m) at 300 m	Limit (dBμV/m) at 300 m	Margin (dB)
DRV Antenna									
0.126	55.60	Average	Н	17.80	0.07	73.47	-6.53	25.60	32.13
AST Antenna									
0.126	54.70	Average	Н	17.80	0.07	72.57	-7.43	25.60	33.03
INT1 Antenna	l								
0.126	57.70	Average	Η	17.80	0.07	75.57	-4.43	25.60	30.03
INT2 Antenna	ı								
0.126	57.00	Average	Н	17.80	0.07	74.87	-5.13	25.60	30.73
TRK Antenna									
0.126	53.75	Average	Η	17.80	0.07	71.62	-8.38	25.60	33.98
BUM Antenna	l								
0.126	50.40	Average	Н	17.80	0.07	68.27	-11.73	25.60	37.33
SSB Antenna	·	·							
0.125	46.60	Average	Н	17.80	0.07	64.47	-15.53	25.67	41.20

#### Remark;


- 1. According to §15.31(f)(2) 300 m Result ( $dB\mu V/m$ ) = 3 m Result ( $dB\mu V/m$ ) 40log (300/3) ( $dB\mu V/m$ ).
- 2. According to §15.209(d), the measurements were tested by using Quasi peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1 GHz in these three bands on measurements employing an average detector.
- 3. The limit above was calculated based on table of §15.209(a).
- 4. According to ANSI C63.10: 2013, For measurement below 30 Mb. conversion factor from E-field to H-field is considered as free-space impedance [1  $\mu$ V/m = (1/377  $\Omega$ ) × 1  $\mu$ A/m] The FCC limits are same to the IC limits.




Report Number: F690501/RF-RTL014483 Page: 11 of 53

## - Test plots

#### **DRV Antenna**



#### **AST Antenna**




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.




Report Number: F690501/RF-RTL014483 Page: 12 of 53

## **INT1 Antenna**



#### **INT2** Antenna



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.




Report Number: F690501/RF-RTL014483 Page: 13 of 53

#### **TRK Antenna**



#### **BUM Antenna**




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 14 of 53

#### **SSB Antenna**





Report Number: F690501/RF-RTL014483 Page: 15 of 53

# 2.5. Spurious Emission Test Result

Ambient temperature : (23 ± 1) °C Relative humidity : 47 % R.H.

#### **DRV Antenna**

#### Below 30 Mb

Radiated Emissions		Ant.	Correction Factors		Total		Limit		
Frequency (썐)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dΒμ//m) at 3 m	Actual (dBμV/m) at 30 m or 300 m	Limit (dBµV/m) at 30 m or 300 m	Margin (dB)
0.023	20.20	Average	Н	18.11	0.01	38.32	-41.68	40.37	82.05
0.067	15.00	Average	Н	17.85	0.03	32.88	-47.12	31.08	78.20
0.137	5.50	Average	Н	17.80	0.08	23.38	-56.62	24.87	81.49
0.351	5.30	Average	Н	17.77	0.23	23.30	-56.70	16.70	73.40
0.629	24.10	Quasi- Peak	Н	17.80	0.38	42.28	2.28	31.63	29.35
Above 1.000	Not detected	-	-	-	-	-	-	-	-

Radiated Emissions			Ant	Correctio	n Factors	Total	Limit	
Frequency (脏)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBµV/m)	Limit (dB#V/m)	Margin (dB)
46.61	34.20	Peak	٧	20.60	-26.76	28.04	40.00	11.96
61.49	32.90	Peak	Н	17.65	-26.40	24.15	40.00	15.85
104.57	34.40	Peak	٧	17.00	-25.61	25.79	43.50	17.71
151.01	35.40	Peak	V	13.90	-25.60	23.70	43.50	19.80
635.32	34.20	Peak	Н	25.11	-24.07	35.24	46.00	10.76
913.55	34.50	Peak	Н	28.30	-22.83	39.97	46.00	6.03



Report Number: F690501/RF-RTL014483 Page: 16 53 of

#### **AST Antenna**

#### Below 30 Mb

Radiated Emissions		Ant.	Correction Factors		Total		Limit		
Frequency (脈)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dΒμV/m) at 3 m	Actual (dBµV/m) at 30 m or 300 m	Limit (dBµV/m) at 30 m or 300 m	Margin (dB)
0.023	19.90	Average	Н	18.11	0.01	38.02	-41.98	40.37	82.35
0.069	15.90	Average	Н	17.84	0.03	33.77	-46.23	30.83	77.06
0.108	6.00	Quasi- Peak	Н	17.80	0.05	23.85	-56.15	26.94	83.09
0.378	22.10	Average	Н	17.76	0.25	40.11	-39.89	16.05	55.94
Above 1.000	Not detected	-	1	-	-	-	-	-	-

Radi	ated Emissior	าร	Ant	Correctio	n Factors	Total	Limi	it
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBµN/m)	Limit (dBµN/m)	Margin (dB)
87.11	34.70	Peak	Н	14.03	-25.60	23.13	40.00	16.87
125.87	36.80	Peak	V	14.80	-25.53	26.07	43.50	17.43
151.01	40.80	Peak	V	13.90	-25.60	29.10	43.50	14.40
201.25	36.30	Peak	V	16.90	-25.51	27.69	43.50	15.81
347.72	36.90	Peak	V	20.96	-25.35	32.51	46.00	13.49
947.54	34.90	Peak	Н	28.10	-22.59	40.41	46.00	5.59



Report Number: F690501/RF-RTL014483 Page: 17 of 53

#### **INT1** Antenna

#### Below 30 Mb

Radia	ated Emission	ns	Ant.	Correction Factors		Total		Limit	
Frequency (脈)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dB	Actual (dBμV/m) at 30 m or 300 m	Limit (dBµV/m) at 30 m or 300 m	Margin (dB)
0.035	16.70	Average	Н	17.89	0.02	34.61	-45.39	36.72	82.11
0.068	17.50	Average	Н	17.85	0.03	35.38	-44.62	30.95	75.57
0.102	4.30	Quasi- Peak	Н	17.80	0.04	22.14	-57.86	27.43	85.29
0.246	10.20	Average	Н	17.80	0.17	28.17	-51.83	19.79	71.62
Above 1.000	Not detected	-	-	-	-	-	-	-	-

ADOVE 30 MILE											
Radi	iated Emission	าร	Ant	Correctio	n Factors	Total	Limi	t			
Frequency (畑)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBµN/m)	Limit (dBµN/m)	Margin (dB)			
51.95	33.50	Peak	Н	19.91	-26.66	26.75	40.00	13.25			
174.17	34.50	Peak	V	14.80	-25.53	23.77	43.50	19.73			
201.49	35.50	Peak	V	16.88	-25.51	26.87	43.50	16.63			
516.82	34.00	Peak	Н	23.34	-25.04	32.30	46.00	13.70			
757.50	34.40	Peak	Н	26.75	-23.45	37.70	46.00	8.30			
853.05	36.00	Peak	V	27.50	-23.18	40.32	46.00	5.68			
Above 900.00	Not detected	-	-	-	-	-	-	-			



Report Number: F690501/RF-RTL014483 Page: 18 53 of

#### **INT2** Antenna

#### Below 30 Mb

Radia	ated Emission	ns	Ant.	Correction Factors		Tot	al	Limit	
Frequency (砸)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dΒμ//m) at 3 m	Actual (dBµV/m) at 30 m or 300 m	Limit (dBµV/m) at 30 m or 300 m	Margin (dB)
0.019	40.10	Average	Н	18.23	0.01	58.34	-21.66	42.03	63.69
0.048	20.50	Average	Н	17.87	0.02	38.39	-41.61	33.98	75.59
0.067	23.40	Average	Н	17.85	0.03	41.28	-38.72	31.08	69.80
0.206	10.50	Average	Н	17.80	0.15	28.45	-51.55	21.33	72.88
Above 1.000	Not detected	-	-	-	-	-	-	-	-

Radi	ated Emission	าร	Ant	Correctio	n Factors	Total	Limi	it
Frequency (畑)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBµV/m)	Limit (dB#V/m)	Margin (dB)
43.94	34.40	Peak	V	20.49	-26.79	28.10	40.00	11.90
44.67	33.70	Peak	Н	20.57	-26.78	27.49	40.00	12.51
261.06	34.80	Peak	Н	18.58	-25.36	28.02	46.00	17.98
301.92	36.70	Peak	V	19.20	-25.39	30.51	46.00	15.49
998.95	35.00	Peak	V	28.50	-22.31	41.19	54.00	12.81
998.99	35.20	Peak	Н	28.50	-22.31	41.39	54.00	12.61



Report Number: F690501/RF-RTL014483 Page: 19 53 of

## **TRK Antenna**

#### Below 30 Mb

Radia	ated Emission	ns	Ant.	Correction Factors		Tot	al	Limit	
Frequency (砸)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dΒμ//m) at 3 m	Actual (dBµV/m) at 30 m or 300 m	Limit (dBµV/m) at 30 m or 300 m	Margin (dB)
0.019	40.10	Average	Н	18.23	0.01	58.34	-21.66	42.03	63.69
0.046	27.30	Average	Н	17.88	0.02	45.20	-34.80	34.35	69.15
0.068	30.00	Average	Н	17.85	0.03	47.88	-32.12	30.95	63.07
0.251	22.30	Average	Н	17.80	0.18	40.28	-39.72	19.61	59.33
Above 1.000	Not detected	-	-	-	-	-	-	-	-

Radi	iated Emission	าร	Ant	Correctio	n Factors	Total	Limi	it
Frequency (畑)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBµN/m)	Limit (dBµV/m)	Margin (dB)
46.64	34.50	Peak	Н	20.60	-26.76	28.34	40.00	11.66
52.46	32.90	Peak	V	19.85	-26.65	26.10	40.00	13.90
104.88	33.80	Peak	V	17.00	-25.60	25.20	43.50	18.30
231.13	34.40	Peak	Н	17.75	-25.47	26.68	46.00	19.32
554.33	36.00	Peak	V	23.70	-24.74	34.96	46.00	11.04
760.56	35.10	Peak	Н	26.69	-23.48	38.31	46.00	7.69
Above 800.00	Not detected	-	-	-	-	-	-	-



Report Number: F690501/RF-RTL014483 Page: 20 53 of

#### **BUM Antenna**

#### Below 30 Mb

Radia	ated Emission	ns	Ant.	Correction Factors		Total		Limit	
Frequency (脈)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dΒμ//m) at 3 m	Actual (dBμV/m) at 30 m or 300 m	Limit (dBµV/m) at 30 m or 300 m	Margin (dB)
0.019	19.40	Average	Н	18.23	0.01	37.64	-42.36	42.03	84.39
0.068	16.60	Average	Н	17.85	0.03	34.48	-45.52	30.95	76.47
0.151	14.10	Average	Н	17.80	0.10	32.00	-48.00	24.02	72.02
0.236	8.10	Average	Н	17.80	0.17	26.07	-53.93	20.15	74.08
Above 1.000	Not detected	-	-	-	-	-	-	-	-

## Above 30 Mb

Radi	ated Emission	าร	Ant	Correctio	n Factors	Total	Limi	it
Frequency (畑)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBµN/m)	Limit (dB#V/m)	Margin (dB)
47.99	33.60	Peak	V	20.50	-26.74	27.36	40.00	12.64
49.44	34.70	Peak	Н	20.30	-26.72	28.28	40.00	11.72
53.56	34.80	Peak	Н	19.69	-26.61	27.88	40.00	12.12
383.44	35.00	Peak	V	21.01	-25.22	30.79	46.00	15.21
916.66	35.50	Peak	V	28.30	-22.75	41.05	46.00	4.95
998.79	34.50	Peak	Н	28.50	-22.31	40.69	54.00	13.31

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 21 53 of

#### **SSB Antenna**

#### Below 30 Mb

Radia	ated Emission	ns	Ant.	Correction Factors		Tot	tal	Limit	
Frequency (砸)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	Actual (dΒμ//m) at 3 m	Actual (dBμV/m) at 30 m or 300 m	Limit (dBµV/m) at 30 m or 300 m	Margin (dB)
0.022	35.30	Average	Н	18.14	0.01	53.45	-26.55	40.76	67.31
0.047	26.90	Average	Н	17.88	0.02	44.80	-35.20	34.16	69.36
0.068	28.40	Average	Н	17.85	0.03	46.28	-33.72	30.95	64.67
0.372	15.90	Average	Н	17.76	0.24	33.90	-46.10	16.19	62.29
Above 1.000	Not detected	-	-	-	-	-	-	-	-

Rad	iated Emission	าร	Ant	Correctio	n Factors	Total	Limi	it
Frequency (脈)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBµN/m)	Limit (dB#V/m)	Margin (dB)
46.49	33.30	Peak	V	20.60	-26.76	27.14	40.00	12.86
46.94	33.10	Peak	Н	20.60	-26.75	26.95	40.00	13.05
431.58	33.20	Peak	Н	22.13	-25.01	30.32	46.00	15.68
988.16	33.30	Peak	Н	28.40	-22.30	39.40	54.00	14.60
996.04	33.10	Peak	V	28.50	-22.30	39.30	54.00	14.70



Report Number: F690501/RF-RTL014483 Page: 22 of 53

#### Remark;

- 1. According to §15.31(f)(2)
  - 300 m Result ( $dB\mu V/m$ ) = 3 m Result ( $dB\mu V/m$ ) 40log (300/3) ( $dB\mu V/m$ )
  - 30 m Result ( $dB\mu V/m$ ) = 3 m Result ( $dB\mu V/m$ ) 40log (30/3) ( $dB\mu V/m$ )
- 2. According to field strength table of general requirement in §15.209(a), field strength limits below 1.705 Mb were calculated as below.
  - 9 kHz to 490 kHz: 20log (2 400 / F (kHz)) at 300 m (dB $\mu$ V/m)
  - 490 kHz to 1 705 kHz: 20log (24 000 / F (kHz)) at 30 m (dB $\mu$ V/m)
- 3. According to §15.209(d), the measurements were tested by using Quasi peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1 GHz in these three bands on measurements employing an average detector.
- 4. According to ANSI C63.10: 2013, For measurement below 30 Mb. conversion factor from E-field to H-field is considered as free-space impedance [1  $\mu$ V/m = (1/377  $\Omega$ ) × 1  $\mu$ A/m] The FCC limits are same to the IC limits.
- 5. For measurement above 30 Mb, the limit was calculated based on table of §15.209(a).
- 6. Actual = Reading + AF + CL or Reading + AF + AMP + CL.
- 7. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.





Report Number: F690501/RF-RTL014483 Page: 23 of 53

#### - Test plots

#### **DRV Antenna**

#### Below 30 Mb






The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 24 of 53







The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 25 of 53



#### Above 30 Mb



## Remark;

- Traces shown in the plot were made by using a peak detector.


The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.




Report Number: F690501/RF-RTL014483 Page: 26 of 53

#### **AST Antenna**

#### Below 30 Mb







The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 27 of 53






The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 28 of 53

## Above 30 Mb



#### Remark;


- Traces shown in the plot were made by using a peak detector.




Report Number: F690501/RF-RTL014483 Page: 29 of 53

#### **INT1** Antenna

#### Below 30 Mb







The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 30 of 53






The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 31 of 53

## Above 30 Mb



#### Remark;


- Traces shown in the plot were made by using a peak detector.




Report Number: F690501/RF-RTL014483 Page: 32 of 53

#### **INT2** Antenna

#### Below 30 Mb







The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 33 of 53






The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 34 of 53

## Above 30 Mb



#### Remark;


- Traces shown in the plot were made by using a peak detector.



Report Number: F690501/RF-RTL014483 Page: 35 of 53

#### **TRK Antenna**

#### Below 30 Mb







The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 36 of 53






The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 37 of 53

# Above 30 Mb



## Remark;


- Traces shown in the plot were made by using a peak detector.




Report Number: F690501/RF-RTL014483 Page: 38 of 53

#### **BUM Antenna**

#### Below 30 Mb







The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 39 of 53






The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 40 of 53

# Above 30 Mb



## Remark;


- Traces shown in the plot were made by using a peak detector.




Report Number: F690501/RF-RTL014483 Page: 41 of 53

#### **SSB Antenna**

#### Below 30 Mb







The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 42 of 53






The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 43 of 53

# Above 30 Mb



## Remark;


- Traces shown in the plot were made by using a peak detector.



Report Number: F690501/RF-RTL014483 Page: of 53

# 3. 20 dB Bandwidth

# 3.1. Test Setup



## 3.2. Limit

None; for reporting purposed only

### 3.3. Test Procedure

- 1. Span = set to capture all products of the modulation process, including the emission skirts. RBW = 200 Hz, VBW = 200 Hz, Sweep = auto, Detector = peak, Trace = max hold.
- 2. The marker-to-peak function to set the mark to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is 20 dB bandwidth of the emission.

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 45 of 53


# 3.4. Test Result

Ambient temperature :  $(23 \pm 1)$  °C Relative humidity : 47 % R.H.

Test Antenna	Frequency (妣)	20 dB Bandwidth (妣)	Limit
DRV Antenna	125	1.054	
AST Antenna	125	1.074	
INT1 Antenna	125	1.054	
INT2 Antenna	125	1.054	Reporting proposed only
TRK Antenna	125	1.014	
BUM Antenna	125	1.024	
SSB Antenna	125	1.054	

## - Test plots

#### **DRV Antenna**




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.




Report Number: F690501/RF-RTL014483 Page: 46 of 53

#### **AST Antenna**



#### **INT1** Antenna




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.




Report Number: F690501/RF-RTL014483 Page: 47 of 53

#### **INT2** Antenna



#### **TRK Antenna**




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.




Report Number: F690501/RF-RTL014483 Page: 48 of 53

#### **BUM Antenna**



#### **SSB Antenna**




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: of 53

# 4. Occupied Bandwidth

# 4.1. Test Setup



## 4.2. Limit

None; for reporting purposed only

# 4.3. Test Procedure

- 1. Set the spectrum analyzer as Span = set to capture all products of the modulation process, including the emission skirts, RBW = 200 Hz, VBW = 200 Hz, Detector = peak, Trace mode = max hold.
- 2. Measure lowest and highest frequencies are placed in a running sum until 0.5 % and 99.5 % of the
- 3. Record the SPAN between the lowest and the highest frequencies for the 99 % occupied bandwidth.

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014483 Page: 50 of 53


# 4.4. Test Result

Ambient temperature :  $(23 \pm 1)$   $^{\circ}$ C Relative humidity : 47  $^{\circ}$  R.H.

Test Antenna	Frequency (ﷺ)	Occupied Bandwidth (쌦)	Limit
DRV Antenna	125	2.836	
AST Antenna	125	2.938	
INT1 Antenna	125	2.721	
INT2 Antenna	125	2.721	Reporting proposed only
TRK Antenna	125	2.735	
BUM Antenna	125	2.735	
SSB Antenna	125	2.808	

# - Test plots

## **DRV Antenna**




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.




Report Number: F690501/RF-RTL014483 Page: 51 of 53

#### **AST Antenna**



#### **INT1** Antenna




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.




Report Number: F690501/RF-RTL014483 Page: 52 of 53

#### **INT2** Antenna



#### **TRK Antenna**




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.




Report Number: F690501/RF-RTL014483 Page: 53 of 53

#### **BUM Antenna**



#### **SSB Antenna**



# - End of the Test Report -

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.