



Report No.: HUAKE180823882E

# FCC TEST REPORT

**Test report  
On Behalf of  
Streamax Technology Co.,Ltd.  
For  
CAMERA  
Model No.: C6D**

**FCC ID: 2AM6L-C6D**

**Prepared for :** Streamax Technology Co.,Ltd.  
21-23/F, Building B1, Zhiyuan, No. 1001, Xueyuan Avenue, Nanshan District,  
Shenzhen, Guangdong,P.R. China.

**Prepared By :** Shenzhen HUAKE Testing Technology Co., Ltd.  
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,  
Bao'an District, Shenzhen City, China

**Date of Test:** Jul. 05, 2018 ~ Aug. 31, 2018

**Date of Report:** Aug. 31, 2018

**Report Number:** HUAKE180823882E

## TEST RESULT CERTIFICATION

**Applicant's name** ..... : Streamax Technology Co.,Ltd.  
 21-23/F, Building B1, Zhiyuan, No. 1001, Xueyuan Avenue,  
**Address** ..... : Nanshan District, Shenzhen, Guangdong,P.R. China.

**Manufacture's Name** ..... : Streamax Electronics Co.,Ltd.  
 5th-6thFloor, West, Chuangxiang 2nd Building, Yanxiang  
**Address** ..... : Technology Park, 11# High-tech West Road, Guangming District,  
 Shenzhen, Guangdong Province, P.R. China .


### Product description


**Trade Mark:** Streamax  
**Product name**..... : CAMERA  
**Model and/or type reference** : C6D


**Standards**..... : FCC Part 15.247  
 KDB 558074 D01 DTS Meas Guidance v04

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test**..... :  
**Date (s) of performance of tests**..... : Jul. 05, 2018 ~ Aug. 31, 2018  
**Date of Issue**..... : Aug. 31, 2018  
**Test Result**..... : Pass

Testing Engineer :   
\_\_\_\_\_  
(Gary Qian)

Technical Manager :   
\_\_\_\_\_  
(Eden Hu)

Authorized Signatory :   
\_\_\_\_\_  
(Jason Zhou)

## Revision History

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Aug. 31, 2018	Valid	Initial Release

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>7</b>
1.1. PRODUCT DESCRIPTION .....	7
1.2. TABLE OF CARRIER FREQUENCIES .....	7
1.3. RECEIVER INPUT BANDWIDTH .....	8
1.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE .....	8
1.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR .....	8
1.6. RELATED SUBMITTAL(S) / GRANT (S).....	9
1.7. TEST METHODOLOGY .....	9
1.8. SPECIAL ACCESSORIES.....	9
1.9. EQUIPMENT MODIFICATIONS .....	9
<b>2. MEASUREMENT UNCERTAINTY .....</b>	<b>10</b>
<b>3. DESCRIPTION OF TEST MODES .....</b>	<b>11</b>
<b>4. SYSTEM TEST CONFIGURATION .....</b>	<b>12</b>
4.1. CONFIGURATION OF EUT SYSTEM .....	12
4.2. EQUIPMENT USED IN EUT SYSTEM .....	12
4.3. SUMMARY OF TEST RESULTS .....	12
<b>5. TEST FACILITY .....</b>	<b>13</b>
<b>6. PEAK OUTPUT POWER.....</b>	<b>14</b>
6.1. MEASUREMENT PROCEDURE .....	14
6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	14
6.3. LIMITS AND MEASUREMENT RESULT .....	15
<b>7. 20DB BANDWIDTH .....</b>	<b>19</b>
7.1. MEASUREMENT PROCEDURE .....	19
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	19
7.3. LIMITS AND MEASUREMENT RESULTS .....	19
<b>8. CONDUCTED SPURIOUS EMISSION .....</b>	<b>22</b>

8.1. MEASUREMENT PROCEDURE .....	22
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	22
8.3. MEASUREMENT EQUIPMENT USED .....	23
8.4. LIMITS AND MEASUREMENT RESULT .....	23
<b>9. RADIATED EMISSION.....</b>	<b>29</b>
9.1. MEASUREMENT PROCEDURE .....	29
9.2. TEST SETUP.....	30
9.3. LIMITS AND MEASUREMENT RESULT .....	31
9.4. TEST RESULT .....	32
<b>10. BAND EDGE EMISSION.....</b>	<b>35</b>
10.1. MEASUREMENT PROCEDURE .....	35
10.2. TEST SET-UP .....	35
10.3. RADIATED TEST RESULT.....	36
10.4. CONDUCTED TEST RESULT .....	38
<b>11. NUMBER OF HOPPING FREQUENCY .....</b>	<b>40</b>
11.1. MEASUREMENT PROCEDURE .....	40
11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) .....	40
11.3. MEASUREMENT EQUIPMENT USED .....	40
11.4. LIMITS AND MEASUREMENT RESULT .....	40
<b>12. TIME OF OCCUPANCY (DWELL TIME).....</b>	<b>42</b>
12.1. MEASUREMENT PROCEDURE .....	42
12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) .....	42
12.3. MEASUREMENT EQUIPMENT USED .....	42
12.4. LIMITS AND MEASUREMENT RESULT .....	43
<b>13. FREQUENCY SEPARATION .....</b>	<b>44</b>
13.1. MEASUREMENT PROCEDURE .....	44
13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) .....	44
13.3. MEASUREMENT EQUIPMENT USED .....	44
13.4. LIMITS AND MEASUREMENT RESULT .....	44
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>	<b>45</b>

# 1. GENERAL INFORMATION

## 1.1. PRODUCT DESCRIPTION

The EUT is “CAMERA” designed as a “Communication Device”. It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following:

<b>Operation Frequency</b>	2.402 GHz to 2.480GHz
<b>Bluetooth Version</b>	V4.1(BR&EDR)
<b>Modulation</b>	GFSK, $\pi/4$ -DQPSK, 8DPSK
<b>Number of channels</b>	79(For BR/EDR)
<b>Hardware Version</b>	1439.02
<b>Software Version</b>	V232
<b>Antenna Designation</b>	PCB Antenna
<b>Antenna Gain</b>	0.5dBi
<b>Power Supply</b>	DC 9~36V
<b>Test Power Supply</b>	DC 12V

## 1.2. TABLE OF CARRIER FREQUENCIES

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

### 1.3. RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.3MHz. In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection (e.g. single or multislotted packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be sent on the same frequency, it is sent on the next frequency of the hopping sequence.

### 1.4. EXAMPLE OF A HOPPING SEQUENCE IN DATA MODE

Example of a 79 hopping sequence in data mode:

40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67  
56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59  
72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75  
09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06  
01, 51, 03, 55, 05, 04

### 1.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.
2. Internal master clock

The LAP (lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24 MSB's of the 48 BD\_ADDRESS.

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For synchronization with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5µs. The clock has a cycle of about one day (23h30). In most cases it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire LAP (24 bits), 4 LSB's (4 bits) (Input 1) and the 27 MSB's of the clock (Input 2) are used. With these input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:

The first connection between the two devices is established, a hopping sequence was generated. For transmitting the wanted data the complete hopping sequence was not used. The connection ended.

The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmissions is longer (and it cannot be shorter) than the minimum resolution of the clock (312.5µs). The hopping sequence will always differ from the first one.

#### **1.6. RELATED SUBMITTAL(S) / GRANT (S)**

This submittal(s) (test report) is intended for **FCC ID: 2AM6L-C6D** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

#### **1.7. TEST METHODOLOGY**

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

#### **1.8. SPECIAL ACCESSORIES**

Refer to section 4.2.

#### **1.9. EQUIPMENT MODIFICATIONS**

Not available for this EUT intended for grant.

## 2. MEASUREMENT UNCERTAINTY

Test	Measurement Uncertainty	Notes
Transmitter power conducted	$\pm 0.57$ dB	(1)
Transmitter power Radiated	$\pm 2.20$ dB	(1)
Conducted spurious emission 9KHz-40 GHz	$\pm 2.20$ dB	(1)
Occupied Bandwidth	$\pm 0.01$ ppm	(1)
Radiated Emission 30~1000MHz	$\pm 4.10$ dB	(1)
Radiated Emission Above 1GHz	$\pm 4.32$ dB	(1)
Conducted Disturbance 0.15~30MHz	$\pm 3.20$ dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

### 3. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel $\pi/4$ -DQPSK
5	Middle channel $\pi/4$ -DQPSK
6	High channel $\pi/4$ -DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	Normal Hopping


**Note:**

1. All the test modes can be supply by Built-in Li-ion battery, only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

## 4. SYSTEM TEST CONFIGURATION

### 4.1. CONFIGURATION OF EUT SYSTEM

Configuration:



### 4.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	CAMERA	C6D	2AM6L-C6D	EUT
2	Antenna	N/A	N/A	Accessory

### 4.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247	Peak Output Power	Compliant
§15.247	20 dB Bandwidth	Compliant
§15.247	Spurious Emission	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.207	Power Line Conduction Emission	Compliant
§15.247	Number of Hopping Frequency	Compliant
§15.247	Time of Occupancy	Compliant
§15.247	Frequency Separation	Compliant

## 5. TEST FACILITY

<b>Test Firm</b>	Shenzhen HUAK Testing Technology Co., Ltd.
<b>Address</b>	1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China
<b>Designation Number</b>	CN1229
<b>Registration Number</b>	616276

### ALL TEST EQUIPMENT LIST

<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>S/N</b>	<b>Cal. Due</b>
Receiver	R&S	ESCI 7	HKE-010	Dec. 28, 2018
LISN	R&S	ENV216	HKE-002	Dec. 28, 2018
Conducted test software	Tonscend	TS+ Rev 2.5.0.0	HKE-081	N/A
Power meter	Agilent	E4417B	HKE-107	Dec. 28, 2018
Power Sensor	Agilent	E9327A	HKE-113	Dec. 28, 2018
RF cable	Times	1-40G	HKE-034	Dec. 28, 2018
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 28, 2018
Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 28, 2018
RF Cable (9KHz-26.5GHz)	Tonscend	170660	N/A	Dec. 28, 2018
Signal generator	Agilent	N5183A	HKE-071	Dec. 28, 2018
Receiver	R&S	ESCI-7	HKE-010	Dec. 28, 2018
Preamplifier	EMCI	EMC051845SE	HKE-015	Dec. 28, 2018
Preamplifier	Agilent	83051A	HKE-016	Dec. 28, 2018
Loop antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 28, 2018
Broadband antenna	Schwarzbeck	VULB 9163	HKE-012	Dec. 28, 2018
Horn antenna	Schwarzbeck	9120D	HKE-013	Dec. 28, 2018
Antenna Mast	Keleto	CC-A-4M	N/A	N/A
Position controller	Taiwan MF	MF7802	HKE-011	Dec. 28, 2018
RF cable (9KHz-1GHz)	Times	381806-001	N/A	N/A



## 6. PEAK OUTPUT POWER

### 6.1. MEASUREMENT PROCEDURE


For peak power test:

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, middle and the bottom operation frequency individually.
3. Use the following spectrum analyzer settings:
  - 1) Span : Approximately five times the 20 dB bandwidth, centered on a hopping channel.
  - 2) RBW > 20 dB bandwidth of the emission being measured.
  - 3) VBW  $\geq$  RBW.
  - 4) Sweep: Auto.
  - 5) Detector function: Peak.
  - 6) Trace: Max hold.
4. Record the maximum power from the Spectrum Analyzer.

**Note:** The EUT was tested according for compliance ANSI C63.10 (2013) requirements.

### 6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

#### PEAK POWER TEST SETUP



**6.3. LIMITS AND MEASUREMENT RESULT**


Mode	Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
GFSK	2.402	3.823	30	Pass
	2.441	4.327	30	Pass
	2.480	4.481	30	Pass

Mode	Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
$\pi$ /4-DQPSK	2.402	5.258	30	Pass
	2.441	5.823	30	Pass
	2.480	5.885	30	Pass


Mode	Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
8DPSK	2.402	5.588	30	Pass
	2.441	6.039	30	Pass
	2.480	6.095	30	Pass

## Test Graph



GFSK-LCH





GFSK-MCH




GFSK-HCH


 $\pi$ /4DQPSK-LCH


$\pi/4$ DQPSK-MCH $\pi/4$ DQPSK-HCH

## 8DPSK-LCH



## 8DPSK-MCH






## 7. 20DB BANDWIDTH

### 7.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel  
RBW  $\geq$  1% of the 20 dB bandwidth, VBW  $\geq$  RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

### 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)




### 7.3. LIMITS AND MEASUREMENT RESULTS

Mode	Channel.	20dB Bandwidth [KHz]	Verdict
GFSK	LCH	998.7	PASS
GFSK	MCH	994.9	PASS
GFSK	HCH	1009	PASS
$\pi/4$ DQPSK	LCH	1296	PASS
$\pi/4$ DQPSK	MCH	1295	PASS
$\pi/4$ DQPSK	HCH	1297	PASS
8DPSK	LCH	1311	PASS
8DPSK	MCH	1311	PASS
8DPSK	HCH	1311	PASS

## Test Graph


GFSK-LCH





GFSK-MCH




GFSK-HCH


 $\pi$ /4DQPSK-LCH

$\pi$ /4DQPSK-MCH $\pi$ /4DQPSK-HCH


## 8DPSK-LCH



## 8DPSK-MCH



## 8DPSK-HCH



## 8. CONDUCTED SPURIOUS EMISSION

### 8.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
3. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.  
RBW = 100 kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak.
4. Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according for compliance ANSI C63.10 (2013) requirements. Owing to satisfy the requirements of the number of measurement points, we set the RBW=1MHz, VBW  $>$  RBW, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the RBW=100KHz, VBW  $>$  RBW) are conform to the requirement.

### 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2

**8.3. MEASUREMENT EQUIPMENT USED**


The same as described in section 5

**8.4. LIMITS AND MEASUREMENT RESULT**


<b>LIMITS AND MEASUREMENT RESULT</b>		
<b>Applicable Limits</b>	<b>Measurement Result</b>	
	<b>Test Data</b>	<b>Criteria</b>
<p>In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.</p> <p>In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))</p>	At least -20dBc than the limit Specified on the BOTTOM Channel	PASS
	At least -20dBc than the limit Specified on the TOP Channel	PASS

## Test Graph


GFSK-LCH




GFSK-LCH




GFSK-LCH




GFSK-MCH




## GFSK-MCH




## GFSK-MCH





## GFSK-HCH











## GFSK-HCH




## GFSK-HCH

 $\pi/4$ DQPSK-LCH


$\pi/4$ DQPSK-LCH $\pi/4$ DQPSK-LCH $\pi/4$ DQPSK-MCH $\pi/4$ DQPSK-MCH $\pi/4$ DQPSK-MCH $\pi/4$ DQPSK-HCH

$\pi$ /4DQPSK-HCH $\pi$ /4DQPSK-HCH


## 8DPSK-LCH




## 8DPSK-LCH




## 8DPSK-LCH




## 8DPSK-MCH




## 8DPSK-MCH




## 8DPSK-MCH




## 8DPSK-HCH



## 8DPSK-HCH



## 8DPSK-HCH




## 9. RADIATED EMISSION

### 9.1. MEASUREMENT PROCEDURE


1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

## 9.2. TEST SETUP


### RADIATED EMISSION TEST-SETUP FREQUENCY BELOW 30MHz



### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



### RADIATED EMISSION TEST SETUP ABOVE 1000MHz



### 9.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


## 9.4. TEST RESULT

### RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

### RADIATED EMISSION BELOW 1GHZ


#### RADIATED EMISSION TEST- (30MHZ-1GHZ) -HORIZONTAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	110.8333	30.97	7.98	38.95	43.50	-4.55	peak			
2	!	185.2000	27.92	11.31	39.23	43.50	-4.27	peak			
3	!	371.1167	22.76	18.88	41.64	46.00	-4.36	peak			
4	*	500.4500	22.99	21.14	44.13	46.00	-1.87	peak			
5	!	519.8500	20.81	21.67	42.48	46.00	-3.52	peak			
6	!	557.0333	18.91	22.66	41.57	46.00	-4.43	peak			
7	!	742.9500	14.56	26.43	40.99	46.00	-5.01	peak			
8		966.0500	14.49	29.85	44.34	54.00	-9.66	peak			

**RESULT: PASS**

## RADIATED EMISSION TEST- (30MHZ-1GHZ) -VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	47.7832	29.22	8.39	37.61	40.00	-2.39	peak			
2	*	68.8000	34.64	4.73	39.37	40.00	-0.63	peak			
3	!	143.1667	26.70	15.22	41.92	43.50	-1.58	peak			
4	!	249.8667	31.39	13.89	45.28	46.00	-0.72	peak			
5	!	333.9332	26.05	17.67	43.72	46.00	-2.28	peak			
6	!	371.1167	24.35	18.88	43.23	46.00	-2.77	peak			

**RESULT: PASS**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

3. All test modes for different EUT are pre-tested. The low channel for GFSK mode is the worst case and recorded in the report.

## RADIATED EMISSION TEST- (ABOVE 1GHZ)

Frequency	Emission Level	Limits	Margin	Detector Type	Comment
(MHz)	(dBμV/m)	(dBμV/m)	(dB)		
Low Channel (2402 MHz)					
4804	48.14	74	-25.86	Pk	Vertical
4804	41.96	54	-12.04	AV	Vertical
4804	48.93	74	-25.07	Pk	Horizontal
4804	41.76	54	-12.24	AV	Horizontal
Mid Channel (2441 MHz)					
4882	48.65	74	-25.35	Pk	Vertical
4882	41.41	54	-12.59	AV	Vertical
4882	48.81	74	-25.19	Pk	Horizontal
4882	41.67	54	-12.33	AV	Horizontal
High Channel (2480 MHz)					
4960	48.39	74	-25.61	pk	Vertical
4960	41.95	54	-12.05	AV	Vertical
4960	48.93	74	-25.07	pk	Horizontal
4960	41.77	54	-12.23	AV	Horizontal

**RESULT: PASS****Note:**

1. 1GHz~25GHz:(Scan with GFSK,  $\pi/4$ -DQPSK,8DPSK, the worst case is GFSK Mode, No recording in the test report at least have 20dB margin)
2. Margin = Emission Level - Limit

## 10. BAND EDGE EMISSION


### 10.1. MEASUREMENT PROCEDURE

1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100kHz. The video bandwidth is set to 300kHz.
2. Transmitter set to the normal hopping mode at 2.4 and 2.4835 GHz.

### 10.2. TEST SET-UP

Radiated same as 9.2

Conducted set up



**10.3. RADIATED TEST RESULT**

Frequency	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	Type	
GFSK					
2399.9	51.31	74	-22.69	peak	Vertical
2399.9	37.42	54	-16.58	AVG	Vertical
2399.9	51.44	74	-22.56	peak	Horizontal
2399.9	39.29	54	-14.71	AVG	Horizontal
2483.6	52.45	74	-21.55	peak	Vertical
2483.6	39.75	54	-14.25	AVG	Vertical
2483.6	53.62	74	-20.38	peak	Horizontal
2483.6	40.63	54	-13.37	AVG	Horizontal
π/4-DQPSK					
2399.9	51.15	74	-22.85	peak	Vertical
2399.9	37.24	54	-16.76	AVG	Vertical
2399.9	51.28	74	-22.72	peak	Horizontal
2399.9	39.12	54	-14.88	AVG	Horizontal
2483.6	52.27	74	-21.73	peak	Vertical
2483.6	39.58	54	-14.42	AVG	Vertical
2483.6	53.45	74	-20.55	peak	Horizontal
2483.6	40.46	54	-13.54	AVG	Horizontal
8DPSK					
2399.9	51.28	74	-22.72	peak	Vertical
2399.9	37.4	54	-16.6	AVG	Vertical
2399.9	51.36	74	-22.64	peak	Horizontal
2399.9	39.28	54	-14.72	AVG	Horizontal
2483.6	52.44	74	-21.56	peak	Vertical
2483.6	39.69	54	-14.31	AVG	Vertical
2483.6	53.57	74	-20.43	peak	Horizontal
2483.6	40.6	54	-13.4	AVG	Horizontal


**RESULT: PASS**



**Note:** The other modes radiation emission have enough 20dB margin.

Margin = Emission Level – Limit


## 10.4. CONDUCTED TEST RESULT

### Test Graph




$\pi$ /4DQPSK/LCH/No Hop $\pi$ /4DQPSK/HCH/No Hop

## 8DPSK/LCH/No Hop



## 8DPSK/HCH/No Hop



**Note:** All modes were tested, only the worst case record in the report.

## 11. NUMBER OF HOPPING FREQUENCY

### 11.1. MEASUREMENT PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer Start = 2.4GHz Stop = 2.4835GHz
4. Set the Spectrum Analyzer as RBW $\geq$ 1%span, VBW $\geq$ RBW.

### 11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2

### 11.3. MEASUREMENT EQUIPMENT USED


The same as described in section 5

### 11.4. LIMITS AND MEASUREMENT RESULT

Mode	Channel.	Number of Hopping Channel	Verdict
GFSK	Hop	79	PASS

Note: All modes were tested, only the worst case record in the report.

## Test Graph



## 12. TIME OF OCCUPANCY (DWEELL TIME)

### 12.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: Zero span, centered on a hopping channel.
2. RBW shall be  $\leq$  channel spacing and where possible RBW should be set  $\gg 1 / T$ , where T is the expected dwell time per channel.
3. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel.
4. Detector function: Peak. Trace: Max hold.
5. Use the marker-delta function to determine the transmit time per hop.
6. Using the following equation:

The dwell time is calculated with the following formula:

$$\text{Dwell time} = t_{\text{pulse}} \times n_{\text{hops}} / \text{number of channels} \times 31.6 \text{ s}$$

Where:

$t_{\text{pulse}}$  is the measured pulse time (pls. refer the plots of the spectrum analyser above) [s],  
 $n_{\text{hops}}$  is the number of hops per second in the actual operating mode of the transmitter [1/s].

The hopping rate of the system is 1600 hops per second and the system uses 79 channels. For this reason one time slot has a length of 625  $\mu\text{s}$ .

With the used hopping mode (DH5) a packet need 5 timeslots for transmitting and the next timeslot for receiving. So the system makes in worst case 266,67 hops per second in transmit mode ( $n_{\text{hops}} = 266.667$  1/s)

### 12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2

### 12.3. MEASUREMENT EQUIPMENT USED


The same as described in section 5


## 12.4. LIMITS AND MEASUREMENT RESULT

Channel.	Burst Width [ms/hop/ch]	Dwell Time[ms]	Verdict	Limit (ms)
LCH	2.900	309.3337	PASS	400
MCH	2.900	309.3337	PASS	400
HCH	2900	309.3337	PASS	400

Note: The DH5 for GFSK modulation is the worst case and recorded in the report.

### Test Graph








## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

RADIATED EMISSION TEST SETUP



RADIATED EMISSION ABOVE 1G TEST SETUP



----END OF REPORT----