



# TEST REPORT

## FCC ID: 2BCZH-W02

Applicant: Shenzhen Huanyu Baijia Technology Co., Ltd  
Address: 505 Huichuang Workshop, Building B, No.8 Factory, Shijie Co., Ltd., Gushu Community, Xixiang Street, Bao'an District, Shenzhen  
Manufacturer: Shenzhen Huanyu Baijia Technology Co., Ltd  
Address: 505 Huichuang Workshop, Building B, No.8 Factory, Shijie Co., Ltd., Gushu Community, Xixiang Street, Bao'an District, Shenzhen  
EUT: Watch Charging Stand  
Trade Mark: N/A  
Model Number: W02  
W03, S2302, S2303  
Date of Receipt: Oct. 19, 2023  
Test Date: Oct. 19, 2023 - Oct. 27, 2023  
Date of Report: Oct. 27, 2023  
Prepared By: Shenzhen DL Testing Technology Co., Ltd.  
Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China  
Applicable Standards: FCC PART 15 Subpart C  
ANSI C63.10:2013  
Test Result: Pass  
Report Number: DL-20231025055E

Prepared (Engineer): Alisa Song

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



*This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.*

**TABLE OF CONTENT**

Test Report Declaration	Page
1. <b>VERSION</b> .....	<b>3</b>
2. <b>TEST SUMMARY</b> .....	<b>3</b>
3. <b>GENERAL INFORMATION</b> .....	<b>4</b>
4. <b>TEST INSTRUMENT USED</b> .....	<b>5</b>
5. <b>CONDUCTED EMISSION TEST</b> .....	<b>6</b>
6. <b>RADIATION EMISSION TEST</b> .....	<b>10</b>
7. <b>BANDWIDTH TEST</b> .....	<b>15</b>
8. <b>ANTENNA REQUIREMENT</b> .....	<b>16</b>
9. <b>SETUP PHOTOGRAPHS</b> .....	<b>16</b>
10. <b>EUT PHOTOGRAPHS</b> .....	<b>16</b>

**1. VERSION**

Version No.	Date	Description
00	Oct. 27, 2023	Original

**2. TEST SUMMARY**

EMC Emission			
Test Item	Section in CFR 47	Result	Remark
AC Power Line Conducted Emission	15.207	PASS	
Spurious Emission	15.209(a)(f)	PASS	
20dB Bandwidth	15.215	PASS	
Antenna requirement	15.203	PASS	

**NOTE:**

(1) "N/A" denotes test is not applicable in this Test Report

(2) Test Facility: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone,  
Baolong Street, Longgang District, Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB ID.: CN0118



### 3. GENERAL INFORMATION


#### 3.1 Description of Device (EUT)

Product Name: Watch Charging Stand  
Trade Mark: N/A  
Model No.: W02  
Model Difference: All samples are the same except the model number and appearance color, so we prepare "W02" for test only.  
Serial No.: N/A  
Hardware version: H1.0  
Software version: S1.0  
Operation Frequency: 115KHz ~ 205KHz  
Modulation type: MSK  
Antenna Type: Inductive loop coil Antenna  
Antenna gain: 0dBi  
Power supply: Input: 5V  $\overline{\text{---}}$  1A  
Watch wireless output: 2.5W

#### 3.2 Tested System Details

None.

#### 3.3 Block Diagram of Test Set-up



#### 3.4 Test Mode Description

Mode1: Watch wireless output Mode(2.5W)

Note: We have evaluated 1%, 50% and 99% battery charging mode, and the worst mode (99%) is showed in this report.

#### 3.5 Test Auxiliary Equipment

Adapter (Provide by test lab):  
Manufacturer: HAIWEI  
Model: HW-0501000E  
I/P: AC 100-240V 50/60Hz  
O/P: DC 5V 1A

Watch(Provide by test lab):  
Manufacturer: Apple  
Model: Watch Series 6

#### 3.6 Test Uncertainty

Conducted Emission Uncertainty(150KHz-30MHz) :  $\pm 2.56\text{dB}$   
20dB Bandwidth :  $\pm 0.5\text{kHz}$   
Radiated Emission Uncertainty(9KHz-1GHz) :  $\pm 3.24\text{dB}$





#### 4. TEST INSTRUMENT USED

##### For Conducted Emission Test (843 Shielded Room)

Equipment	Manufacturer	Model	Serial	Last Cal.	Next Cal.
843 Shielded Room	ChengYu	843 Room	843	Sep. 20, 2022	Sep. 19, 2025
EMI Receiver	R&S	ESR	101421	Nov. 05, 2022	Nov. 04, 2023
LISN	R&S	ENV216	102417	Nov. 05, 2022	Nov. 04, 2023
Clamp	COM-POWER	CLA-050	431071	Nov. 05, 2022	Nov. 04, 2023
3-Loop Antenna	DAZE	ZN30401	13021	Nov. 05, 2022	Nov. 04, 2023
ISN T8	Schwarzbeck	NTFM 8158	101135	Nov. 05, 2022	Nov. 04, 2023
ISN T5	Schwarzbeck	NTFM 8158	101136	Nov. 05, 2022	Nov. 04, 2023
843 Cable 1#	ChengYu	CE Cable	001	Nov. 05, 2022	Nov. 04, 2023
843 Cable 1#	ChengYu	CE Cable	002	Nov. 05, 2022	Nov. 04, 2023

##### For Radiated Emission Test (966 chamber)


Equipment	Manufacturer	Model	Serial	Last Cal.	Next Cal.
966 Chamber	ChengYu	966 Room	966	Sep. 20, 2022	Sep. 19, 2025
Spectrum Analyzer	Agilent	E4408B	MY50140780	Nov. 05, 2022	Nov. 04, 2023
EMI Receiver	R&S	ESRP7	101393	Nov. 05, 2022	Nov. 04, 2023
Amplifier	Schwarzbeck	BBV9743B	00153	Nov. 05, 2022	Nov. 04, 2023
Amplifier	EMEC	EM01G8GA	00270	Nov. 05, 2022	Nov. 04, 2023
Broadband Trilog Antenna	Schwarzbeck	VULB9162	00306	Nov. 05, 2022	Nov. 04, 2023
Horn Antenna	Schwarzbeck	BBHA9120D	02139	Nov. 05, 2022	Nov. 04, 2023
Loop Antenna	ZHINAN	ZN30900A	/	Nov. 05, 2022	Nov. 04, 2023
966 Cable 1#	ChengYu	966	004	Nov. 05, 2022	Nov. 04, 2023
966 Cable 2#	ChengYu	966	003	Nov. 05, 2022	Nov. 04, 2023



## 5. CONDUCTED EMISSION TEST

### 5.1 Block Diagram of Test Setup

#### For Mains Terminals Test



**Note: 1.Support units were connected to second LISN.**

**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

### 5.2 Test Standard and Limit

#### FCC Part 15 Subpart C

Frequency MHz	Limits dB( $\mu$ V)	
	Quasi-peak Level	Average Level
0.15~0.50	66 ~ 56*	55 ~ 46*
0.50~5.00	56	46
5.00~30.00	60	50

Notes: 1. \*Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

### 5.3 EUT Configuration on Test

The following equipment's are installed on conducted emission test to meet FCC Part 15 Subpart C requirement and operating in a manner which tends to maximize its emission characteristics in a normal application.

### 5.4 Operating Condition of EUT

5.4.1 Setup the EUT and simulators as shown in Section 5.1.

5.4.2 Turn on the power of all equipments.

5.4.3 Let the EUT work in test modes and test it.



### 5.5 Test Procedure

The EUT is put on the table and connected to the AC mains through a Artificial Mains Network (AMN) or ISN. This provided a 50ohm coupling impedance for the tested equipments. Both sides of AC line are checked to find out the maximum conducted emission levels according to the **ANSI C63.10** regulations during conducted emission test.

The bandwidth of the test receiver (R&S Test Receiver ESR) is set at 10KHz.

The frequency range from 150 KHz to 30 MHz is investigated.

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Measurement Level = Reading level + Correct Factor

### 5.6 Test Result


PASS

Please refer to the following page.



## Conducted Emission Test Data

Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Phase:	Line
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.352500	31.07	9.06	40.13	58.90	-18.77	QP	P	
2	0.352500	16.09	9.06	25.15	48.90	-23.75	AVG	P	
3	0.523400	35.71	9.21	44.92	56.00	-11.08	QP	P	
4	0.523400	24.56	9.21	33.77	46.00	-12.23	AVG	P	
5	0.896900	33.26	9.31	42.57	56.00	-13.43	QP	P	
6	0.896900	19.53	9.31	28.84	46.00	-17.16	AVG	P	
7	1.490900	27.86	9.56	37.42	56.00	-18.58	QP	P	
8	1.490900	14.41	9.56	23.97	46.00	-22.03	AVG	P	
9	2.269400	26.68	9.52	36.20	56.00	-19.80	QP	P	
10	2.269400	12.77	9.52	22.29	46.00	-23.71	AVG	P	
11 *	10.270500	40.90	9.89	50.79	60.00	-9.21	QP	P	
12	10.270500	28.94	9.89	38.83	50.00	-11.17	AVG	P	

Remark:


Margin = Level - Limit, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor





## Conducted Emission Test Data

Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Phase:	Neutral
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.370400	35.57	9.18	44.75	58.49	-13.74	QP	P	
2	0.370400	24.92	9.18	34.10	48.49	-14.39	AVG	P	
3 *	0.519000	42.49	9.35	51.84	56.00	-4.16	QP	P	
4	0.519000	29.86	9.35	39.21	46.00	-6.79	AVG	P	
5	0.896900	37.74	9.33	47.07	56.00	-8.93	QP	P	
6	0.896900	25.91	9.33	35.24	46.00	-10.76	AVG	P	
7	1.531400	33.78	9.63	43.41	56.00	-12.59	QP	P	
8	1.531400	20.73	9.63	30.36	46.00	-15.64	AVG	P	
9	2.228900	33.03	9.84	42.87	56.00	-13.13	QP	P	
10	2.228900	20.16	9.84	30.00	46.00	-16.00	AVG	P	
11	10.320000	43.79	10.08	53.87	60.00	-6.13	QP	P	
12	10.320000	31.31	10.08	41.39	50.00	-8.61	AVG	P	

Remark:


Margin = Level - Limit, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor




## 6. RADIATION EMISSION TEST

### 6.1 Block Diagram of Test Setup

Radiated Emission Test-Up Frequency Below 30MHz



Below 1GHz



### 6.2 Test Standard and Limit

FCC Part 15 Subpart C



Limits for frequency below 30MHz

Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.090	2400/F(kHz)	300	AVERAGE
0.090-0.110	2400/F(kHz)	300	Quasi-peak Value
0.110-0.490	2400/F(kHz)	300	AVERAGE
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value

Above 30MHz

Frequency (MHz)	Distance (Meters)	Field Strengths Limits (dBμV/m)	Remark
30 ~ 88	3	40.0	Quasi-peak Value
88 ~ 216	3	43.5	Quasi-peak Value
216 ~ 960	3	46.0	Quasi-peak Value
960 ~ 1000	3	54.0	Quasi-peak Value
Above 1000	3	74.0	PEAK
		54.0	AVERAGE

Remark:

(1) The smaller limit shall apply at the cross point between two frequency bands.

(2) Distance refers to the distance in meters between the measuring instrument, antenna and the closed point of any part of the device or system.

### 6.3 EUT Configuration on Test

The FCC Part 15 Subpart C regulations test method must be used to find the maximum emission during radiated emission test.

The configuration of EUT is the same as used in conducted emission test.

Please refer to Section 5.3.

### 6.4 Operating Condition of EUT

Same as conducted emission test, which is listed in Section 5.4 except the test set up replaced as Section 6.2.

### 6.5 Test Procedure

- 1) The radiated emissions test was conducted in a semi-anechoic chamber.
- 2) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
- 3) Before final measurements of radiated emissions, a pre-scan was performed in the spectrum mode with the peak detector to find out the maximum emissions spectrum plots of the EUT.
- 4) The frequencies of maximum emission were determined in the final radiated emissions measurement. At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum disturbance. Measurements were performed for both horizontal and vertical antenna polarization.
- 5) The bandwidth setting on the field strength meter (R&S Test Receiver ESCI) is set at 120KHz.
- 6) The frequency range from 9KHz to 1000MHz is checked.


### 6.6 Test Result

PASS, Please refer to the following page.



## Radiation Emission Test Data 9 kHz~30 MHz

Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Polarization:	/
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1



Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
0.0558	34.40	20.11	54.51	113.02	-58.51	AVERAGE
0.1385	51.89	20.22	72.11	105.06	-32.95	AVERAGE
0.5500	28.57	20.32	48.89	72.98	-24.09	QP
2.2559	24.15	20.39	44.54	70	-25.46	QP
7.8041	23.56	20.47	44.03	70	-25.97	QP
19.8353	21.42	20.58	42	70	-28	QP

## Note:

Pre-scan in the all of mode, the worst case in of was recorded.

Factor = antenna factor + cable loss – pre-amplifier.


Margin = Emission Level(Meter Reading+ Factor) - Limit.





## Radiation Emission Test Data

Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV/m	dB/m	dB	
1		32.6340	33.52	-14.01	19.51	40.00	-20.49	QP
2		50.2323	33.96	-11.49	22.47	40.00	-17.53	QP
3	*	78.4133	39.30	-15.99	23.31	40.00	-16.69	QP
4		139.3610	38.36	-16.10	22.26	43.50	-21.24	QP
5		222.1697	36.81	-12.62	24.19	46.00	-21.81	QP
6		428.0192	37.19	-8.59	28.60	46.00	-17.40	QP



## Radiation Emission Test Data

Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Margin dB	Detector
1	*	37.2854	38.43	-13.20	25.23	40.00	-14.77	QP
2		57.5940	36.53	-11.75	24.78	40.00	-15.22	QP
3		96.4360	32.75	-15.17	17.58	43.50	-25.92	QP
4		148.4410	39.03	-16.45	22.58	43.50	-20.92	QP
5		297.2238	35.35	-9.68	25.67	46.00	-20.33	QP
6		622.8900	34.82	-4.22	30.60	46.00	-15.40	QP

## Remarks:

- 1.Final Level =Receiver Read level + Correct factor (Antenna Factor + Cable Loss – Preamplifier Factor )
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.




## 7. BANDWIDTH TEST

### 7.1 TEST SETUP

1. Set RBW = 3kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

### 7.2 TEST SETUP



### 7.3 TEST Result

Frequency (KHz)	20dB bandwidth (KHz)	Result
138	8.188	Pass





## 8. ANTENNA REQUIREMENT

### a) STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### b) EUT ANTENNA

The EUT antenna is Inductive loop coil Antenna. It comply with the standard requirement.

## 9. SETUP PHOTOGRAPHS

Reference to the setup photo for details.

## 10. EUT PHOTOGRAPHS

Reference to the external and internal photo for details.

\*\*\*\*\* END OF REPORT \*\*\*\*\*