



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20250200351E -02

Applicant: Shenzhen ICHECKKEY Technology Co.,Ltd.

Address of Applicant: B302, Building 4, TianYanXuan, No.1 Lane14, Bantian East Village, Bantian Street, LongGang District, Shenzhen China. 518000

Equipment Under Test (EUT):

Product: T18 3-in-1 Foldable Magnetic Wireless Charging Stand

Model No.: T18

Test Model No.: T18

Brand Name: ICHECKKEY

FCC ID: 2AYA5-T18

Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB 680106 D01 RF Exposure Wireless Charging Base App v04r01

Date of Receipt: 2025-2-25

Date of Test: 2025-2-25 to 2025-3-31

Date of Issue: 2025-4-2

Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

(Joe Wang)

Reviewed By:

(Timo Lei)

Approved By:

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20250200351E -02	Rev.01	Initial report	2025-4-2

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
3.4 TEST ENVIRONMENT	5
3.5 DESCRIPTION OF SUPPORT UNITS	5
3.6 TEST LOCATION	6
3.7 TEST FACILITY	6
3.8 EQUIPMENT LIST	6
4 RF EXPOSURE EVALUATION	7
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
4.1.1 Limits	7
4.1.2 Test Procedure	7
4.1.3 Test Setup	8
4.1.4 Test Results	8
4.1.5 Test Results	10
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	13

3 General Information

3.1 Client Information

Applicant:	Shenzhen ICHECKKEY Technology Co.,Ltd.
Address of Applicant:	B302, Building 4, TianYanXuan, No.1 Lane14, Bantian East Village, Bantian Street, LongGang District, Shenzhen China. 518000
Manufacturer:	Shenzhen ICHECKKEY Technology Co.,Ltd.
Address of Manufacturer:	B302, Building 4, TianYanXuan, No.1 Lane14, Bantian East Village, Bantian Street, LongGang District, Shenzhen China. 518000
Factory:	Shenzhen ICHECKKEY Technology Co.,Ltd.
Address of Factory:	B302, Building 4, TianYanXuan, No.1 Lane14, Bantian East Village, Bantian Street, LongGang District, Shenzhen China. 518000

3.2 General Description of EUT

Product Name:	T18 3-in-1 Foldable Magnetic Wireless Charging Stand
Model No.:	T18
Test Model No.:	T18
Brand Name:	ICHECKKEY
Software Version:	V2.0
Hardware Version:	V2.0
EUT Power Supply:	5V $\Rightarrow$ 3A /9V $\Rightarrow$ 2.22A/12V $\Rightarrow$ 1.67A

3.3 Product Specification subjective to this standard

Equipment Category:	Non-ISM frequency
Operation Frequency range:	115kHz~205kHz, 315kHz~330kHz
Modulation Type:	Induction
Antenna Type:	Induction coil
Antenna Gain:	0dBi

Note:

1. In section 15.31(m), regards to the operating frequency range less 1 MHz.

3.4 Test Environment

Operating Environment:	
Temperature:	25.5 °C
Humidity:	53 % RH
Atmospheric Pressure:	100.1 kpa
Test Mode:	
Mode a:	Keep the EUT at Wireless Out Put for Watch 2.5W
Mode b:	Keep the EUT at Wireless Out Put for Earbuds 3.5W
Mode c:	Keep the EUT at Wireless Out Put for Phone 5W
Mode d:	Keep the EUT at Wireless Out Put for Phone 7.5W
Mode e:	Keep the EUT at Wireless Out Put for Phone 10W
Mode f:	Keep the EUT at Wireless Out Put for Phone 15W (Max)
Mode g:	Keep the EUT at wireless output phone 15W+watch 2.5W
Mode h:	Keep the EUT at wireless output phone 15W +Earbuds 3.5W
Mode i:	Keep the EUT at wireless output phone 10W+watch 2.5W
Mode j:	Keep the EUT at wireless output phone 10W +Earbuds 3.5W
Mode k:	Keep the EUT at wireless output phone 7.5W +Earbuds 2.5W
Mode l:	Keep the EUT at wireless output phone 7.5W +Earbuds 3.5W
Mode m:	Keep the EUT at wireless output phone 5W +Earbuds 2.5W
Mode n:	Keep the EUT at wireless output phone 5W +Earbuds 3.5W
Mode o:	Keep the EUT Wireless Out Put for Phone 15W+for Watch 2.5W+Earbuds 3.5W 21W (Total MAX)
Note: The above test modes all include full load,empty load,and half load, The worst-case state reflected in this report is the fully loaded state	

3.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
Adapter	/	/	/	CQA
Phone	APPLE	/	/	CQA
watch	APPLE	/	/	CQA
earphone	/	/	/	CQA

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

3.6 Test Location

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

3.7 Test Facility

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

3.8 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
Electromagnetic field analyzer	Narda	EHP-200A	AC-012	2024/3/12	2026/3/11

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

Note 1: f = frequency in MHz ; *Plane-wave equivalent power density

Note 2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v04


Note 3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

Note 4: The aggregate H-field strengths 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit .

4.1.2 Test Procedure

For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 20 cm(Top) . E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 20 cm(Top) from the center of the probe(s) to the edge of the device.

4.1.3 Test Setup



Note: Position A: Front of EUT; Position B: Left of EUT; Position C: back of EUT; Position D: Right of EUT; Position E: Top of EUT(20 cm measure distance);

4.1.4 Test Results

The EUT does comply with item 5 KDB680106 D01 v04r01.

Requirement	Device
1.Power transfer frequency is less than 1 MHz	Yes. The operating frequency range are.Operating frequency range: 115 kHz - 205KHz, 315kHz~330kHz
2. Output power from each primary coil is less than or equal to 15 watts.	Yes. The maximum output power is:Wireless Output: 15W(Max)
3.For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions.	Yes, the EUT has Three coil,all test modes met the conditions specified in (5).
4. Client device is placed directly in contact with the transmitter.	Yes. The client device is placed directly in contact with the transmitter.
5.Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion)	Yes. Mobile exposure conditions only.

6. The aggregate H-field strengths anywhere at or beyond 20 cm surrounding the device, and 20cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	Yes. See the test result in item 4.1.5

4.1.5 Test Results

Test condition: Mode f 115KHz-205KHz

Point A

Maximum permissible Exposure				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<1%	Top	20	0.8430	0.0223
<1%	Left	20	0.7320	0.0312
<1%	Right	20	0.4152	0.0413
<1%	Front	20	1.3130	0.0631
<1%	Back	20	0.2481	0.0221
Limit			614	1.63
test result			PASS	PASS

Maximum permissible Exposure				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<50%	Top	20	0.5252	0.0423
<50%	Left	20	0.6461	0.0311
<50%	Right	20	0.3851	0.0211
<50%	Front	20	1.1414	0.0402
<50%	Back	20	0.4122	0.0211
Limit			614	1.63
test result			PASS	PASS

Maximum permissible Exposure				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<99%	Top	20	0.6210	0.0434
<99%	Left	20	0.3162	0.0133
<99%	Right	20	0.3325	0.0341
<99%	Front	20	1.2386	0.0223
<99%	Back	20	0.2483	0.0321
Limit			614	1.63
test result			PASS	PASS

Test condition: Mode a 315KHz-330KHz

Point B

Maximum permissible Exposure				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<1%	Top	20	0.6421	0.0411
<1%	Left	20	0.6351	0.0301
<1%	Right	20	0.1051	0.0321
<1%	Front	20	1.1133	0.0521
<1%	Back	20	0.3655	0.0321
Limit			614	1.63
test result			PASS	PASS

Maximum permissible Exposure				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<50%	Top	20	0.6332	0.0221
<50%	Left	20	0.6364	0.0321
<50%	Right	20	0.2254	0.0615
<50%	Front	20	1.2428	0.0302
<50%	Back	20	0.5151	0.0417
Limit			614	1.63
test result			PASS	PASS

Maximum permissible Exposure				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<99%	Top	20	0.7122	0.0331
<99%	Left	20	0.7263	0.0332
<99%	Right	20	0.3123	0.0624
<99%	Front	20	1.6116	0.0114
<99%	Back	20	0.3628	0.0413
Limit			614	1.63
test result			PASS	PASS

Test condition: Mode o 115KHz-205KHz


Point C

Maximum permissible Exposure				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<1%	Top	20	0.6114	0.0213
<1%	Left	20	0.6251	0.0303
<1%	Right	20	0.3011	0.0123
<1%	Front	20	1.2132	0.0125
<1%	Back	20	0.3351	0.0121
Limit			614	1.63
test result			PASS	PASS

Maximum permissible Exposure				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<50%	Top	20	0.6136	0.0121
<50%	Left	20	0.4363	0.0235
<50%	Right	20	0.2250	0.0412
<50%	Front	20	1.1220	0.0201
<50%	Back	20	0.3150	0.0314
Limit			614	1.63
test result			PASS	PASS

Maximum permissible Exposure				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<99%	Top	20	0.6121	0.0453
<99%	Left	20	0.6223	0.0123
<99%	Right	20	0.4122	0.0312
<99%	Front	20	1.5124	0.0566
<99%	Back	20	0.3622	0.0478
Limit			614	1.63
test result			PASS	PASS

APPENDIX A: PHOTOGRAPHS OF TEST SETUP



*** END OF REPORT ***