

FCC Part 15 EMI TEST REPORT of

E.U.T. : WIRELESS RECEIVER
MODEL : EM-XSW1 DUAL, EM-XSW1,
EM-XSW2
FCC ID : DMOEMXSW1D
Frequency Range : 2433MHz~2473MHz

for

APPLICANT : Sennheiser Electric Corp.
ADDRESS : 1 Enterprise Drive, Old Lyme, CT 06371, USA

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN
NO. 34. LIN 5, DINGFU VIL., LINKOU DIST.,
NEW TAIPEI CITY, TAIWAN, 24442, R.O.C.
TEL : (02)26023052 FAX: (02)26010910

http : // www.etc.org.tw; e-mail : emc@etc.org.tw

Report Number : 19-10-RBF-028-01-A

TEST REPORT CERTIFICATION

Applicant : Sennheiser Electric Corp.
1 Enterprise Drive, Old Lyme, CT 06371, USA

Manufacturer : Sennheiser electronic GmbH & Co. KG
Am Labor 1
30900 Wedemark, Germany

Factory : MASCOT ELECTRIC CO., LTD
NO. 85, CHANGXING 1ST ST., RENDE DIST., TAINAN CITY 717,
TAIWAN

Description of EUT

- a) Type of EUT : WIRELESS RECEIVER
- b) Trade Name : SENNHEISER
- c) Model No. : EM-XSW1 DUAL, EM-XSW1, EM-XSW2
- d) Power Supply : Model: SSC-5WVI-12 (Type: NT12-5CW)
I/P: AC100-240V, 50-60Hz,0.2A ; O/P: 12Vdc, 500mA
- e) Frequency Range : 2433MHz~2473MHz

Regulation Applied : FCC Rules and Regulations Part 15 Subpart C

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.10-2013, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note: 1. The result of the testing report relate only to the item tested.
2. The testing report shall not be reproduced expect in full, without the written approval of ETC.

Summary of Tests

Test	Results
Radiated Emission	Pass
Conducted Emission	Pass
Band Edge Requirement	Pass
Duty Cycle	N.A.
20dB Bandwidth	Pass

Date Test Item Received : Oct. 29 , 2019
Date Test Campaign Completed : Mar. 11, 2020
Date of Issue : Mar. 25, 2020

Test Engineer : Brian Huang
(Brian-Huang , Engineer)

Checked By: Neo Lao
(Neo Lao)

Approve & Authorized : Vincent Chang
Vincent Chang, Supervisor
EMC Dept. II of ELECTRONICS
TESTING CENTER, TAIWAN



Table of ContentsPage

Cover Page.....	I
TEST REPORT CERTIFICATION.....	II
Table of Contents.....	IV
1 GENERAL INFORMATION	1
1.1 Product Description.....	1
1.2 Characteristics of Device	1
1.3 Test Methodology.....	1
1.4 Test Facility.....	1
2 PROVISIONS APPLICABLE	2
2.1 Definition	2
2.2 Requirement for Compliance	3
2.3 Restricted Bands of Operation	5
2.4 Labeling Requirement	5
2.5 User Information	6
3. SYSTEM TEST CONFIGURATION	7
3.1 Justification	7
3.2 Devices for Tested System	7
4 RADIATED EMISSION MEASUREMENT	8
4.1 Applicable Standard	8
4.2 Measurement Procedure	8
4.3 Measuring Instrument.....	10
4.4 Radiated Emission Data	11
4.4.1 RF Portion.....	11
4.4.2 Other Emissions	41
4.5 Field Strength Calculation.....	53
4.6 Photos of Radiation Measuring Setup.....	54
5 CONDUCTED EMISSION MEASUREMENT	60
5.1 Standard Applicable	60
5.2 Measurement Procedure	60
5.3 Conducted Emission Data	61
5.4 Result Data Calculation.....	73
5.5 Conducted Measurement Equipment	73
5.6 Photos of Conduction Measuring Setup.....	74
6 ANTENNA REQUIREMENT	77
6.1 Standard Applicable	77

6.2 Antenna Construction..... 77

7 BAND EDGES MEASUREMENT 78

7.1 Standard Applicable 78

7.2 Measurement Procedure 78

7.3 Measurement Equipment..... 79

7.4 Measurement Data..... 79

8. DTTY CYCLE 92

8.1 Standard Applicable 92

8.2 Measurement Equipment..... 92

8.3 Measurement Data..... 92

9. BANDWIDTH OF EMISSION..... 99

9.1 Applicable Standard 99

9.2 Measurement Procedure 99

9.3 Measurement Equipment..... 100

9.4 Measurement Data..... 101

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : WIRELESS RECEIVER
- b) Trade Name : SENNHEISER
- c) Model No. : EM-XSW1 DUAL, EM-XSW1, EM-XSW2
- d) Power Supply : Model: SSC-5WVI-12 (Type: NT12-5CW)
I/P: AC100-240V, 50-60Hz, 0.2A ; O/P: 12Vdc, 500mA
- e) Frequency Range : 2433MHz~2473MHz

1.2 Characteristics of Device

The EUT is a Wireless Microphone Receiver with 2.4GHz SYNC function.

1.3 Test Methodology

Both conducted and radiated emissions were performed according to the procedures illustrated in ANSI C63.10-2013. Other required measurements were illustrated in separate sections of this test report for details.

Measurement Software

Software	Version	Note
e3	Version 6.100618f	Radiated Emission Test
e3	Version 6.100421	Conducted Emission Test

1.4 Test Facility

Location of the Test site: No.34, Lin 5, Dingfu Vil., Linkou Dist., New Taipei City, Taiwan 24442, R.O.C.

Designation Number: TW2628.

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business of industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50MH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56	56-46
0.5 - 5.0	56	46
5.0 - 30.0	60	50

(2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

For intentional radiator device, per §15.249(a), the field strength of emissions shall comply with the following :

Frequency MHz	Distance Meters	Fundamental		Harmonic	
		dB μ V/m	mV/m	dB μ V/m	μ V/m
902 - 928	3	94	50	54	500
2400 - 2483.5	3	94	50	54	500
5725 - 5875	3	94	50	54	500
24000 - 24250	3	108	250	68	2500

In accordance with §15.249(e), limits shown in above table are based on average limits for frequencies above 1000 MHz, and frequencies below 1000 MHz are based on quasi peak. However, the peak field strength of any emission shall not exceed the maximum permitted average limits by more than 20 dB.

(3) Spurious in Out Band Requirement

For intentional device, according to §15.249 (d), emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of fundamental or to the general radiated emission limits in §15.209.

(4) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

3. SYSTEM TEST CONFIGURATION

3.1 Justification

For both radiated and conducted emissions, the system was configured for testing in a typical fashion as a customer would normally use it. The peripherals other than EUT were connected in normally standing by situation.

All measurement were intentional to maximum the emissions from EUT by varying the connection cables(if applicable), therefore, the test result is sure to meet the applicable requirement.

3.2 Devices for Tested System

Device	Manufacturer	Model / FCC ID	Description
WIRELESS RECEIVER*	Sennheiser electronic GmbH & Co. KG	EM-XSW1 DUAL, EM-XSW1, EM-XSW2 / DMOEMXSW1D	1.5m Unshielded AC Adapter

Remark “*” means equipment under test.

4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For intentional radiators, according to §15.249 (a), the fundamental field strength shall not exceed 94 dB μ V/m and the harmonics shall not exceed 54 dB μ V/m. For out band emission except for harmonics shall be comply with §15.209 or at least attenuated by 50 dB below the level of the fundamental.

4.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the placement of cables associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement:

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Keysight	N9038A	2019/11/21	2020/11/20
Bi-Log Antenna	ETC & JYEBAO	MCTD 2786 & FAT- NM5NF5 T3G2W6	2019/08/20	2020/08/19
Double Ridged Guide Horn Antenna	EMCO	3116	2019/11/26	2020/11/25
Double Ridged Antenna	EMCO	3117	2019/03/13	2020/03/12
Amplifier	HP	8449B	2019/10/04	2020/10/03
Amplifier	HP	8447D	2019/10/04	2020/10/03

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz or $\geq 1/T$ (Note 1)


Note 1:

VBW = 10 Hz, when the duty cycle is no less than 98%.

VBW $\geq 1/T$, when duty cycle is less than 98% where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

4.4 Radiated Emission Data

4.4.1 RF Portion




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:HORIZONTAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2433.0000	81.41	-0.62	80.79	114.00	-33.21	Peak
2452.8000	81.04	-0.52	80.52	114.00	-33.48	Peak
2472.8000	80.73	-0.49	80.24	114.00	-33.76	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:VERTICAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2433.0000	86.08	-0.62	85.46	114.00	-28.54	Peak
2452.8000	85.81	-0.52	85.29	114.00	-28.71	Peak
2472.8000	85.61	-0.49	85.12	114.00	-28.88	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4866.0000	44.89	2.95	47.84	74.00	-26.16	Peak
4905.6000	44.84	2.85	47.69	74.00	-26.31	Peak
4945.6000	44.58	2.97	47.55	74.00	-26.45	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4866.0000	44.95	2.95	47.90	74.00	-26.10	Peak
4905.6000	44.87	2.85	47.72	74.00	-26.28	Peak
4945.6000	44.42	2.97	47.39	74.00	-26.61	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Standby Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4905.6000	43.57	4.04	47.61	74.00	-26.39	Peak
4945.6000	43.24	4.15	47.39	74.00	-26.61	Peak
4980.0000	43.27	4.19	47.46	74.00	-26.54	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Standby Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4866.0000	43.43	4.15	47.58	74.00	-26.42	Peak
4905.6000	43.69	4.04	47.73	74.00	-26.27	Peak
4945.6000	43.46	4.15	47.61	74.00	-26.39	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2334.5000	46.39	-1.05	45.34	74.00	-28.66	Peak
2361.8000	46.61	-0.90	45.71	74.00	-28.29	Peak
2490.2400	46.51	-0.43	46.08	74.00	-27.92	Peak
2498.1000	46.24	-0.42	45.82	74.00	-28.18	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2334.1000	46.34	-1.06	45.28	74.00	-28.72	Peak
2368.5000	46.74	-0.87	45.87	74.00	-28.13	Peak
2486.2000	46.09	-0.44	45.65	74.00	-28.35	Peak
2498.2000	46.27	-0.42	45.85	74.00	-28.15	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:62 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2322.5000	43.01	-1.18	41.83	74.00	-32.17	Peak
2352.7500	44.11	-0.96	43.15	74.00	-30.85	Peak
2485.0000	45.69	-0.47	45.22	74.00	-28.78	Peak
2499.7500	45.26	-0.45	44.81	74.00	-29.19	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:62 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2338.2500	44.05	-1.06	42.99	74.00	-31.01	Peak
2359.7500	47.32	-0.94	46.38	74.00	-27.62	Peak
2486.7500	45.84	-0.47	45.37	74.00	-28.63	Peak
2498.7500	46.28	-0.45	45.83	74.00	-28.17	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.

4.4. 2 RF Portion




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:HORIZONTAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2433.0000	74.20	-0.62	73.58	114.00	-40.42	Peak
2452.8000	73.83	-0.52	73.31	114.00	-40.69	Peak
2472.8000	73.67	-0.49	73.18	114.00	-40.82	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:VERTICAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2433.0000	75.02	-0.62	74.40	114.00	-39.60	Peak
2452.8000	74.74	-0.52	74.22	114.00	-39.78	Peak
2472.8000	74.68	-0.49	74.19	114.00	-39.81	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4866.0000	43.32	2.95	46.27	74.00	-27.73	Peak
4905.6000	43.32	2.85	46.17	74.00	-27.83	Peak
4945.6000	43.34	2.97	46.31	74.00	-27.69	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4866.0000	43.40	2.95	46.35	74.00	-27.65	Peak
4905.6000	43.42	2.85	46.27	74.00	-27.73	Peak
4945.6000	43.01	2.97	45.98	74.00	-28.02	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Standby Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4866.0000	43.53	4.15	47.68	74.00	-26.32	Peak
4905.6000	43.71	4.04	47.75	74.00	-26.25	Peak
4945.6000	43.68	4.15	47.83	74.00	-26.17	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Standby Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4866.0000	43.79	4.15	47.94	74.00	-26.06	Peak
4905.6000	43.43	4.04	47.47	74.00	-26.53	Peak
4945.6000	43.60	4.15	47.75	74.00	-26.25	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2346.0000	46.61	-0.96	45.65	74.00	-28.35	Peak
2360.7000	46.18	-0.90	45.28	74.00	-28.72	Peak
2487.2000	46.23	-0.44	45.79	74.00	-28.21	Peak
2493.6000	45.93	-0.43	45.50	74.00	-28.50	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	:EM-XSW1	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2334.5000	46.82	-1.05	45.77	74.00	-28.23	Peak
2358.2000	46.81	-0.90	45.91	74.00	-28.09	Peak
2487.3000	46.26	-0.44	45.82	74.00	-28.18	Peak
2495.3000	46.12	-0.43	45.69	74.00	-28.31	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:62 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2331.0000	46.50	-1.11	45.39	74.00	-28.61	Peak
2350.7500	46.90	-0.97	45.93	74.00	-28.07	Peak
2486.2500	46.88	-0.47	46.41	74.00	-27.59	Peak
2496.0000	46.32	-0.46	45.86	74.00	-28.14	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:62 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2327.5000	45.97	-1.15	44.82	74.00	-29.18	Peak
2358.7500	46.63	-0.94	45.69	74.00	-28.31	Peak
2485.5000	46.50	-0.47	46.03	74.00	-27.97	Peak
2497.7500	45.66	-0.45	45.21	74.00	-28.79	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2433.0000	78.93	-0.62	78.31	114.00	-35.69	Peak
2452.8000	78.81	-0.52	78.29	114.00	-35.71	Peak
2472.8000	78.54	-0.49	78.05	114.00	-35.95	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2433.0000	79.28	-0.62	78.66	114.00	-35.34	Peak
2452.8000	78.86	-0.52	78.34	114.00	-35.66	Peak
2472.8000	78.71	-0.49	78.22	114.00	-35.78	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4866.0000	44.09	2.95	47.04	74.00	-26.96	Peak
4905.6000	43.94	2.85	46.79	74.00	-27.21	Peak
4945.6000	43.62	2.97	46.59	74.00	-27.41	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4866.0000	43.96	2.95	46.91	74.00	-27.09	Peak
4905.6000	44.00	2.85	46.85	74.00	-27.15	Peak
4945.6000	43.80	2.97	46.77	74.00	-27.23	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Standby Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4866.0000	43.62	4.15	47.77	74.00	-26.23	Peak
4905.6000	42.96	4.04	47.00	74.00	-27.00	Peak
4945.6000	43.45	4.15	47.60	74.00	-26.40	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Standby Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4866.0000	43.43	4.15	47.58	74.00	-26.42	Peak
4905.6000	43.69	4.04	47.73	74.00	-26.27	Peak
4945.6000	43.46	4.15	47.61	74.00	-26.39	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2339.2000	46.29	-1.01	45.28	74.00	-28.72	Peak
2366.3000	46.05	-0.88	45.17	74.00	-28.83	Peak
2486.7000	46.13	-0.44	45.69	74.00	-28.31	Peak
2498.5100	46.14	-0.42	45.72	74.00	-28.28	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2351.5000	46.84	-0.93	45.91	74.00	-28.09	Peak
2371.3000	46.53	-0.87	45.66	74.00	-28.34	Peak
2487.3000	46.26	-0.44	45.82	74.00	-28.18	Peak
2498.5240	45.70	-0.42	45.28	74.00	-28.72	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:62 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2329.7500	45.79	-1.13	44.66	74.00	-29.34	Peak
2358.7500	46.63	-0.94	45.69	74.00	-28.31	Peak
2488.2500	46.39	-0.47	45.92	74.00	-28.08	Peak
2502.0000	46.65	-0.45	46.20	74.00	-27.80	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.



Site	:Chamber #2	Date	:2020-03-10
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:62 %
Test Mode	:Stand by Mode		


Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2340.7500	46.19	-1.05	45.14	74.00	-28.86	Peak
2360.2500	46.53	-0.94	45.59	74.00	-28.41	Peak
2488.7500	45.47	-0.47	45.00	74.00	-29.00	Peak
2501.5000	46.88	-0.45	46.43	74.00	-27.57	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.

4.4.2 Other Emissions

a) Emission frequencies below 1 GHz




Site	:Chamber#2	Date	:2020-02-27
Limit	:FCC CLASS-B	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
117.6210	32.37	-8.23	24.14	43.50	-19.36	QP
188.5260	34.39	-9.46	24.93	43.50	-18.57	QP
281.6250	33.62	-4.00	29.62	46.00	-16.38	QP
351.6200	32.33	-2.26	30.07	46.00	-15.93	QP
395.9210	34.96	-1.04	33.92	46.00	-12.08	QP
481.2650	35.47	0.13	35.60	46.00	-10.40	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:FCC CLASS-B	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
132.0550	31.78	-7.59	24.19	43.50	-19.31	QP
177.4950	34.23	-8.95	25.28	43.50	-18.22	QP
286.5140	32.66	-3.67	28.99	46.00	-17.01	QP
351.4500	32.50	-2.25	30.25	46.00	-15.75	QP
394.2500	34.46	-1.09	33.37	46.00	-12.63	QP
457.4100	34.46	-0.37	34.09	46.00	-11.91	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:FCC CLASS-B	Ant. Pol.	:HORIZONTAL
EUT	: WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
102.7500	34.83	-9.57	25.26	43.50	-18.24	QP
210.4200	34.48	-6.66	27.82	43.50	-15.68	QP
261.8300	34.83	-4.68	30.15	46.00	-15.85	QP
375.3200	35.26	-1.53	33.73	46.00	-12.27	QP
437.4000	34.86	-0.33	34.53	46.00	-11.47	QP
504.3300	35.00	0.24	35.24	46.00	-10.76	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:FCC CLASS-B	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
125.0600	33.41	-7.78	25.63	43.50	-17.87	QP
226.9100	35.10	-7.17	27.93	46.00	-18.07	QP
375.3200	35.26	-1.53	33.73	46.00	-12.27	QP
463.5900	35.90	-0.37	35.53	46.00	-10.47	QP
521.7900	34.98	0.44	35.42	46.00	-10.58	QP
585.8100	35.02	1.62	36.64	46.00	-9.36	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:FCC CLASS-B	Ant. Pol.	:HORIZONTAL
EUT	:EM-XSW1	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
110.3200	33.03	-8.82	24.21	43.50	-19.29	QP
196.2150	35.32	-9.24	26.08	43.50	-17.42	QP
273.5100	34.30	-4.49	29.81	46.00	-16.19	QP
342.5100	33.75	-2.50	31.25	46.00	-14.75	QP
388.5100	34.53	-1.28	33.25	46.00	-12.75	QP
460.2840	34.43	-0.37	34.06	46.00	-11.94	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:FCC CLASS-B	Ant. Pol.	:VERTICAL
EUT	:EM-XSW1	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
120.1350	31.87	-8.06	23.81	43.50	-19.69	QP
240.5600	30.77	-6.55	24.22	46.00	-21.78	QP
384.6200	32.32	-1.37	30.95	46.00	-15.05	QP
427.1500	32.82	-0.83	31.99	46.00	-14.01	QP
470.1600	34.11	-0.17	33.94	46.00	-12.06	QP
522.2700	31.85	0.45	32.30	46.00	-13.70	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:FCC CLASS-B	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
132.8200	32.48	-7.51	24.97	43.50	-18.53	QP
214.3000	31.12	-6.94	24.18	43.50	-19.32	QP
301.6000	31.67	-2.93	28.74	46.00	-17.26	QP
324.8800	32.69	-2.69	30.00	46.00	-16.00	QP
418.9700	33.21	-0.79	32.42	46.00	-13.58	QP
531.4900	32.72	0.73	33.45	46.00	-12.55	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:FCC CLASS-B	Ant. Pol.	:VERTICAL
EUT	WIRELESS RECEIVER	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
154.1600	34.27	-7.63	26.64	43.50	-16.86	QP
295.7800	34.95	-3.07	31.88	46.00	-14.12	QP
362.7100	34.11	-1.87	32.24	46.00	-13.76	QP
444.1900	34.57	-0.34	34.23	46.00	-11.77	QP
539.2500	33.85	0.76	34.61	46.00	-11.39	QP
618.7900	33.86	1.92	35.78	46.00	-10.22	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:FCC CLASS-B	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
117.1600	31.72	-8.27	23.45	43.50	-20.05	QP
166.4000	32.47	-8.15	24.32	43.50	-19.18	QP
241.2800	35.12	-6.47	28.65	46.00	-17.35	QP
351.4700	33.94	-2.25	31.69	46.00	-14.31	QP
415.0200	33.38	-0.87	32.51	46.00	-13.49	QP
486.2540	33.09	0.13	33.22	46.00	-12.78	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:FCC CLASS-B	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
124.1640	31.42	-7.88	23.54	43.50	-19.96	QP
198.6500	35.15	-8.90	26.25	43.50	-17.25	QP
284.6500	32.40	-3.79	28.61	46.00	-17.39	QP
324.1600	32.95	-2.70	30.25	46.00	-15.75	QP
394.6510	34.36	-1.07	33.29	46.00	-12.71	QP
454.1900	34.99	-0.37	34.62	46.00	-11.38	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:FCC CLASS-B	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
137.6700	34.00	-7.42	26.58	43.50	-16.92	QP
211.3900	33.99	-6.73	27.26	43.50	-16.24	QP
261.8300	34.83	-4.68	30.15	46.00	-15.85	QP
333.6100	35.41	-2.63	32.78	46.00	-13.22	QP
408.3000	34.56	-0.87	33.69	46.00	-12.31	QP
504.3300	35.00	0.24	35.24	46.00	-10.76	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.



Site	:Chamber #2	Date	:2020-03-10
Limit	:FCC CLASS-B	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
121.1800	33.60	-8.04	25.56	43.50	-17.94	QP
211.3900	33.99	-6.73	27.26	43.50	-16.24	QP
295.7800	34.95	-3.07	31.88	46.00	-14.12	QP
336.5200	33.77	-2.57	31.20	46.00	-14.80	QP
408.3000	34.56	-0.87	33.69	46.00	-12.31	QP
437.4000	34.86	-0.33	34.53	46.00	-11.47	QP

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.

b) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 26.5 GHz were too low to be measured with a pre-amplifier of 35 dB.

c) Emission frequencies below 30MHz (9kHz - 30MHz)

According to exploratory test no any obvious emission were detected from 9kHz to 30MHz.

4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\textbf{Result} = \textbf{Reading} + \textbf{Corrected Factor}$$

where Corrected Factor

$$= \text{Antenna FACTOR} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

5 CONDUCTED EMISSION MEASUREMENT


5.1 Standard Applicable

For unintentional and intentional device, Line Conducted Emission Limits are in accordance to §15.107(a) and §15.207(a) respectively. Both Limits are identical specification.


5.2 Measurement Procedure

1. Setup the configuration per figure 3.
2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
3. Record the 6 or 8 highest emissions relative to the limit.
4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
6. Repeat all above procedures on measuring each operation mode of EUT.

Figure 3 : Conducted emissions measurement configuration



5.3 Conducted Emission Data




Site	: conducted #1	Date	: 2020-03-11
Condition	: FCC CLASS-B QP	LISN	: NEUTRAL
Tem / Hum	: 21 °C / 65%	Test Mode	: TX Mode
EUT	: WIRELESS RECEIVER	Power Rating	: 120Vac60Hz
Engineer	: Brian Huang		
Model	: EM-XSW1 DUAL		

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1549	33.96	9.98	43.94	65.74	-21.80	QP
0.1768	31.17	9.97	41.14	64.64	-23.50	QP
0.1986	28.54	9.97	38.51	63.67	-25.16	QP
0.2208	25.87	9.97	35.84	62.79	-26.95	QP
0.2280	25.53	9.97	35.50	62.52	-27.02	QP
0.3976	22.54	9.97	32.51	57.90	-25.39	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor



Site : conducted #1

Date : 2020-03-11

Condition : FCC CLASS-B QP

LISN : LINE

Tem / Hum : 21 °C / 65%

Test Mode : TX Mode

EUT : WIRELESS RECEIVER

Power Rating : 120Vac60Hz

Engineer : Brian Huang


Model : EM-XSW1 DUAL

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1557	34.55	9.97	44.52	65.69	-21.17	QP
0.1825	31.77	9.96	41.73	64.37	-22.64	QP
0.1986	28.83	9.95	38.78	63.67	-24.89	QP
0.2329	24.79	9.95	34.74	62.35	-27.61	QP
0.3035	19.43	9.94	29.37	60.15	-30.78	QP
0.3955	21.54	9.95	31.49	57.95	-26.46	QP

Note :

1. Result = Reading + Factor

2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor




Site	: conducted #1	Date	: 2020-03-11
Condition	: FCC CLASS-B QP	LISN	: NEUTRAL
Tem / Hum	: 21 °C / 65%	Test Mode	: TX Mode
EUT	: WIRELESS RECEIVER	Power Rating	: 120Vac60Hz
Engineer	: Brian Huang	Model	: EM-XSW1

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1549	34.53	9.98	44.51	65.74	-21.23	QP
0.1825	32.79	9.97	42.76	64.37	-21.61	QP
0.1874	31.81	9.97	41.78	64.15	-22.37	QP
0.2061	30.21	9.97	40.18	63.36	-23.18	QP
0.2208	28.14	9.97	38.11	62.79	-24.68	QP
0.4237	24.48	9.97	34.45	57.37	-22.92	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor



Site : conducted #1

Date : 2020-03-11

Condition : FCC CLASS-B QP

LISN : LINE

Tem / Hum : 21 °C / 65%

Test Mode : TX Mode

EUT : WIRELESS RECEIVER

Power Rating : 120Vac60Hz

Engineer : Brian Huang


Model : EM-XSW1

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1599	34.57	9.97	44.54	65.47	-20.93	QP
0.1768	31.82	9.96	41.78	64.64	-22.86	QP
0.1997	29.76	9.95	39.71	63.62	-23.91	QP
0.2268	27.25	9.95	37.20	62.57	-25.37	QP
0.2442	25.83	9.95	35.78	61.95	-26.17	QP
0.4193	22.46	9.95	32.41	57.46	-25.05	QP

Note :

1. Result = Reading + Factor

2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor



Site : conducted #1

Date : 2020-03-11

Condition : FCC CLASS-B QP

LISN : NEUTRAL

Tem / Hum : 21 °C / 65%

Test Mode : TX Mode

EUT : WIRELESS RECEIVER

Power Rating : 120Vac60Hz

Engineer : Brian Huang


Model : EM-XSW2

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1540	32.95	9.98	42.93	65.78	-22.85	QP
0.1815	31.33	9.97	41.30	64.42	-23.12	QP
0.1997	28.72	9.97	38.69	63.62	-24.93	QP
0.2280	26.57	9.97	36.54	62.52	-25.98	QP
0.2495	23.93	9.97	33.90	61.78	-27.88	QP
0.4193	25.03	9.97	35.00	57.46	-22.46	QP

Note :

1. Result = Reading + Factor

2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor



Site : conducted #1

Date : 2020-03-11

Condition : FCC CLASS-B QP

LISN : LINE

Tem / Hum : 21 °C / 65%

Test Mode : TX Mode

EUT : WIRELESS RECEIVER

Power Rating : 120Vac60Hz

Engineer : Brian Huang


Model : EM-XSW2

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1549	33.66	9.97	43.63	65.74	-22.11	QP
0.1768	31.28	9.96	41.24	64.64	-23.40	QP
0.1997	29.09	9.95	39.04	63.62	-24.58	QP
0.2197	26.45	9.95	36.40	62.83	-26.43	QP
0.2353	25.99	9.95	35.94	62.26	-26.32	QP
0.4171	22.20	9.95	32.15	57.51	-25.36	QP

Note :

1. Result = Reading + Factor

2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor



Site : conducted #1

Date : 2020-03-11

Condition : FCC CLASS-B QP

LISN : NEUTRAL

Tem / Hum : 21 °C / 65%

Test Mode : Standby Mode

EUT : WIRELESS RECEIVER

Power Rating : 120Vac60Hz

Engineer : Brian Huang


Model : EM-XSW1 DUAL

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1549	36.24	9.98	46.22	65.74	-19.52	QP
0.1768	33.03	9.97	43.00	64.64	-21.64	QP
0.1986	29.93	9.97	39.90	63.67	-23.77	QP
0.2208	26.61	9.97	36.58	62.79	-26.21	QP
0.2442	24.79	9.97	34.76	61.95	-27.19	QP
0.4215	24.36	9.97	34.33	57.42	-23.09	QP

Note :

1. Result = Reading + Factor

2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor



Site : conducted #1

Date : 2020-03-11

Condition : FCC CLASS-B QP

LISN : LINE

Tem / Hum : 21 °C / 65%

Test Mode : Standby Mode

EUT : WIRELESS RECEIVER

Power Rating : 120Vac60Hz

Engineer : Brian Huang


Model : EM-XSW1 DUAL

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1573	36.06	9.97	46.03	65.60	-19.57	QP
0.1777	33.02	9.96	42.98	64.59	-21.61	QP
0.1997	29.90	9.95	39.85	63.62	-23.77	QP
0.2521	23.73	9.95	33.68	61.69	-28.01	QP
0.2672	23.29	9.95	33.24	61.20	-27.96	QP
0.4127	21.24	9.95	31.19	57.59	-26.40	QP

Note :

1. Result = Reading + Factor

2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor




Site : conducted #1 Date : 2020-03-11
 Condition : FCC CLASS-B QP LISN : NEUTRAL
 Tem / Hum : 21 °C / 65%
 Test Mode : Standby Mode
 EUT : WIRELESS RECEIVER Power Rating : 120Vac60Hz
 Engineer : Brian Huang Model : EM-XSW1

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1590	31.02	9.98	41.00	65.52	-24.52	QP
0.1758	27.85	9.97	37.82	64.68	-26.86	QP
0.1986	26.33	9.97	36.30	63.67	-27.37	QP
0.2197	24.07	9.97	34.04	62.83	-28.79	QP
0.3051	19.64	9.96	29.60	60.10	-30.50	QP
0.4040	21.53	9.97	31.50	57.77	-26.27	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor




Site : conducted #1 Date : 2020-03-11
 Condition : FCC CLASS-B QP LISN : LINE
 Tem / Hum : 21 °C / 65%
 Test Mode : Standby Mode
 EUT : WIRELESS RECEIVER Power Rating : 120Vac60Hz
 Engineer : Brian Huang Model : EM-XSW1

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1549	30.73	9.97	40.70	65.74	-25.04	QP
0.1768	28.45	9.96	38.41	64.64	-26.23	QP
0.1997	26.66	9.95	36.61	63.62	-27.01	QP
0.2268	24.48	9.95	34.43	62.57	-28.14	QP
0.2508	22.72	9.95	32.67	61.73	-29.06	QP
0.4215	21.56	9.95	31.51	57.42	-25.91	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor



Site : conducted #1

Date : 2020-03-11

Condition : FCC CLASS-B QP

LISN : NEUTRAL

Tem / Hum : 21 °C / 65%

Test Mode : Standby Mode

EUT : WIRELESS RECEIVER

Power Rating : 120Vac60Hz

Engineer : Brian Huang


Model : EM-XSW2

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1599	34.49	9.98	44.47	65.47	-21.00	QP
0.1758	31.01	9.97	40.98	64.68	-23.70	QP
0.1997	29.33	9.97	39.30	63.62	-24.32	QP
0.2208	26.96	9.97	36.93	62.79	-25.86	QP
0.2429	25.02	9.97	34.99	62.00	-27.01	QP
0.4083	24.55	9.97	34.52	57.68	-23.16	QP

Note :

1. Result = Reading + Factor

2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor



Site : conducted #1

Date : 2020-03-11

Condition : FCC CLASS-B QP

LISN : LINE

Tem / Hum : 21 °C / 65%

Test Mode : Standby Mode

EUT : WIRELESS RECEIVER

Power Rating : 120Vac60Hz

Engineer : Brian Huang

Model : EM-XSW2

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1599	34.26	9.97	44.23	65.47	-21.24	QP
0.1825	31.76	9.96	41.72	64.37	-22.65	QP
0.1986	28.83	9.95	38.78	63.67	-24.89	QP
0.2094	28.47	9.95	38.42	63.23	-24.81	QP
0.2208	26.83	9.95	36.78	62.79	-26.01	QP
0.4083	21.71	9.95	31.66	57.68	-26.02	QP

Note :

1. Result = Reading + Factor

2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor

5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$\text{RESULT} = \text{READING} + \text{LISN FACTOR}$$

Assume a receiver reading of 22.5 dB μ V is obtained, and LISN Factor is 0.1 dB, then the total of disturbance voltage is 22.6 dB μ V.

$$\text{RESULT} = 22.5 + 0.1 = 22.6 \text{ dB}\mu\text{V}$$

$$\begin{aligned}\text{Level in } \mu\text{V} &= \text{Common Antilogarithm}[(22.6 \text{ dB}\mu\text{V})/20] \\ &= 13.48 \mu\text{V}\end{aligned}$$

5.5 Conducted Measurement Equipment

The following test equipment are used during the conducted test.

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESCI	2019/01/10	2020/01/09
LISN	Shibasoku	563	2018/10/14	2019/10/13
LISN	Rohde & Schwarz	ESH2-Z5	2019/05/16	2020/05/15

6 ANTENNA REQUIREMENT

6.1 Standard Applicable

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2 Antenna Construction

The device is equipped with the permanently attached on-board PCB antenna. No consideration of replacement. Please refer to the construction Photo for details.

7 BAND EDGES MEASUREMENT

7.1 Standard Applicable

According to 15.249(d), out band emission except for harmonics shall be comply with §15.209 or at least attenuated by 50 dB below the level of the fundamental.

7.2 Measurement Procedure

A) 50 dB attenuation method

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
4. Repeat above procedures until all measured frequencies were complete.

B) Radiated Emission method

1. Following the measurement procedures in section 4.2 with the EUT set to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
2. Measure the highest amplitude appearing on spectral displayed.
3. Repeat above procedures until all measured frequencies were complete.

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz or $\geq 1/T$ (Note 1)

Note 1:

VBW = 10 Hz, when the duty cycle is no less than 98%.

VBW \geq 1/T, when duty cycle is less than 98% where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

7.3 Measurement Equipment

A) 50 dB attenuation method

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Keysight	N9038A	2019/11/21	2020/11/20

B) Radiated Emission method


Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Keysight	N9038A	2019/11/21	2020/11/20
Bi-Log Antenna	ETC & JYEBAO	MCTD 2786 & FAT- NM5NF5T3 G2W6	2019/08/20	2020/08/19
Double Ridged Guide Horn Antenna	EMCO	3116	2019/11/26	2020/11/25
Double Ridged Antenna	EMCO	3117	2019/03/13	2020/03/12
Amplifier	HP	8449B	2019/10/04	2020/10/03
Amplifier	HP	8447D	2019/10/04	2020/10/03

7.4 Measurement Data

Test Result: (Radiated Emission method)

The radiated emission test results of the lower and the upper band edges were comply with §15.209. Please refer to the following pages for test results.

(1) Radiated Emission Test Results of the Band Edges




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	46.41	-0.79	45.62	74.00	-28.38	Peak
2483.5000	46.00	-0.47	45.53	74.00	-28.47	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	46.45	-0.79	45.66	74.00	-28.34	Peak
2483.5000	46.17	-0.47	45.70	74.00	-28.30	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:2.4GHZ PEAK	Ant. Pol.	:HORIZONTAL
EUT	:EM-XSW1 DUAL	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	44.10	-0.79	43.31	74.00	-30.69	Peak
2483.5000	44.30	-0.47	43.83	74.00	-30.17	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:2.4GHZ PEAK	Ant. Pol.	:VERTICAL
EUT	:EM-XSW1 DUAL	Model	:EM-XSW1 DUAL
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	46.92	-0.79	46.13	74.00	-27.87	Peak
2483.5000	45.08	-0.47	44.61	74.00	-29.39	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:HORIZONTAL
EUT	:EM-XSW1	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	46.07	-0.79	45.28	74.00	-28.72	Peak
2483.5000	46.25	-0.47	45.78	74.00	-28.22	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:VERTICAL
EUT	:EM-XSW1	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	46.34	-0.79	45.55	74.00	-28.45	Peak
2483.5000	46.25	-0.47	45.78	74.00	-28.22	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:2.4GHZ PEAK	Ant. Pol.	:HORIZONTAL
EUT	:EM-XSW1	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	45.63	-0.79	44.84	74.00	-29.16	Peak
2483.5000	45.11	-0.47	44.64	74.00	-29.36	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:2.4GHZ PEAK	Ant. Pol.	:VERTICAL
EUT	:EM-XSW1	Model	:EM-XSW1
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	44.81	-0.79	44.02	74.00	-29.98	Peak
2483.5000	44.63	-0.47	44.16	74.00	-29.84	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	46.60	-0.79	45.81	74.00	-28.19	Peak
2483.5000	46.10	-0.47	45.63	74.00	-28.37	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber#2	Date	:2020-02-27
Limit	:2.4GHZ PEAK	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:22°C
Engineer	: Brian Huang	Humi.	:72 %
Test Mode	:TX Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	46.62	-0.79	45.83	74.00	-28.17	Peak
2483.5000	45.92	-0.47	45.45	74.00	-28.55	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-03-10
Limit	:2.4GHZ PEAK	Ant. Pol.	:HORIZONTAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	46.61	-0.79	45.82	74.00	-28.18	Peak
2483.5000	45.11	-0.47	44.64	74.00	-29.36	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.



Site	:Chamber #2	Date	:2020-03-10
Limit	:2.4GHZ PEAK	Ant. Pol.	:VERTICAL
EUT	:WIRELESS RECEIVER	Model	:EM-XSW2
Power Rating	:120Vac60Hz	Temp.	:20°C
Engineer	: Brian Huang	Humi.	:63 %
Test Mode	:Stand by Mode		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2400.0000	46.23	-0.79	45.44	74.00	-28.56	Peak
2483.5000	45.38	-0.47	44.91	74.00	-29.09	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.

8. DUTY CYCLE

8.1 Standard Applicable

None. Reference only.

8.2 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP 40	2020/01/15	2021/01/14

8.3 Measurement Data

1) Test model : EM-XSW1 DUAL

Test Date : Mar. 11, 2020 Temperature : 21 °C Humidity : 65 %

Duty Cycle Calculation

1) L : Period = 5.14ms

Transmission duration (T) = 1.54ms + 0.38ms = 1.92ms

Duty Cycle (%) = $(1.92 / 5.14) * 100 \% = 37.3 \%$

2) R : Period = 5.18ms

Transmission duration (T) = 1.58ms + 0.42ms = 2.0ms

Duty Cycle (%) = $(2.0 / 5.18) * 100 \% = 38.6 \%$

The duty cycle is less than 98%. For the average measurement of the radiated emission test, the VBW setting is $>1/T$ where the T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


L: $1/T = 1 / 1.92\text{ms} = 520 \text{ Hz}$

R: $1/T = 1 / 2.0\text{ms} = 500 \text{ Hz}$

Hence the VBW setting for the average measurement is 1kHz.


Refer to the following page for data plots.

Period(L)




Date: 11.MAR.2020 09:37:03

Transmission duration (T)




Date: 11.MAR.2020 09:37:21




Date: 11.MAR.2020 09:37:41

Period(R)




Date: 11.MAR.2020 09:44:40

Transmission duration (T)



Date: 11.MAR.2020 09:44:58



Date: 11.MAR.2020 09:45:19

2)Test model : EM-XSW1Test Date : Mar. 11, 2020 Temperature : 21 °C Humidity : 65 %**Duty Cycle Calculation**

Period = 6.74ms

Transmission duration (T) = 1.58ms + 2.38ms = 3.96ms

Duty Cycle (%) = $(3.96 / 6.74) * 100 \% = 58.8 \%$


The duty cycle is less than 98%. For the average measurement of the radiated emission test, the VBW setting is $>1/T$ where the T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

 $1/T = 1 / 3.96\text{ms} = 252\text{Hz}$

Hence the VBW setting for the average measurement is 1kHz.


Refer to the following page for data plots.

Period




Date: 11.MAR.2020 10:05:59

Transmission duration (T)



Date: 11.MAR.2020 10:06:10



Date: 11.MAR.2020 10:06:31

(3)Test model : EM-XSW2Test Date : Mar. 11, 2020 Temperature : 21 °C Humidity : 65 %**Duty Cycle Calculation**

Period = 42.1ms

Transmission duration (T) = 4.7ms + 4.3ms = 9.0ms

Duty Cycle (%) = $(9.0 / 42.1) * 100 \% = 21.4\%$


The duty cycle is less than 98%. For the average measurement of the radiated emission test, the VBW setting is $>1/T$ where the T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

$$1/T = 1 / 9.0\text{ms} = 111 \text{ Hz}$$

Hence the VBW setting for the average measurement is 1kHz.


Refer to the following page for data plots.

Period




Date: 11.MAR.2020 09:55:06

Transmission duration (T)



Date: 11.MAR.2020 09:55:21



Date: 11.MAR.2020 09:55:34

9. BANDWIDTH OF EMISSION

9.1 Applicable Standard

Per FCC rule §15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. The settings of spectrum analyzer is as followings.
 - 1) Set RBW in the range of 1% to 5% of the OBW.
 - 2) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - 3) Detector = Peak.
 - 4) Trace mode = max hold.
 - 5) Sweep = auto couple.
 - 6) Allow the trace to stabilize.
 - 7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission. Alternatively, use the -20 dB bandwidth function of the spectrum analyzer.
3. Repeat above procedures until all frequencies measured were complete.

Figure 4: Emission bandwidth measurement configuration.



9.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP 40	2020/01/15	2021/01/14

9.4 Measurement Data

(1) Test model : EM-XSW1 DUAL


Test Date : Mar. 11, 2020 Temperature : 21 °C Humidity : 65 %

- a) Lower Band Edge : The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.
- b) Upper Band Edge : The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.

Note : The expanded uncertainty: $\text{frequency} \times 1.65 \times 10^{-6}$ ($1 \text{ GHz} < f \leq 18 \text{ GHz}$).

1) L


Lower band edge / -20dB BW plot of the lowest channel




Date: 11.MAR.2020 09:40:05

The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.

Upper band edge / -20dB BW plot of the highest channel



Date: 11.MAR.2020 09:41:48




Date: 11.MAR.2020 09:43:15

The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.

1) R


Lower band edge / -20dB BW plot of the lowest channel




Date: 11.MAR.2020 09:46:30

The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.

Upper band edge / -20dB BW plot of the highest channel



Date: 11.MAR.2020 09:48:18



Date: 11.MAR.2020 09:50:40

The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.


2) Test model : EM-XSW1

Test Date : Mar. 11, 2020Temperature : 21 °C Humidity : 65 %

- a) Lower Band Edge : The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.
- b) Upper Band Edge : The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.

Note : The expanded uncertainty: $\text{frequency} \times 1.65 \times 10^{-6}$ ($1 \text{ GHz} < f \leq 18 \text{ GHz}$).


Lower band edge / -20dB BW plot of the lowest channel




Date: 11.MAR.2020 10:07:30

The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.

Upper band edge / -20dB BW plot of the highest channel



Date: 11.MAR.2020 10:09:09



Date: 11.MAR.2020 10:10:41

The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.


3) Test model : EM-XSW2

Test Date : Mar. 11, 2020Temperature : 21 °C Humidity : 65 %

- a) Lower Band Edge : The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.
- b) Upper Band Edge : The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.

Note : The expanded uncertainty: $\text{frequency} \times 1.65 \times 10^{-6}$ ($1 \text{ GHz} < f \leq 18 \text{ GHz}$).

Lower band edge / -20dB BW plot of the lowest channel




Date: 11.MAR.2020 09:57:14

The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.

Upper band edge / -20dB BW plot of the highest channel



Date: 11.MAR.2020 10:00:40



Date: 11.MAR.2020 10:02:32

The 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section 15.249.