

FCC Test Report

Report No.: AGC13779250301FR02

FCC ID	:	Z63-H0LA87
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	WIRELESS MECHANICAL KEYBOARD
BRAND NAME	:	AUSDOM
MODEL NAME	:	Hola87, Hola87 pro, Hola87 ultra, Hola75, Hola75 pro, Hola75 Ultra, Hola98, Hola98Ultra, Hola98 X, Hola108, Hola108 pro, Hola104, Hola104 pro, Hola104L, Hola68, Hola68 pro
APPLICANT	:	SHENZHEN AONI ELECTRONIC CO., LTD.
DATE OF ISSUE	:	Apr. 17, 2025
STANDARD(S)	:	FCC Part 15 Subpart C §15.247
REPORT VERSION	:	V1.0
<u>Attestation Of</u>	<u> Glc</u>	bal Compliance (Shenzhen) Co., Ltd





Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	Apr. 17, 2025	Valid	Initial Release	



Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Test Frequency List	6
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Special Accessories	7
2.6 Equipment Modifications	7
2.7 Antenna Requirement	7
3. Test Environment	
3.1 Address of the Test Laboratory	
3.2 Test Facility	
3.3 Environmental Conditions	9
3.4 Measurement Uncertainty	9
3.5 List of Equipment Use	
4.System Test Configuration	
4.1 EUT Configuration	
4.2 EUT Exercise	
4.3 Configuration of Tested System	
4.4 Equipment Used In Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	14
6. Duty Cycle Measurement	
7. RF Output Power Measurement	
7.1 Provisions Applicable	
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	
7.4 Measurement Result	
8. 6dB Bandwidth Measurement	
8.1 Provisions Applicable	
8.2 Measurement Procedure	
8.3 Measurement Setup (Block Diagram of Configuration)	
8.4 Measurement Results	21
9. Power Spectral Density Measurement	
9.1 Provisions Applicable	
9.2 Measurement Procedure	
9.3 Measurement Setup (Block Diagram of Configuration)	
9.4 Measurement Results	
10. Conducted Band Edge and Out-of-Band Emissions	
10.1 Provisions Applicable	



10.2 Measurement Procedure	
10.3 Measurement Setup (Block Diagram of Configuration)	
10.4 Measurement Results	
11. Radiated Spurious Emission	35
11.1 Measurement Limit	
11.2 Measurement Procedure	
11.3 Measurement Setup (Block Diagram of Configuration)	
11.4 Measurement Result	
12. AC Power Line Conducted Emission Test	48
12.1 Measurement Limit	
12.2 Measurement Setup (Block Diagram of Configuration)	48
12.2 Measurement Setup (Block Diagram of Configuration)	49
12.2 Measurement Setup (Block Diagram of Configuration) 12.3 Preliminary Procedure of Line Conducted Emission Test	49 49
12.2 Measurement Setup (Block Diagram of Configuration) 12.3 Preliminary Procedure of Line Conducted Emission Test 12.4 Final Procedure of Line Conducted Emission Test	



1. General Information

Applicant	SHENZHEN AONI ELECTRONIC CO., LTD.
Address	No.5, Bldg., Honghui Industrial Park, 2nd Liuxian Road, Xin'An streets, Bao'an District, ShenZhen, China
Manufacturer	SHENZHEN AONI ELECTRONIC CO., LTD.
Address	No.5,Bldg., Honghui Industrial Park, 2nd Liuxian Road, Xin'An streets, Bao'an District, ShenZhen, China
Factory	SHENZHEN AONI ELECTRONIC CO., LTD.
Address	No.5,Bldg., Honghui Industrial Park, 2nd Liuxian Road, Xin'An streets, Bao'an District, ShenZhen, China
Product Designation	WIRELESS MECHANICAL KEYBOARD
Brand Name	AUSDOM
Test Model	Hola87
Series Model	Hola87 pro, Hola87 ultra, Hola75, Hola75 pro, Hola75 Ultra, Hola98, Hola98Ultra, Hola98 X, Hola108, Hola108 pro, Hola104, Hola104 pro, Hola104L, Hola68, Hola68 pro
Declaration of Difference	All the same except the model name.
Date of receipt of test item	Apr. 08, 2025
Date of Test	Apr. 08, 2025~Apr. 17, 2025
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-BLE-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Jack Gai Prepared By Jack Gui Apr. 17, 2025 (Project Engineer) Calvin Lin **Reviewed By** Calvin Liu Apr. 17, 2025 (Reviewer) /mole Approved By Angela Li Apr. 17, 2025 (Authorized Officer)



2. Product Information

2.1 Product Technical Description

Technology Type	Bluetooth Low Energy
Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.0
Modulation Type	BLE GFSK 1Mbps GFSK 2Mbps
Number of channels	40
Carrier Frequency of Each Channel	40 Channels (37 Data channels + 3 Advertising channels)
Channel Separation	2 MHz
Maximum Transmitter Power	Bluetooth LE (1Mbps):3.626dBm
Hardware Version	RX117-BYK916+BK3632 REV:1.0
Software Version	B073
Antenna Designation	PCB Antenna
Antenna Gain	2.34dBi
Power Supply	DC 3.7V 5000mAh by battery or DC 5V from adapter

2.2 Test Frequency List

Frequency Band	Channel Number	Test Frequency		
	0	2402 MHz		
	1	2404 MHz		
	:	:		
2400~2483.5MHz	19	2440MHz		
	:	:		
	38	2478 MHz		
	39	2480 MHz		
Note: f = 2402 + 2*k MHz, k = 0,, 39 f is the operating frequency (MHz); k is the operating channel.				



2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **Z63-HOLA87**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

2.5 Special Accessories

Not available for this EUT intended for grant.

2.6 Equipment Modifications

Not available for this EUT intended for grant.

2.7 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

EUT Antenna

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 2.34dBi.



3. Test Environment

3.1 Address of the Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 3.7V

3.4 Measurement Uncertainty

The reported uncertainty of measurement y $\pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$		
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$		
Uncertainty of total RF Power, Conducted	$U_c = \pm 0.8 \text{ dB}$		
Uncertainty of RF Power Density, Conducted	$U_c = \pm 2.6 \text{ dB}$		
Uncertainty of Spurious Emissions, Conducted	$U_c = \pm 2 \%$		
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$		
Uncertainty of Dwell Time	$U_c = \pm 2 \%$		



3.5 List of Equipment Use

• F	RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
\boxtimes	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23	
	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2025-01-14	2026-01-13	
	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2025-01-14	2026-01-13	
	AGC-ER-A007	6dB Fixed Attenuator	Mini circuits	BW-S6-2W263A+	N/A	2025-01-30	2026-01-29	
	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2024-05-23	2025-05-22	
\boxtimes	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A	
	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A	
● F	Radiated Spurio	ous Emission						
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2025-01-14	2026-01-13	
	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23	
	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27	
	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04	
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBEC	K VULB9168	D69250	2023-05-11	2025-05-10	
		Broadband Ridged	ETS	2117	00024600	2024 05 24	2025 05 22	

	AGC-EIVI-EU01	Spectrum Analyzer	Aglient	N90TUA	WI153470504	2024-05-28	2025-05-27
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-05-24	2025-05-23
\square	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23
\boxtimes	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22
	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08
\boxtimes	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08

• A	AC Power Line Conducted Emission						
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27
\boxtimes	AGC-EM-A171	10dB Attenuator	Mini-Circuits	UNAT-10A+	N/A	2024-02-01	2026-01-31
\boxtimes	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27



• Tes	Test Software						
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information		
\square	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71		
\boxtimes	AGC-EM-S003	RE Test System	FARA	EZ-EMC	VRA-03A		
\boxtimes	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6		
\boxtimes	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0		



4.System Test Configuration

4.1 EUT Configuration


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



Conducted Emission Configure:



4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

☑ Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Adapter	Redmi	AD100G	Input:100-240V 50/60Hz 1.6A Output:5V/3A;9V/3A;11V/5A; 12V/3A;15V/3A;20V/5A	1.2m, unshielded
2	Control Box	USB-TTL		-	

Test Accessories Come From The Manufacturer

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1					



4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(3)	RF Output Power	Pass
3	§15.247 (a)(2)	6 dB Bandwidth	Pass
4	§15.247 (e)	Power Spectral Density	Pass
5	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
6	§15.209	Radiated Emission& Band Edge	Pass
7	§15.207	AC Power Line Conducted Emission	Pass



5. Description of Test Modes

	Summary Table of Test Cases
Test Item	Data Rate / Modulation
iest tielti	Bluetooth–LE(1Mbps/2Mbps)/GFSK
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps(Battery powered or AC/DC adapter)
Radiated & Conducted Test Cases	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps(Battery powered or AC/DC adapter)
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps(Battery powered or AC/DC adapter)
AC Conducted Emission	Mode 1: Bluetooth Link + Battery + USB Cable (Charging from AC Adapter)

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. 3. The battery is full-charged during the test.
- For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4.

COMM COM4 Close
SW TEST TX RX DUT Power 3 AFH 0 DateRate 11Mbps v
☐ Hopping ☐ BLE ☐ JPN(TELEC)
g,d_mode:1,freq:40, power:3, p_mode:1, hopping:0, rx_mode:0, afh:0, jpn:0, ble:1,dr:1Mbps. g,d_mode:1,freq:40, power:3, p_mode:1, hopping:0, rx_mode:0, afh:0, jpn:0, ble:1,dr:1Mbps.
t




6. Duty Cycle Measurement

The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(µs)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)
BLE_1Mbps	293.3	27	5.69	3.41

Remark:

- 1. Duty Cycle factor = $10 * \log (1/ \text{Duty cycle})$
- 2. The duty cycle of each frequency band mode reflects the determination requirements of the low channel measurement value
- The test plots as follows:





7. RF Output Power Measurement

7.1 Provisions Applicable

For DTSs employing digital modulation techniques operating in the bands 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W.


7.2 Measurement Procedure

For Peak Power, the testing follows ANSI C63.10 Section 11.9.1.1 Method Max peak power:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the RBW≥DTS bandwidth
- 3. Set the VBW≥[3 × RBW].
- 4. Span≥[3 × RBW].
- 5. Sweep= auto couple.
- 6. Detector Function= Peak.
- 7. Trace mode= Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- For Average power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G:
- 1. The RF output of EUT was connected to the power meter by RF cable and attenuator.
- 2. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.


7.3 Measurement Setup (Block Diagram of Configuration)

For Average power test setup






For peak power test setup



7.4 Measurement Result

Test Data of Conducted Output Power					
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail	
	2402	3.626	≪30	Pass	
GFSK_1Mbps	2440	3.601	≪30	Pass	
	2480	3.488	≤30	Pass	





Test Graphs of Conducted Output Power



Inclusion Mikr1 2.479 937 GHz 3.488 dBm Auto Tu 10 dB/div Ref 30.00 dBm 3.488 dBm Center Fr 2.48000000 G 100 1 1 1 2.48000000 G 100 1 1 1 1 100 1 1 1 1 1 100 1 1 1 1 1 1 100 1	Agilent Spectrum Analyzer - Swept SA XI RL RF 50 Ω A Center Freq 2.4800000	00 GHz PNO: East +++ Trig: Free Run	ALIGNAUTO : Avg Type: Log-Pwr Avg Hold: 100/100	11:17:45 AM Apr 08, 2025 TRACE 1 2 3 4 5 6 TYPE M	Frequency
200 Center Fr 200 Center Fr 100 Center Fr <td< th=""><th></th><th>in Guine Gw</th><th>Mkr1 2</th><th>479 937 GHz</th><th>Auto Tune</th></td<>		in Guine Gw	Mkr1 2	479 937 GHz	Auto Tune
1000 Image: start Fr 2.477500000 G 1000 Image: start Fr 2.477500000 G 1000 Image: start Fr 2.477500000 G 1000 Image: start Fr 2.482500000 G 1000 Image: start Fr 1mage: start Fr 1000					Center Freq 2.480000000 GHz
-300 CF St -400 Auto -600 Freq Offs -600 Image: State of the		T UT			Start Fred 2.477500000 GHz
-300 CF St -400 Auto -600 Freq Offs -600 Image: State of the	-10.0			A A A A A A A A A A A A A A A A A A A	Stop Fred 2.482500000 GHz
	-30.0				CF Step 500.000 kH Auto Mar
					Freq Offse 0 H
#Res BW 1.5 MHz #VBW 5.0 MHz Sweep 1.066 ms (1000 pts)	Center 2.480000 GHz	#)/DM(5 0 MU-	Swoon-44	Span 5.000 MHz	
Test_Graph_LE1M_ANT1_2480_1Mbps_Peak Power	MSG				



8. 6dB Bandwidth Measurement


8.1 Provisions Applicable

The minimum 6dB bandwidth shall be 500 kHz.

8.2 Measurement Procedure

- The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
- 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW.
- 5. Measure and record the results in the test report.

8.3 Measurement Setup (Block Diagram of Configuration)







8.4 Measurement Results

Test Data of Occupied Bandwidth and DTS Bandwidth					
Test Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	DTS BW (MHz)	DTS BW Limits	Pass or Fail
	2402	1.198	0.764	≥0.5	Pass
GFSK_1Mbps	2440	1.156	0.740	≥0.5	Pass
	2480	1.107	0.722	≥0.5	Pass

Test Graphs of Occupied Bandwidth
















Agilent Spectrum Analyzer - Occupi Center Freq 2.48000 10 dB/div Ref 20.01	AC CORREC 0000 GHz Center #IFGain:Low #Atten	sense:INT FFreq: 2.480000000 GHz ree Run Avg Hold : 30 dB	ALIGNAUTO 11:17:30 AM Apr 08, 2025 Radio Std: None Radio Device: BTS Mkr1 2.480042 GHz 2.2513 dBm	Frequency	
Log 10.0 0.00 -10.0		↓ ¹		Center Freq 2.480000000 GHz	
-20.0 -30.0 -40.0 -50.0					
60.0 -70.0 Center 2.48 GHz #Res BW 100 kHz	#	VBW 300 kHz	Span 3 MHz Sweep 1 ms	300.000 kHz	
Occupied Bandwidth Total Power 9.69 dBm Aut					
Transmit Freq Err x dB Bandwidth	or -30.518 kHz 722.4 kHz	OBW Power x dB	99.00 % -6.00 dB	0 Hz	
MSG	Test_Graph_LE1M	1_ANT1_2480	©status _1Mbps_DTSBW		



9. Power Spectral Density Measurement


9.1 Provisions Applicable

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

9.2 Measurement Procedure

- The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
- 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz in order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 5. Measure and record the results in the test report.
- 6. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

9.3 Measurement Setup (Block Diagram of Configuration)







9.4 Measurement Results

Test Data of Conducted Output Power Spectral Density						
Test Mode	Test Frequency (MHz) Power density (dBm/3kHz)		Limit (dBm/3kHz)	Pass or Fail		
GFSK_1Mbps	2402	-11.681	≪8	Pass		
	2440	-12.067	≪8	Pass		
	2480	-12.193	≪8	Pass		

Test Graphs of Conducted Output Power Spectral Density









10. Conducted Band Edge and Out-of-Band Emissions


10.1 Provisions Applicable


The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure.

10.2 Measurement Procedure

- Reference level measurement
- 1. Set instrument center frequency to DTS channel center frequency
- 2. Set the span to \geq 1.5 times the DTS bandwidth
- 3. Set the RBW = 100 kHz
- 4. Set the VBW \ge 3 x RBW
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Allow trace to fully stabilize
- Emission level measurement
- 1. Set the center frequency and span to encompass frequency range to be measured
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep time = auto couple
- 7. The trace was allowed to stabilize

10.3 Measurement Setup (Block Diagram of Configuration)








10.4 Measurement Results




Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands

















LXI RL	im Analyzer - Swept SA RF 50 Ω AC Teq 13.7500000	CORREC 00 GHz PNO: Fast ↔	SENSE:INT	ALIGN AUTO Avg Type: Log-Pwr Avg Hold: 10/10	11:18:48 AM Apr 08, 2025 TRACE 1 2 3 4 5 6 TYPE M	Frequency
10 dB/div	Ref 20.00 dBm	IFGain:Low	#Atten: 30 dB	MI	оет <mark>РИМИМИ</mark> kr1 7.440 4 GHz -47.908 dBm	Auto Tune
10.0						Center Freq 13.750000000 GHz
0.00						Start Freq 2.500000000 GHz
-20.0					-17.79 dBm	Stop Freq 25.000000000 GHz
-40.0	∮ ¹					CF Step 2.250000000 GHz <u>Auto</u> Man
-50.0			المراجع المراجع (معالم مراجع مراجع المراجع من المراجع من المراجع من المراجع من المراجع من المراجع من المراجع م مراجع من المراجع من الم مراجع من المراجع من الم			Freq Offset 0 Hz
-70.0 Center 13					Span 22.50 GHz	
#Res BW	100 kHz	#VBW	300 kHz	Sweep	2.152 s (30000 pts) s	
	Test_Graph_LE1M_ANT1_2480_1Mbps_Higher Band Emissions					



Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands



11. Radiated Spurious Emission

11.1 Measurement Limit

• FCC Part 15.209 Limit in the below table to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.



- 8. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 9. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 10. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 11. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum ParameterSettingStart ~Stop Frequency9kHz~150kHz/RB 200Hz for QPStart ~Stop Frequency150kHz~30MHz/RB 9kHz for QPStart ~Stop Frequency30MHz~1000MHz/RB 120kHz for QPStart ~Stop Frequency1GHz~26.5GHzStart ~Stop Frequency1MHz/3MHz for Peak, 1MHz/3MHz for Average

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting	
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP	
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP	
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP	



Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

• Peak Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

• Average Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. $VBW \ge [3 \times RBW]$
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




11.3 Measurement Setup (Block Diagram of Configuration)



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz





11.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

1				F	Rad	iate	ed Ei	miss	sion Test F	esu	ts at 3	OM	Hz-1	GH	Z							
EUT N	lame	WIR	ELES	SSN	ИЕС	НА	NIC	AL K	EYBOARD)	Mod	lel N	lam	е		н	ola	187				
Tempe	erature	23.2	°C								Rela	ative	e Hu	ımid	ity	59	9.6	%				
Press	ure	960ł	nPa								Test	: Vo	Itag	е		D	СЗ	3.7	Vb	y b	attery	
Test M	lode	Mod	le 1							Antenna Polarity			н	ori	zor	ntal						
	72.0	dBuV/m																				
	32								2	 	Whatthe	*****	Luc	5		Limit: Margin	n:	-				
		Allerwood	gitt-sonrietso	1 mm	ywerne	velation	do-Malada	nanderson	Burnhau Mayor	, MV.	a é côtr.											
	-8 30.00					yslytha 70 81	dan Maria	n de la companya de la	(MHz)	en de la companya de		300		00	500 €	600 70	00	10	000.0	00		
Final [-8 30.00 Data List	00 4	0 5	50 6	60 7		0		(MHz)			300								00		
Final I NO.	-8	00 4	0 5		60 7 21		dan Maria	tor				300 300		He	ight m]		An	10 igle °]			Polarity	/
	-8 30.00 Data List Freq.]	0 5 L [dE	50 6 _eve	50 7 9] /m]		o Fac	tor 3]	(MHz)		Marg	300 gin		He [c	ight		An [igle			Polarity	
NO.	-8 30.00 Data List Freq. [MHz]] 6	0 5 L [dE	_eve BµV/	50 7 91 /m] 1		o Fac [df	etor 3] 04	(MHz) Limit [dBµV/n		Marg [dB	300 gin 3]		He [c 1(ight m]		An [ˈ 1(igle °]		H		al
NO. 1	-8 30.00 Data List Freq. [MHz] 51.661	00 44] 6 86	0 5 [dE 1 2	_eve 3µV/ 18.01	50 7 91 /m] 1 6		• Fac [dE 13.0	etor 3] 04 31	(мн ₂) Limit [dBµV/n 40.00		Marg [dB 21.9	gin 300 99 04		He [c 1(ight m] D0		An [['] 1(igle °] 60		н	orizonta	al al
NO. 1 2	-8 30.00 Data List Freq. [MHz] 51.661 121.54	00 4] 6 86 36	0 5 [dE 1 2 2	_eve 3µV/ 18.0 ²	50 7 91 /m] 1 6 4		• Fac [dE 13.0 16.3	ttor 3] 04 31 74	(MHz) Limit [dBµV/n 40.00 43.50		Marg [dB 21.9 22.0	gin 300 300 300 300 300 300 300 300 300 30		He [c 1(1(ight m] DO		An [10 17 9	igle °] 60 70		H	orizonta	al al al
NO. 1 2 3	-8 30.00 Data List Freq. [MHz] 51.661 121.54 226.89	00 4] 6 86 36 49	0 5 [dE 2 2 2	_eve 3µV/ 18.0 [°] 21.46	50 7 91 /m] 1 6 4 3		• Fac [dE 13. 16. 14.	ttor 3] 04 31 74 81	(MHz) Limit [dBµV/n 40.00 43.50 46.00		Marg [dB 21.9 22.0 17.8	gin 300 99 04 86 27		He [c 1(1(1(ight m] 00 00		An [['] 10 11 9 22	igle °] 60 70		H H H	orizonta orizonta orizonta	al al al



				Radia						
EUT N	lame	WIR	RELESS	MECH	ANICAL K	EYBOARD	Model Na	ame	Hola87	
Tempe	erature	23.2	2℃				Relative	Humidity	59.6%	
Press	ure	960	hPa				Test Volt	age	DC 3.7V b	y battery
Test N	lode	Moc	le 1				Antenna	Polarity	Vertical	
	72.0	dBu¥/m	1							
									Limit: — Margin: —	
									_	
	_						• •		5 5	
	32							Junio	Mar Mar	
	32	ophotological design	kunner kunner	Aynorth Markelling	and an a charles and	all manuformer	after and	and the second	, Marine Ma	
	-8					will reader when the states				20
	-8 30.00		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		80	(MHz)	-1/44.04.04.04.04.04.04.04.04.04.04.04.04.0		0 700 1000.0	00
	-8 30.00	00 4	0 50	60 70	80	(MHz)	300	400 500 60		00
Final I NO.	-8 30.00			60 70						Polarity
	-8 30.00 Data List Freq		0 50	60 70 el //m]	80 Factor	(MHz)	300 Margin	400 500 60	0 700 1000.0	
NO.	-8 30.00 Data List Freq [MHz] 60	0 50 Lev [dBµ\	60 70 rel //m]	80 Factor [dB]	(мн _z) Limit [dBµV/m]	300 Margin [dB]	400 500 60 Height [cm]	Angle	Polarity
NO. 1	-8 30.00 Data List Freq [MHz 50.586]] 60 29	0 50 Lev [dBµ\ 23.6	60 70 rel //m] 69 65	80 Factor [dB] 16.96	(мн ₂) Limit [dBµV/m] 40.00	300 Margin [dB] 16.31	400 500 60 Height [cm] 100	Angle [°] 160	Polarity Vertical
NO. 1 2	-8 30.00 Data List Freq [MHz 50.586 67.912	00 4] 60 29 63	0 50 Lev [dBµ\ 23.6 21.6	el //m] 69 65 04	80 Factor [dB] 16.96 17.02	(мнг) [dBµV/m] 40.00 40.00	300 Margin [dB] 16.31 18.35	400 500 60 Height [cm] 100 100	Angle [°] 160 170	Polarity Vertical Vertical
NO. 1 2 3	-8 30.00 Data List Freq [MHz 50.586 67.912 179.38	00 4] 60 29 63 85	0 50 Lev [dBµ\ 23.6 21.6 24.0	60 70 rel //m] 69 65 04 94	80 Factor [dB] 16.96 17.02 18.49	(MHz) [MHz] Limit [dBµV/m] 40.00 40.00 43.50	300 Margin [dB] 16.31 18.35 19.46	400 500 60 Height [cm] 100 100 100	Angle [°] 160 170 90	Polarity Vertical Vertical Vertical

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 1 is the worst case and recorded in the report.



Radiated Emissions Test Results for Above 1GHz

EUT Name	WIRELESS MECHANICAL KEYBOARD	Model Name	Hola87	
Temperature	25℃	Relative Humidity	55.4%	
Pressure	960hPa	Test Voltage	DC 3.7V by battery	
Test Mode	Mode 1	Antenna Polarity	Horizontal	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	— Туре
4804.000	51.11	0.08	51.19	74.00	-22.81	peak
4804.000	40.52	0.08	40.6	54.00	-13.40	AVG
7206.000	49.63	2.21	51.84	74.00	-22.16	peak
7206.000	41.52	2.21	43.73	54.00	-10.27	AVG
Remark:						

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	WIRELESS MECHANICAL KEYBOARD	Model Name	Hola87
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	— Туре
4804.000	50.52	0.08	50.6	74.00	-23.40	peak
4804.000	41.36	0.08	41.44	54.00	-12.56	AVG
7206.000	49.51	2.21	51.72	74.00	-22.28	peak
7206.000	40.58	2.21	42.79	54.00	-11.21	AVG
Remark:						
Factor = Ante	enna Factor +	- Cable Loss – Pre	e-amplifier.			

RESULT: PASS



Radiated Emissions Test Results for Above 1GHz

EUT Name	WIRELESS MECHANICAL KEYBOARD	Model Name	Hola87	
Temperature	25 ℃	Relative Humidity	55.4%	
Pressure	960hPa	Test Voltage	DC 3.7V by battery	
Test Mode	Mode 2	Antenna Polarity	Horizontal	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре	
4880.000	50.12	0.14	50.26	74.00	-23.74	peak	
4880.000	40.52	0.14	40.66	54.00	-13.34	AVG	
7320.000	48.51	2.36	50.87	74.00	-23.13	peak	
7320.000	41.53	2.36	43.89	54.00	-10.11	AVG	
Remark:							

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	WIRELESS MECHANICAL KEYBOARD	Model Name	Hola87	
Temperature	25 ℃	Relative Humidity	55.4%	
Pressure	960hPa	Test Voltage	DC 3.7V by battery	
Test Mode	Mode 2	Antenna Polarity	Vertical	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
4880.000	50.58	0.14	50.72	74.00	-23.28	peak
4880.000	41.11	0.14	41.25	54.00	-12.75	AVG
7320.000	49.36	2.36	51.72	74.00	-22.28	peak
7320.000	40.58	2.36	42.94	54.00	-11.06	AVG
Remark:						
Factor = Ante	enna Factor -	⊦ Cable Loss – Pre	e-amplifier.			

RESULT: Pass

Radiated Emissions Test Results for Above 1GHz

EUT Name	WIRELESS MECHANICAL KEYBOARD	Model Name	Hola87
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
4960.000	50.51	0.22	50.73	74.00	-23.27	peak
4960.000	41.52	0.22	41.74	54.00	-12.26	AVG
7440.000	49.61	2.64	52.25	74.00	-21.75	peak
7440.000	40.52	2.64	43.16	54.00	-10.84	AVG
Remark:						
7440.000 7440.000 Remark:	49.61 40.52	2.64 2.64	52.25	74.00	-21.75	

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	WIRELESS MECHANICAL KEYBOARD	Model Name	Hola87
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
4960.000	51.51	0.22	51.73	74.00	-22.27	peak
4960.000	40.11	0.22	40.33	54.00	-13.67	AVG
7440.000	49.63	2.64	52.27	74.00	-21.73	peak
7440.000	40.28	2.64	42.92	54.00	-11.08	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

RESULT: PASS


Note:

- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.




EUT Name	WIRELESS MECHANICAL KEYBOARD	Model Name	Hola87
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 1	Antenna Polarity	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: PASS




EUT Name	WIRELESS MECHANICAL KEYBOARD	Model Name	Hola87
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: PASS



EUT Name	WIRELESS MECHANICAL KEYBOARD	Model Name	Hola87
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS




EUT Name	WIRELESS MECHANICAL KEYBOARD	Model Name	Hola87
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



12. AC Power Line Conducted Emission Test


12.1 Measurement Limit

Fragueney	Maximum RF Line Voltage		
Frequency	Q.P. (dBµV)	Average (dBµV)	
150kHz~500kHz	66-56	56-46	
500kHz~5MHz	56	46	
5MHz~30MHz	60	50	

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

12.2 Measurement Setup (Block Diagram of Configuration)





12.3 Preliminary Procedure of Line Conducted Emission Test


- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side).
- Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 8. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 9. During the above scans, the emissions were maximized by cable manipulation.
- 10. The test mode(s) were scanned during the preliminary test.
- 11. Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- 3. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 4. The test data of the worst case condition(s) was reported on the Summary Data page.
- 5. A conducted emission is calculated by the following equation:
 - Measurement Level (dBµV) = Receiver reading (dBµV) + Transd (dB)
 - Transd (dB)= AMN Factor(dB)+Cable Loss(dB)+Attenuation(dB)
 - Margin= Limit-Level


12.5 Measurement Result





RESULT: PASS





RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com



Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC13779250301AP01

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC13779250301AP02



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders. 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

-----End of Report-----