

## FCC 47 CFR MPE REPORT

Zylux Acoustic Corporation

YARRA 3DX Sound Bar System

Model Number: Y1-1121-02-00

Additional Model: Y1-1121-01-00

FCC ID: XN6-Y12121

Prepared for:	Zylux Acoustic Corporation
	3F, 22, Lane 35, Jihu Road, Taipei Neihsu Technology Park, Taipei 114, Taiwan.
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R1808082
Date of Test:	June 26 ~ August 20, 2018
Date of Report:	August 21, 2018

## Maximum Permissible Exposure

### 1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### (a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   2 ,   H   2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

#### (b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   2 ,   H   2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

### 2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G) / 0.5/d \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2/377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

**3、Conducted Power Result**

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
GFSK	2402	6.94	4.943	$6 \pm 2$	2.28	1.69
	2441	6.59	4.560	$6 \pm 2$	2.28	1.69
	2480	5.70	3.715	$5 \pm 2$	2.28	1.69
8-DPSK	2402	5.79	3.793	$5 \pm 2$	2.28	1.69
	2441	5.27	3.365	$5 \pm 2$	2.28	1.69
	2480	4.10	2.570	$4 \pm 2$	2.28	1.69
BLE	2402	6.65	4.624	$6 \pm 2$	2.28	1.69
	2440	6.46	4.426	$6 \pm 2$	2.28	1.69
	2480	5.88	3.873	$5 \pm 2$	2.28	1.69

**4、Calculated Result and Limit**

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm <sup>2</sup> )	Limited of Power Density (S) (mW /cm <sup>2</sup> )	Test Result
		(dBi)	(Linear)			
GFSK	8	2.28	1.69	<b>0.00212</b>	1	Compiles
8-DPSK	7	2.28	1.69	<b>0.00169</b>	1	Compiles
BLE	8	2.28	1.69	<b>0.00212</b>	1	Compiles