

TEST REPORT

Applicant Name: Shenzhen Hollyland Technology Co.,Ltd
Address: 8F, Building 5D, Skyworth Innovation Valley, Tangtou Road,
Shiyan Street, Baoan District, Shenzhen, 518055 China
Report Number: 2401U43539E-RF-00
FCC ID: 2ADZC-9622T

Test Standard (s)
FCC PART 15.407

Sample Description

Product Type: WIRELESS VIDEO TRANSMISSION SYSTEM
Model No.: Cosmo C2
Multiple Model(s) No.: N/A
Trade Mark:  **HOLLYLAND**
Date Received: 2024/07/01
Issue Date: 2024/11/19

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Ekko Wu

Ekko Wu
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	8
EQUIPMENT MODIFICATIONS	9
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS	14
TEST EQUIPMENT LIST	15
FCC 1.1307 (B) & §2.1091- MPE-BASED EXEMPTION	17
APPLICABLE STANDARD	17
RESULT	17
FCC §15.203 - ANTENNA REQUIREMENT.....	18
APPLICABLE STANDARD	18
ANTENNA CONNECTOR CONSTRUCTION	18
FCC §15.407 (B) (6) §15.207 (A) - CONDUCTED EMISSIONS.....	19
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER SETUP.....	19
TEST PROCEDURE	19
FACTOR & OVER LIMIT CALCULATION.....	20
TEST DATA	20
§15.205 & §15.209 & §15.407(B) - UNDESIRABLE EMISSION.....	25
APPLICABLE STANDARD	25
EUT SETUP	25
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	27
TEST PROCEDURE	27
FACTOR & OVER LIMIT/MARGIN CALCULATION	28
TEST DATA	28
FCC §15.407(A), (E) - 26 DB & 6DB EMISSION BANDWIDTH	74
APPLICABLE STANDARD	74
TEST PROCEDURE	74
TEST DATA	75

FCC §15.407(A) - CONDUCTED TRANSMITTER OUTPUT POWER	81
APPLICABLE STANDARD	81
TEST PROCEDURE	81
TEST DATA	82
FCC §15.407(A) - POWER SPECTRAL DENSITY	83
TEST PROCEDURE	83
TEST DATA	84
EUT PHOTOGRAPHS.....	89
TEST SETUP PHOTOGRAPHS	90

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2401U43539E-RF-00	Original Report	2024/11/19

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	WIRELESS VIDEO TRANSMISSION SYSTEM
Tested Model	Cosmo C2
Multiple Model(s)	N/A
Frequency Range	5G: 5185-5225MHz; 5760-5820MHz
Maximum Conducted Average Output Power	5185-5225MHz: 11.77dBm 5760-5820MHz: 21.28dBm
Modulation Technique	OFDM
Antenna Specification [#]	5185-5225MHz: 5.45dBi (Blade Antenna), 3.31dBi (Mushroom Antenna) 5760-5820MHz: 4.34dBi (Blade Antenna), 3.14dBi (Mushroom Antenna) (provided by the applicant)
Voltage Range	DC 6-16V from DC Port or DC6.8-8.4V from Battery
Sample serial number	2NRQ-2 for Conducted and Radiated Emissions Test 2NRQ-3 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	Model: GQ24-120200-AX Input: AC 100-240V, 50/60Hz, 1.0A Max Output: DC 12.0V, 2.0A, 24.0W
Note: Test Voltage: Battery: 7.4V _{DC} , DC Port: 12V _{DC}	

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB789033 D02 General U-NII Test Procedures New Rules v02r01.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Frequency		213.55 Hz(k=2, 95% level of confidence)
RF output power, conducted		0.72 dB(k=2, 95% level of confidence)
Unwanted Emission, conducted		1.75 dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz-150kHz	3.94dB(k=2, 95% level of confidence)
	150kHz-30MHz	3.84dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.30dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	4.48dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	4.55dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	4.85dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.05dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.35dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.44dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.16dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

Frequency List[#]

For 5150-5250MHz Band, 3 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5185	2	5205
3	5225	/	/

EUT was tested with channel 1, 2 and 3.

For 5725-5850MHz Band, 4 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5760	2	5780
3	5800	4	5820

EUT was tested with channel 1, 2 and 4.

CE/RE Test Modes:

Test Mode1: Transmitting + HDMI Input

Test Mode2: Transmitting + SDI Input +SDI Loopout

Test Mode3: Transmitting

EUT Exercise Software


“Artosyn8030PCTool”[#] software was used and power level as below. The software and power level was provided by the applicant. The device was tested with the worst case was performed as below:

Band	Mode	Data rate	Power Level [#]		
			Low Channel	Middle Channel	High Channel
5185-5225MHz	OFDM	MCS0	0B	0B	0B
5760-5820MHz	OFDM	MCS0	0B	0B	0B

Note:

1. The worst-case data rates are determined to be as above for each mode based upon investigation by measuring the average power and PSD across all data rates bandwidths, and modulations.
2. The device supports SISO and MIMO 2T2R modes, per pretest, 2T2R mode was the worst mode and reported.
3. All the antenna ports have the same power level.

ProjectNo.:2401U43539E-RF Tester:Rainbow Zhu
Date: 31.AUG.2024 18:54:33



ProjectNo.:2401U43539E-RF Tester:Rainbow Zhu
Date: 31.AUG.2024 18:58:25


Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Redmi	Monitor	A22FAB-RA	47366/206100029128
Redmi	Monitor Adapter	Unknown	Unknown
UGREEN	Converter*2	CM131	Unknown
Hollyland	Battery	Unknown	Unknown
DELL	PC	Latitude E6520	DL0ZCS1

Test Mode2




For Radiated Emissions (Below 1GHz):


Test Mode1_ Powered by Adapter




Test Mode1_ Powered by Battery



Test Mode2



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b) & §2.1091	MPE-Based Exemption	Compliant
§15.203	Antenna Requirement	Compliant
§15.407(b)(9)& §15.207(a)	Conducted Emissions	Compliant
§15.205& §15.209 &§15.407(b)	Undesirable Emission& Restricted Bands	Compliant
§15.407(a) (e)	26 dB Emission Bandwidth & 6dB Bandwidth	Compliant
§15.407(a)	Conducted Transmitter Output Power	Compliant
§15.407 (a)	Power Spectral Density	Compliant
§15.407 (h)	Transmit Power Control (TPC)	Not Applicable
§15.407 (h)	Dynamic Frequency Selection (DFS)	Not Applicable

Not Applicable: The device cannot operate at 5250-5350MHz/5470-5725MHz.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/01/16	2025/01/15
Rohde & Schwarz	LISN	ENV216	101613	2024/01/16	2025/01/15
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2024/05/21	2025/05/20
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2024/05/21	2025/05/20
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
Radiated Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/01/16	2025/01/15
Sonoma instrument	Pre-amplifier	310 N	186238	2024/05/21	2025/05/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	Chamber A Cable 1	N/A	2024/06/18	2025/06/17
Unknown	Cable	XH500C	J-10M-A	2024/06/18	2025/06/17
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Cable	2Y194	0735	2024/05/21	2025/05/20
Unknown	Cable	PNG214	1354	2024/05/21	2025/05/20
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
COM-POWER	Pre-amplifier	PA-122	181919	2024/06/18	2025/06/17
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	735	2024/06/18	2025/06/17
Unknown	RF Cable	UFA147	219661	2024/06/18	2025/06/17
Unknown	RF Cable	XH750A-N	J-10M	2024/06/18	2025/06/17
JD	Multiplex Switch Test Control Set	DT7220FSU	DQ77926	2024/06/18	2025/06/17
A.H.System	Pre-amplifier	PAM-1840VH	190	2024/06/18	2025/06/17
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2024/06/18	2025/06/17
Audix	EMI Test software	E3	191218(V9)	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200982	2023/12/18	2024/12/17
ANRITSU	Microwave peak power sensor	MA24418A	12622	2024/05/21	2025/05/20
Unknown	10dB Attenuator	Unknown	F-03-EM190	2024/06/27	2025/06/26

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC 1.1307 (B) & §2.1091- MPE-BASED EXEMPTION

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

For Worst Case:

Frequency (MHz)	Tune up conducted power [#]	Antenna Gain [#]		ERP		Evaluation Distance (m)	ERP Limit (mW)
	(dBm)	(dBi)	(dBd)	(dBm)	(mW)		
5185-5225	12.0	5.45	3.30	15.30	33.88	0.2	768
5760-5820	21.5	4.34	2.19	23.69	233.88	0.2	768

Note: The tune up conducted power and antenna gain was declared by the applicant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connector Construction

The EUT has two external antennas with a unique antenna connector, and the maximum antenna gain[#] is below, fulfill the requirement of this section. Please refer to the EUT photos.

Type	Antenna Gain [#]	Impedance	Frequency Range
Blade Antenna	5.45dBi	50Ω	5150-5250MHz
	4.34dBi	50Ω	5725-5850MHz
Mushroom Antenna	3.31dBi	50Ω	5150-5250MHz
	3.14dBi	50Ω	5725-5850MHz


Result: Compliant

FCC §15.407 (b) (6) §15.207 (a) - CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207, §15.407(b) (6)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and Average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

Test Data

Environmental Conditions


Temperature:	26 °C
Relative Humidity:	70 %
ATM Pressure:	101 kPa

The testing was performed by Macy Shi from 2024-09-30 to 2024-10-09.

EUT operation mode: Transmitting (Maximum output power mode, 5780MHz)

Test Model

AC 120V/60 Hz, Line



Condition: Line


Project : 2401U43539E-RF

tester : Macy.shi

Note : TX

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.152	22.88	43.91	10.90	10.13	55.91	-12.00	Average
2	0.152	33.44	54.47	10.90	10.13	65.91	-11.44	QP
3	0.200	16.25	37.14	10.80	10.09	53.62	-16.48	Average
4	0.200	24.80	45.69	10.80	10.09	63.62	-17.93	QP
5	0.447	7.08	27.74	10.54	10.12	46.93	-19.19	Average
6	0.447	10.58	31.24	10.54	10.12	56.93	-25.69	QP
7	0.524	8.35	28.99	10.50	10.14	46.00	-17.01	Average
8	0.524	11.71	32.35	10.50	10.14	56.00	-23.65	QP
9	2.358	5.25	25.96	10.53	10.18	46.00	-20.04	Average
10	2.358	11.34	32.05	10.53	10.18	56.00	-23.95	QP
11	10.620	9.03	29.84	10.60	10.21	50.00	-20.16	Average
12	10.620	13.54	34.35	10.60	10.21	60.00	-25.65	QP

AC 120V/60 Hz, Neutral




Condition: Neutral
Project : 2401U43539E-RF
tester : Macy.shi
Note : TX

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.160	20.36	41.04	10.56	10.12	55.47	-14.43	Average
2	0.160	32.31	52.99	10.56	10.12	65.47	-12.48	QP
3	0.211	15.51	36.02	10.42	10.09	53.18	-17.16	Average
4	0.211	23.12	43.63	10.42	10.09	63.18	-19.55	QP
5	0.486	14.69	35.51	10.69	10.13	46.23	-10.72	Average
6	0.486	18.27	39.09	10.69	10.13	56.23	-17.14	QP
7	0.502	13.90	34.74	10.70	10.14	46.00	-11.26	Average
8	0.502	17.61	38.45	10.70	10.14	56.00	-17.55	QP
9	2.055	6.01	26.60	10.40	10.19	46.00	-19.40	Average
10	2.055	13.24	33.83	10.40	10.19	56.00	-22.17	QP
11	10.072	12.68	33.69	10.80	10.21	50.00	-16.31	Average
12	10.072	16.89	37.90	10.80	10.21	60.00	-22.10	QP

Test Mode2

AC 120V/60 Hz, Line



Condition: Line


Project : 2401U43539E-RF

tester : Macy.shi

Note : TX

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.191	19.28	40.19	10.82	10.09	53.98	-13.79	Average
2	0.191	29.02	49.93	10.82	10.09	63.98	-14.05	QP
3	0.222	14.95	35.81	10.77	10.09	52.74	-16.93	Average
4	0.222	22.75	43.61	10.77	10.09	62.74	-19.13	QP
5	0.466	8.41	29.06	10.52	10.13	46.58	-17.52	Average
6	0.466	16.18	36.83	10.52	10.13	56.58	-19.75	QP
7	0.507	11.41	32.05	10.50	10.14	46.00	-13.95	Average
8	0.507	17.38	38.02	10.50	10.14	56.00	-17.98	QP
9	2.261	6.17	26.90	10.55	10.18	46.00	-19.10	Average
10	2.261	12.08	32.81	10.55	10.18	56.00	-23.19	QP
11	10.288	12.78	33.59	10.60	10.21	50.00	-16.41	Average
12	10.288	17.10	37.91	10.60	10.21	60.00	-22.09	QP

AC 120V/60 Hz, Neutral



Condition: Neutral
Project : 2401U43539E-RF
tester : Macy.shi
Note : TX

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.150	25.20	45.93	10.60	10.13	56.00	-10.07	Average
2	0.150	36.10	56.83	10.60	10.13	66.00	-9.17	QP
3	0.183	19.92	40.48	10.46	10.10	54.33	-13.85	Average
4	0.183	30.27	50.83	10.46	10.10	64.33	-13.50	QP
5	0.224	14.89	35.42	10.44	10.09	52.66	-17.24	Average
6	0.224	26.26	46.79	10.44	10.09	62.66	-15.87	QP
7	0.369	12.31	33.02	10.60	10.11	48.52	-15.50	Average
8	0.369	19.38	40.09	10.60	10.11	58.52	-18.43	QP
9	0.507	13.44	34.28	10.70	10.14	46.00	-11.72	Average
10	0.507	16.91	37.75	10.70	10.14	56.00	-18.25	QP
11	9.757	15.60	36.60	10.79	10.21	50.00	-13.40	Average
12	9.757	19.70	40.70	10.79	10.21	60.00	-19.30	QP

§15.205 & §15.209 & §15.407(B) - UNDESIRABLE EMISSION

Applicable Standard

FCC §15.407 (b); §15.209; §15.205;


(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:



- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

EUT Setup

9 kHz-30MHz:



30MHz-1GHz:**Above 1 GHz:**

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK

1-40GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Average	>98%	1MHz	≥10 Hz ^{Note 1}
	<98%	1MHz	≥1/Ton ^{Note 2}
Note 1: The detail test parameters please refer to duty cycle section.			
Note 2: Ton is minimum transmission duration.			

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Radiated Spurious Emission

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

According to ANSI C63.10-2013,9.4: For field strength measurements made at other than the distance at which the applicable limit is specified, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance). In some cases, a different distance correction factor may be required;

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left(\frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$	is the field strength of the emission at the distance specified by the limit, in dB μ V/m
E_{Meas}	is the field strength of the emission at the measurement distance, in dB μ V/m
d_{Meas}	is the measurement distance, in m
$d_{\text{SpecLimit}}$	is the distance specified by the limit, in m

So the extrapolation factor of 1m is $20 \cdot \log(1/3) = -9.5$ dB, for 18-40GHz range, the limit of 1m distance was added by 9.5dB from limit of 3m to compared with the result measurement at 1m distance.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit} &= \text{Level} - \text{Limit}; \text{Margin} = \text{Limit} - \text{Corrected Amplitude} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	22 ~25.3 °C
Relative Humidity:	53~60 %
ATM Pressure:	101 kPa

The testing was performed by Anson Su from 2024-10-11 to 2024-10-31 for below 1GHz, Dylan Yang from 2024-09-12 to 2024-10-31 for above 1GHz.

EUT operation mode: Transmitting


Note: Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.

9 kHz-30MHz: (Maximum output power mode, 5780MHz; Worst case, parallel)

Powered by Adapter:


Mushroom Antenna

Test Model



Site : Chamber A
Condition : 3m
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.01	36.04	28.45	64.49	125.17	-60.68	Peak
2	0.03	29.27	23.92	53.19	119.14	-65.95	Peak
3	0.04	25.30	22.15	47.45	115.59	-68.14	Peak
4	0.06	21.08	23.83	44.91	111.38	-66.47	Peak
5	0.10	17.05	22.35	39.40	107.61	-68.21	Peak
6	0.12	15.94	21.74	37.68	105.75	-68.07	Peak



Site : Chamber A
Condition : 3m
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su


	Freq	Factor	Read Level	Level	Limit	Over	Remark
	MHz		dBuV	dBuV/m	dBuV/m	dB	
1	0.55	2.91	39.20	42.11	72.82	-30.71	Peak
2	0.67	1.49	36.73	38.22	71.07	-32.85	Peak
3	0.78	0.17	38.80	38.97	69.72	-30.75	Peak
4	1.00	-1.56	34.39	32.83	67.50	-34.67	Peak
5	1.20	-2.29	33.15	30.86	65.84	-34.98	Peak
6	1.48	-3.26	33.28	30.02	63.99	-33.97	Peak

Test Mode2



Site : Chamber A
Condition : 3m
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.01	36.10	28.09	64.19	125.25	-61.06	Peak
2	0.03	29.22	22.55	51.77	119.11	-67.34	Peak
3	0.04	25.31	24.64	49.95	115.60	-65.65	Peak
4	0.05	22.77	23.36	46.13	113.24	-67.11	Peak
5	0.08	19.28	24.77	44.05	109.75	-65.70	Peak
6	0.12	16.21	22.50	38.71	106.16	-67.45	Peak




Site : Chamber A
Condition : 3m
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.55	2.90	38.10	41.00	72.80	-31.80	Peak
2	0.63	1.95	35.35	37.30	71.60	-34.30	Peak
3	0.77	0.24	38.49	38.73	69.78	-31.05	Peak
4	0.98	-1.45	34.24	32.79	67.64	-34.85	Peak
5	1.36	-2.83	33.78	30.95	64.77	-33.82	Peak
6	1.56	-3.54	31.61	28.07	63.53	-35.46	Peak


Blade Antenna

Test Model



Site : Chamber A
Condition : 3m
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.01	36.10	24.09	60.19	125.25	-65.06	Peak
2	0.03	29.22	22.55	51.77	119.11	-67.34	Peak
3	0.04	25.31	21.64	46.95	115.60	-68.65	Peak
4	0.05	22.77	21.36	44.13	113.24	-69.11	Peak
5	0.08	19.28	19.77	39.05	109.75	-70.70	Peak
6	0.12	16.21	19.50	35.71	106.16	-70.45	Peak



Site : Chamber A
Condition : 3m
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.56	2.78	37.44	40.22	72.65	-32.43	Peak
2	0.65	1.69	36.07	37.76	71.29	-33.53	Peak
3	0.76	0.38	36.45	36.83	69.91	-33.08	Peak
4	0.97	-1.37	32.92	31.55	67.75	-36.20	Peak
5	1.19	-2.24	33.60	31.36	65.95	-34.59	Peak
6	1.36	-2.86	32.76	29.90	64.71	-34.81	Peak

Test Mode2



Site : Chamber A
 Condition : 3m
 Project Number: 2401U43539E-RF
 Test Mode : Transmitting
 Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.01	36.10	25.09	61.19	125.25	-64.06	Peak
2	0.03	29.22	17.55	46.77	119.11	-72.34	Peak
3	0.04	25.31	18.64	43.95	115.60	-71.65	Peak
4	0.07	20.91	18.15	39.06	111.21	-72.15	Peak
5	0.09	17.80	18.64	36.44	108.29	-71.85	Peak
6	0.13	15.52	17.84	33.36	105.15	-71.79	Peak




Site : Chamber A
Condition : 3m
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.49	3.62	35.50	39.12	73.74	-34.62	Peak
2	0.62	2.10	35.90	38.00	71.78	-33.78	Peak
3	0.77	0.29	35.64	35.93	69.83	-33.90	Peak
4	0.98	-1.44	32.81	31.37	67.65	-36.28	Peak
5	1.19	-2.24	33.60	31.36	65.95	-34.59	Peak
6	1.36	-2.86	32.76	29.90	64.71	-34.81	Peak


Powered by Battery:

Mushroom Antenna, Test Model (Worst Case)



Site : Chamber A
Condition : 3m
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.01	37.57	27.50	65.07	127.41	-62.34	Peak
2	0.02	31.79	21.31	53.10	120.93	-67.83	Peak
3	0.03	27.25	24.93	52.18	117.76	-65.58	Peak
4	0.06	22.06	27.95	50.01	112.42	-62.41	Peak
5	0.09	18.08	20.61	38.69	108.56	-69.87	Peak
6	0.13	15.64	19.36	35.00	105.31	-70.31	Peak



Site : Chamber A
Condition : 3m
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.28	8.84	35.26	44.10	98.78	-54.68	Peak
2	0.59	2.37	35.14	37.51	72.12	-34.61	Peak
3	1.47	-3.23	32.64	29.41	64.05	-34.64	Peak
4	4.61	-6.83	32.22	25.39	69.54	-44.15	Peak
5	10.96	-6.26	31.18	24.92	69.54	-44.62	Peak
6	20.62	-4.78	31.37	26.59	69.54	-42.95	Peak


30 MHz–1 GHz: (Maximum output power mode, 5780MHz)

Powered by Adapter:

Mushroom Antenna

Test Model


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	30.73	-6.85	28.22	21.37	40.00	-18.63	QP
2	90.66	-18.66	35.99	17.33	43.50	-26.17	QP
3	189.24	-13.07	38.84	25.77	43.50	-17.73	QP
4	378.42	-11.48	39.80	28.32	46.00	-17.68	QP
5	699.92	-6.61	32.82	26.21	46.00	-19.79	QP
6	757.04	-5.52	46.20	40.68	46.00	-5.32	QP

Vertical




Site : Chamber A
Condition : 3m Vertical
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq Factor		Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	44.67	-16.50	43.99	27.49	40.00	-12.51	QP
2	64.49	-18.72	40.19	21.47	40.00	-18.53	QP
3	169.15	-14.40	37.79	23.39	43.50	-20.11	QP
4	372.66	-11.62	36.04	24.42	46.00	-21.58	QP
5	521.57	-9.02	40.21	31.19	46.00	-14.81	QP
6	900.15	-3.66	32.46	28.80	46.00	-17.20	QP

Test Mode2


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	30.48	-6.70	27.04	20.34	40.00	-19.66	QP
2	91.58	-18.60	34.05	15.45	43.50	-28.05	QP
3	169.01	-14.40	40.85	26.45	43.50	-17.05	QP
4	396.07	-11.08	36.73	25.65	46.00	-20.35	QP
5	699.92	-6.61	33.24	26.63	46.00	-19.37	QP
6	900.15	-3.66	34.20	30.54	46.00	-15.46	QP

Vertical




Site : Chamber A
Condition : 3m Vertical
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	42.04	-14.74	37.51	22.77	40.00	-17.23 QP
2	67.56	-18.59	37.24	18.65	40.00	-21.35 QP
3	166.65	-14.26	37.62	23.36	43.50	-20.14 QP
4	374.95	-11.54	33.52	21.98	46.00	-24.02 QP
5	567.87	-8.37	40.14	31.77	46.00	-14.23 QP
6	900.15	-3.66	33.15	29.49	46.00	-16.51 QP

Blade Antenna

Test Model


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	30.48	-6.70	28.04	21.34	40.00	-18.66	QP
2	91.58	-18.60	37.05	18.45	43.50	-25.05	QP
3	169.01	-14.40	42.85	28.45	43.50	-15.05	QP
4	225.70	-14.61	42.19	27.58	46.00	-18.42	QP
5	396.07	-11.08	40.73	29.65	46.00	-16.35	QP
6	700.22	-6.61	38.30	31.69	46.00	-14.31	QP

Vertical




Site : Chamber A
Condition : 3m Vertical
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

Freq Factor		Read Level	Level	Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	Limit	
1	44.41	-16.32	40.95	24.63	40.00	-15.37 QP
2	67.14	-18.60	40.59	21.99	40.00	-18.01 QP
3	167.97	-14.29	38.13	23.84	43.50	-19.66 QP
4	372.66	-11.62	36.42	24.80	46.00	-21.20 QP
5	489.24	-9.04	37.66	28.62	46.00	-17.38 QP
6	900.15	-3.66	32.97	29.31	46.00	-16.69 QP

Test Mode2


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	30.48	-6.70	29.04	22.34	40.00	-17.66	QP
2	99.40	-16.84	31.93	15.09	43.50	-28.41	QP
3	169.01	-14.40	44.85	30.45	43.50	-13.05	QP
4	225.70	-14.61	43.29	28.68	46.00	-17.32	QP
5	396.07	-11.08	40.73	29.65	46.00	-16.35	QP
6	699.92	-6.61	37.24	30.63	46.00	-15.37	QP

Vertical




Site : Chamber A
Condition : 3m Vertical
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	44.41	-16.32	41.95	25.63	40.00	-14.37	QP
2	67.14	-18.60	41.59	22.99	40.00	-17.01	QP
3	167.97	-14.29	39.13	24.84	43.50	-18.66	QP
4	369.57	-11.73	38.37	26.64	46.00	-19.36	QP
5	489.24	-9.04	38.66	29.62	46.00	-16.38	QP
6	900.15	-3.66	34.97	31.31	46.00	-14.69	QP

Powered by Battery:

Mushroom Antenna, Test Model (Worst Case)


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	Limit	
1	95.80	-17.82	39.66	21.84	43.50	-21.66 QP
2	143.77	-13.31	44.06	30.75	43.50	-12.75 QP
3	239.36	-14.53	52.70	38.17	46.00	-7.83 QP
4	287.23	-12.93	55.20	42.27	46.00	-3.73 QP
5	335.30	-12.43	47.18	34.75	46.00	-11.25 QP
6	431.98	-10.16	41.37	31.21	46.00	-14.79 QP

Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number: 2401U43539E-RF
Test Mode : Transmitting
Tester : Anson Su

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	47.89	-18.14	43.09	24.95	40.00	-15.05	QP
2	71.86	-18.55	48.03	29.48	40.00	-10.52	QP
3	95.80	-17.82	50.71	32.89	43.50	-10.61	QP
4	195.99	-12.69	45.11	32.42	43.50	-11.08	QP
5	287.61	-12.93	45.26	32.33	46.00	-13.67	QP
6	431.98	-10.16	35.87	25.71	46.00	-20.29	QP

Above 1GHz: (Test Mode3)**5150-5250 MHz:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/AV					
Mushroom Antenna							
5185MHz							
5148.15	58.02	PK	H	2.70	60.72	74	-13.28
5148.15	47.32	AV	H	2.70	50.02	54	-3.98
5137.08	55.65	PK	V	2.71	58.36	74	-15.64
5137.08	44.42	AV	V	2.71	47.13	54	-6.87
10370.00	45.12	PK	H	12.88	58.00	68.2	-10.20
10370.00	45.19	PK	V	12.88	58.07	68.2	-10.13
5205MHz							
10410.00	45.37	PK	H	12.98	58.35	68.2	-9.85
10410.00	45.63	PK	V	12.98	58.61	68.2	-9.59
5225MHz							
5400.02	54.23	PK	H	2.99	57.22	74	-16.78
5400.02	44.04	AV	H	2.99	47.03	54	-6.97
5361.34	54.42	PK	V	2.92	57.34	74	-16.66
5361.34	44.36	AV	V	2.92	47.28	54	-6.72
10450.00	45.66	PK	H	13.26	58.92	68.2	-9.28
10450.00	45.87	PK	V	13.26	59.13	68.2	-9.07
Blade Antenna							
5185MHz							
5146.51	61.80	PK	H	2.70	64.50	74	-9.50
5148.71	47.39	AV	H	2.71	50.10	54	-3.90
4814.26	54.52	PK	V	2.44	56.96	74	-17.04
5150.00	42.62	AV	V	2.71	45.33	54	-8.67
10370.00	44.81	PK	H	12.88	57.69	68.2	-10.51
10370.00	44.69	PK	V	12.88	57.57	68.2	-10.63
5205MHz							
10410.00	44.63	PK	H	12.98	57.61	68.2	-10.59
10410.00	44.76	PK	V	12.98	57.74	68.2	-10.46
5225MHz							
5361.38	55.26	PK	H	2.92	58.18	74	-15.82
5361.38	43.53	AV	H	2.92	46.45	54	-7.55
5353.75	54.02	PK	V	2.92	56.94	74	-17.06
5353.75	42.12	AV	V	2.92	45.04	54	-8.96
10450.00	44.94	PK	H	13.26	58.20	68.2	-10.00
10450.00	44.88	PK	V	13.26	58.14	68.2	-10.06

5725-5850 MHz:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/AV					
Mushroom Antenna							
5760MHz							
5650.00	55.61	PK	H	3.59	59.20	68.20	-9.00
5700.00	59.50	PK	H	4.09	63.59	105.20	-41.61
5720.00	66.05	PK	H	4.09	70.14	110.80	-40.66
5725.00	67.84	PK	H	4.09	71.93	122.20	-50.27
5650.00	56.42	PK	V	3.59	60.01	68.20	-8.19
5700.00	59.58	PK	V	4.09	63.67	105.20	-41.53
5720.00	66.67	PK	V	4.09	70.76	110.80	-40.04
5725.00	68.28	PK	V	4.09	72.37	122.20	-49.83
11520.00	44.17	PK	H	14.23	58.40	74	-15.60
11520.00	30.45	AV	H	14.23	44.68	54	-9.32
11520.00	44.79	PK	V	14.23	59.02	74	-14.98
11520.00	30.59	AV	V	14.23	44.82	54	-9.18
5780MHz							
11560.00	44.33	PK	H	14.13	58.46	74	-15.54
11560.00	30.75	AV	H	14.13	44.88	54	-9.12
11560.00	45.10	PK	V	14.13	59.23	74	-14.77
11560.00	31.14	AV	V	14.13	45.27	54	-8.73
5820MHz							
5850.00	70.76	PK	H	4.09	74.85	122.20	-47.35
5855.00	67.70	PK	H	4.09	71.79	110.80	-39.01
5875.00	59.04	PK	H	4.19	63.23	105.20	-41.97
5925.00	55.23	PK	H	4.69	59.92	68.20	-8.28
5850.00	70.95	PK	V	4.09	75.04	122.20	-47.16
5855.00	68.37	PK	V	4.09	72.46	110.80	-38.34
5875.00	59.41	PK	V	4.19	63.60	105.20	-41.60
5925.00	55.59	PK	V	4.69	60.28	68.20	-7.92
11640.00	45.52	PK	H	13.83	59.35	74	-14.65
11640.00	31.69	AV	H	13.83	45.52	54	-8.48
11640.00	45.15	PK	V	13.83	58.98	74	-15.02
11640.00	31.37	AV	V	13.83	45.20	54	-8.80

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/AV					
Blade Antenna							
5760MHz							
5650.00	57.82	PK	H	3.59	61.41	68.20	-6.79
5700.00	62.92	PK	H	4.09	67.01	105.20	-38.19
5720.00	72.45	PK	H	4.09	76.54	110.80	-34.26
5725.00	75.45	PK	H	4.09	79.54	122.20	-42.66
5650.00	56.93	PK	V	3.59	60.52	68.20	-7.68
5700.00	61.94	PK	V	4.09	66.03	105.20	-39.17
5720.00	72.38	PK	V	4.09	76.47	110.80	-34.33
5725.00	75.43	PK	V	4.09	79.52	122.20	-42.68
11520.00	44.23	PK	H	14.23	58.46	74	-15.54
11520.00	30.53	AV	H	14.23	44.76	54	-9.24
11520.00	44.09	PK	V	14.23	58.32	74	-15.68
11520.00	30.41	AV	V	14.23	44.64	54	-9.36
5780MHz							
11560.00	44.48	PK	H	14.13	58.61	74	-15.39
11560.00	31.10	AV	H	14.13	45.23	54	-8.77
11560.00	45.28	PK	V	14.13	59.41	74	-14.59
11560.00	30.46	AV	V	14.13	44.59	54	-9.41
5820MHz							
5850.28	59.44	PK	H	3.67	63.11	121.56	-58.45
5860.80	59.21	PK	H	3.71	62.92	109.17	-46.25
5876.76	56.24	PK	H	3.78	60.02	103.89	-43.87
5943.73	57.74	PK	H	3.74	61.48	68.20	-6.72
5854.79	55.24	PK	V	3.70	58.94	111.27	-52.33
5855.94	54.95	PK	V	3.70	58.65	110.54	-51.89
5885.99	54.97	PK	V	3.81	58.78	97.04	-38.26
5936.60	54.05	PK	V	3.77	57.82	68.20	-10.38
11640.00	44.82	PK	H	13.83	58.65	74	-15.35
11640.00	31.28	AV	V	13.83	45.11	54	-8.89
11640.00	45.51	PK	V	13.83	59.34	74	-14.66
11640.00	31.47	AV	V	13.83	45.30	54	-8.70

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Factor + Reading


Margin = Corrected. Amplitude - Limit


The other spurious emission which is in the noise floor level was not recorded.


Test plots for Band Edge Measurements (Radiated) (worst case)

5150-5250MHz:












5725-5850 MHz:








Listed with the worst harmonic margin test plot:


Mushroom Antenna, 5225MHz:

























Mushroom Antenna, 5820MHz:




















FCC §15.407(a), (e) - 26 dB & 6dB EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure

According to KDB789033 D02 section II.C and section II.D

1. Emission Bandwidth (EBW)

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


3. 99% Occupied Bandwidth:

According to ANSI C63.10-2013 Section 12.4.2&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.

- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Test Data

Environmental Conditions

Temperature:	23~28°C
Relative Humidity:	47~58 %
ATM Pressure:	101 kPa

The testing was performed by Rainbow Zhu from 2024-08-31 to 2024-11-08

EUT operation mode: Transmitting

Test Result: Compliant.


5150-5250MHz:

Test Modes	Test Frequency (MHz)	26 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
OFDM	5185	41.410	37.564
	5205	41.282	37.564
	5225	41.539	37.564
Note: Test only was performed at Chain 0. Note: The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.			




5725-5850MHz:




Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
OFDM	5760	38.000	37.564
	5780	38.154	37.564
	5820	38.154	37.564
Note: 6dB Emission Bandwidth Limit: $\geq 0.5\text{MHz}$. The 99% Occupied Bandwidth have not fall into the band 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth. Test only was performed at Chain 0.			

5150-5250MHz:



5725-5850MHz:

<p>5760 MHz</p>	<p>6dB Emission Bandwidth</p>  <p>ProjectNo.:2401U43539E-RF Tester:Rainbow Zhu Date: 31.AUG.2024 18:37:16</p>
<p>5780 MHz</p>	 <p>ProjectNo.:2401U43539E-RF Tester:Rainbow Zhu Date: 31.AUG.2024 18:39:40</p>
<p>5820 MHz</p>	 <p>ProjectNo.:2401U43539E-RF Tester:Rainbow Zhu Date: 31.AUG.2024 18:43:29</p>

<p>5760 MHz</p>	<p>99% Emission Bandwidth</p>  <p>ProjectNo.:2401U43539E-RF Tester:Rainbow Zhu Date: 8.NOV.2024 01:24:37</p>
<p>5780 MHz</p>	 <p>ProjectNo.:2401U43539E-RF Tester:Rainbow Zhu Date: 8.NOV.2024 01:26:58</p>
<p>5820 MHz</p>	 <p>ProjectNo.:2401U43539E-RF Tester:Rainbow Zhu Date: 8.NOV.2024 01:28:37</p>

FCC §15.407(a) - CONDUCTED TRANSMITTER OUTPUT POWER

Applicable Standard

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method PM-G should be applied

- a. Place the EUT on a bench and set it in transmitting mode.
- b. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.



Test Data**Environmental Conditions**

Temperature:	23~28°C
Relative Humidity:	47 ~58 %
ATM Pressure:	101 kPa

The testing was performed by Rainbow Zhu from 2024-08-31 to 2024-09-09.

EUT operation mode: Transmitting

Test Result: Compliant.

5150-5250 MHz:

Test Modes	Test Frequency (MHz)	Max. Conducted Average Output Power (dBm)			
		Chain 0	Chain 1	Total	Limit
OFDM	5185	8.66	8.16	11.43	21.53
	5205	8.72	8.08	11.42	21.53
	5225	9.02	8.49	11.77	21.53
Note: 1. The device is a client unit. 2. The device employed Cyclic Delay Diversity (CDD) for MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on the devices: Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB					
Antenna Gain:	5.45	dBi	Directional gain:	8.45	dBi

5725-5850 MHz:

Test Modes	Test Frequency (MHz)	Max. Conducted Average Output Power (dBm)			
		Chain 0	Chain 1	Total	Limit
OFDM	5760	17.73	18.44	21.11	28.66
	5780	17.97	18.55	21.28	28.66
	5820	17.61	18.48	21.08	28.66
Note: The device employed Cyclic Delay Diversity (CDD) for MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on the devices: Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB					
Antenna Gain:	4.34	dBi	Directional gain:	7.34	dBi

FCC §15.407(a) - POWER SPECTRAL DENSITY

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Duty cycle $\geq 98\%$


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

Duty cycle $< 98\%$, duty cycle variations exceed $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.



Test Data

Environmental Conditions

Temperature:	23~28°C
Relative Humidity:	47 ~58 %
ATM Pressure:	101 kPa

The testing was performed by Rainbow Zhu from 2024-08-31 to 2024-10-28.

EUT operation mode: Transmitting

Test Result: Compliant.


5150-5250 MHz:

Test Modes	Test Frequency (MHz)	Reading (dBm/MHz)			Duty Cycle Factor (dB)	Maximum Power Spectral Density (dBm/MHz)	
		Chain 0	Chain 1	Total		Result	Limit
OFDM	5185	-6.19	-6.19	-3.18	1.14	-2.04	8.55
	5205	-6.67	-6.33	-3.49	1.14	-2.35	8.55
	5225	-6.22	-5.46	-2.81	1.14	-1.67	8.55
Note: 1. The device is a client unit. 2. The device employed Cyclic Delay Diversity (CDD) for MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices: Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB 3. Method SA-2 in KDB 789033 D02 General UNII Test Procedures New Rules v02r01 was used for PSD test. 4. PSD = Total + Duty Cycle Factor							
Antenna Gain:		5.45	dBi	Directional Gain:		8.45	dBi




5725-5850 MHz:

Test Modes	Test Frequency (MHz)	Reading (dBm/500kHz)			Duty Cycle Factor (dB)	Maximum Power Spectral Density (dBm/500kHz)	
		Chain 0	Chain 1	Total		Result	Limit
OFDM	5760	0.27	-0.11	3.09	0.98	4.07	28.66
	5780	0.48	0.06	3.29	0.98	4.27	28.66
	5820	0.17	0.07	3.13	0.98	4.11	28.66
Note: 1. The device employed Cyclic Delay Diversity (CDD) for MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices: Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB 2. Method SA-2 in KDB 789033 D02 General UNII Test Procedures New Rules v02r01 was used for PSD test. 3. PSD = Total + Duty Cycle Factor							
Antenna Gain:		4.34	dBi	Directional gain:		7.34	dBi

5150-5250 MHz: Chain 0




Chain 1

5185 MHz	<div>Maximum Power Spectral Density</div> <div><p>Ref: 30 dBm *Att: 30 dB *RBW: 1 MHz Marker 1 [T1] -6.19 dBm *VSW: 3 MHz SWT: 20 ms 5.185282051 GHz</p><p>30 Offset 11 dB</p><p>SWP 100 OF 200</p><p>Center 5.185 GHz 8 MHz/ Span 80 MHz</p><p>ProjectNo.: 2401U43539E-RF Tester:Rainbow Zhu Date: 28.OCT.2024 18:35:50</p></div>
5205 MHz	<div><p>Ref: 30 dBm *Att: 30 dB *RBW: 1 MHz Marker 1 [T1] -6.23 dBm *VSW: 3 MHz SWT: 20 ms 5.205000000 GHz</p><p>30 Offset 11 dB</p><p>SWP 100 OF 200</p><p>Center 5.205 GHz 8 MHz/ Span 80 MHz</p><p>ProjectNo.: 2401U43539E-RF Tester:Rainbow Zhu Date: 28.OCT.2024 18:38:28</p></div>
5225 MHz	<div><p>Ref: 30 dBm *Att: 30 dB *RBW: 1 MHz Marker 1 [T1] -5.46 dBm *VSW: 3 MHz SWT: 20 ms 5.224871795 GHz</p><p>30 Offset 11 dB</p><p>SWP 100 OF 200</p><p>Center 5.225 GHz 8 MHz/ Span 80 MHz</p><p>ProjectNo.: 2401U43539E-RF Tester:Rainbow Zhu Date: 28.OCT.2024 18:35:07</p></div>

Chain 1


Maximum Power Spectral Density

5760 MHz




ProjectNo.:2401U43539E-RF Tester:Rainbow Zhu
Date: 6.SEP.2024 11:44:52

5780 MHz



ProjectNo.:2401U43539E-RF Tester:Rainbow Zhu
Date: 6.SEP.2024 11:46:21

5820 MHz



ProjectNo.:2401U43539E-RF Tester:Rainbow Zhu
Date: 6.SEP.2024 11:47:03

EUT PHOTOGRAPHS

Please refer to the attachment 2401U43539E-RF External photo and 2401U43539E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2401U43539E-RF Test Setup photo.

******* END OF REPORT *******