

RF Exposure Report

FCC ID: 2AR2STAB4500

Applicant: MMD Hong Kong Holding Limited

Address: Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Manufacturer: MMD Hong Kong Holding Limited

Address: Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Product(s): Soundbar Speaker

Brand: PHILIPS or



Test Model(s): TAB4500/37

Series Model(s): See section 2.1

Test Date: Dec. 18, 2024 ~ Feb. 11, 2025

Issued Date: Feb. 11, 2025

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China

Test Firm Registration No.: 915896

Standards: FCC Part 2(Section 2.1093)
KDB 447498 D01 General RF Exposure Guidance v06


The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Wendy Lee

Reviewed by :



Sye Yang

Approved by :



Scott He

"This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. Our report includes all the tests requested by you and the results thereof based upon the information that you provided to us. The report would be invalid without specific stamp of test institute and the signatures of tester and approver."

Table of contents

Release control record	3
1 General Information	4
1.1 General Description of EUT	4
2 RF exposure limit	5
2.1 MPE calculation formula	5
3 Calculation SAR test exclusion thresholds	6
Appendix – Information on the Testing Laboratories	7

Release control record


Issue No.	Reason for change	Date Issued
2409250340-SE-US-01	Original Release	Feb. 11, 2025

1 General Information**1.1 General Description of EUT**

Product(s)	Soundbar Speaker
Test Model(s)	TAB4500/37
Sample No.	HS2409250340002, HS2409250340003
Series Model(s)	TAB4500, TAB4500/10, TAB4500/98, TAB4500/61, TAB4500xx/yy (x=A-Z or Nil for different colour or package, yy=00-99 or Nil for country code)
Status of EUT	Engineering Prototype
Power Supply Rating	DC 15V 1.6A from Adapter
Modulation Type	GFSK, $\pi/4$ DQPSK for FHSS GFSK for DTS
Transfer Rate	1Mbps, 2Mbps
Operating Frequency	2402 ~ 2480MHz
Number of Channel	79 for FHSS 40 for DTS
Maximum Output Power (Peak)	-2.498 dBm for FHSS 2.042dBm for DTS
Antenna Type and Antenna Gain	PCB Antenna; 1.26dBi Gain
Antenna Connector	N/A
Accessory Device	IR remote controller
Cable Supplied	N/A

Note:

1. Please refer to the EUT photo document (Reference No.: 2409250340-01&02) for detailed product photo.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
3. Model difference: These models are only different from model name for trade purpose.
4. Adapter information as below:

Adapter (fixed Plug)	
Brand:	
Model:	PG241-1501600U
Input:	100-240V~50/60Hz 0.8A
Output:	DC 15.0V 1.6A 24.0W
DC Line:	Unshielded, Non-detachable, 155cm

2 RF exposure limit

Limits for maximum permissible exposure (MPE)

Limits for general population / uncontrolled exposure				
Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Average time (minutes)
300-1500	F/1500	30
1500-100,000	1.0	30

Note: F = Frequency in MHz

2.1 MPE calculation formula

$$Pd = (P_{out} * G) / (4 * \pi * r^2)$$

Where:

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Classification:

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

3 Calculation SAR test exclusion thresholds

The antennas provided to the EUT, please refer to the following table:

Function	Transmit and Receive Chain	Antenna Gain (dBi)	Maximum Power		Distance (cm)	Power density (mW/cm ²)	Limit (mW/cm ²)
			(dBm)	(mW)			
BT	1TX,1RX	1.26	-2.498	0.5626	20	0.00150	1.0
BLE	1TX,1RX	1.26	2.042	1.6003	20	0.00426	1.0

Note: The above wireless function can not be transmission simultaneous.

Conclusion:

Therefore, the worst-case situation is 0.00426 mW/cm², which is less than "1". This confirmed that the device compliance with FCC 1.1310 MPE limit.

Appendix – Information on the Testing Laboratories

We, [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values "HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT", commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Contact Tel: [0769-83078199](tel:0769-83078199)

Email: Customerservice.dg@hwa-hsing.com

Web Site: www.hwa-hsing.com

--- END ---