

FCC PART 15.247

TEST REPORT

For

Acegame S.A

Gorriti 4539 - C.A.B.A., Buenos Aires, Argentina

FCC ID: 2ADTU-ZENAIR

Report Type: Original Report	Product Type: Mobile Phone
Test Engineer:	Allen Qiao
Report Number:	RDG160217001-00B
Report Date:	2016-02-25
Reviewed By:	Sula Huang RF Leader
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	9
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	10
APPLICABLE STANDARD	10
FCC §15.203 - ANTENNA REQUIREMENT.....	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	12
MEASUREMENT UNCERTAINTY.....	12
EUT SETUP.....	12
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
CORRECTED AMPLITUDE & MARGIN CALCULATION	13
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	19
APPLICABLE STANDARD	19
MEASUREMENT UNCERTAINTY.....	19
EUT SETUP	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST RESULTS SUMMARY	21
TEST DATA	22
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST EQUIPMENT LIST AND DETAILS.....	36
TEST DATA	36
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	45

APPLICABLE STANDARD	45
TEST PROCEDURE	45
TEST EQUIPMENT LIST AND DETAILS.....	45
TEST DATA	45
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	47
APPLICABLE STANDARD	47
TEST PROCEDURE	47
TEST EQUIPMENT LIST AND DETAILS.....	47
TEST DATA	47
FCC §15.247(e) - POWER SPECTRAL DENSITY	53
APPLICABLE STANDARD	53
TEST PROCEDURE	53
TEST EQUIPMENT LIST AND DETAILS.....	53
TEST DATA	53

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Acegame S.A's* product, model number: *Zen Air (FCC ID: 2ADTU-ZENAIR)* (the "EUT") in this report was a *Mobile Phone*, which was measured approximately: 14.6cm (L) x 7.2 cm (W) x 0.8 cm (H), rated input voltage: DC 3.8V rechargeable Li-ion battery or DC5V charging from adapter.

All measurement and test data in this report was gathered from production sample serial number: 160217001 (Assigned by BACL, Dongguan). The EUT was received on 2016-02-17.

Objective

This report is prepared on behalf of *Acegame S.A* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ADTU-ZENAIR.
FCC Part 15C DSS submissions with FCC ID: 2ADTU-ZENAIR.
FCC Part 22H, 24E, 27 PCE submissions with FCC ID: 2ADTU-ZENAIR.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer. For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with channel 1, 6 and 11. For 802.11n ht40 mode were tested with Channel 3, 6 and 9.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

The worst condition (maximum power with 100% duty cycle) was setting by the software as following table:

Test Mode	Test Software Version	Engineering Mode		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	10	10	10
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	10	9	9
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	9	9	9
802.11n ht40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	12	11	11
BLE	Test Frequency	2402MHz	2440MHz	2480MHz
	Power Level Setting	N/A	N/A	N/A

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	no	no	1.0	USB Port of Adapter	EUT
Earphone Cable	no	no	1.2	Audio Port of EUT	Earphone


Block Diagram of Test Setup

AC power-line conducted emissions:




Radiated Emissions:

Below 1GHz:



Above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE**Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

For 100 MHz to 6 GHz and *test separation distances* ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as *numeric thresholds* in step b) below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test

Measurement Result**For Wi-Fi mode:**

The tune-up conducted average output power = 9.8 dBm (9.55 mW) at 2462 MHz
 $[(\text{max. power of channel, mW}) / (\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 9.55/5 \cdot (\sqrt{2.462}) = 3.0$

For bluetooth LE mode:

The tune-up conducted output power = -1.7 dBm (0.68 mW) at 2480 MHz
 $[(\text{max. power of channel, mW}) / (\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 0.68/5 \cdot (\sqrt{2.48}) = 0.2 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one integral antenna arrangement for WiFi, which was permanently attached and the antenna gain is -1.1dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner

FINAL

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-12-10	2016-12-09
R&S	L.I.S.N	ESH2-Z5	892107/021	2015-07-16	2016-07-15
R&S	Two-line V-network	ENV 216	3560.6550.12	2015-11-26	2016-11-25
N/A	Coaxial Cable	1.8m	N/A	2015-05-06	2016-05-06
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

13.2 dB at 0.184529 MHz in the **Line** conducted mode for BLE.


Test Data**Environmental Conditions**

Temperature:	23.6°C
Relative Humidity:	42%
ATM Pressure:	101.7 kPa

The testing was performed by Allen Qiao on 2016-02-23.


Test Mode: Transmitting (Wi-Fi)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.151200	45.1	9.000	L1	9.8	20.8	65.9	Compliance
0.183065	49.3	9.000	L1	9.7	15.0	64.3	Compliance
0.228823	43.2	9.000	L1	9.7	19.3	62.5	Compliance
0.274848	39.5	9.000	L1	9.7	21.5	61.0	Compliance
0.363254	35.4	9.000	L1	9.7	23.3	58.7	Compliance
0.715082	38.9	9.000	L1	9.8	17.1	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.183065	32.2	9.000	L1	9.7	22.1	54.3	Compliance
0.692650	22.5	9.000	L1	9.8	23.5	46.0	Compliance
0.732382	20.3	9.000	L1	9.8	25.7	46.0	Compliance
1.239175	25.7	9.000	L1	9.8	20.3	46.0	Compliance
1.407671	26.4	9.000	L1	9.8	19.6	46.0	Compliance
17.739864	23.7	9.000	L1	10.1	26.3	50.0	Compliance


AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	47.0	9.000	N	9.7	19.0	66.0	Compliance
0.181612	48.2	9.000	N	9.7	16.2	64.4	Compliance
0.227007	42.0	9.000	N	9.7	20.6	62.6	Compliance
0.288307	37.8	9.000	N	9.7	22.8	60.6	Compliance
0.624492	38.7	9.000	N	9.7	17.3	56.0	Compliance
0.709407	37.7	9.000	N	9.7	18.3	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.186006	30.5	9.000	N	9.7	23.7	54.2	Compliance
0.644717	22.9	9.000	N	9.7	23.1	46.0	Compliance
0.692650	23.8	9.000	N	9.7	22.2	46.0	Compliance
1.239175	25.5	9.000	N	9.8	20.5	46.0	Compliance
1.289541	26.3	9.000	N	9.8	19.7	46.0	Compliance
1.430284	26.5	9.000	N	9.8	19.5	46.0	Compliance


Test Mode: Transmitting (BLE)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	46.7	9.000	L1	9.8	19.3	66.0	Compliance
0.184529	51.1	9.000	L1	9.7	13.2	64.3	Compliance
0.228823	45.0	9.000	L1	9.7	17.5	62.5	Compliance
0.272666	40.9	9.000	L1	9.7	20.1	61.0	Compliance
0.319773	39.4	9.000	L1	9.7	20.3	59.7	Compliance
0.715082	38.4	9.000	L1	9.8	17.6	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.183065	34.5	9.000	L1	9.7	19.8	54.3	Compliance
0.692650	22.1	9.000	L1	9.8	23.9	46.0	Compliance
1.239175	24.7	9.000	L1	9.8	21.3	46.0	Compliance
1.289541	26.2	9.000	L1	9.8	19.8	46.0	Compliance
1.385415	26.5	9.000	L1	9.8	19.5	46.0	Compliance
17.739864	22.2	9.000	L1	10.1	27.8	50.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	46.6	9.000	N	9.7	19.4	66.0	Compliance
0.181612	49.8	9.000	N	9.7	14.6	64.4	Compliance
0.228823	44.0	9.000	N	9.7	18.5	62.5	Compliance
0.319773	38.8	9.000	N	9.7	20.9	59.7	Compliance
0.629488	36.2	9.000	N	9.7	19.8	56.0	Compliance
0.715082	40.9	9.000	N	9.7	15.1	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.184529	34.1	9.000	N	9.7	20.2	54.3	Compliance
0.644717	25.3	9.000	N	9.7	20.7	46.0	Compliance
0.738241	20.1	9.000	N	9.7	25.9	46.0	Compliance
1.023481	21.6	9.000	N	9.8	24.4	46.0	Compliance
1.239175	26.4	9.000	N	9.8	19.6	46.0	Compliance
1.430284	26.7	9.000	N	9.8	19.3	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS


Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner

FINAL

Above 1GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-05-09	2016-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
R&S	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS LINDGREN	Horn Antenna	3115	000 527 35	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2015-09-06	2016-09-06
N/A	Coaxial Cable	14m	N/A	2015-05-06	2016-05-06
N/A	Coaxial Cable	8m	N/A	2015-05-06	2016-05-06
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

11.05 dB at 2483.5 MHz in the **Horizontal** polarization for WiFi Mode (802.11 n ht20)

Test Data**Environmental Conditions**

Temperature:	18.8 ~ 19.1°C
Relative Humidity:	58 %
ATM Pressure:	101.7 ~ 101.9kPa

** The testing was performed by Allen Qiao from 2016-02-17 to 2016-02-18.*

Test Mode: Transmitting

802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	53.36	PK	H	25.67	3.68	0.00	82.71	N/A	N/A
2412	49.8	AV	H	25.67	3.68	0.00	79.15	N/A	N/A
2412	52.81	PK	V	25.67	3.68	0.00	82.16	N/A	N/A
2412	49.18	AV	V	25.67	3.68	0.00	78.53	N/A	N/A
2400	25.93	PK	H	25.64	3.65	0.00	55.22	74.00	18.78
2400	12.88	AV	H	25.64	3.65	0.00	42.17	54.00	11.83
4824	32.25	PK	H	30.64	5.03	27.41	40.51	74.00	33.49
4824	19.2	AV	H	30.64	5.03	27.41	27.46	54.00	26.54
7236	31.98	PK	H	34.17	6.65	25.90	46.90	74.00	27.10
7236	18.77	AV	H	34.17	6.65	25.90	33.69	54.00	20.31
9648	29.96	PK	H	36.06	8.55	27.46	47.11	74.00	26.89
9648	16.18	AV	H	36.06	8.55	27.46	33.33	54.00	20.67
3131	33.12	PK	H	27.62	6.93	27.43	40.24	74.00	33.76
3131	20.49	AV	H	27.62	6.93	27.43	27.61	54.00	26.39
176.5	33.5	QP	V	11.43	1.60	21.45	25.08	43.50	18.42
Middle Channel: 2437 MHz									
2437	53.75	PK	H	25.74	3.75	0.00	83.24	N/A	N/A
2437	50.17	AV	H	25.74	3.75	0.00	79.66	N/A	N/A
2437	53.05	PK	V	25.74	3.75	0.00	82.54	N/A	N/A
2437	49.44	AV	V	25.74	3.75	0.00	78.93	N/A	N/A
4874	32.2	PK	H	30.77	5.14	27.42	40.69	74.00	33.31
4874	19.15	AV	H	30.77	5.14	27.42	27.64	54.00	26.36
7311	31.97	PK	H	34.35	6.74	25.88	47.18	74.00	26.82
7311	18.82	AV	H	34.35	6.74	25.88	34.03	54.00	19.97
9748	29.89	PK	H	36.30	8.61	27.24	47.56	74.00	26.44
9748	16.12	AV	H	36.30	8.61	27.24	33.79	54.00	20.21
3265	32.93	PK	H	28.05	5.96	27.31	39.63	74.00	34.37
3265	20.38	AV	H	28.05	5.96	27.31	27.08	54.00	26.92
3535	32.56	PK	H	28.88	4.51	27.25	38.70	74.00	35.30
3535	20.03	AV	H	28.88	4.51	27.25	26.17	54.00	27.83
176.5	33.4	QP	V	11.43	1.60	21.45	24.98	43.50	18.52
High Channel: 2462 MHz									
2462	54.23	PK	H	25.80	3.75	0.00	83.78	N/A	N/A
2462	50.7	AV	H	25.80	3.75	0.00	80.25	N/A	N/A
2462	53.68	PK	V	25.80	3.75	0.00	83.23	N/A	N/A
2462	50.13	AV	V	25.80	3.75	0.00	79.68	N/A	N/A
2483.5	25.16	PK	H	25.86	3.67	0.00	54.69	74.00	19.31
2483.5	13.34	AV	H	25.86	3.67	0.00	42.87	54.00	11.13
4924	32.45	PK	H	30.90	5.34	27.43	41.26	74.00	32.74
4924	19.61	AV	H	30.90	5.34	27.43	28.42	54.00	25.58
7386	32.41	PK	H	34.53	6.83	25.86	47.91	74.00	26.09
7386	19.2	AV	H	34.53	6.83	25.86	34.70	54.00	19.30
9848	30.33	PK	H	36.54	8.66	26.94	48.59	74.00	25.41
9848	16.56	AV	H	36.54	8.66	26.94	34.82	54.00	19.18
3265	33.43	PK	H	28.05	5.96	27.31	40.13	74.00	33.87
3265	20.85	AV	H	28.05	5.96	27.31	27.55	54.00	26.45
176.5	33.6	QP	V	11.43	1.60	21.45	25.18	43.50	18.32

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	56.97	PK	H	25.67	3.68	0.00	86.32	N/A	N/A
2412	48.61	AV	H	25.67	3.68	0.00	77.96	N/A	N/A
2412	56.48	PK	V	25.67	3.68	0.00	85.83	N/A	N/A
2412	48.26	AV	V	25.67	3.68	0.00	77.61	N/A	N/A
2400	25.32	PK	H	25.64	3.65	0.00	54.61	74.00	19.39
2400	13.14	AV	H	25.64	3.65	0.00	42.43	54.00	11.57
4824	32.94	PK	H	30.64	5.03	27.41	41.20	74.00	32.80
4824	19.66	AV	H	30.64	5.03	27.41	27.92	54.00	26.08
7236	32.57	PK	H	34.17	6.65	25.90	47.49	74.00	26.51
7236	19.38	AV	H	34.17	6.65	25.90	34.30	54.00	19.70
9648	30.43	PK	H	36.06	8.55	27.46	47.58	74.00	26.42
9648	16.67	AV	H	36.06	8.55	27.46	33.82	54.00	20.18
3265	33.7	PK	H	28.05	5.96	27.31	40.40	74.00	33.60
3265	21.06	AV	H	28.05	5.96	27.31	27.76	54.00	26.24
176.5	33.4	QP	V	11.43	1.60	21.45	24.98	43.50	18.52
Middle Channel: 2437 MHz									
2437	56.35	PK	H	25.74	3.75	0.00	85.84	N/A	N/A
2437	47.95	AV	H	25.74	3.75	0.00	77.44	N/A	N/A
2437	55.63	PK	V	25.74	3.75	0.00	85.12	N/A	N/A
2437	47.34	AV	V	25.74	3.75	0.00	76.83	N/A	N/A
4874	32.73	PK	H	30.77	5.14	27.42	41.22	74.00	32.78
4874	19.48	AV	H	30.77	5.14	27.42	27.97	54.00	26.03
7311	32.2	PK	H	34.35	6.74	25.88	47.41	74.00	26.59
7311	18.99	AV	H	34.35	6.74	25.88	34.20	54.00	19.80
9748	30.11	PK	H	36.30	8.61	27.24	47.78	74.00	26.22
9748	16.32	AV	H	36.30	8.61	27.24	33.99	54.00	20.01
3265	33.28	PK	H	28.05	5.96	27.31	39.98	74.00	34.02
3265	20.68	AV	H	28.05	5.96	27.31	27.38	54.00	26.62
3535	33.01	PK	H	28.88	4.51	27.25	39.15	74.00	34.85
3535	20.42	AV	H	28.88	4.51	27.25	26.56	54.00	27.44
176.5	33.3	QP	V	11.43	1.60	21.45	24.88	43.50	18.62
High Channel: 2462 MHz									
2462	55.6	PK	H	25.80	3.75	0.00	85.15	N/A	N/A
2462	47.35	AV	H	25.80	3.75	0.00	76.90	N/A	N/A
2462	55.03	PK	V	25.80	3.75	0.00	84.58	N/A	N/A
2462	46.71	AV	V	25.80	3.75	0.00	76.26	N/A	N/A
2483.5	25.19	PK	H	25.86	3.67	0.00	54.72	74.00	19.28
2483.5	13.37	AV	H	25.86	3.67	0.00	42.90	54.00	11.10
4924	32.79	PK	H	30.90	5.34	27.43	41.60	74.00	32.40
4924	19.41	AV	H	30.90	5.34	27.43	28.22	54.00	25.78
7386	32.26	PK	H	34.53	6.83	25.86	47.76	74.00	26.24
7386	19.02	AV	H	34.53	6.83	25.86	34.52	54.00	19.48
9848	30.13	PK	H	36.54	8.66	26.94	48.39	74.00	25.61
9848	16.34	AV	H	36.54	8.66	26.94	34.60	54.00	19.40
3265	33.29	PK	H	28.05	5.96	27.31	39.99	74.00	34.01
3265	20.7	AV	H	28.05	5.96	27.31	27.40	54.00	26.60
176.5	33.4	QP	V	11.43	1.60	21.45	24.98	43.50	18.52

802.11 n ht20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	56.74	PK	H	25.67	3.68	0.00	86.09	N/A	N/A
2412	48.01	AV	H	25.67	3.68	0.00	77.36	N/A	N/A
2412	56.2	PK	V	25.67	3.68	0.00	85.55	N/A	N/A
2412	47.58	AV	V	25.67	3.68	0.00	76.93	N/A	N/A
2400	25.62	PK	H	25.64	3.65	0.00	54.91	74.00	19.09
2400	13.15	AV	H	25.64	3.65	0.00	42.44	54.00	11.56
4824	32.72	PK	H	30.64	5.03	27.41	40.98	74.00	33.02
4824	19.45	AV	H	30.64	5.03	27.41	27.71	54.00	26.29
7236	32.59	PK	H	34.17	6.65	25.90	47.51	74.00	26.49
7236	19.13	AV	H	34.17	6.65	25.90	34.05	54.00	19.95
9648	30.55	PK	H	36.06	8.55	27.46	47.70	74.00	26.30
9648	16.45	AV	H	36.06	8.55	27.46	33.60	54.00	20.40
3265	33.7	PK	H	28.05	5.96	27.31	40.40	74.00	33.60
3265	20.97	AV	H	28.05	5.96	27.31	27.67	54.00	26.33
176.5	33.4	QP	V	11.43	1.60	21.45	24.98	43.50	18.52
Middle Channel: 2437 MHz									
2437	55.91	PK	H	25.74	3.75	0.00	85.40	N/A	N/A
2437	47.25	AV	H	25.74	3.75	0.00	76.74	N/A	N/A
2437	55.48	PK	V	25.74	3.75	0.00	84.97	N/A	N/A
2437	46.74	AV	V	25.74	3.75	0.00	76.23	N/A	N/A
4874	32.8	PK	H	30.77	5.14	27.42	41.29	74.00	32.71
4874	19.45	AV	H	30.77	5.14	27.42	27.94	54.00	26.06
7311	32.25	PK	H	34.35	6.74	25.88	47.46	74.00	26.54
7311	18.9	AV	H	34.35	6.74	25.88	34.11	54.00	19.89
9748	30.18	PK	H	36.30	8.61	27.24	47.85	74.00	26.15
9748	16.4	AV	H	36.30	8.61	27.24	34.07	54.00	19.93
3265	33.32	PK	H	28.05	5.96	27.31	40.02	74.00	33.98
3265	20.5	AV	H	28.05	5.96	27.31	27.20	54.00	26.80
3535	32.89	PK	H	28.88	4.51	27.25	39.03	74.00	34.97
3535	20.26	AV	H	28.88	4.51	27.25	26.40	54.00	27.60
176.5	33.3	QP	V	11.43	1.60	21.45	24.88	43.50	18.62
High Channel: 2462 MHz									
2462	55.41	PK	H	25.80	3.75	0.00	84.96	N/A	N/A
2462	46.74	AV	H	25.80	3.75	0.00	76.29	N/A	N/A
2462	54.89	PK	V	25.80	3.75	0.00	84.44	N/A	N/A
2462	46.16	AV	V	25.80	3.75	0.00	75.71	N/A	N/A
2483.5	25.62	PK	H	25.86	3.67	0.00	55.15	74.00	18.85
2483.5	13.35	AV	H	25.86	3.67	0.00	42.88	54.00	11.12
4924	32.66	PK	H	30.90	5.34	27.43	41.47	74.00	32.53
4924	19.46	AV	H	30.90	5.34	27.43	28.27	54.00	25.73
7386	32.34	PK	H	34.53	6.83	25.86	47.84	74.00	26.16
7386	19.03	AV	H	34.53	6.83	25.86	34.53	54.00	19.47
9848	30.09	PK	H	36.54	8.66	26.94	48.35	74.00	25.65
9848	16.29	AV	H	36.54	8.66	26.94	34.55	54.00	19.45
3265	33.37	PK	H	28.05	5.96	27.31	40.07	74.00	33.93
3265	20.54	AV	H	28.05	5.96	27.31	27.24	54.00	26.76
176.5	33.2	QP	V	11.43	1.60	21.45	24.78	43.50	18.72

802.11 n ht40 Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2422 MHz									
2422	56.35	PK	H	25.70	3.71	0.00	85.76	N/A	N/A
2422	47.72	AV	H	25.70	3.71	0.00	77.13	N/A	N/A
2422	55.78	PK	V	25.70	3.71	0.00	85.19	N/A	N/A
2422	47.11	AV	V	25.70	3.71	0.00	76.52	N/A	N/A
2400	26.29	PK	H	25.64	3.65	0.00	55.58	74.00	18.42
2400	13.56	AV	H	25.64	3.65	0.00	42.85	54.00	11.15
4844	32.44	PK	H	30.69	4.99	27.42	40.70	74.00	33.30
4844	19.13	AV	H	30.69	4.99	27.42	27.39	54.00	26.61
7266	32.15	PK	H	34.24	6.68	25.89	47.18	74.00	26.82
7266	18.92	AV	H	34.24	6.68	25.89	33.95	54.00	20.05
9688	30.51	PK	H	36.15	8.58	27.37	47.87	74.00	26.13
9688	16.39	AV	H	36.15	8.58	27.37	33.75	54.00	20.25
3265	33.72	PK	H	28.05	5.96	27.31	40.42	74.00	33.58
3265	20.95	AV	H	28.05	5.96	27.31	27.65	54.00	26.35
176.5	33.3	QP	V	11.43	1.60	21.45	24.88	43.50	18.62
Middle Channel: 2437 MHz									
2437	56.38	PK	H	25.74	3.75	0.00	85.87	N/A	N/A
2437	47.78	AV	H	25.74	3.75	0.00	77.27	N/A	N/A
2437	55.59	PK	V	25.74	3.75	0.00	85.08	N/A	N/A
2437	47.04	AV	V	25.74	3.75	0.00	76.53	N/A	N/A
4874	32.37	PK	H	30.77	5.14	27.42	40.86	74.00	33.14
4874	19.08	AV	H	30.77	5.14	27.42	27.57	54.00	26.43
7311	32.23	PK	H	34.35	6.74	25.88	47.44	74.00	26.56
7311	19.04	AV	H	34.35	6.74	25.88	34.25	54.00	19.75
9748	30.19	PK	H	36.30	8.61	27.24	47.86	74.00	26.14
9748	16.3	AV	H	36.30	8.61	27.24	33.97	54.00	20.03
3265	33.35	PK	H	28.05	5.96	27.31	40.05	74.00	33.95
3265	20.65	AV	H	28.05	5.96	27.31	27.35	54.00	26.65
3535	33.07	PK	H	28.88	4.51	27.25	39.21	74.00	34.79
3535	20.57	AV	H	28.88	4.51	27.25	26.71	54.00	27.29
176.5	33.2	QP	V	11.43	1.60	21.45	24.78	43.50	18.72
High Channel: 2452 MHz									
2452	56.06	PK	H	25.78	3.78	0.00	85.62	N/A	N/A
2452	47.37	AV	H	25.78	3.78	0.00	76.93	N/A	N/A
2452	55.41	PK	V	25.78	3.78	0.00	84.97	N/A	N/A
2452	46.82	AV	V	25.78	3.78	0.00	76.38	N/A	N/A
2483.5	25.67	PK	H	25.86	3.67	0.00	55.20	74.00	18.80
2483.5	13.42	AV	H	25.86	3.67	0.00	42.95	54.00	11.05
4904	32.76	PK	H	30.85	5.31	27.43	41.49	74.00	32.51
4904	19.36	AV	H	30.85	5.31	27.43	28.09	54.00	25.91
7356	32.13	PK	H	34.45	6.79	25.87	47.50	74.00	26.50
7356	19.02	AV	H	34.45	6.79	25.87	34.39	54.00	19.61
9808	30.13	PK	H	36.44	8.64	27.09	48.12	74.00	25.88
9808	16.22	AV	H	36.44	8.64	27.09	34.21	54.00	19.79
3265	33.29	PK	H	28.05	5.96	27.31	39.99	74.00	34.01
3265	20.55	AV	H	28.05	5.96	27.31	27.25	54.00	26.75
176.5	33.1	QP	V	11.43	1.60	21.45	24.68	43.50	18.82

BLE Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	49.2	PK	H	25.65	3.66	0.00	78.51	N/A	N/A
2402	44.09	AV	H	25.65	3.66	0.00	73.40	N/A	N/A
2402	51.72	PK	V	25.65	3.66	0.00	81.03	N/A	N/A
2402	46.6	AV	V	25.65	3.66	0.00	75.91	N/A	N/A
2400	25.05	PK	V	25.64	3.65	0.00	54.34	74.00	19.66
2400	13.93	AV	V	25.64	3.65	0.00	43.22	54.00	10.78
4804	32.35	PK	V	30.59	5.06	27.41	40.59	74.00	33.41
4804	18.81	AV	V	30.59	5.06	27.41	27.05	54.00	26.95
7206	31.68	PK	V	34.09	6.61	25.91	46.47	74.00	27.53
7206	18.51	AV	V	34.09	6.61	25.91	33.30	54.00	20.70
9608	29.24	PK	V	35.96	8.53	27.55	46.18	74.00	27.82
9608	15.93	AV	V	35.96	8.53	27.55	32.87	54.00	21.13
3265	32.41	PK	V	28.05	5.96	27.31	39.11	74.00	34.89
3265	19.82	AV	V	28.05	5.96	27.31	26.52	54.00	27.48
176.5	33.2	QP	V	11.43	1.60	21.45	24.78	43.50	18.72
Middle Channel: 2440 MHz									
2440	48.4	PK	H	25.74	3.76	0.00	77.90	N/A	N/A
2440	43.23	AV	H	25.74	3.76	0.00	72.73	N/A	N/A
2440	50.77	PK	V	25.74	3.76	0.00	80.27	N/A	N/A
2440	45.68	AV	V	25.74	3.76	0.00	75.18	N/A	N/A
4880	32.28	PK	V	30.79	5.18	27.42	40.83	74.00	33.17
4880	18.8	AV	V	30.79	5.18	27.42	27.35	54.00	26.65
7320	31.73	PK	V	34.37	6.75	25.88	46.97	74.00	27.03
7320	18.54	AV	V	34.37	6.75	25.88	33.78	54.00	20.22
9760	29.28	PK	V	36.32	8.62	27.21	47.01	74.00	26.99
9760	15.9	AV	V	36.32	8.62	27.21	33.63	54.00	20.37
3085	32.33	PK	V	27.47	6.78	27.46	39.12	74.00	34.88
3085	19.8	AV	V	27.47	6.78	27.46	26.59	54.00	27.41
3265	32.36	PK	V	28.05	5.96	27.31	39.06	74.00	34.94
3265	19.81	AV	V	28.05	5.96	27.31	26.51	54.00	27.49
176.5	33.1	QP	V	11.43	1.60	21.45	24.68	43.50	18.82
High Channel: 2480 MHz									
2480	47.88	PK	H	25.85	3.68	0.00	77.41	N/A	N/A
2480	42.56	AV	H	25.85	3.68	0.00	72.09	N/A	N/A
2480	50.37	PK	V	25.85	3.68	0.00	79.90	N/A	N/A
2480	45.05	AV	V	25.85	3.68	0.00	74.58	N/A	N/A
2483.5	26	PK	V	25.86	3.67	0.00	55.53	74.00	18.47
2483.5	13.28	AV	V	25.86	3.67	0.00	42.81	54.00	11.19
4960	32.34	PK	V	31.00	5.34	27.43	41.25	74.00	32.75
4960	18.93	AV	V	31.00	5.34	27.43	27.84	54.00	26.16
7440	31.74	PK	V	34.66	6.89	25.97	47.32	74.00	26.68
7440	18.59	AV	V	34.66	6.89	25.97	34.17	54.00	19.83
9920	29.53	PK	V	36.71	8.71	26.66	48.29	74.00	25.71
9920	16.03	AV	V	36.71	8.71	26.66	34.79	54.00	19.21
3265	32.33	PK	V	28.05	5.96	27.31	39.03	74.00	34.97
3265	19.75	AV	V	28.05	5.96	27.31	26.45	54.00	27.55
176.5	33.2	QP	V	11.43	1.60	21.45	24.78	43.50	18.72


Conducted Spurious Emissions at Antenna Port

802.11b Low Channel




Date: 18.FEB.2016 09:48:16

802.11b Middle Channel




Date: 18.FEB.2016 09:50:58

802.11b High Channel




Date: 18.FEB.2016 09:54:07

802.11g Low Channel




Date: 18.FEB.2016 09:57:03

802.11g Middle Channel




Date: 18.FEB.2016 09:59:58

802.11g High Channel




Date: 18.FEB.2016 10:03:29

802.11n ht20 Low Channel




Date: 18.FEB.2016 10:06:33

802.11n ht20 Middle Channel




Date: 18.FEB.2016 10:09:30

802.11n ht20 High Channel




Date: 18.FEB.2016 10:12:23

802.11n ht40 Low Channel




Date: 18.FEB.2016 10:15:40

802.11n ht40 Middle Channel




Date: 18.FEB.2016 10:22:29

802.11n ht40 High Channel




Date: 18.FEB.2016 10:29:03

BLE Low Channel




Date: 17.FEB.2016 17:15:39

BLE Middle Channel



Date: 17.FEB.2016 17:12:13

BLE High Channel



Date: 17.FEB.2016 17:13:45

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)


FINAL

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.60	

802.11b Middle Channel




Date: 18.FEB.2016 09:49:20

802.11b High Channel




Date: 26.FEB.2016 16:42:32

802.11g Low Channel




Date: 18.FEB.2016 09:55:17

802.11g Middle Channel




Date: 18.FEB.2016 09:58:12

802.11g High Channel



Date: 18.FEB.2016 10:01:33

802.11n ht20 Low Channel



Date: 18.FEB.2016 10:04:42

1 PK MAXH

Ref 20 dBm *Att 30 dB

*RBW 100 kHz Delta 1 [T1]
 *VBW 300 kHz 0.96 dB
 SWT 5 ms 16.480000000 MHz

20 Offset 0.5 dB

Marker 1 [T1] -11.98 dBm
 Marker 2 [T1] -5.24 dBm


D1 -5.24 dBm
 D2 -11.24 dBm

Center 2.437 GHz 4 MHz/ Span 40 MHz

802.11n ht20 High Channel




802.11n ht40 Low Channel




Date: 18.FEB.2016 10:13:34

802.11n ht40 Middle Channel




Date: 18.FEB.2016 10:20:27

802.11n ht40 High Channel




Date: 18.FEB.2016 10:26:56

BLE Low Channel




Date: 17.FEB.2016 17:14:46

BLE Middle Channel



Date: 17.FEB.2016 17:11:13

BLE High Channel



Date: 17.FEB.2016 17:12:50

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2015-11-03	2016-11-03
Agilent	Wideband Power Sensor	N1921A	MY54170013	2015-11-03	2016-11-03
Agilent	P-Series Power Meter	N1912A	MY5000448	2015-11-03	2016-11-03
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	19.1°C
Relative Humidity:	58 %
ATM Pressure:	101.9kPa

* The testing was performed by Allen Qiao from 2016-02-17 to 2016-02-18.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Max Conducted Average Output Power	Limit
		(MHz)	(dBm)	(dBm)	(dBm)
802.11b	Low	2412	10.07	9.19	30
	Middle	2437	10.69	9.79	30
	High	2462	10.47	9.58	30
802.11g	Low	2412	13.05	9.65	30
	Middle	2437	12.59	9.21	30
	High	2462	12.64	9.24	30
802.11n20	Low	2412	11.76	8.51	30
	Middle	2437	12.50	9.31	30
	High	2462	12.59	9.29	30
802.11n40	Low	2422	15.70	9.21	30
	Middle	2437	16.01	9.58	30
	High	2452	16.15	9.68	30
BLE	Low	2402	-3.47	/	30
	Middle	2440	-1.76	/	30
	High	2480	-4.26	/	30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	18.8 ~ 19.1°C
Relative Humidity:	58 %
ATM Pressure:	101.7~ 101.9kPa

* The testing was performed by Allen Qiao from 2016-02-17 to 2016-02-18.

Test mode: Transmitting


Test Result: Compliant. Please refer to following plots.

802.11b: Band Edge, Left Side




Date: 18.FEB.2016 09:48:37

802.11b: Band Edge, Right Side




Date: 18.FEB.2016 09:54:25

802.11g: Band Edge, Left Side




Date: 18.FEB.2016 09:57:21

802.11g: Band Edge, Right Side




Date: 18.FEB.2016 10:03:47

802.11n ht20 Band Edge, Left Side




Date: 18.FEB.2016 10:06:51

802.11n ht20 Band Edge, Right Side




Date: 18.FEB.2016 10:12:41

802.11n ht40 Band Edge, Left Side




Date: 18.FEB.2016 10:15:59

802.11n ht40 Band Edge, Right Side




Date: 18.FEB.2016 10:29:28

BLE Band Edge, Left Side



Date: 17.FEB.2016 17:16:03

BLE Band Edge, Right Side



Date: 17.FEB.2016 17:14:08

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance


- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW ≥ 3

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots


Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-17.19	

Power Spectral Density, 802.11b Middle Channel




Date: 18.FEB.2016 09:50:39

Power Spectral Density, 802.11b High Channel




Date: 18.FEB.2016 09:53:43

Power Spectral Density, 802.11g Low Channel




Date: 18.FEB.2016 09:56:45

Power Spectral Density, 802.11g Middle Channel




Date: 18.FEB.2016 09:59:36

Power Spectral Density, 802.11g High Channel




Date: 18.FEB.2016 10:03:08

Power Spectral Density, 802.11n ht20 Low Channel




Date: 18.FEB.2016 10:06:11

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 18.FEB.2016 10:09:12

Power Spectral Density, 802.11n ht20 High Channel




Date: 18.FEB.2016 10:11:55

Power Spectral Density, 802.11n ht40 Low Channel




Date: 18.FEB.2016 10:15:19

Power Spectral Density, 802.11n ht40 Middle Channel




Date: 18.FEB.2016 10:22:07

Power Spectral Density, 802.11n ht40 High Channel




Date: 18.FEB.2016 10:28:43

Power Spectral Density, BLE Low Channel




Date: 17.FEB.2016 17:15:21

Power Spectral Density, BLE Middle Channel



Date: 17.FEB.2016 17:11:49

Power Spectral Density, BLE High Channel



Date: 17.FEB.2016 17:13:26

***** END OF REPORT *****