



# TEST REPORT

Applicant Name : Meizhou Guo Wei Electronics Co., Ltd  
Address : AD1 Section, Economic Development Area, Dongsheng Industrial District, Meizhou, Guangdong, China.  
Report Number : SZ1210926-54083E-RF-00A  
FCC ID: 2ARRB-PIP1510PU  
IC 20353-PIP1510PU

## Test Standard (s)

FCC PART 15.247; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2; RSS-247, ISSUE 2, FEBRUARY 2017

## Sample Description

Product Type: Video baby monitor  
Model No.: PIP1510 CONNECT PU  
Multiple Model(s) No.: PIP1500 CONNECT PU, PIP1510 PU, PIP1500 PU( Please refer to DOS for Model difference)  
Trade Mark: Motorola  
Date Received: 2021/09/26  
Date of Test: 2021/09/29~2021/11/18  
Report Date: 2021/11/24

|              |       |
|--------------|-------|
| Test Result: | Pass* |
|--------------|-------|

\* In the configuration tested, the EUT complied with the standards above.

**Prepared and Checked By:**

*Black Ding*

Black Ding  
EMC Engineer

**Approved By:**

*Candy Li*

Candy Li  
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

**Shenzhen Accurate Technology Co., Ltd.**

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China  
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

## **TABLE OF CONTENTS**

|                                                                                           |           |
|-------------------------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                                           | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                                  | 4         |
| OBJECTIVE .....                                                                           | 4         |
| TEST METHODOLOGY .....                                                                    | 4         |
| MEASUREMENT UNCERTAINTY .....                                                             | 5         |
| TEST FACILITY .....                                                                       | 5         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                                     | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                                   | 6         |
| EUT EXERCISE SOFTWARE .....                                                               | 6         |
| SPECIAL ACCESSORIES.....                                                                  | 6         |
| EQUIPMENT MODIFICATIONS .....                                                             | 7         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                                  | 7         |
| EXTERNAL I/O CABLE.....                                                                   | 7         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                         | 7         |
| <b>FOR CONDUCTED EMISSION .....</b>                                                       | <b>7</b>  |
| <b>FOR RADIATED EMISSION BELOW 1G .....</b>                                               | <b>8</b>  |
| <b>SUMMARY OF TEST RESULTS.....</b>                                                       | <b>9</b>  |
| <b>TEST EQUIPMENT LIST .....</b>                                                          | <b>10</b> |
| <b>FCC§15.247 (I), §1.1307 (B) (1) &amp; §2.1093 – RF EXPOSURE .....</b>                  | <b>11</b> |
| APPLICABLE STANDARD .....                                                                 | 11        |
| <b>RSS-102 – RF EXPOSURE.....</b>                                                         | <b>12</b> |
| APPLICABLE STANDARD .....                                                                 | 12        |
| <b>FCC §15.203 &amp; RSS-GEN §6.8– ANTENNA REQUIREMENT .....</b>                          | <b>13</b> |
| APPLICABLE STANDARD .....                                                                 | 13        |
| ANTENNA CONNECTOR CONSTRUCTION .....                                                      | 13        |
| <b>FCC §15.207 (A) &amp; RSS-GEN §8.8 – AC LINE CONDUCTED EMISSIONS .....</b>             | <b>14</b> |
| APPLICABLE STANDARD .....                                                                 | 14        |
| EUT SETUP .....                                                                           | 15        |
| EMI TEST RECEIVER SETUP.....                                                              | 15        |
| TEST PROCEDURE .....                                                                      | 15        |
| CORRECTED FACTOR & MARGIN CALCULATION .....                                               | 16        |
| TEST DATA .....                                                                           | 16        |
| <b>FCC §15.205, §15.209 &amp; §15.247(D) &amp; RSS-247§ 5.5 – RADIATED EMISSIONS.....</b> | <b>21</b> |
| APPLICABLE STANDARD .....                                                                 | 21        |
| EUT SETUP .....                                                                           | 21        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                                         | 22        |
| TEST PROCEDURE .....                                                                      | 22        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                                            | 23        |
| TEST DATA .....                                                                           | 23        |

|                                                                                                                                  |           |
|----------------------------------------------------------------------------------------------------------------------------------|-----------|
| <b>FCC §15.247(A) (1) &amp; RSS-247 § 5.1 (B)-CHANNEL SEPARATION TEST .....</b>                                                  | <b>29</b> |
| APPLICABLE STANDARD .....                                                                                                        | 29        |
| TEST PROCEDURE .....                                                                                                             | 29        |
| TEST DATA .....                                                                                                                  | 29        |
| <b>FCC §15.247(A) (1) &amp; RSS-GEN § 6.7 &amp; RSS-247 § 5.1 (A)-99% OCCUPIED BANDWIDTH &amp; 20 DB EMISSION BANDWIDTH.....</b> | <b>31</b> |
| APPLICABLE STANDARD .....                                                                                                        | 31        |
| TEST PROCEDURE .....                                                                                                             | 31        |
| TEST DATA .....                                                                                                                  | 32        |
| <b>FCC §15.247(A) (1) (III) &amp; RSS-247 § 5.1 (D)-QUANTITY OF HOPPING CHANNEL TEST.....</b>                                    | <b>35</b> |
| APPLICABLE STANDARD .....                                                                                                        | 35        |
| TEST PROCEDURE .....                                                                                                             | 35        |
| TEST DATA .....                                                                                                                  | 35        |
| <b>FCC §15.247(A) (1) (III) &amp; RSS-247 § 5.1 (D) - TIME OF OCCUPANCY (DWELL TIME) .....</b>                                   | <b>37</b> |
| APPLICABLE STANDARD .....                                                                                                        | 37        |
| TEST PROCEDURE .....                                                                                                             | 37        |
| TEST DATA .....                                                                                                                  | 37        |
| <b>FCC §15.247(B) (1) &amp; RSS-247§ 5.1(B) &amp;§ 5.4(B) - PEAK OUTPUT POWER MEASUREMENT .....</b>                              | <b>39</b> |
| APPLICABLE STANDARD .....                                                                                                        | 39        |
| TEST PROCEDURE .....                                                                                                             | 39        |
| TEST DATA .....                                                                                                                  | 39        |
| <b>FCC §15.247(D) &amp; RSS-247 § 5.5 - BAND EDGES TESTING .....</b>                                                             | <b>42</b> |
| APPLICABLE STANDARD .....                                                                                                        | 42        |
| TEST PROCEDURE .....                                                                                                             | 42        |
| TEST DATA .....                                                                                                                  | 42        |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                                     |                                                                                                |
|-------------------------------------|------------------------------------------------------------------------------------------------|
| HVIN                                | PIP1510PU                                                                                      |
| Frequency Range                     | 2402-2477 MHz                                                                                  |
| Maximum conducted Peak output power | 13.69 dBm                                                                                      |
| Modulation Technique                | GFSK                                                                                           |
| Antenna Specification*              | 0dBi(It is provided by the applicant)                                                          |
| Voltage Range                       | DC3.8V from Battery or DC 5V From Adapter                                                      |
| Sample number                       | SZ1210926-54083E-RF-S11 (for radiated test)<br>SZ1210926-54083E-RF-S12 (for RF conducted test) |
| Sample/EUT Status                   | Good condition                                                                                 |
| Adapter 1 information               | Model: BQ12G-0501500-U<br>Input: AC 100-240V~50/60Hz Max, 400mA<br>Output: DC 5.0V, 1500mA     |
| Adapter 2 information               | Model: S012-1B050150VU<br>Input: AC 100-240V~50/60Hz, 0.3A<br>Output: DC 5.0V, 1.5A            |

### Objective

This report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules and RSS-GEN issue 5, February 2021 amendment 2 and RSS-247, Issue 2, February 2017 of the Innovation, Science and Economic Development Canada rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Measurement Uncertainty

| Parameter                          |                 | Uncertainty |
|------------------------------------|-----------------|-------------|
| Occupied Channel Bandwidth         |                 | 5%          |
| RF output power, conducted         |                 | 0.73dB      |
| Unwanted Emission, conducted       |                 | 1.6dB       |
| AC Power Lines Conducted Emissions |                 | 2.72dB      |
| Emissions,<br>Radiated             | 30MHz - 1GHz    | 4.28dB      |
|                                    | 1GHz - 18GHz    | 4.98dB      |
|                                    | 18GHz - 26.5GHz | 5.06dB      |
| Temperature                        |                 | 1 °C        |
| Humidity                           |                 | 6%          |
| Supply voltages                    |                 | 0.4%        |

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

## SYSTEM TEST CONFIGURATION

---

### Description of Test Configuration

The system was configured for testing in an engineering mode.

22 channels are provided:

| Channel | TX Frequency (MHz) | Channel | TX Frequency (MHz) |
|---------|--------------------|---------|--------------------|
| 1       | 2402               | 12      | 2445               |
| 2       | 2404               | 13      | 2450               |
| 3       | 2406               | 14      | 2455               |
| 4       | 2408               | 15      | 2460               |
| 5       | 2410               | 16      | 2465               |
| 6       | 2415               | 17      | 2467               |
| 7       | 2420               | 18      | 2469               |
| 8       | 2425               | 19      | 2471               |
| 9       | 2430               | 20      | 2473               |
| 10      | 2435               | 21      | 2475               |
| 11      | 2440               | 22      | 2477               |

EUT was tested with Channel 1, 11 and 22.

### EUT Exercise Software

“Teraterm”\* software was used to the EUT tested and power level is default\*. The software and power level was provided by the applicant.

### Special Accessories

No special accessory.

## Equipment Modifications

No modification was made to the EUT tested.

## Support Equipment List and Details


| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| /            | /           | /     | /             |

## External I/O Cable


| Cable Description                   | Length (m) | From Port | To  |
|-------------------------------------|------------|-----------|-----|
| Un-shielding Un-Detachable DC Cable | 3.0        | Adapter   | EUT |

## Block Diagram of Test Setup


For conducted emission



For radiated emission below 1G



For radiated emission above 1G



**SUMMARY OF TEST RESULTS**

| <b>FCC Rules</b>                                | <b>ISED Rules</b>                  | <b>Description of Test</b>                           | <b>Result</b> |
|-------------------------------------------------|------------------------------------|------------------------------------------------------|---------------|
| FCC§15.247 (i),<br>§1.1307 (b) (1) &<br>§2.1093 | RSS-102                            | RF Exposure                                          | Compliant     |
| §15.203                                         | RSS-Gen §6.8                       | Antenna Requirement                                  | Compliant     |
| §15.207(a)                                      | RSS-Gen §8.8                       | AC Line Conducted<br>Emissions                       | Compliant     |
| §15.205, §15.209 &<br>§15.247(d)                | RSS-247 § 5.5                      | Radiated Emissions                                   | Compliant     |
| §15.247(a)(1)                                   | RSS- Gen§6.7,<br>RSS-247 § 5.1 (a) | 99% Occupied Bandwidth &<br>20 dB Emission Bandwidth | Compliant     |
| §15.247(a)(1)                                   | RSS-247 § 5.1 (b)                  | Channel Separation Test                              | Compliant     |
| §15.247(a)(1)(iii)                              | RSS-247 § 5.1 (d)                  | Time of Occupancy (Dwell<br>Time)                    | Compliant     |
| §15.247(a)(1)(iii)                              | RSS-247 § 5.1 (d)                  | Quantity of hopping channel<br>Test                  | Compliant     |
| §15.247(b)(1)                                   | RSS-247 § 5.1(b) & § 5.4(b)        | Peak Output Power<br>Measurement                     | Compliant     |
| §15.247(d)                                      | RSS-247 § 5.5                      | Band edges                                           | Compliant     |

**TEST EQUIPMENT LIST**

| Manufacturer                                    | Description       | Model             | Serial Number | Calibration Date | Calibration Due Date |
|-------------------------------------------------|-------------------|-------------------|---------------|------------------|----------------------|
| <b>Conducted Emissions Test</b>                 |                   |                   |               |                  |                      |
| Rohde& Schwarz                                  | EMI Test Receiver | ESCI              | 100784        | 2021/02/03       | 2022/02/02           |
| R & S                                           | L.I.S.N.          | ENV216            | 101314        | 2020/12/25       | 2021/12/24           |
| Anritsu Corp                                    | 50ΩCoaxial Switch | MP59B             | 6200506474    | 2020/12/25       | 2021/12/24           |
| Unknown                                         | RF Coaxial Cable  | N-2m              | No.2          | 2020/12/25       | 2021/12/24           |
| Conducted Emission Test Software: ES-K1 V1.71   |                   |                   |               |                  |                      |
| <b>Radiated Emission Test</b>                   |                   |                   |               |                  |                      |
| Rohde& Schwarz                                  | Test Receiver     | ESR               | 101817        | 2020/12/24       | 2021/12/23           |
| Rohde&Schwarz                                   | Spectrum Analyzer | FSV40             | 101495        | 2020/12/24       | 2021/12/23           |
| SONOMA INSTRUMENT                               | Amplifier         | 310 N             | 186131        | 2020/12/25       | 2021/12/24           |
| A.H. Systems, inc.                              | Preamplifier      | PAM-0118P         | 531           | 2021/11/09       | 2022/11/08           |
| Quinstar                                        | Amplifier         | QLW-18405536-J0   | 15964001002   | 2020/11/28       | 2021/11/27           |
| Anritsu Corp                                    | 50 Coaxial Switch | MP59B             | 6100237248    | 2020/12/25       | 2021/12/24           |
| Schwarzbeck                                     | Bilog Antenna     | VULB9163          | 9163-323      | 2020/01/05       | 2023/01/04           |
| Schwarzbeck                                     | Horn Antenna      | BBHA9120D         | 9120D-1067    | 2020/01/05       | 2023/01/04           |
| Schwarzbeck                                     | HORN ANTENNA      | BBHA9170          | 9170-359      | 2020/01/05       | 2023/01/04           |
| Unknown                                         | RF Coaxial Cable  | N-5m              | No.3          | 2020/12/25       | 2021/12/24           |
| Unknown                                         | RF Coaxial Cable  | N-1m              | No.5          | 2020/12/25       | 2021/12/24           |
| Unknown                                         | RF Coaxial Cable  | N-10m             | No.7          | 2021/11/09       | 2022/11/08           |
| Unknown                                         | RF Coaxial Cable  | N-2m              | No.8          | 2021/11/09       | 2022/11/08           |
| Wainwright                                      | High Pass Filter  | WHKX3.6/18 G-10SS | 5             | 2020/12/25       | 2021/12/24           |
| Radiated Emission Test Software: e3 19821b (V9) |                   |                   |               |                  |                      |
| <b>RF Conducted Test</b>                        |                   |                   |               |                  |                      |
| Rohde & Schwarz                                 | Spectrum Analyzer | FSV-40            | 101495        | 2020/12/24       | 2021/12/23           |
| WEINSCHL                                        | 10dB Attenuator   | 5324              | AU 3842       | 2020/12/25       | 2021/12/24           |

\* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

---

## **FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE**

---

### **Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

### **Measurement Result**

Please refer to SAR test report: SZ1210926-54083E-SA.

## **RSS-102 – RF EXPOSURE**

---

### **Applicable Standard**

According to RSS-102, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

### **Measurement Result: Compliant.**

Please refer to SAR test report: SZ1210926-54083E-SA.

## FCC §15.203 & RSS-GEN §6.8– ANTENNA REQUIREMENT

### Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device. Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

### Antenna Connector Construction

The EUT has one external antenna arrangements which were permanently attached and the gain is 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

| Type     | Antenna Gain | Impedance |
|----------|--------------|-----------|
| Monopole | 0dBi         | 50 Ω      |

**Result:** Compliant.

## **FCC §15.207 (a) & RSS-GEN §8.8 – AC LINE CONDUCTED EMISSIONS**

### **Applicable Standard**

FCC §15.207(a) & RSS-Gen §8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50  $\mu$ H / 50  $\Omega$  line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.


| <b>Table 4 - AC Power Lines Conducted Emission Limits</b> |                                              |                       |
|-----------------------------------------------------------|----------------------------------------------|-----------------------|
| <b>Frequency range<br/>(MHz)</b>                          | <b>Conducted limit (dB<math>\mu</math>V)</b> |                       |
|                                                           | <b>Quasi-Peak</b>                            | <b>Average</b>        |
| 0.15 – 0.5                                                | 66 to 56 <sup>1</sup>                        | 56 to 46 <sup>1</sup> |
| 0.5 – 5                                                   | 56                                           | 46                    |
| 5 – 30                                                    | 60                                           | 50                    |

**Note 1:** The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

- Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.
- Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

## EUT Setup



**Note:** 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207 and RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

## Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


## Test Data

### Environmental Conditions

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 24 °C     |
| <b>Relative Humidity:</b> | 48 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

*The testing was performed by Bin Duan on 2021-10-01*

*EUT operation mode: Transmitting*

*For Adapter 1: BQ12G-0501500-U***AC 120V/60 Hz, Line****MEASUREMENT RESULT: "54083E-L1\_fin"**


2021-10-01 19:17

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000         | 51.70         | 10.8         | 66            | 14.3         | QP       | L1   | GND |
| 0.475000         | 37.40         | 11.0         | 56            | 18.6         | QP       | L1   | GND |
| 1.120000         | 24.30         | 11.2         | 56            | 31.7         | QP       | L1   | GND |
| 2.150000         | 22.80         | 11.3         | 56            | 33.2         | QP       | L1   | GND |
| 9.800000         | 17.90         | 11.6         | 60            | 42.1         | QP       | L1   | GND |
| 28.000000        | 19.50         | 11.8         | 60            | 40.5         | QP       | L1   | GND |

**MEASUREMENT RESULT: "54083E-L1\_fin2"**

2021-10-01 19:17

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000         | 34.50         | 10.8         | 56            | 21.5         | AV       | L1   | GND |
| 0.475000         | 31.20         | 11.0         | 46            | 14.8         | AV       | L1   | GND |
| 1.400000         | 14.40         | 11.2         | 46            | 31.6         | AV       | L1   | GND |
| 2.650000         | 10.10         | 11.3         | 46            | 35.9         | AV       | L1   | GND |
| 9.910000         | 8.80          | 11.6         | 50            | 41.2         | AV       | L1   | GND |
| 27.500000        | 8.20          | 11.8         | 50            | 41.8         | AV       | L1   | GND |

**AC 120V/60 Hz, Neutral****MEASUREMENT RESULT: "54083E-N1\_fin"**

2021-10-01 19:19

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000         | 50.20         | 10.8         | 66            | 15.8         | QP       | N    | GND |
| 0.475000         | 40.50         | 11.0         | 56            | 15.5         | QP       | N    | GND |
| 0.900000         | 24.30         | 11.1         | 56            | 31.7         | QP       | N    | GND |
| 2.340000         | 23.40         | 11.3         | 56            | 32.6         | QP       | N    | GND |
| 9.140000         | 20.20         | 11.6         | 60            | 39.8         | QP       | N    | GND |
| 24.475000        | 18.00         | 11.7         | 60            | 42.0         | QP       | N    | GND |


**MEASUREMENT RESULT: "54083E-N1\_fin2"**

2021-10-01 19:19

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.350000         | 27.00         | 10.9         | 49            | 22.0         | AV       | N    | GND |
| 0.475000         | 38.50         | 11.0         | 46            | 7.5          | AV       | N    | GND |
| 1.395000         | 20.40         | 11.2         | 46            | 25.6         | AV       | N    | GND |
| 2.370000         | 16.90         | 11.3         | 46            | 29.1         | AV       | N    | GND |
| 9.190000         | 12.90         | 11.6         | 50            | 37.1         | AV       | N    | GND |
| 23.500000        | 9.70          | 11.7         | 50            | 40.3         | AV       | N    | GND |

For Adapter 2: S012-1B050150VU

AC 120V/60 Hz, Line



#### MEASUREMENT RESULT: "54083E-L2\_fin"


2021-10-01 19:34

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000         | 50.90         | 10.8         | 66            | 15.1         | QP       | L1   | GND |
| 0.470000         | 38.60         | 11.0         | 57            | 18.4         | QP       | L1   | GND |
| 0.950000         | 22.30         | 11.1         | 56            | 33.7         | QP       | L1   | GND |
| 2.450000         | 22.20         | 11.3         | 56            | 33.8         | QP       | L1   | GND |
| 10.775000        | 16.40         | 11.6         | 60            | 43.6         | QP       | L1   | GND |
| 28.175000        | 12.40         | 11.8         | 60            | 47.6         | QP       | L1   | GND |

#### MEASUREMENT RESULT: "54083E-L2\_fin2"

2021-10-01 19:34

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000         | 31.70         | 10.8         | 56            | 24.3         | AV       | L1   | GND |
| 0.475000         | 37.20         | 11.0         | 46            | 8.8          | AV       | L1   | GND |
| 0.950000         | 16.20         | 11.1         | 46            | 29.8         | AV       | L1   | GND |
| 2.370000         | 16.20         | 11.3         | 46            | 29.8         | AV       | L1   | GND |
| 10.775000        | 10.00         | 11.6         | 50            | 40.0         | AV       | L1   | GND |
| 27.200000        | 6.30          | 11.8         | 50            | 43.7         | AV       | L1   | GND |

**AC 120V/60 Hz, Neutral****MEASUREMENT RESULT: "54083E-N2\_fin"**

2021-10-01 19:21

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.150000         | 50.70         | 10.8         | 66            | 15.3         | QP       | N    | GND |
| 0.475000         | 40.30         | 11.0         | 56            | 15.7         | QP       | N    | GND |
| 0.900000         | 24.30         | 11.1         | 56            | 31.7         | QP       | N    | GND |
| 2.340000         | 23.40         | 11.3         | 56            | 32.6         | QP       | N    | GND |
| 9.400000         | 19.80         | 11.6         | 60            | 40.2         | QP       | N    | GND |
| 24.300000        | 18.30         | 11.7         | 60            | 41.7         | QP       | N    | GND |

**MEASUREMENT RESULT: "54083E-N2\_fin2"**

2021-10-01 19:21

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.345000         | 27.80         | 10.9         | 49            | 21.2         | AV       | N    | GND |
| 0.475000         | 38.30         | 11.0         | 46            | 7.7          | AV       | N    | GND |
| 1.345000         | 20.40         | 11.2         | 46            | 25.6         | AV       | N    | GND |
| 2.340000         | 17.10         | 11.3         | 46            | 28.9         | AV       | N    | GND |
| 9.450000         | 12.90         | 11.6         | 50            | 37.1         | AV       | N    | GND |
| 23.575000        | 9.90          | 11.7         | 50            | 40.1         | AV       | N    | GND |

## FCC §15.205, §15.209 & §15.247(d) & RSS-247§ 5.5 – RADIATED EMISSIONS


### Applicable Standard


FCC §15.205; §15.209; §15.247(d) and RSS-247 §5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### EUT Setup

Below 1 GHz:



**Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limits and RSS-247/RSS-Gen limits.

**EMI Test Receiver & Spectrum Analyzer Setup**

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW     | Video B/W | IF B/W  | Measurement |
|-------------------|---------|-----------|---------|-------------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz   | 120 kHz | QP          |
| Above 1 GHz       | 1 MHz   | 3 MHz     | /       | PK          |
|                   | 1 MHz   | 10 Hz     | /       | Average     |

**Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for Over Limit/margin calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

## Test Data

### Environmental Conditions

|                           |                 |
|---------------------------|-----------------|
| <b>Temperature:</b>       | 25~26.8 °C      |
| <b>Relative Humidity:</b> | 51~54 %         |
| <b>ATM Pressure:</b>      | 101.0~101.2 kPa |


*The testing was performed by Bin Duan on 2021-10-01 for below 1GHz and Caro hu on 2021-11-18 for above 1GHz.*

*EUT operation mode: Transmitting*

*(Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded)*


**30MHz-1GHz:** (worst case for Low channel)

For Adapter 1: BQ12G-0501500-U

**Horizontal:**

Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : SZ1210926-54083E-RF  
Mode : 2.4G 2402MHz  
M/N : PU  
Adapter : BQ12G-0501500-U

|   | Freq   | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|--------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz    | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 99.97  | -19.17 | 42.57         | 23.40  | 43.50         | -20.10        | Peak   |
| 2 | 110.91 | -19.30 | 41.77         | 22.47  | 43.50         | -21.03        | Peak   |
| 3 | 186.69 | -20.57 | 45.68         | 25.11  | 43.50         | -18.39        | Peak   |
| 4 | 222.27 | -18.96 | 47.53         | 28.57  | 46.00         | -17.43        | Peak   |
| 5 | 320.08 | -16.75 | 43.21         | 26.46  | 46.00         | -19.54        | Peak   |
| 6 | 595.65 | -10.87 | 34.47         | 23.60  | 46.00         | -22.40        | Peak   |


**Vertical**

Site : chamber  
Condition: 3m VERTICAL  
Job No. : SZ1210926-54083E-RF  
Mode : 2.4G 2402MHz  
M/N : PU  
Adapter : BQ12G-0501500-U

|   | Freq   | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|--------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz    | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 36.38  | -19.23 | 47.69         | 28.46  | 40.00         | -11.54        | Peak   |
| 2 | 99.97  | -19.17 | 47.81         | 28.64  | 43.50         | -14.86        | Peak   |
| 3 | 182.24 | -21.10 | 46.55         | 25.45  | 43.50         | -18.05        | Peak   |
| 4 | 320.08 | -16.75 | 36.75         | 20.00  | 46.00         | -26.00        | Peak   |
| 5 | 480.11 | -14.42 | 37.55         | 23.13  | 46.00         | -22.87        | Peak   |
| 6 | 929.42 | -7.87  | 32.36         | 24.49  | 46.00         | -21.51        | Peak   |

## For Adapter 2: S012-1B050150VU


## Horizontal:



Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : SZ1210926-54083E-RF  
Mode : 2.4G 2402MHz  
M/N : PU  
Adapter : S012-1B050150VU

|   | Freq   | Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|--------|--------|------------|--------|------------|------------|--------|
|   | MHz    | dB/m   | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 60.92  | -19.69 | 36.37      | 16.68  | 40.00      | -23.32     | Peak   |
| 2 | 159.99 | -21.78 | 47.84      | 26.06  | 43.50      | -17.44     | Peak   |
| 3 | 199.99 | -19.06 | 43.81      | 24.75  | 43.50      | -18.75     | Peak   |
| 4 | 222.27 | -18.96 | 44.81      | 25.85  | 46.00      | -20.15     | Peak   |
| 5 | 320.08 | -16.75 | 40.45      | 23.70  | 46.00      | -22.30     | Peak   |
| 6 | 346.66 | -16.17 | 43.48      | 27.31  | 46.00      | -18.69     | Peak   |

## Vertical



Site : chamber  
Condition: 3m VERTICAL  
Job No. : SZ1210926-54083E-RF  
Mode : 2.4G 2402MHz  
M/N : PU  
Adapter : S012-1B050150VU

|   | Freq   | Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|--------|--------|------------|--------|------------|------------|--------|
|   | MHz    | dB/m   | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 37.70  | -19.02 | 45.68      | 26.66  | 40.00      | -13.34     | Peak   |
| 2 | 60.17  | -19.55 | 48.05      | 28.50  | 40.00      | -11.50     | Peak   |
| 3 | 159.99 | -21.78 | 45.54      | 23.76  | 43.50      | -19.74     | Peak   |
| 4 | 199.99 | -19.06 | 39.35      | 20.29  | 43.50      | -23.21     | Peak   |
| 5 | 320.08 | -16.75 | 37.45      | 20.70  | 46.00      | -25.30     | Peak   |
| 6 | 480.11 | -14.42 | 40.25      | 25.83  | 46.00      | -20.17     | Peak   |

**Above 1GHz: (worst case)**

| Frequency<br>(MHz)        | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBuV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2402 MHz)    |                   |            |                     |               |                |                               |                                    |                   |                |
| 2310                      | 68.59             | PK         | 71                  | 2.2           | H              | -6.84                         | 61.75                              | 74                | -12.25         |
| 2310                      | 53.95             | Ave        | 71                  | 2.2           | H              | -6.84                         | 47.11                              | 54                | -6.89          |
| 2310                      | 66.67             | PK         | 273                 | 2.1           | V              | -6.84                         | 59.83                              | 74                | -14.17         |
| 2310                      | 53.23             | Ave        | 273                 | 2.1           | V              | -6.84                         | 46.39                              | 54                | -7.61          |
| 2390                      | 67.53             | PK         | 32                  | 1.3           | H              | -6.44                         | 61.09                              | 74                | -12.91         |
| 2390                      | 53.65             | Ave        | 32                  | 1.3           | H              | -6.44                         | 47.21                              | 54                | -6.79          |
| 2390                      | 65.82             | PK         | 108                 | 1.7           | V              | -6.44                         | 59.38                              | 74                | -14.62         |
| 2390                      | 52.78             | Ave        | 108                 | 1.7           | V              | -6.44                         | 46.34                              | 54                | -7.66          |
| 4804                      | 48.88             | PK         | 263                 | 2.4           | H              | 2.81                          | 51.69                              | 74                | -22.31         |
| 4804                      | 47.80             | PK         | 263                 | 2.4           | V              | 2.81                          | 50.61                              | 74                | -23.39         |
| 7206                      | 60.28             | PK         | 332                 | 2.3           | H              | 7.46                          | 67.74                              | 74                | -6.26          |
| 7206                      | 33.44             | Ave        | 332                 | 2.3           | H              | 7.46                          | 40.9                               | 54                | -13.1          |
| 7206                      | 58.59             | PK         | 272                 | 1.8           | V              | 7.46                          | 66.05                              | 74                | -7.95          |
| 7206                      | 31.43             | Ave        | 272                 | 1.8           | V              | 7.46                          | 38.89                              | 54                | -15.11         |
| Middle Channel (2440 MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4880                      | 48.61             | PK         | 224                 | 1.5           | H              | 3.04                          | 51.65                              | 74                | -22.35         |
| 4880                      | 47.39             | PK         | 224                 | 1.5           | V              | 3.04                          | 50.43                              | 74                | -23.57         |
| 7320                      | 54.95             | PK         | 99                  | 1.3           | H              | 8.29                          | 63.24                              | 74                | -10.76         |
| 7320                      | 31.96             | Ave        | 99                  | 1.3           | H              | 8.29                          | 40.25                              | 54                | -13.75         |
| 7320                      | 54.05             | PK         | 351                 | 1.4           | V              | 8.29                          | 62.34                              | 74                | -11.66         |
| 7320                      | 30.55             | Ave        | 351                 | 1.4           | V              | 8.29                          | 38.84                              | 54                | -15.16         |
| High Channel (2477 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2483.5                    | 67.24             | PK         | 285                 | 1.7           | H              | -5.96                         | 61.28                              | 74                | -12.72         |
| 2483.5                    | 53.22             | Ave        | 285                 | 1.7           | H              | -5.96                         | 47.26                              | 54                | -6.74          |
| 2483.5                    | 65.79             | PK         | 293                 | 2.1           | V              | -5.96                         | 59.83                              | 74                | -14.17         |
| 2483.5                    | 51.93             | Ave        | 293                 | 2.1           | V              | -5.96                         | 45.97                              | 54                | -8.03          |
| 2500                      | 75.85             | PK         | 341                 | 1.1           | H              | -5.88                         | 69.97                              | 74                | -4.03          |
| 2500                      | 53.50             | Ave        | 341                 | 1.1           | H              | -5.88                         | 47.62                              | 54                | -6.38          |
| 2500                      | 74.22             | PK         | 23                  | 2.2           | V              | -5.88                         | 68.34                              | 74                | -5.66          |
| 2500                      | 52.07             | Ave        | 23                  | 2.2           | V              | -5.88                         | 46.19                              | 54                | -7.81          |
| 4954                      | 48.28             | PK         | 158                 | 1.9           | H              | 3.24                          | 51.52                              | 74                | -22.48         |
| 4954                      | 47.21             | PK         | 105                 | 1.2           | V              | 3.24                          | 50.45                              | 74                | -23.55         |
| 7431                      | 54.53             | PK         | 114                 | 2.1           | H              | 8.9                           | 63.43                              | 74                | -10.57         |
| 7431                      | 32.05             | Ave        | 114                 | 2.1           | H              | 8.9                           | 40.95                              | 54                | -13.05         |
| 7431                      | 52.58             | PK         | 227                 | 1.6           | V              | 8.9                           | 61.48                              | 74                | -12.52         |
| 7431                      | 30.44             | Ave        | 227                 | 1.6           | V              | 8.9                           | 39.34                              | 54                | -14.66         |

**Note:**



Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude – Limit

The other spurious emission is in the noise floor level was not recorded.

The test result of peak was less than the limit of average, so just peak value were recorded.


**1-18GHz****Pre-scan for Peak****Low Channel****Horizontal:****Vertical:**

18-25GHz


Pre-scan for Peak

Low Channel

Horizontal:



Vertical:



## FCC §15.247(a) (1) & RSS-247 § 5.1 (b)-CHANNEL SEPARATION TEST

### Applicable Standard

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel and in Operating mode, RBW was set at 500 kHz, VBW  $\geq$  RBW max-hold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27.7 °C   |
| Relative Humidity: | 53 %      |
| ATM Pressure:      | 101.0 kPa |

The testing was performed by Paul liu on 2021-09-29.


EUT operation mode: Transmitting

Test Result: Compliant.

| Frequency (MHz) | Channel Separation (MHz) | 20 dBc BW (MHz) | Two-thirds of the 20 dB bandwidth (MHz) | Channel Separation Limit            |
|-----------------|--------------------------|-----------------|-----------------------------------------|-------------------------------------|
| GFSK            |                          |                 |                                         |                                     |
| 2473-2475       | 1.99                     | 2.954           | 1.969                                   | > two-thirds of the 20 dB bandwidth |

Please refer to the below plots:

Hop



Date: 29.SEP.2021 19:21:23

## **FCC §15.247(a) (1) & RSS-GEN § 6.7 & RSS-247 § 5.1 (a)–99% OCCUPIED BANDWIDTH & 20 dB EMISSION BANDWIDTH**

### **Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “20 dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 20 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

### **Test Procedure**


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



## Test Data

### Environmental Conditions

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 27.7 °C   |
| <b>Relative Humidity:</b> | 53 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

The testing was performed by Paul liu on 2021-09-29.

EUT operation mode: Transmitting


Test Result: Compliant.

| Mode | Channel | Frequency (MHz) | 20 dB Emission Bandwidth (MHz) | OBW (MHz) |
|------|---------|-----------------|--------------------------------|-----------|
| GFSK | Low     | 2402            | 2.954                          | 2.866     |
|      | Middle  | 2440            | 2.467                          | 2.483     |
|      | High    | 2477            | 2.478                          | 2.750     |


Please refer to the below plots:

## 20 dB emission bandwidth &amp; 99% emission bandwidth


## Low Channel



## Middle Channel



## High Channel



Date: 29.SEP.2021 16:07:32

## FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d)-QUANTITY OF HOPPING CHANNEL TEST

### Applicable Standard

Frequency hopping systems (FHSs) in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27.7 °C   |
| Relative Humidity: | 53 %      |
| ATM Pressure:      | 101.0 kPa |


*The testing was performed by Paul liu on 2021-09-29.*

*EUT operation mode: Transmitting*

Test Result: Compliant.

| Mode | Frequency Range (MHz) | Number of Hopping Channel (CH) | Limit (CH) |
|------|-----------------------|--------------------------------|------------|
| GFSK | 2400-2483.5           | 22                             | ≥15        |

## Hop



Date: 29.SEP.2021 10:24:29

## FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d) - TIME OF OCCUPANCY (DWELL TIME)

### Applicable Standard

Frequency hopping systems (FHSs) in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### Test Procedure

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27.7 °C   |
| Relative Humidity: | 53 %      |
| ATM Pressure:      | 101.0 kPa |

The testing was performed by Paul liu on 2021-09-29.

EUT operation mode: Transmitting

Test Result: Compliant.

| Test Mode | Channel | Burst Width<br>[ms] | Total Hops<br>[Num] | Result[s] | Limit[s]   | Verdict |
|-----------|---------|---------------------|---------------------|-----------|------------|---------|
| GFSK      | Middle  | 0.162               | 130                 | 0.021     | $\leq 0.4$ | PASS    |


Note 1: A period time= $0.4 \times 22 = 8.8$ (S), Result=Burst Width\*Total hops

Note 2: Total hops=Hopping Number in 0.88s\*10


Note 3: Hopping Number in 0.88s=Total of highest signals in 0.88s (Second high signals were other channel)

Note 4: From test plots, the worst case hopping number would be 13 within 0.88s.

## Hop



Date: 29.SEP.2021 10:54:01



Date: 29.SEP.2021 10:49:23

## FCC §15.247(b) (1) & RSS-247§ 5.1(b) &§ 5.4(b) - PEAK OUTPUT POWER MEASUREMENT

### Applicable Standard


According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

For frequency hopping systems (FHSs) operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W (see Section 5.4(e) for exceptions).

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the -20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

### Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27.7 °C   |
| Relative Humidity: | 53 %      |
| ATM Pressure:      | 101.0 kPa |


*The testing was performed by Paul liu on 2021-09-29.*

*EUT operation mode: Transmitting*


Test Result: Compliant.

| Mode | Channel | Frequency<br>(MHz) | Peak Output Power | Limit<br>(dBm) |
|------|---------|--------------------|-------------------|----------------|
|      |         |                    | (dBm)             |                |
| GFSK | Low     | 2402               | 12.90             | 21             |
|      | Middle  | 2440               | 13.28             | 21             |
|      | High    | 2477               | 13.69             | 21             |

## Low Channel




## Middle Channel



Date: 29.SEP.2021 16:16:35

## High Channel



Date: 29.SEP.2021 16:17:36

## **FCC §15.247(d) & RSS-247 § 5.5 - BAND EDGES TESTING**

### **Applicable Standard**

According to FCC §15.247(d) & RSS-247 § 5.5.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)) & RSS-Gen.

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### **Test Data**


#### **Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 27.7 °C   |
| <b>Relative Humidity:</b> | 53 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |


*The testing was performed by Paul liu on 2021-09-29.*

*EUT operation mode: Transmitting*

Test Result: Compliant.


**Conducted Band Edge Result:****GFSK\_Low Channel**

Date: 29.SEP.2021 10:07:13

**GFSK\_High Channel**


Date: 29.SEP.2021 19:16:11

## GFSK\_Hop\_Low Channel



Date: 29.SEP.2021 10:18:42

## GFSK\_Hop\_High Channel



Date: 29.SEP.2021 10:17:30

\*\*\*\*\* END OF REPORT \*\*\*\*\*