

# Shenzhen Sinexcel Electric Co., Ltd

# **TEST REPORT**

SCOPE OF WORK EMC TESTING–See page 2

**REPORT NUMBER** 230927017GZU-001

**ISSUE DATE** 

[REVISED DATE]

09-January-2024 [------]

PAGES 31

**DOCUMENT CONTROL NUMBER** FCC Part 15.225-f © 2017 INTERTEK





Room101/301/401/102/202/302/ 402/502/602/702/802, No. 7-2, Caipin Road, Huangpu District, Guangzhou, Guangdong, China Telephone: +86 20 8213 9688 Facsimile: +86 20 3205 7538 www.intertek.com.cn

Applicant Name &	:	Shenzhen Sinexcel Electric Co., Ltd
Address		Building 6, BaiWangXin High-tech Industrial Park, NANSHAN DISTRICT
		Shenzhen, China
Manufacturing Site	:	Huizhou Sinexcel Electric Co., Ltd
		No.31, Huifeng West 2nd Road, Zhongkai Hi-tech District, HUIZHOU
		CITY, Guangdong, China
Intertek Report No:		230927017GZU-001
FCC ID:		2BDNM-SINEXCEL-Y

## Test standards

#### 47 CFR PART 15 Subpart C: 2021 section 15.225

### Sample Description

Product	:	Izar EV AC Charger
Model No.	:	SEA240/48I-U-HY, SEA240/40I-U-6Y, SEA240/40I-U-14Y
Electrical Rating	:	See page 4
Serial No.	:	Not Labeled
Date Received	:	27 September 2023
Date Test	:	27 September 2023-09 January 2024
Conducted		

Prepared and Checked By

Richard Liu

Richard Liu Engineer Approved By:

en, Lm

Dean Liu Project Engineer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

 Room101/301/401/102/202/302/402/502/602/702/802, No. 7-2, Caipin Road, Huangpu District, Guangzhou, Guangdong, China

 Version: 14 December 2022
 Page 2 of 30
 FCC Part 15.225-f



## **TEST REPORT**

## CONTENT

TEST RE	PORT1
CONTI	ENT3
1.0	TEST RESULT SUMMARY
2.0	GENERAL DESCRIPTION
2.1 2.2 2.3 2.4	PRODUCT DESCRIPTION
3.0	SYSTEM TEST CONFIGURATION
3.1 3.2 3.3 3.4 3.5 3.6	JUSTIFICATION6EUT EXERCISING SOFTWARE.7SPECIAL ACCESSORIES.7MEASUREMENT UNCERTAINTY.7EQUIPMENT MODIFICATION8SUPPORT EQUIPMENT LIST AND DESCRIPTION8
4.0	MEASUREMENT RESULTS9
4.1 4.2 4.3 4.4 4.5	ANTENNA REQUIREMENT
5.0	TEST EQUIPMENT LIST



## 1.0 TEST RESULT SUMMARY

Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC PART 15 C Section 15.203	FCC PART 15 C Section 15.203	PASS
Occupied Bandwidth	FCC PART 15 C section 15.215(c)	ANSI C63.10: Clause 6.9	PASS
Radiated Emission	FCC PART 15 C section 15.225 (a), (b), (c), (d)	ANSI C63.10: Clause 6.4 & 6.5	PASS
Frequency Stability	FCC PART 15 C section 15.225 (e)	ANSI C63.10: Clause 6.8	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	PASS

#### **Remark:**

N/A: not applicable. Refer to the relative section for the details.

EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radio Frequency.

ANSI C63.10: the detail version is ANSI C63.10:2013 in the whole report

All models of housing and motherboard are the same, different models due to different currents and input power cable's plug.

All models use the same wireless modules

Electrical Rating:240V/60Hz

Model No.	Current	Plug type	NFC module	WIFI/Bluetooth module	4G module
SEA240/48I-U-HY	48A		with	with	with
SEA240/40I-U-6Y	40A	6-50P plug	with	with	with
SEA240/40I-U14Y	40A	14-50P plug	with	with	with

After Pre-scanning all models , the worst test data for the model SEA240/48I-U-HY was recorded in the report.



## 2.0 General Description

## 2.1 Product Description

Operating Frequency	13.56 MHz
Type of Modulation:	ASK
Number of Channels	1 Channel
Channel Separation:	N/A
Antenna Type	Integral loop antenna
Power Supply:	240V/60Hz
Power cord:	N/A

### 2.2 Related Submittal(s) Grants

This is an application for certification of: DXX(Part 15 Low Power Communication Device Transmitter).

Remaining portions are subject to the following procedures: 1. Receiver portion: exempt from technical requirement of this Part.

#### 2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans and final tests were performed in the semi-anechoic chamber to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise.

#### 2.4 Test Facility

All tests were performed at: Intertek Testing Services Shenzhen Ltd. Guangzhou Branch Room102/104, No 203, KeZhu Road, Science City, GETDD Guangzhou, China Except Conducted Emissions was performed at: Room101/301/401/102/202/302/402/502/602/702/802, No. 7-2, Caipin Road, Huangpu District, Guangzhou, Guangdong, China



## **TEST REPORT**

#### A2LA Certificate Number 0078.10

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch is accredited by A2LA and Listed in FCC website. FCC accredited test labs may perform both Certification testing under Parts 15 and 18 and Declaration of Conformity testing.

### **3.0** System Test Configuration

#### 3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, AC power line was manipulated to produce worst case emissions. It was powered by AC 240V/60Hz supply.

When below 30MHz, the measurement antenna was positioned with its plane perpendicular to the ground at the specified distance. When perpendicular to the ground plane, the lowest height of the magnetic antenna was 1 m above the ground and was positioned at 3m distance from the EUT. During testing the loop antenna was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. For each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable.

When above 30MHz, the antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. The spurious emissions more than 20 dB below the permissible value are not reported.

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to
9 KHZ to below 10 GHZ	40 GHz, whichever is lower
At or above 10 GHz to below	5th harmonic of highest fundamental frequency or to
30 GHz	100 GHz, whichever is lower
	5th harmonic of highest fundamental frequency or to
At or above 30 GHz	200 GHz, whichever is lower, unless otherwise
	specified

Frequency range of radiated emission measurements



#### Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device	Number of	Location in frequency
operates	frequencies	range of operation
1 MHz or less	1	Middle
	2	1 near top and 1 near
	Z	bottom
		1 near top, 1 near
More than 10 MHz	3	middle and 1 near
		bottom

### 3.2 EUT Exercising Software

## The NFC starts automatically.

### **3.3** Special Accessories

No special accessories used.

#### 3.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	20 dB Bandwidth	2.3%
2	Carrier Frequencies Separated	2.3%
		4.24 dB (9KHz-30MHz)
3 Radiate	Padiated Emissions	4.7 dB (25 MHz-1 GHz)
		4.8 dB (1 GHz-18 GHz)
		5.21dB (18GZH-26GHz)
4	Conducted Emissions at Mains Terminals	2.58dB
5	Temperature	0.5 °C
6	Humidity	0.4 %
7	Time	1.2%

The measurement uncertainty describes the overall uncertainty of the given measured value during the operation of the EUT.

Measurement uncertainty is calculated in accordance with ETSI TR 100 028-2001. The measurement uncertainty is given with a confidence of 95%, k=2.

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.



## **TEST REPORT**

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value

#### 3.5 Equipment Modification

Any modifications installed previous to testing by Shenzhen Sinexcel Electric Co., Ltd will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

#### **3.6** Support Equipment List and Description

This product was tested with corresponding support equipment as below:

Cable				
Description	Model No.	Connector type	Cable length/type	Supplied by
Antenna cable	RF-01	SMA	0.2 m(shielded)	Intertek

Description	Model No.	Rating	Supplied by
Resistor cabinet	STK-20KW	20KW max.	Intertek



## **TEST REPORT**

## 4.0 Measurement Results

#### 4.1 Antenna Requirement

Standard requirement:

15.203 requirement:

For intentional device. According to 15.203 an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

EUT Antenna

The antenna is an integral loop antenna and no consideration of replacement.



Antenna dimension design





### 4.2 Occupied Bandwidth

Test Requirement:	FCC PART 15 C section 15.215(c)
	(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated
Test Method:	ANSI C63.10: Clause 6.9
Test Status:	Pre-Scan has been conducted to determine the worst-case mode.

Test Configuration:



#### Test Procedure:

The transmitter was operated at its maximum carrier power measured under normal test conditions.

- a) The instrument center frequency was set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer was between 1.5 times and 5.0 times the OBW(20 dB Bandwidth).
- b) The nominal IF filter bandwidth (3 dB RBW) was in the range of 1% to 5% of the OBW, and VBW was approximately three times the RBW.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope was more than [10 log (OBW/RBW)] below the reference level.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) The dynamic range of the instrument at the selected RBW was more than 10 dB below the target "-20 dB down" requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW was at least 30 dB below the reference value.



## **TEST REPORT**

- f) Peak detection and max hold mode (until the trace stabilizes) was used.
- g) Used the 20dB bandwidth function of the instrument and reported the measured bandwidth.
- h) The occupied bandwidth was reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division was clearly labeled. Tabular data was reported in addition to the plot(s).

#### **Used Test Equipment List**

Spectrum Analyzer. Refer to Clause 5 Test Equipment List for details.

20 dB bandwidth:

Frequency (MHz)	20 dB bandwidth (kHz)	lower frequency (MHz)	upper frequency (MHz)	Assigned Band (MHz)	Result
13.56	1.23	13.5601	13.5613	13.110-14.010	Pass

Result plot as follows:

Spectrum											
Ref Level ·	-25.00 di	Bm	👄 RB	<b>W</b> 500 Hz							
Att	0	dB <b>SWT</b> 3.8	ms 👄 VB	W 1 kHz	Mo	ode Auto	) FFT				
⊖1Pk Max											
-30 dBm						M	1[1]			-	45.40 dBm
							10			13.56	07240 MHz
-40 dBm					<u></u>	n	ав 			1 2200	20.00 dB
					X.	0	factor			1.2300	11024 1
-50 dBm					Ή	<u>ب</u>	Taccor				11024.1
					$ \rangle$						
-60 dBm				<u>τ</u>	+	2					
				y y	1						
-70 dBm											
-80 dBm											
00 40-0						1					
-90 dBm											
-100 dBm			$\frown$				$\wedge$				
	$\frown$					$\sim$	$1 \lor$	~	$  \land  $		$\wedge \wedge$
-110 dBm			$\sim$					~	$\sim \sim$	$\sim$ $\sim$	$\sim$
-120 dBm-					_						
05 10 5607	04 MU-			60	L mtr	_					
Markor	OF 13.000724 MIR2         O91 pts         Span 25.0 KHZ										
Tuno	Trol	V-ualuo	1	Y_ualuo	_	Euro	tion		Eupe	tion Bocult	
M1	1	13.56072	4 MHz	-45.40 d	Bm	ndB	down		i uni	aon result	1.23 kHz
T1	1	13.56010	9 MHz	-65.19 d	Bm		ndB				20.00 dB
T2	1	13.56133	9 MHz	-64.94 d	Bm	Q	factor				11024

Test result: The unit does meet the FCC requirements.



## **TEST REPORT**

## 4.3 Radiated Emission

Test Requirement:	FCC PART 15 C section	15.225 (a), (b), (c), (d)			
The field strength of emissions from intentional radiators operated under this Section shall not exceed the following: 15.225(a): The field strength of any emissions within the bar 13.553-13.567 MHz shall not exceed 15,848 microvolts/mete 30 meters.i.e. 124.0dBµV/m @ 3 m. 15.225(b): Within the bands 13.410-13.553 MHz and 13.567 13.710 MHz, the field strength of any emissions shall not exc 334 microvolts/meter at 30 meters. i.e. 90.5dBµV/m @ 3 m. 15.225(c): Within the bands 13.110-13.410 MHz and 13.710 14.010 MHz the field strength of any emissions shall not exc 106 microvolts/meter at 30 meters. i.e. 80.5dBµV/m @ 3 m. 15.225(d) :The field strength of any emissions appearing out of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209. Convert the units of microvolts/meter to dBµV/m:					
	20*log Value(microvolts/meter)= Value (dBμV/m)				
	convert the field strength limits at 30m and 300m to 3m: Value (dBµV/m)@30m+40= Value (dBµV/m)@3m				
	Value (dBµV/m)@300m+80= Value (dBµV/m)@3m				
	§ 15.209 Limit:				
	Frequency (MHz)	Field Strength (dBµV/m @ 3m)			
	1.705-30.0	69.5			
	30-88	40			
	88-216	43.5			
	216-960	46			
	Above 960	54			
Test Method:	ANSI C63.10: Clause 6	.4 and 6.5.			
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible configuration.				
l'est site:					
Detector:	Quasi-Peak detector: RBW=200 Hz for 9 kHz to 150 kHz RBW=9 kHz for 150 kHz to 30 MHz RBW=120 kHz for 30 MHz to 1GHz Sweep = auto Trace = max hold				
Field Strength Calculation:	The field strength is ca	lculated by adding the reading on the			



TEST REPORT	
Where:	Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below: FS = RA + AF + CF - AG + PD + AV FS = RA + Correct Factor + AV FS = Field Strength in dBµV/m RA = Receiver Amplitude (including preamplifier) in dBµV AF = Antenna Factor in dB
	CF = Cable Attenuation Factor in dB
	AG = Amplifier Gain in dB
	PD = Pulse Desensitization in dB
	AV = Average Factor in -dB
	Correct Factor = AF + CF – AG + PD
	In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows: FS = RA + AF + CF - AG + PD + AV Assume a receiver reading of 62.0 dBµV is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was - 10 dB. The net field strength for comparison to the appropriate emission limit is 32 dBµV/m. RA = 62.0 dBµV AF = 7.4 dB CF = 1.6 dB AG = 29.0 dB PD = 0 dB AV = -10 dB Correct Factor = 7.4 + 1.6 - 29.0 + 0 = -20 dB
	FS = 62 + (-20) + (-10) = 32 dBµV/m

Version: 14 December 2022



## **TEST REPORT**

MHz	MHz	MHz	GHz
$\begin{array}{c} 0.090 - 0.110 \\ {}^{1}0.495 - 0.505 \\ 2.1735 - 2.1905 \\ 4.125 - 4.128 \\ 4.17725 - 4.17775 \\ 4.20725 - 4.20775 \\ 6.215 - 6.218 \\ 6.26775 - 6.26825 \\ 6.31175 - 6.31225 \\ 8.291 - 8.294 \\ 8.362 - 8.366 \\ 8.37625 - 8.38675 \\ 8.41425 - 8.41475 \\ 12.29 - 12.293 \\ 12.51975 - 12.52025 \\ 12.57675 - 12.57725 \\ 13.36 - 13.41 \end{array}$	$\begin{array}{c} 16.42 - 16.423 \\ 16.69475 - 16.69525 \\ 16.80425 - 16.80475 \\ 25.5 - 25.67 \\ 37.5 - 38.25 \\ 73 - 74.6 \\ 74.8 - 75.2 \\ 108 - 121.94 \\ 123 - 138 \\ 149.9 - 150.05 \\ 156.52475 - \\ 156.52525 \\ 156.7 - 156.9 \\ 162.0125 - 167.17 \\ 167.72 - 173.2 \\ 240 - 285 \\ 322 - 335.4 \end{array}$	399.9 - 410 608 - 614 960 - 1240 1300 - 1427 1435 - 1626.5 1645.5 - 1646.5 1660 - 1710 1718.8 - 1722.2 2200 - 2300 2310 - 2390 2483.5 - 2500 2655 - 2900 3260 - 3267 3332 - 3339 3345.8 - 3358 3600 - 4400	$\begin{array}{r} 4.5 - 5.15 \\ 5.35 - 5.46 \\ 7.25 - 7.75 \\ 8.025 - 8.5 \\ 9.0 - 9.2 \\ 9.3 - 9.5 \\ 10.6 - 12.7 \\ 13.25 - 13.4 \\ 14.47 - 14.5 \\ 15.35 - 16.2 \\ 17.7 - 21.4 \\ 22.01 - 23.12 \\ 23.6 - 24.0 \\ 31.2 - 31.8 \\ 36.43 - 36.5 \end{array}$

Section 15.205 Restricted bands of operation.

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in 15.209.

Test Configuration:

1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:





#### **Test Procedure:**

1) 9 kHz to 30 MHz emissions:

For testing performed with the loop antenna. the lowest height of the magnetic antenna shall be 1 m above the ground and shall be positioned at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.



## **TEST REPORT**

### 2) 30 MHz to 1 GHz emissions:

For testing performed with the TRILOG Super Broadband test Antenna. The measurement is performed with the EUT rotated 360<sup>o</sup>, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

3)The receiver was scanned from 9 kHz to 25 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

#### **Used Test Equipment List:**

3m Semi-Anechoic Chamber, EMI Test Receiver (9 kHz~7 GHz), Signal and Spectrum Analyzer (10 Hz~40 GHz), Loop antenna (9 kHz-30 MHz). TRILOG Super Broadband test Antenna(30 MHz-3 GHz) (RX), Bouble-Ridged Waveguide Horn Antenna (800 MHz-18 GHz)(RX) and High Frequency Antenna & preamplifier(18 GHz~26.5 GHz) (RX). Refer to Clause 5 Test Equipment List for details.

#### Radiated Emissions (Below 30 MHz)

Operation Mode: Continuously transmitting

#### Horizontal



All emission levels are more than 6 dB below the limit.



## **TEST REPORT**

Vertical



All emission levels are more than 6 dB below the limit.



Horizontal

Frequency (MHz)	Receiver Reading Level (dBμV)	Correction factors (dB/m)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)
13.56	19.8	21.0	40.8	124.0	83.2



Vertical



Frequency (MHz)	Receiver Reading Level (dBµV)	Correction factors (dB/m)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dBµV/m)
13.56	20.8	21.0	41.8	124.0	82.2

The emission limits shown above are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

Remark:

- 1. Corr. (dB) = Antenna Factor (dB) + Cable Loss (dB)
- 2. Level (dB $\mu$ V/m) = Corr. (dB) + Read Level (dB $\mu$ V)
- 3. Margin (dB) = Limit (dB $\mu$ V/m) –Level (dB $\mu$ V/m)
- 4. Only record the date closed to limit
- 5. The emission is worst case on Veritcal

6. When Peak emission level was below AV or QP limit, the AV and QP emission level was not recorded.



## **TEST REPORT**

## Radiated Emissions (Above 30MHz)

Operation Mode: Continuously transmitting Horizontal



All emission levels are more than 6 dB below the limit.

Vertical



All emission levels are more than 6 dB below the limit.



## **TEST REPORT**

Test in NFC, WIFI, Bluetooth, LTE continuous transmission status
9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement
The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.
30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement
Horizontal



All emission levels are more than 6 dB below the limit.

100 80 Level in dBuV/m 60 FCC 15 40 20 0 100M 200 300 30M 50 60 80 400 500 800 1G Frequency in Hz

Vertical



All emission levels are more than 6 dB below the limit.

### 1GHz-13GHz Radiated Emissions

#### **PK Measurement:**

Frequency	PK Reading Level	Correction factors	PK Emission Level	PK Limit	Antenna polarization
(MHz)	(dBuV)	(dB)	(dBµV/m)	(dBµV/m)	
3167.5	58.2	-5.3	52.9	74	V
6337.0	46.3	1.2	47.5	74	V
3167.5	50.1	-5.3	44.8	74	Н
10015.0	41.7	6.6	48.3	74	Н

#### **AV Measurement:**

Frequency	PK Reading Level	Correction factors	PK Emission Level	PK Limit	Antenna polarization
(MHz)	(dBuV)	(dB)	(dBµV/m)	(dBµV/m)	
3167.5	-	-5.3	-	54	V
6337.0	-	1.2	-	54	V
3167.5	-	-5.3	-	54	Н
10015.0	-	6.6	-	54	Н

Remark: When Peak emission level was below AV limit, the AV emission level did not be recorded.

## 4.4 Frequency Stability

Test Requirement:	FCC Part 15 C section 15.225 (e)				
	(e) The frequency tolerance of the carrier signal shall be maintained within ±0.01% of the operating frequency over a temperature variation of -20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.				
Test Method:	ANSI C63.10: Clause 6.8				
Test Procedure:	<ol> <li>Supply the EUT with a new battery. Turn the EUT OFF and place it inside the environmental temperature chamber.</li> <li>Set the temperature control on the chamber to +50 degrees C and allow the oscillator heater and the chamber temperature to stabilize.</li> <li>While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.</li> <li>Switch OFF the EUT. Lower the chamber temperature by not</li> </ol>				



## **TEST REPORT**

more that 10 °C, and allow the temperature inside the chamber to stabilize. Repeat step 3) through step 4) down to the lowest specified temperature.

(5) At a temperature of 20°C, record the frequency at 85% and 115% of the nominal supply voltage.

#### Used Test Equipment List:

Signal and Spectrum Analyzer, Programmable Temperature & Humidity Test Chamber, Regulated DC Power supply. Refer to Clause 5 Test Equipment List for details.

The frequency is 13.561MHz, under unnormal conditions, it's should be within ±0.01%: 13.558644 - 13.561356MHz

#### Temperature: 50°C:

time	Measured Frequency (MHz)	Result
0 minutes	13.559234	Pass
2 minutes	13.559235	Pass
5 minutes	13.559233	Pass
10 minutes	13.559234	Pass

#### Temperature: 40°C:

time	Measured Frequency	Result
	(MHz)	
0 minutes	13.559236	Pass
2 minutes	13.559235	Pass
5 minutes	13.559237	Pass
10 minutes	13.559236	Pass

#### Temperature: 30°C:

time	Measured Frequency	Result
	(MHz)	
0 minutes	13.559236	Pass
2 minutes	13.559236	Pass
5 minutes	13.559236	Pass
10 minutes	13.559236	Pass

#### Temperature: 20°C:

time	Measured Frequency (MHz)	Result
0 minutes	13.559236	Pass
2 minutes	13.559237	Pass
5 minutes	13.559237	Pass
10 minutes	13.559236	Pass



## Temperature: 10°C:

time	Measured Frequency	Result
	(MHz)	
0 minutes	13.559235	Pass
2 minutes	13.559236	Pass
5 minutes	13.559237	Pass
10 minutes	13.559236	Pass

### Temperature: 0°C:

time	Measured Frequency (MHz)	Result
0 minutes	13.559236	Pass
2 minutes	13.559235	Pass
5 minutes	13.559237	Pass
10 minutes	13.559235	Pass

## Temperature: -10°C:

time	Measured Frequency (MHz)	Result
0 minutes	13.559236	Pass
2 minutes	13.559236	Pass
5 minutes	13.559236	Pass
10 minutes	13.559236	Pass

#### Temperature: -20°C:

time	Measured Frequency (MHz)	Result
0 minutes	13.559235	Pass
2 minutes	13.559236	Pass
5 minutes	13.559235	Pass
10 minutes	13.559236	Pass

## Temperature: 20°C:

Power Supply (V AC)	Measured Frequency (MHz)	Result
85%	13.559235	Pass
95%	13.559235	Pass



## **TEST REPORT**

105%	13.559235	Pass
115%	13.559236	Pass

## 4.5 Conducted Emission Test

Test Configuration:





## **TEST REPORT**

#### Test Setup and Procedure:

Test was performed according to ANSI C63.10 Clause 6.2. The EUT was set to achieve the maximum emission level. The mains terminal disturbance voltage was measured with the EUT in a shielded room. The EUT was connected to AC power source through an Artificial Mains Network which provides a  $50\Omega$  linear impedance Artificial hand is used if appropriate (for handheld apparatus). The load/control terminal disturbance voltage was measured with passive voltage probe if appropriate.

The table-top EUT was placed on a 0.8m high non-metallic table above earthed ground plane (Ground Reference Plane). And for floor standing EUT, was placed on a 12 mm high non-metallic supported on GRP. The EUT keeps a distance of at least 0.8m from any other of the metallic surface. The Artificial Mains Network is situated at a distance of 0.8m from the EUT.

During the test, mains lead of EUT excess 0.8m was folded back and forth parallel to the lead so as to form a horizontal bundle with a length between 0.3m and 0.4m

The bandwidth of test receiver was set at 9 kHz. The frequency range from 150 kHz to 30MHz was checked.

#### Test Data and Curve

At main terminal: Pass(perform the AC power-line conducted tests with the antenna connected) Tested Wire: Live Operation Mode: transmitting mode



# Final\_Result



Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Corr. (dB)
()	(	(	(	()	(ms)	(		()
0.238000		44.27	52.17	7.90	1000.0	9.000	L1	10.4
0.242000	52.22		62.03	9.81	1000.0	9.000	L1	10.4
0.278000		39.61	50.88	11.27	1000.0	9.000	L1	10.4
0.398000	46.52		57.90	11.38	1000.0	9.000	L1	10.4
0.442000	41.23		57.02	15.80	1000.0	9.000	L1	10.4
0.446000		32.93	46.95	14.02	1000.0	9.000	L1	10.4
0.750000	34.10		56.00	21.90	1000.0	9.000	L1	10.4
0.762000		26.84	46.00	19.16	1000.0	9.000	L1	10.4
1.922000		27.60	46.00	18.40	1000.0	9.000	L1	10.4
3.570000	41.88		56.00	14.12	1000.0	9.000	L1	10.5
3.570000		38.45	46.00	7.55	1000.0	9.000	L1	10.5
3.774000		39.92	46.00	6.08	1000.0	9.000	L1	10.5
3.774000	44.93		56.00	11.08	1000.0	9.000	L1	10.5
8.958000		34.86	50.00	15.14	1000.0	9.000	L1	10.6
9.258000	35.53		60.00	24.47	1000.0	9.000	L1	10.6
13.562000		77.41	50.00	-27.41	1000.0	9.000	L1	10.6
13.562000	77.49		60.00	-17.49	1000.0	9.000	L1	10.6

Remark:

- 1. Corr. (dB) = LISN Factor (dB) + Cable Loss (dB)
- 2. Level (dB $\mu$ V) = Corr. (dB) + Read Level (dB $\mu$ V)
- 3. Delta Limit (dB) = Level (dB $\mu$ V)-Limit (dB $\mu$ V)



#### Tested Wire: Neutral

Operation Mode: transmitting mode

## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.238000		46.84	52.17	5.32	1000.0	9.000	N	10.4



## **TEST REPORT**

0.238000	55.05		62.17	7.11	1000.0	9.000	Ν	10.4
0.374000	50.40		58.41	8.01	1000.0	9.000	Ν	10.4
0.374000		39.46	48.41	8.95	1000.0	9.000	Ν	10.4
0.462000	40.62		56.66	16.03	1000.0	9.000	Ν	10.4
0.706000		36.04	46.00	9.96	1000.0	9.000	Ν	10.4
0.738000	36.73		56.00	19.27	1000.0	9.000	Ν	10.4
1.178000		31.49	46.00	14.51	1000.0	9.000	Ν	10.4
1.650000		29.05	46.00	16.95	1000.0	9.000	Ν	10.4
3.570000	38.20		56.00	17.80	1000.0	9.000	Ν	10.5
3.574000		31.82	46.00	14.18	1000.0	9.000	Ν	10.5
3.774000		37.56	46.00	8.44	1000.0	9.000	Ν	10.5
3.778000	39.50		56.00	16.50	1000.0	9.000	Ν	10.5
7.074000	42.03		60.00	17.97	1000.0	9.000	Ν	10.6
7.074000		41.49	50.00	8.51	1000.0	9.000	Ν	10.6
13.562000		76.84	50.00	-26.84	1000.0	9.000	Ν	10.6
13.562000	77.13		60.00	-17.13	1000.0	9.000	Ν	10.6

Remark:

1. Corr. (dB) = LISN Factor (dB) + Cable Loss (dB)

2. Level (dBµV) = Corr. (dB) + Read Level (dBµV)

3. Delta Limit (dB) = Level (dBµV)-Limit (dBµV)Test Data and Curve

At main terminal: Pass(retest with a dummy load in lieu of the antenna)



Operation Mode: transmitting mode



# Final\_Result

Version: 14 December 2022



Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Corr. (dB)
					(ms)			
0.234000	51.86		62.31	10.45	1000.0	9.000	L1	10.4
0.242000		42.89	52.03	9.14	1000.0	9.000	L1	10.4
0.258000	48.41		61.50	13.09	1000.0	9.000	L1	10.4
0.274000		39.88	51.00	11.12	1000.0	9.000	L1	10.4
0.434000	42.91		57.18	14.27	1000.0	9.000	L1	10.4
0.434000		33.97	47.18	13.21	1000.0	9.000	L1	10.4
0.738000		25.54	46.00	20.46	1000.0	9.000	L1	10.4
0.746000	33.83		56.00	22.17	1000.0	9.000	L1	10.4
1.922000		27.30	46.00	18.70	1000.0	9.000	L1	10.4
3.570000		38.35	46.00	7.65	1000.0	9.000	L1	10.5
3.574000	38.50		56.00	17.50	1000.0	9.000	L1	10.5
3.770000	46.45		56.00	9.55	1000.0	9.000	L1	10.5
3.770000		41.50	46.00	4.50	1000.0	9.000	L1	10.5
8.950000		32.26	50.00	17.74	1000.0	9.000	L1	10.6
8.950000	38.55		60.00	21.45	1000.0	9.000	L1	10.6

Remark:

1. Corr. (dB) = LISN Factor (dB) + Cable Loss (dB)

2. Level (dBµV) = Corr. (dB) + Read Level (dBµV)

3. Delta Limit (dB) = Level (dB $\mu$ V)-Limit (dB $\mu$ V)

## Tested Wire: Neutral

Operation Mode: transmitting mode





## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Corr. (dB)
					(ms)			
0.250000		45.75	51.76	6.01	1000.0	9.000	Ν	10.4
0.254000	53.06		61.63	8.57	1000.0	9.000	Ν	10.4
0.390000	49.33		58.06	8.74	1000.0	9.000	Ν	10.4
0.390000		39.21	48.06	8.86	1000.0	9.000	Ν	10.4
0.434000	43.03		57.18	14.14	1000.0	9.000	Ν	10.4
0.706000		36.34	46.00	9.66	1000.0	9.000	Ν	10.4
0.762000	36.68		56.00	19.32	1000.0	9.000	Ν	10.4
1.178000		31.61	46.00	14.39	1000.0	9.000	Ν	10.4
1.650000		28.63	46.00	17.37	1000.0	9.000	Ν	10.4
3.570000		34.33	46.00	11.67	1000.0	9.000	Ν	10.5
3.570000	38.73		56.00	17.27	1000.0	9.000	Ν	10.5
3.770000		37.60	46.00	8.40	1000.0	9.000	Ν	10.5
3.770000	42.14		56.00	13.86	1000.0	9.000	Ν	10.5
7.070000		38.65	50.00	11.35	1000.0	9.000	Ν	10.6
7.070000	42.58		60.00	17.42	1000.0	9.000	Ν	10.6

Remark:

- 1. Corr. (dB) = LISN Factor (dB) + Cable Loss (dB)
- 2. Level (dB $\mu$ V) = Corr. (dB) + Read Level (dB $\mu$ V)
- 3. Delta Limit (dB) = Level (dBµV)-Limit (dBµV)



## **TEST REPORT**

## 5.0 Test Equipment List

#### **Radiated Emission/Radio**

Equipment No.	Equipment	Model	Manufaatuman	Cal. Due date	Calibration
Equipment No.	Equipment	Model	Manufacturer	(YYYY-MM-DD)	Interval
EM030-04	3m Semi-Anechoic Chamber	9×6×6 m <sup>3</sup>	ETS•LINDGRE N	2024-04-10	1Y
EM031-02	EMI Test Receiver (9 kHz~7 GHz)	R&S ESR7	R&S	2024-11-15	1Y
EM031-03	Signal and Spectrum Analyzer (10 Hz~40 GHz)	R&S FSV40	R&S	2024-11-12	1Y
EM011-04	Loop antenna (9 kHz-30 MHz)	HFH2-Z2	R&S	2024-07-02	1Y
EM033-01	TRILOG Super Broadband test Antenna(30 MHz-3 GHz) (RX)	VULB 9163	SCHWARZBECK	2024-12-05	1Y
EM033-02	Bouble-Ridged Waveguide Horn Antenna (800 MHz-18 GHz)(RX)	R&S HF907	R&S	2024-07-02	1Y
EM033-03	High Frequency Antenna & preamplifier(18 GHz~26.5 GHz) (RX)	R&S SCU-26	R&S	2024-04-22	1 <b>Y</b>
EM033-04	High Frequency Antenna & preamplifier (26 GHz-40 GHz)	R&S SCU-40	R&S	2024-04-22	1 <b>Y</b>
EM031-02-01	Coaxial cable(9 kHz-1 GHz)	N/A	R&S	2024-04-10	1Y
EM033-02-02	Coaxial cable(1 GHz-18 GHz)	N/A	R&S	2024-04-10	1Y
EM033-04-02	Coaxial cable(18 GHz~40 GHz)	N/A	R&S	2024-04-22	1Y
EM031-01	Signal Generator (9 kHz~6 GHz)	SMB100A	R&S	2024-07-19	1Y
EM040-01	Band Reject/Notch Filter	WRHFV	Wainwright	N/A	1Y
EM040-02	Band Reject/Notch Filter	WRCGV	Wainwright	N/A	1Y
EM040-03	Band Reject/Notch Filter	WRCGV	Wainwright	N/A	1Y
EM022-03	2.45 GHz Filter	BRM50702	Micro-Tronics	2024-05-09	1Y
SA016-29	Climatic Test Chamber	MHU-80L	JIANQIAO	2025-01-03	1Y
EM046-05	Power meter	NPR6A	R&S	2024-04-19	1Y
EM046-06	Power meter	NPR6A	R&S	2024-04-19	1Y
EM045-01-01	EMC32 software (RE/RS)	V10.01.00	R&S	N/A	N/A

#### **Conducted Disturbance-Mains Terminal**

Equipment No.	Equipment	Model	Manufacturer	Cal. Due date (DD-MM-YYYY)	Calibration Interval
EM031-02	EMI Test Receiver (9 kHz~7 GHz)	R&S ESR7	R&S	15/11/2024	1Y
EM032-01	LISN	ENV4200	R&S	04/09/2024	1Y
SA047-118	Digital Temperature- Humidity Recorder	RS210	YIJIE	16/07/2024	1Y
EM045-01-01	EMC32 software (RE/RS)	V10.01.00	R&S	N/A	N/A