FCC Emissions Designators for LoCate (LOCA01):

R. Braathen Oct 19, 2001

Per instruction (g) of section 2.201, the necessary bandwidth is to be included before these designators for the full designation. These designations are identical to those for NJICVDM-3 and NJICVDM-2000 as noted on the FCC OET website.

Control Channel:

Necessary bandwidth is +/-20 KHz, which has the symbol: 40K0

Symbol Number	Symbol Requirement	Choice	Designator
First	type of modulation of the carrier	Frequency Modulation	F
Second	nature of signals modulating the carrier	Single channel containing quantized or digital information without the use of a modulating sub-carrier	1
Third	Type of information to be transmitted	Data transmission, telemetry, telecommand	D

Designator for Control Channel: 40K0F1D

Voice Channel:

Voice Channel is analog communications, FM modulation with 15 KHz bandwidth plus a short burst of telecommand.

Signalling Tone and Handoff Commands:

Necessary bandwidth is +/-20 KHz, which has the symbol: 40K0

Symbol	Symbol	Choice	Designator
Number	Requirement		
First	type of modulation of the carrier	Frequency Modulation	F
Second	nature of signals modulating the carrier	Single channel containing quantized or digital information without the use of a modulating sub-carrier	1
Third	Type of information to be transmitted	Data transmission, telemetry, telecommand	D

Voice Channel:

Voice Communications:

Necessary bandwidth is +/-20 KHz, which has the symbol: 40K0

Symbol	Symbol	Choice	Designator
Number	Requirement		
First	type of modulation	Frequency Modulation	F
	of the carrier		
Second	nature of signals	Two or more channels	8
	modulating the	containing analogue	
	carrier	information	
Third	Type of information	Telephony (E) and Telemetry	W
	to be transmitted	(D) for a combination (W)	

Although the LoCate does not use the modem at this time, the standard designation for a cellular telephone should be used to allow future additions of the modem.

Designator for Voice Channel: 40K0F1D and 40K0F8W

The designators to be applied for in the FCC application for LoCate (LOCA01) are:

40K0F1D	
40K0F8W	