

Robosen Robotics (ShenZhen) Co., Ltd.

TEST REPORT

SCOPE OF WORK

FCC TESTING-K1JD

REPORT NUMBER

221121049SZN-002

ISSUE DATE

22 December 2022

[REVISED DATE]

[-----]

PAGES

61

DOCUMENT CONTROL NUMBER

FCC ID 247_b

© 2017 INTERTEK



Robosen Robotics (ShenZhen) Co., Ltd.

Application
For
Certification

FCC ID: 2ATNWK1ZNJD**Robosen AI Base Lite****Model: K1JD****2.4GHz Wi-Fi Transceiver****Report No.: 221121049SZN-002**

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-21]

Prepared and Checked by:**Approved by:****Mandy Chen**
Engineer

Ryan Chen
Project Engineer
Date: 22 December 2022

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China.

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

MEASUREMENT/TECHNICAL REPORT

This report concerns (check one) Original Grant ☒ Class II Change ☐

Equipment Type: DTS - Part 15 Digital Transmission Systems (Wi-Fi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-21 Edition] provision.

Report prepared by:

Mandy Chen
Intertek Testing Services Shenzhen Ltd. Longhua Branch
101, 201, Building B, No. 308 Wuhe Avenue,
Zhangkengjing Community, GuanHu Subdistrict, LongHua
District, Shenzhen, P.R. China.
Tel: (86 755) 8614 0752 Fax: (86 755) 8601 6661

Table of Contents

1.0	<u>Summary of Test results</u>	4
2.0	<u>General Description</u>	5
2.1	Product Description	5
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	5
3.0	<u>System Test Configuration</u>	6
3.1	Justification	6
3.2	EUT Exercising Software	6
3.3	Special Accessories	6
3.4	Measurement Uncertainty	7
3.5	Equipment Modification	7
3.6	Support Equipment List and Description	7
4.0	<u>Measurement Results</u>	8
4.1	Maximum Conducted Output Power at Antenna Terminals	8
4.2	Minimum 6 dB RF Bandwidth	10
4.3	Maximum Power Density Reading	15
4.4	Out of Band Conducted Emissions	20
4.5	Out of Band Radiated Emissions	37
4.6	Transmitter Radiated Emissions in Restricted Bands	38
4.7	Field Strength Calculation	39
4.8	Radiated Spurious Emission	40
4.9	Conducted Emission	55
4.10	Radiated Emissions from Digital Section of Transceiver	58
4.11	Transmitter Duty Cycle Calculation and Measurements	59
5.0	<u>Equipment Photographs</u>	60
6.0	<u>Product Labelling</u>	60
7.0	<u>Technical Specifications</u>	60
8.0	<u>Instruction Manual</u>	60
9.0	<u>Confidentiality Request</u>	60
10.0	<u>Discussion of Pulse Desensitization</u>	60
11.0	<u>Test Equipment List</u>	61

1.0 Summary of Test results

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Applicant Address: A3703, Bldg 11, Shenzhen Bay ECO-Tech Park, No.16, Gaoxin South Science and Tech Rd., Nanshan Dist. Shenzhen, Guangdong, China

Manufacturer: Robosen Robotics (ShenZhen) Co., Ltd.

Manufacturer Address: A3703, Bldg 11, Shenzhen Bay ECO-Tech Park, No.16, Gaoxin South Science and Tech Rd., Nanshan Dist. Shenzhen, Guangdong, China

Model: K1JD

FCC ID: 2ATNWK1ZNJD

TEST ITEM	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d), 15.209, FCC 15.205	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is a Robosen AI Base Lite with Bluetooth 4.2 BLE function operating in 2402-2480MHz and Wi-Fi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing and 2422-2452MHz for 802.11n-HT40, 7 channels with 5MHz channel spacing. The EUT is powered by DC 12V from adapter. For more detailed features description, please refer to the user's manual.

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM for OFDM; CCK, DQPSK, DBPSK for DSSS.

Antenna Type: Integral Antenna

Antenna Gain: 0.18dBi

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

2.2 Related Submittal(s) Grants

This is an application for certification of:

DTS- Part 15 Digital Transmission Systems (2.4GHz Wi-Fi transmitter portion).

Remaining portions are subject to the following procedures:

1. Bluetooth function: Subject to 221121049SZN-001.
2. Other Digital Function: Subject to FCC Part 15B SDOC 221121049SZN-003.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013) and KDB 558074 D01 v05r02. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

2.4 Test Facility

The Semi-anechoic chamber and shielded room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by DC 12V from adapter during the test.

On 802.11b/g/n-HT20/n-HT40 mode, only one antenna is used, and all data rate were tested and only the worst case data is shown in the report.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m up to 1GHz and 1.5 m above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

The EUT and transmitting antenna was centered on the turntable.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program command (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

Test Software: Windows PowerShell

3.3 Special Accessories

N/A.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

3.5 Equipment Modification

Any modifications installed previous to testing by Robosen Robotics (ShenZhen) Co., Ltd. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

3.6 Support Equipment List and Description

Description	Manufacturer	Model No.
Charging Cable	N/A (provided by Client)	Unshielded, Length 34.5cm
AC/DC ADAPTER	N/A (provided by Client)	Model: KA1801A-1201500US Input: 100-240V~ 50/60Hz 0.55A Max Output: 12V/1500mA
INTERSTELLAR SCOUT	ROBOSEN (provided by Client)	Model: K1

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 22 December 2022

Model: K1JD

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter has a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (Antenna Gain = 0.18dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	18.9	77.62
Middle Channel: 2437	18.1	64.57
High Channel: 2462	18.0	63.1

IEEE 802.11g (Antenna Gain = 0.18dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	20.9	123.03
Middle Channel: 2437	20.6	114.82
High Channel: 2462	19.8	95.5

IEEE 802.11n-HT20 (Antenna Gain = 0.18dBi) (64QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	21.0	125.89
Middle Channel: 2437	20.2	104.71
High Channel: 2462	20.1	102.33

IEEE 802.11n-HT40 (Antenna Gain = 0.18 dBi) (64QAM, 13.5Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2422	20.8	120.23
Middle Channel: 2437	20.8	120.23
High Channel: 2452	20.6	114.82

Cable loss: 1.5 dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 21.0dBm

EUT max. E.I.R.P = 21.0dBm + 0.18dBi = 21.18dBm = 131.22mW

For RF Exposure, the information is saved with filename: RF exposure.pdf.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v05r02. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.


IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	9.600
2437	9.630
2462	9.630

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	14.760
2437	16.440
2462	15.090


IEEE 802.11n-HT20 (64QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	14.280
2437	13.860
2462	15.120

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2422	35.280
2437	35.280
2452	35.280


The test plots are attached as below.




11B_2412




11B_2437




11B_2462




11G_2412




11G_2437




11G_2462




11N20_2412




11N20_2437




11N20_2462



11N40_2422



11N40_2437



11N40_2452

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v05r02.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/3 kHz.


IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	Power Density with RBW 3KHz
2412	-5.84
2437	7.2
2462	7.13

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 3KHz
2412	-11.3
2437	-10.86
2462	-11.11


IEEE 802.11n-HT20 (64QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 3KHz
2412	-10.34
2437	-10.69
2462	-11.48

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	Power Density with RBW 3KHz
2422	-14.85
2437	-13.78
2452	-14.06


The test plots are attached as below.




11B_2412




11B_2437




11B_2462




11G_2412




11G_2437




11G_2462




11N20_2412




11N20_2437




11N20_2462



11N40_2422



11N40_2437



11N40_2452

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v05r02.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.


Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b and 6Mbps for 802.11g and 6Mbps for 802.11n-HT20 and 13.5Mbps for 802.11n-HT40.

The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.


The test plots are attached as below.




11B_2412_Reference




11B_2412_0.009~2400




11B_2412_2483.5~25000




11B_Low bandedge




11B_2437_Reference




11B_2437_0.009~2400




11B_2437_2483.5~25000




11B_2462_Reference




11B_2462_0.009~2400




11B_2462_2483.5~25000




11B_High bandedge




11G_2412_0~Reference




11G_2412_0.009~2400




11G_2412_2483.5~25000




11G_low bandedge




11G_2437_0~Reference




11G_2437_0.009~2400




11G_2437_2483.5~25000




11G_2462_0~Reference




11G_2462_0.009~2400




11G_2462_2483.5~25000




11G high bandedge




11N20_2412_0~Reference




11N20_2412_0.009~2400




11N20_2412_2483.5~25000




11N20_low bandedge




11N20_2437_Reference




11N20_2437_0.009~2400




11N20_2437_2483.5~25000



11N20_2462_Reference




11N20_2462_0.009~2400




11N20_2462_2483.5~25000




11N20_high bandedge




11N40_2422_Reference




11N40_2422_0.009~2400




11N40_2422_2483.5~25000




11N40_low bandedge




11N40_2437_Reference




11N40_2437_0.009~2400




11N40_2437_2483.5~25000




11N40_2452_Reference



11N40_2452_0.009~2400



11N40_2452_2483.5~25000



11N40_high bandedge

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

☒ Not required, since all emissions are more than 20dB below fundamental

☐ See attached data sheet

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b) (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Simultaneous transmission has been tested and only the worst data was reported in this report.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB/m
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB/m and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB/m}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission
at 2390.0MHz
is passed by 1.4dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

TEST PERSONNEL:*Sign on file*

Mandy Chen, Engineer
Typed/Printed Name

29 November 2022
Date

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022


Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11b-Channel 01)

ANT Polarity: Horizontal

FCC Part 15



Frequency (MHz)	Quasi Peak (dBμV/m)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
31.422667	20.4	120.000	H	21.8	19.6	40.0
600.004333	36.2	120.000	H	28.6	9.8	46.0
800.040000	40.2	120.000	H	32.0	5.8	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022


Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11b-Channel 01)

ANT Polarity: Vertical

FCC Part 15



Frequency (MHz)	Quasi Peak (dBμV/m)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
145.656333	28.4	120.000	V	15.9	15.1	43.5
399.990333	41.6	120.000	V	25.1	4.4	46.0
800.018333	40.7	120.000	V	32.0	5.3	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11b-Channel 01)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	55.4	36.8	33.5	52.1	74.0	-21.9
Horizontal	*2390.000	69.7	36.4	29.1	62.4	74.0	-11.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	52.2	36.8	33.5	48.9	54.0	-5.1
Horizontal	*2390.000	59.9	36.4	29.1	52.6	54.0	-1.4

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11b-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	54.4	36.7	33.4	51.1	74.0	-22.9
Horizontal	*7311.000	58.4	36.6	35.8	57.6	74.0	-16.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	48.5	36.7	33.4	45.2	54.0	-8.8
Horizontal	*7311.000	47.7	36.6	35.8	46.9	54.0	-7.1

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11b-Channel 11)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	55.8	36.8	33.3	52.3	74.0	-21.7
Horizontal	*7386.000	65.3	36.5	29.3	58.1	74.0	-15.9
Horizontal	*2483.500	67.4	36.4	29.1	60.1	74.0	-13.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	46.4	36.8	33.3	42.9	54.0	-11.1
Horizontal	*7386.000	54.8	36.5	29.3	47.6	54.0	-6.4
Horizontal	*2483.500	58.2	36.4	29.1	50.9	54.0	-3.1

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11g-Channel 01)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	49.5	36.8	33.5	46.2	74.0	-27.8
Horizontal	*2390.000	67.0	36.4	29.1	59.7	74.0	-14.3

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	44.0	36.8	33.5	40.7	54.0	-13.3
Horizontal	*2390.000	57.0	36.4	29.1	49.7	54.0	-4.3

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11g-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	50.0	36.7	33.4	46.7	74.0	-27.3
Horizontal	*7311.000	58.4	36.6	35.8	57.6	74.0	-16.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	45.1	36.7	33.4	41.8	54.0	-12.2
Horizontal	*7311.000	48.4	36.6	35.8	47.6	54.0	-6.4

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11g-Channel 11)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	55.1	36.8	33.3	51.6	74.0	-22.4
Horizontal	*7386.000	64.1	36.5	29.3	56.9	74.0	-17.1
Horizontal	*2483.500	68.4	36.4	29.1	61.1	74.0	-12.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	46.3	36.8	33.3	42.8	54.0	-11.2
Horizontal	*7386.000	55.7	36.5	29.3	48.5	54.0	-5.5
Horizontal	*2483.500	58.2	36.4	29.1	50.9	54.0	-3.1

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11n20-Channel 01)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	55.6	36.8	33.5	52.3	74.0	-21.7
Horizontal	*2390.000	64.2	36.4	29.1	56.9	74.0	-17.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	44.0	36.8	33.5	40.7	54.0	-13.3
Horizontal	*2390.000	52.9	36.4	29.1	45.6	54.0	-8.4

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11n20-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	56.4	36.7	33.4	53.1	74.0	-20.9
Horizontal	*7311.000	59.7	36.6	35.8	58.9	74.0	-15.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	44.8	36.7	33.4	41.5	54.0	-12.5
Horizontal	*7311.000	48.5	36.6	35.8	47.7	54.0	-6.3

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11n20-Channel 11)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	56.2	36.8	33.3	52.7	74.0	-21.3
Horizontal	*7386.000	64.9	36.5	29.3	57.7	74.0	-16.3
Horizontal	*2483.500	69.6	36.4	29.1	62.3	74.0	-11.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	44.8	36.8	33.3	41.3	54.0	-12.7
Horizontal	*7386.000	55.0	36.5	29.3	47.8	54.0	-6.2
Horizontal	*2483.500	58.4	36.4	29.1	51.1	54.0	-2.9

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11n40-Channel 03)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	55.2	36.8	33.5	51.9	74.0	-22.1
Horizontal	*2390.000	62.1	36.4	29.1	54.8	74.0	-19.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	45.0	36.8	33.5	41.7	54.0	-12.3
Horizontal	*2390.000	56.1	36.4	29.1	48.8	54.0	-5.2

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11n40-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	55.4	36.7	33.4	52.1	74.0	-21.9
Horizontal	*7311.000	58.8	36.6	35.8	58.0	74.0	-16.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	45.4	36.7	33.4	42.1	54.0	-11.9
Horizontal	*7311.000	50.0	36.6	35.8	49.2	54.0	-4.8

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 29 November 2022

Model: K1JD

Worst Case Operating Mode:

Transmitting (802.11n40-Channel 09)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	56.4	36.8	33.3	52.9	74.0	-21.1
Horizontal	*7356.000	65.1	36.5	29.3	57.9	74.0	-16.1
Horizontal	*2483.500	68.9	36.4	29.1	61.6	74.0	-12.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	45.3	36.8	33.3	41.8	54.0	-12.2
Horizontal	*7356.000	55.3	36.5	29.3	48.1	54.0	-5.9
Horizontal	*2483.500	58.1	36.4	29.1	50.8	54.0	-3.2

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 02 December 2022

Model: K1JD

4.9 Conducted Emission

Worst Case Conducted Emission (802.11b-Channel 01)
at 0.374000MHz
is passed by 18.3dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: conducted photos.pdf.

Simultaneous transmission has been tested and only the worst data was reported in this report.

TEST PERSONNEL:

Sign on file

Mandy Chen, Engineer

Typed/Printed Name

02 December 2022

Date

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 02 December 2022

Model: K1JD


Worst Case Operating Mode: Transmitting (802.11b-Channel 01)

Phase: Live

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement

Conducted Emission Test FCC Part 15



Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	41.6	9.000	L1	9.6	23.9	65.6
0.366000	34.5	9.000	L1	9.6	24.1	58.6
0.498000	30.7	9.000	L1	9.6	25.3	56.0
0.898000	27.5	9.000	L1	9.7	28.5	56.0
1.518000	28.1	9.000	L1	9.7	27.9	56.0
10.494000	33.1	9.000	L1	10.0	26.9	60.0

Limit and Margin AV

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	27.4	9.000	L1	9.6	28.1	55.6
0.366000	27.6	9.000	L1	9.6	21.0	48.6
0.498000	25.3	9.000	L1	9.6	20.7	46.0
0.898000	22.3	9.000	L1	9.7	23.7	46.0
1.518000	22.6	9.000	L1	9.7	23.4	46.0
10.494000	23.7	9.000	L1	10.0	26.3	50.0

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 02 December 2022

Model: K1JD


Worst Case Operating Mode: Transmitting (802.11b-Channel 01)

Phase: Neutral

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement

Conducted Emission Test FCC Part 15



Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.162000	42.4	9.000	N	9.6	23.0	65.4
0.314000	35.8	9.000	N	9.6	24.1	59.9
0.374000	35.1	9.000	N	9.6	23.3	58.4
0.478000	31.7	9.000	N	9.6	24.7	56.4
0.886000	28.7	9.000	N	9.6	27.3	56.0
10.290000	33.5	9.000	N	9.9	26.5	60.0

Limit and Margin AV

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.162000	27.8	9.000	N	9.6	27.6	55.4
0.314000	29.3	9.000	N	9.6	20.6	49.9
0.374000	30.1	9.000	N	9.6	18.3	48.4
0.478000	25.1	9.000	N	9.6	21.3	46.4
0.886000	22.4	9.000	N	9.6	23.7	46.0
10.290000	23.7	9.000	N	9.9	26.3	50.0

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 02 December 2022

Model: K1JD

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

☐ Not required - No digital part

☐ Test results are attached

☒ Included in the separated report.

Applicant: Robosen Robotics (ShenZhen) Co., Ltd.

Date of Test: 02 December 2022

Model: K1JD

4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	2022-05-16	2023-05-16
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	2022-05-16	2023-05-16
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	2021-08-04	2024-08-04
SZ185-03	EMI Receiver	R&S	ESR7	101975	2021-12-20	2022-12-20
SZ061-08	Horn Antenna	ETS	3115	00092346	2021-09-05	2024-09-05
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2021-05-18	2023-05-18
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	2022-05-16	2023-05-16
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	2021-12-20	2022-12-20
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	2022-05-16	2023-05-16
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	2021-12-12	2024-12-12
SZ062-02	RF Cable	RADIAL	RG 213U	--	2022-11-15	2023-05-15
SZ062-05	RF Cable	RADIAL	0.04-26.5GHz	--	2022-11-15	2023-05-15
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	--	2022-11-15	2023-05-15
SZ067-04	Notch Filter	Micro-Tronics	BRM50702-02	--	2022-05-17	2023-05-17
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	2022-07-08	2023-07-08
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	2022-10-24	2023-10-24
SZ188-03	Shielding Room	ETS	RFD-100	4100	2020-01-07	2023-01-07

***** End of Report*****