



TEST REPORT

No. 2013TAR914

for

TCT Mobile Limited

**HSDPA/HSUPA/HSPA+/UMTS Quad bands / GSM quad bands/LTE 5
bands mobile phone**

Model Name: Miata LATAM

Marketing Name: 6036A

FCC ID: RAD449

with

Hardware Version: PIO

Software Version: v4E18

Issued Date: 2014-04-02

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. D-PL-12123-01-01

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629B

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai Dian District, Beijing, P. R. China, 100191.

Tel: +86(0)10-62304633-2604, Fax: +86(0)10-62304793, Email: welcome@emcrite.com, web: www.emcrite.com

CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION	4
2.1. APPLICANT INFORMATION	4
2.2. MANUFACTURER INFORMATION	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. NORMAL ACCESSORY SETTING	6
3.5. GENERAL DESCRIPTION	6
4. REFERENCE DOCUMENTS	7
4.1. REFERENCE DOCUMENTS FOR TESTING	7
5. LABORATORY ENVIRONMENT	8
6. SUMMARY OF TEST RESULTS	9
7. TEST EQUIPMENTS UTILIZED	10
ANNEX A: MEASUREMENT RESULTS	11
A.1 OUTPUT POWER	11
A.2 EMISSION LIMIT	18
A.3 CONDUCTED EMISSION	24
A.4 FREQUENCY STABILITY	29
A.5 OCCUPIED BANDWIDTH	31
A.6 EMISSION BANDWIDTH	43
A.7 BAND EDGE COMPLIANCE	55
A.8 CONDUCTED SPURIOUS EMISSION	62

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: 3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai
Dian District, Beijing, P. R. China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304793


1.2. Testing Environment

Normal Temperature: 15-35℃
Relative Humidity: 20-75%


1.3. Project data

Testing Start Date: 2014-02-25
Testing End Date: 2014-04-02

1.4. Signature



Zi Xiaogang
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@jrdcom.com
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	HSDPA/HSUPA/HSPA+/UMTS Quad bands / GSM quad bands/LTE 5 bands mobile phone
Model Name	Miata LATAM
Marketing Name	6036A
FCC ID	RAD449
Antenna	Integrated
Output power	31.49dBm maximum EIRP measured for PCS1900
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.9VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version
R06a	014010000000250	PIO	v4E18
N33	014010000053234	PIO	v4E18

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN	Remarks
AE1	Battery	/	/
AE2	Battery	/	/
AE3	Travel charger	/	TCT-CHR-0136
AE4	Travel charger	/	TCT-CHR-1557
AE5	USB cable	/	TCT-DC-0493
AE6	USB cable	/	TCT-DC-0331
AE1			
	Model	CAB2000013C2	
	Manufacturer	BYD	
	Capacitance	2000 mAh	
	Nominal voltage	3.8V	
AE2			
	Model	CAB2000010C1	
	Manufacturer	SCUD	
	Capacitance	2000 mAh	
	Nominal voltage	3.8V	
AE3			

Model	CBA3000AG0C1
Manufacturer	TEN PAO
Length of cable	/

AE4

Model	CBA3000AG0C2
Manufacturer	BYD
Length of cable	/

AE5

Model	CDA3122002C1
Manufacturer	/
Length of cable	98cm

AE6

Model	CDA3122002C2
Manufacturer	/
Length of cable	98cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. Normal Accessory setting

Fully charged battery was used during the test.

3.5. General Description

The Equipment Under Test (EUT) is a model of HSDPA/HSUPA/HSPA+/UMTS Quad bands / GSM quad bands/LTE 5 bands mobile phone with integrated antenna. Manual and specifications of the EUT were provided to fulfil the test.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-13 Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-13 Edition
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003
KDB971168 D01	Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems	2011

5. LABORATORY ENVIRONMENT

Control room / conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber 2 (8.6 meters×6.1 meters×3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 1 Ω
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

Semi-anechoic chamber 2 / Fully-anechoic chamber 3 (10 meters×6.7 meters×6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

6. SUMMARY OF TEST RESULTS

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913(a)/24.232(c)	P
2	Emission Limit	2.1051/22.917/24.238	P
3	Conducted Emission	15.107/15.207	P
4	Frequency Stability	2.1055/24.235	P
5	Occupied Bandwidth	2.1049(h)(i)	P
6	Emission Bandwidth	22.917(b)/24.238(b)	P
7	Band Edge Compliance	22.917(b)/24.238(b)	P
8	Conducted Spurious Emission	2.1057/22.917/24.238	P

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE
1	Test Receiver	ESCI	100344	R&S	2015-03-03
2	Test Receiver	ESU26	100376	R&S	2014-11-05
3	EMI Antenna	VULB 9163	514	Schwarzbeck	2014-11-10
4	EMI Antenna	3117	00139065	ETS-Lindgren	2014-07-31
5	LISN	ESH2-Z5	829991/012	R&S	2014-04-14
6	Universal Radio Communication Tester	CMU200	102228	R&S	2014-06-23
7	Universal Radio Communication Tester	E5515C	MY48361083	Agilent	2015-02-27
8	Spectrum Analyzer	E4440A	MY48250642	Agilent	2015-02-27
9	EMI Antenna	9117	177	Schwarzbeck	2014-06-29
10	EMI Antenna	VULB 9163	9163 175	Schwarzbeck	2014-07-13
11	EMI Antenna	3117	00119021	ETS-Lindgren	2014-04-19
12	Signal Generator	N5183A	MY49060052	Agilent	2015-03-02
13	Climate chamber	SH-241	92003546	ESPEC	2014-05-11
14	Loop Antenna	HFH2-Z2	829324/007	R&S	2014-12-12

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation. The power was measured with Rhode & Schwarz Universal Radio Communication Tester CMU200. These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band; 824.4MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

GSM850

	Power step	Nominal Peak output power (dBm)
GSM	5	33dBm(2W)
GPRS	3	33dBm(2W)
EGPRS	6	27dBm(0.5W)

Measurement result

GSM(GMSK)

Frequency(MHz)	Power Step	Output power(dBm)
824.2	5	32.97
836.6	5	33.28
848.8	5	33.18

GPRS(GMSK, 1Slot)

Frequency(MHz)	Power Step	Output power(dBm)
824.2	3	33.08
836.6	3	33.04
848.8	3	33.27

EGPRS(8PSK, 1Slot)

Frequency(MHz)	Power Step	Output power(dBm)
824.2	6	27.63
836.6	6	27.70
848.8	6	27.70

PCS1900

	Power step	Nominal Peak output power (dBm)
GSM	0	30dBm(1W)
GPRS	3	30dBm(1W)
EGPRS	5	26dBm(0.4W)

Measurement result
GSM(GMSK)

Frequency(MHz)	Power Step	Output power(dBm)
1850.2	0	30.28
1880.0	0	30.25
1909.8	0	30.27

GPRS(GMSK, 1Slot)

Frequency(MHz)	Power Step	Output power(dBm)
1850.2	3	30.32
1880.0	3	30.28
1909.8	3	30.29

EGPRS(8PSK, 1Slot)

Frequency(MHz)	Power Step	Output power(dBm)
1850.2	5	26.48
1880.0	5	26.41
1909.8	5	26.46

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is

connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.

The cable loss (P_{cl}) ,the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

GSM 850-ERP 22.913(a)
Limits

	Power Step	Burst Peak ERP (dBm)
GSM	5	≤38.45dBm (7W)
GPRS	3	≤38.45dBm (7W)
EGPRS	6	≤38.45dBm (7W)

Measurement result
GSM

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
824.20	-19.10	2.07	-53.00	0.84	2.15	28.84	38.45	9.61	V
836.60	-19.29	2.08	-53.00	0.90	2.15	28.58	38.45	9.87	V
848.80	-21.34	2.09	-53.00	0.95	2.15	26.47	38.45	11.98	V

GPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
824.20	-19.03	2.07	-53.00	0.84	2.15	28.91	38.45	9.54	V
836.60	-19.22	2.08	-53.00	0.90	2.15	28.65	38.45	9.80	V
848.80	-21.34	2.09	-53.00	0.95	2.15	26.47	38.45	11.98	V

EGPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
824.20	-24.14	2.07	-53.00	0.84	2.15	23.80	38.45	14.65	V
836.60	-23.39	2.08	-53.00	0.90	2.15	24.48	38.45	13.97	V
848.80	-24.90	2.09	-53.00	0.95	2.15	22.91	38.45	15.54	V

Frequency: 824.20MHz

Peak ERP(dBm)=P_{Mea}(-19.03dBm)-P_{cl}(2.07dB)-P_{Ag}(-53.00dB)-G_a (0.84dB)-2.15dB=28.91dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

PCS1900-EIRP 24.232(c)
Limits

	Power Step	Burst Peak EIRP (dBm)
GSM	0	≤33dBm (2W)
GPRS	3	≤33dBm (2W)
EGPRS	5	≤33dBm (2W)

Measurement result
GSM

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1850.20	-21.43	3.19	-50.00	-4.56	29.94	33.00	3.06	H
1880.00	-19.86	3.11	-50.00	-4.43	31.46	33.00	1.54	H
1909.80	-20.60	3.18	-50.00	-4.30	30.52	33.00	2.48	H

GPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1850.20	-21.42	3.19	-50.00	-4.56	29.95	33.00	3.05	H
1880.00	-19.83	3.11	-50.00	-4.43	31.49	33.00	1.51	H
1909.80	-20.53	3.18	-50.00	-4.30	30.59	33.00	2.41	H

EGPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1850.20	-24.26	3.19	-50.00	-4.56	27.11	33.00	5.89	H
1880.00	-23.16	3.11	-50.00	-4.43	28.16	33.00	4.84	H
1909.80	-23.66	3.18	-50.00	-4.30	27.46	33.00	5.54	H

Frequency: 1880.00MHz

Peak EIRP(dBm)= P_{Mea}(-19.83dBm) - P_{cl}(3.11dB) - P_{Ag}(-50.00dB) - G_a (-4.43dB) =31.49dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.2 EMISSION LIMIT


A.2.1 Measurement Method

The measurement procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (P_r).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{pl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.2.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz) and GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
GSM 850MHz	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
GSM 1900MHz	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
850MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
1900MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

GSM Mode Channel 128/824.2MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3324.40	-59.25	4.15	-7.48	2.15	-58.07	-13.00	45.07	V
4475.78	-53.10	4.86	-8.79	2.15	-51.32	-13.00	38.32	H
5279.46	-59.32	5.34	-9.87	2.15	-56.94	-13.00	43.94	H
6159.16	-61.90	5.83	-10.33	2.15	-59.55	-13.00	46.55	H
7162.53	-60.55	6.35	-11.20	2.15	-57.85	-13.00	44.85	V
7877.65	-59.17	6.95	-11.78	2.15	-56.49	-13.00	43.49	V

GSM Mode Channel 190/836.6MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
1673.38	-62.38	2.97	-5.34	2.15	-62.16	-13.00	49.16	V
3526.46	-53.34	4.33	-7.93	2.15	-51.89	-13.00	38.89	H
4673.07	-60.18	4.93	-9.11	2.15	-58.15	-13.00	45.15	H
5815.24	-60.73	5.71	-10.13	2.15	-58.46	-13.00	45.46	H
6977.22	-57.36	6.27	-11.08	2.15	-54.70	-13.00	41.70	V
8664.11	-58.83	7.42	-12.33	2.15	-56.07	-13.00	43.07	H

GSM Mode Channel 251/848.8MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3575.45	-54.04	4.35	-7.99	2.15	-52.55	-13.00	39.55	H
4476.33	-55.88	4.86	-8.79	2.15	-54.10	-13.00	41.10	H
6309.15	-60.08	5.91	-10.45	2.15	-57.69	-13.00	44.69	H
7220.34	-60.93	6.37	-11.23	2.15	-58.22	-13.00	45.22	H
8186.66	-57.69	6.83	-12.01	2.15	-54.66	-13.00	41.66	V
9614.68	-58.54	7.91	-12.55	2.15	-56.05	-13.00	43.05	V

GSM Mode Channel 512/1850.2MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3700.49	-49.66	4.44	-8.14	-45.96	-13.00	32.96	H
5550.76	-50.39	5.46	-10.02	-45.83	-13.00	32.83	V
9251.27	-49.55	7.65	-12.60	-44.60	-13.00	31.60	H
10208.93	-56.41	7.63	-12.44	-51.60	-13.00	38.60	H
12587.95	-52.71	8.91	-12.81	-48.81	-13.00	35.81	V
13789.47	-52.68	9.09	-13.92	-47.85	-13.00	34.85	V

GSM Mode Channel 661/1880.0MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3919.81	-56.02	4.51	-8.40	-52.13	-13.00	39.13	H
5640.15	-48.69	5.45	-10.06	-44.08	-13.00	31.08	H
7683.93	-58.03	6.58	-11.58	-53.03	-13.00	40.03	V
9399.89	-48.54	7.45	-12.60	-43.39	-13.00	30.39	H
12348.58	-55.62	8.70	-12.64	-51.68	-13.00	38.68	H
14479.13	-51.94	9.34	-13.62	-47.66	-13.00	34.66	H

GSM Mode Channel 810/1909.8MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
3819.21	-53.37	4.49	-8.28	-49.58	-13.00	36.58	V
5729.48	-47.26	5.55	-10.09	-42.72	-13.00	29.72	H
6871.70	-59.79	6.07	-10.97	-54.89	-13.00	41.89	V
8374.16	-59.16	7.32	-12.12	-54.36	-13.00	41.36	V
11485.34	-54.36	8.52	-12.40	-50.48	-13.00	37.48	H
14909.59	-50.91	9.73	-13.52	-47.12	-13.00	34.12	H

A.3 CONDUCTED EMISSION


The measurement procedure in ANSI C63.4-1003 is used. Conducted Emission is measured with travel charger.

A.3.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50
* Decreases with logarithm of the frequency		

A.3.2 Measurement result

GSM850MHz




Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.779000	40.0	GND	L1	9.7	16.0	56.0
1.810500	39.7	GND	L1	9.7	16.3	56.0
2.436000	40.1	GND	L1	9.7	15.9	56.0
2.508000	43.0	GND	L1	9.7	13.0	56.0
2.755500	40.7	GND	L1	9.7	15.3	56.0
2.845500	42.9	GND	L1	9.7	13.1	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.765500	26.7	GND	L1	9.7	19.3	46.0
2.508000	27.4	GND	L1	9.7	18.6	46.0
2.553000	27.7	GND	L1	9.7	18.3	46.0
2.755500	28.0	GND	L1	9.7	18.0	46.0
2.800500	29.8	GND	L1	9.7	16.2	46.0
2.836500	27.9	GND	L1	9.7	18.1	46.0

PCS1900MHz




Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.810500	42.6	GND	L1	9.7	13.4	56.0
1.887000	41.0	GND	L1	9.7	15.0	56.0
2.508000	43.8	GND	L1	9.7	12.2	56.0
2.580000	39.7	GND	L1	9.7	16.3	56.0
2.710500	42.0	GND	L1	9.7	14.0	56.0
2.755500	43.1	GND	L1	9.7	12.9	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.765500	28.0	GND	L1	9.7	18.0	46.0
1.810500	30.6	GND	L1	9.7	15.4	46.0
2.472000	29.1	GND	L1	9.7	16.9	46.0
2.508000	30.7	GND	L1	9.7	15.3	46.0
2.625000	27.8	GND	L1	9.7	18.2	46.0
2.755500	30.1	GND	L1	9.7	15.9	46.0

MP3




Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.851000	38.1	GND	L1	9.7	17.9	56.0
2.467500	41.4	GND	L1	9.7	14.6	56.0
2.643000	41.4	GND	L1	9.7	14.6	56.0
2.796000	42.2	GND	L1	9.7	13.8	56.0
2.890500	38.8	GND	L1	9.7	17.2	56.0
2.935500	37.2	GND	L1	9.7	18.8	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.852000	27.4	GND	L1	9.8	18.6	46.0
1.851000	26.2	GND	L1	9.7	19.8	46.0
1.896000	26.5	GND	L1	9.7	19.5	46.0
2.512500	28.6	GND	L1	9.7	17.4	46.0
2.557500	29.6	GND	L1	9.7	16.4	46.0
2.890500	26.5	GND	L1	9.7	19.5	46.0

CAMERA



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.159000	38.3	GND	L1	9.8	27.2	65.5
0.177000	27.6	GND	L1	9.8	37.0	64.6
0.190500	29.2	GND	L1	9.8	34.8	64.0
0.204000	36.6	GND	L1	9.8	26.9	63.4
0.217500	23.3	GND	L1	9.8	39.6	62.9
0.249000	30.9	GND	L1	9.8	30.9	61.8

Final Result 2

Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.771000	28.4	GND	L1	9.8	17.6	46.0
1.801500	29.4	GND	L1	9.7	16.6	46.0
1.878000	27.1	GND	L1	9.7	18.9	46.0
2.512500	30.4	GND	L1	9.7	15.6	46.0
2.760000	28.1	GND	L1	9.7	17.9	46.0
2.805000	29.7	GND	L1	9.7	16.3	46.0

A.4 FREQUENCY STABILITY

A.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of PCS 1900 and GSM850, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.4.2 Measurement Limit

A.4.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.9VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.4.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.4.3 Measurement results

GSM 850

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	13	0.016
3.9	12	0.015
4.2	24	0.028

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	9	0.011
-20	10	0.012
-10	10	0.012
0	9	0.011
10	13	0.016
20	15	0.018
30	10	0.012
40	9	0.011
50	13	0.016

PCS 1900

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	50	0.027
3.9	51	0.027
4.2	51	0.027

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	52	0.027
-20	69	0.037
-10	49	0.026
0	52	0.028
10	54	0.029
20	59	0.031
30	62	0.033
40	51	0.027
50	57	0.030

A.5 OCCUPIED BANDWIDTH

A.5.1 Occupied Bandwidth Results

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

Test Condition

RBW	VBW	Span	SweepTime	Detector	Trace Mode
5KHz	20KHz	500KHz	20ms	Peak	Max Hold


The EUT was set up for the max output power with pseudo random data modulation. Use the Occupied Bandwidth function of SA to measure the 99% bandwidth.

GSM 850(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	243.590
836.6	246.795
848.8	245.192


GSM 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 14.MAR.2014 15:38:40

Channel 190-Occupied Bandwidth (99% BW)



Date: 14.MAR.2014 15:39:12

Channel 251-Occupied Bandwidth (99% BW)




Date: 14.MAR.2014 15:39:45

GPRS 850(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	244.391
836.6	244.391
848.8	243.590


GPRS 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 14.MAR.2014 16:08:05

Channel 190-Occupied Bandwidth (99% BW)



Date: 14.MAR.2014 16:08:37

Channel 251-Occupied Bandwidth (99% BW)




Date: 14.MAR.2014 16:09:09

EGPRS 850-8PSK(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	241.987
836.6	245.994
848.8	245.192


EGPRS 850-8PSK

Channel 128-Occupied Bandwidth (99% BW)




Date: 14.MAR.2014 16:39:06

Channel 190-Occupied Bandwidth (99% BW)



Date: 14.MAR.2014 16:39:38

Channel 251-Occupied Bandwidth (99% BW)




Date: 14.MAR.2014 16:40:10

PCS 1900(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	247.596
1880.0	247.596
1909.8	243.590


PCS 1900

Channel 512-Occupied Bandwidth (99% BW)




Date: 14.MAR.2014 15:52:03

Channel 661-Occupied Bandwidth (99% BW)



Date: 14.MAR.2014 15:52:35

Channel 810-Occupied Bandwidth (99% BW)




Date: 14.MAR.2014 15:53:07

GPRS 1900(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	245.192
1880.0	245.192
1909.8	243.590


GPRS 1900

Channel 512-Occupied Bandwidth (99% BW)




Date: 14.MAR.2014 16:22:26

Channel 661-Occupied Bandwidth (99% BW)



Date: 14.MAR.2014 16:22:58

Channel 810-Occupied Bandwidth (99% BW)




Date: 14.MAR.2014 16:23:30

EGPRS 1900-8PSK(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	243.590
1880.0	244.391
1909.8	241.987


EGPRS 1900-8PSK

Channel 512-Occupied Bandwidth (99% BW)




Date: 14.MAR.2014 16:43:40

Channel 661-Occupied Bandwidth (99% BW)



Date: 14.MAR.2014 16:44:12

Channel 810-Occupied Bandwidth (99% BW)



Date: 14.MAR.2014 16:44:44

A.6 EMISSION BANDWIDTH

A.6.1 Emission Bandwidth Results

Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. Table below lists the measured 100% BW. Spectrum analyzer plots are included on the following pages.

Test Condition

RBW	VBW	Span	Sweptime	Detector	Trace Mode
5KHz	20KHz	500KHz	20ms	Peak	Max Hold


The EUT was set up for the max output power with pseudo random data modulation. Use the Occupied Bandwidth function of SA to measure the 100% bandwidth.

GSM 850(100% BW)

Frequency(MHz)	Emission Bandwidth (100% BW)(kHz)
824.2	306.090
836.6	305.288
848.8	307.692


GSM 850

Channel 128-Emission Bandwidth (100% BW)




Date: 14.MAR.2014 15:40:18

Channel 190-Emission Bandwidth (100% BW)



Date: 14.MAR.2014 15:40:50

Channel 251-Emission Bandwidth (100% BW)




Date: 14.MAR.2014 15:41:23

GPRS 850(100% BW)

Frequency(MHz)	Emission Bandwidth (100% BW)(kHz)
824.2	306.891
836.6	306.090
848.8	306.891


GPRS 850

Channel 128-Emission Bandwidth (100% BW)




Date: 14.MAR.2014 16:09:43

Channel 190-Emission Bandwidth (100% BW)



Date: 14.MAR.2014 16:10:15

Channel 251-Emission Bandwidth (100% BW)




Date: 14.MAR.2014 16:10:47

EGPRS 850-8PSK(100% BW)

Frequency(MHz)	Emission Bandwidth (100% BW)(kHz)
824.2	302.885
836.6	301.282
848.8	298.878


EGPRS 850-8PSK

Channel 128-Emission Bandwidth (100% BW)




Date: 14.MAR.2014 16:40:44

Channel 190-Emission Bandwidth (100% BW)



Date: 14.MAR.2014 16:41:16

Channel 251-Emission Bandwidth (100% BW)




Date: 14.MAR.2014 16:41:48

PCS 1900(100% BW)

Frequency(MHz)	Emission Bandwidth (100% BW)(kHz)
1850.2	306.891
1880.0	307.692
1909.8	307.692


PCS 1900

Channel 512-Emission Bandwidth (100% BW)




Date: 14.MAR.2014 15:53:41

Channel 661-Emission Bandwidth (100% BW)



Date: 14.MAR.2014 15:54:13

Channel 810-Emission Bandwidth (100% BW)




Date: 14.MAR.2014 15:54:45

GPRS 1900(100% BW)

Frequency(MHz)	Emission Bandwidth (100% BW)(kHz)
1850.2	304.487
1880.0	303.686
1909.8	305.288


GPRS 1900

Channel 512-Emission Bandwidth (100% BW)




Date: 14.MAR.2014 16:24:04

Channel 661-Emission Bandwidth (100% BW)



Date: 14.MAR.2014 16:24:36

Channel 810-Emission Bandwidth (100% BW)




Date: 14.MAR.2014 16:25:08

EGPRS 1900-8PSK(100% BW)

Frequency(MHz)	Emission Bandwidth (100% BW)(kHz)
1850.2	301.282
1880.0	301.282
1909.8	299.679


EGPRS 1900-8PSK

Channel 512-Emission Bandwidth (100% BW)




Date: 14.MAR.2014 16:45:18

Channel 661-Emission Bandwidth (100% BW)



Date: 14.MAR.2014 16:45:50

Channel 810-Emission Bandwidth (100% BW)



Date: 14.MAR.2014 16:46:22

A.7 BAND EDGE COMPLIANCE


Test Condition

RBW	VBW	Span	Sweptime	Detector	Trace Mode
5KHz	10KHz	1MHz	300ms	Average	Max Hold

Search the peak marker below low frequency for low band edge or above high frequency for high band edge.


GSM 850

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128



Date: 14.MAR.2014 15:41:37


HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251



Date: 14.MAR.2014 15:41:50


GPRS 850

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 14.MAR.2014 16:11:01

HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251




Date: 14.MAR.2014 16:11:15

EGPRS 850-8PSK LOW BAND EDGE BLOCK-A (GSM850)-Channel 128



Date: 14.MAR.2014 16:42:02


HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251



Date: 14.MAR.2014 16:42:16


PCS 1900

LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 14.MAR.2014 15:54:59


HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810



Date: 14.MAR.2014 15:55:13


GPRS 1900

LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512




Date: 14.MAR.2014 16:25:22

HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810




Date: 14.MAR.2014 16:25:36

EGPRS 1900-8PSK LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 14.MAR.2014 16:46:36

HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810



Date: 14.MAR.2014 16:46:50

A.8 CONDUCTED SPURIOUS EMISSION

A.8.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 10 GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:
The trace mode is set to MaxHold to get the highest signal at each frequency;
Wait 25 seconds;
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

GSM850 Transmitter

Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

PCS1900 Transmitter

Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

A. 8.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.


A. 8.3 Measurement result

GSM850

A.8.3.1 Channel 128: 30MHz – 1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 14.MAR.2014 15:42:19

A.8.3.2 Channel 128: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:42:47

A.8.3.3 Channel 128: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:43:15

A.8.3.4 Channel 128: 7.5GHz –10GHz

Spurious emission limit –13dBm.




Date: 14.MAR.2014 15:43:44

A.8.3.5 Channel 190: 30MHz – 1GHz

Spurious emission limit –13dBm


NOTE: peak above the limit line is the carrier frequency.



Date: 14.MAR.2014 15:44:12

A.8.3.6 Channel 190: 1GHz –2.5GHz


Spurious emission limit –13dBm



Date: 14.MAR.2014 15:44:41

A.8.3.7 Channel 190: 2.5GHz –7.5GHz


Spurious emission limit –13dBm



Date: 14.MAR.2014 15:45:09

A.8.3.8 Channel 190: 7.5GHz –10GHz

Spurious emission limit –13dBm




Date: 14.MAR.2014 15:45:37

A.8.3.9 Channel 251: 30MHz – 1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 14.MAR.2014 15:46:06

A.8.3.10 Channel 251: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:46:34

A.8.3.11 Channel 251: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:47:02

A.8.3.12 Channel 251: 7.5GHz – 10GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:47:30

A.8.3.13 Idle mode: 30MHz – 1GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:47:58

A.8.3.14 Idle mode: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:48:27

A.8.3.15 Idle mode: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:48:55

A.8.3.16 Idle mode: 7.5GHz – 10GHz

Spurious emission limit –13dBm.




Date: 14.MAR.2014 15:49:23

PCS1900

A.8.3.17 Channel 512: 30MHz – 1GHz

Spurious emission limit –13dBm.




Date: 14.MAR.2014 15:55:42

A.8.3.18 Channel 512: 1GHz – 2.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 14.MAR.2014 15:56:10

A.8.3.19 Channel 512: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:56:38

A.8.3.20 Channel 512: 7.5GHz –10GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:57:06

A.8.3.21 Channel 512: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:57:35

A.8.3.22 Channel 512: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 15:58:03

A.8.3.23 Channel 661: 30MHz – 1GHz

Spurious emission limit –13dBm




Date: 14.MAR.2014 15:58:32

A.8.3.24 Channel 661: 1GHz – 2.5GHz

Spurious emission limit –13dBm


NOTE: peak above the limit line is the carrier frequency.



Date: 14.MAR.2014 15:59:00

A.8.3.25 Channel 661: 2.5GHz –7.5GHz


Spurious emission limit –13dBm



Date: 14.MAR.2014 15:59:28

A.8.3.26 Channel 661: 7.5GHz –10GHz


Spurious emission limit –13dBm



Date: 14.MAR.2014 15:59:56

A.8.3.27 Channel 661: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:00:24

A.8.3.28 Channel 661: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:00:52

A.8.3.29 Channel 810: 30MHz – 1GHz

Spurious emission limit –13dBm.




Date: 14.MAR.2014 16:01:21

A.8.3.30 Channel 810: 1GHz – 2.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 14.MAR.2014 16:01:49

A.8.3.31 Channel 810:2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:02:18

A.8.3.32 Channel 810: 7.5GHz – 10GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:02:46

A.8.3.33 Channel 810: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:03:14

A.8.3.34 Channel 810: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:03:42

A.8.3.35 Idle mode: 30MHz – 1GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:04:11

A.8.3.36 Idle mode: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:04:39

A.8.3.37 Idle mode: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:05:07

A.8.3.38 Idle mode: 7.5GHz – 10GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:05:36

A.8.3.39 Idle mode: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:06:04

A.8.3.40 IDLE mode: 15GHz –20GHz

Spurious emission limit –13dBm.



Date: 14.MAR.2014 16:06:32

END OF REPORT