

FCC PART 15.247

TEST REPORT

For

XIAMEN RONGTA TECHNOLOGY CO.,LTD.

3F-1/E Building, No.195 Gaoqishe, Gaodian Village, Dianqian Street Office,
Huli District, Xiamen City, China

FCC ID: 2AD6G-IMACHINE-A1

Report Type: Original Report	Product Name: ALL IN ONE
Report Number: RXM180419050-00B	
Report Date: 2018-05-22	
Reviewed By: Jerry Zhang EMC Manager	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).
This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	6
SUPPORT CABLE LIST AND DETAILS	7
CONFIGURATION OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	8
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE	11
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST DATA	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	16
TEST PROCEDURE	16
TEST EQUIPMENT LIST AND DETAILS.....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST DATA	17
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	25
APPLICABLE STANDARD	25
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST PROCEDURE	25
TEST DATA	25
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING.....	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31

TEST EQUIPMENT LIST AND DETAILS.....	31
TEST DATA	31
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA	37
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST EQUIPMENT LIST AND DETAILS.....	41
TEST DATA	41
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	57
APPLICABLE STANDARD	57
TEST PROCEDURE	57
TEST EQUIPMENT LIST AND DETAILS.....	57
TEST DATA	57
FCC §15.247(d) - BAND EDGES TESTING	59
APPLICABLE STANDARD	59
TEST PROCEDURE	59
TEST EQUIPMENT LIST AND DETAILS.....	59
TEST DATA	60

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		ALL IN ONE
EUT Model:		iMachine A1
Multiple Model:		iMachine B1, iMachine C1, iMachine D1, iMachine E1, iMachine F1, iMachine G1, iMachine H1, iMachine I1, iMachine J1
FCC ID:		2AD6G-IMACHINE-A1
Rated Input Voltage:		DC 24V from adapter
Adapter Information	Model:	DJ-240250-SA
	Input:	AC 100-240V~ 50/60Hz 1.5A MAX
	Output:	DC 24V , 2.5A MAX
External Dimension:		Length (353.2 mm)*Width (207.1 mm)*High (402.7 mm)
Serial Number:		180419050
EUT Received Date:		2018.04.19
The highest operation frequency:		2480MHz

Note: The series product, models iMachine A1, iMachine B1, iMachine C1, iMachine D1, iMachine E1, iMachine F1, iMachine G1, iMachine H1, iMachine I1, iMachine J1 are electrically identical, we selected iMachine A1 for full test, and please refer to the declaration letter for details.

Objective

This report is prepared on behalf of **XIAMEN RONGTA TECHNOLOGY CO.,LTD.** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DTS submissions with FCC ID: 2AD6G-IMACHINE-A1.
FCC Part 15B JBC submissions with FCC ID: 2AD6G-IMACHINE-A1.

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB,200M~1GHz: 5.92 dB,1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218,the FCC Designation No. : CN1220.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062D.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

The test software 'RTLBTAPP' configured the maximum power level as below setting:

Test Software Version	RTLBTAPP		
Test Frequency	2402MHz	2441MHz	2480MHz
GFSK	7	7	7
$\pi/4$ -DQPSK	7	7	7
8DPSK	7	7	7

Equipment Modifications

No modification was made to the EUT.


Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HUAWEI	Earphone	/	/
TOSHIBA	USB HDD	v63700-A	62J5P3USTN69
Sandisk	U-DISK	4GB	001
Sandisk	U-DISK	4GB	002
Sandisk	U-DISK	4GB	003
Sandisk	U-DISK	4GB	004
Tenda	Router	D301	E3941017710003629
MAKEN	Cash Drawer	MT-350T	/
YD	PIN Pad	YD511DA-RJ	/
Sandisk	TF Card	4GB	008

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	0.45	USB HDD	EUT
RJ45 Cable	No	No	5.00	Router	EUT
RJ11 Cable	No	No	5.00	Cash Drawer	EUT
RS232 Cable	No	No	5.00	PIN Pad	EUT
Earphone	No	No	1.2	EUT	Earphone
DC Cable	No	No	1.2	Adapter	EUT

Configuration of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Prediction of power density at the distance of the applicable MPE limit:

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency Range (MHz)	Antenna Gain		Maximum Power Including Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2402-2480	3	2.00	9.2	8.32	20.00	0.003	1.0

Note: The Maximum Power Including Tolerance was declared by manufacturer.
Bluetooth and WLAN can't transmit simultaneously.

Result: Compliance, The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for BT, and the antenna gain is 3 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2017-12-11	2018-12-11
R&S	Two-line V-network	ENV 216	101614	2017-12-08	2018-12-08
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2017-09-05	2018-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	26.6 °C
Relative Humidity:	57 %
ATM Pressure:	100.5kPa

The testing was performed by Sider Huang on 2018-05-16.

Test Mode: *Transmitting***AC120V, 60 Hz, Line:**

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.152410	50.1	9.000	L1	11.2	15.8	65.9	Compliance
0.166371	43.6	9.000	L1	11.0	21.5	65.1	Compliance
0.190505	38.4	9.000	L1	10.7	25.6	64.0	Compliance
0.375019	45.9	9.000	L1	10.0	12.5	58.4	Compliance
1.239175	43.0	9.000	L1	9.8	13.0	56.0	Compliance
1.259081	47.4	9.000	L1	9.8	8.6	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.319773	23.3	9.000	L1	10.1	26.4	49.7	Compliance
0.375019	44.9	9.000	L1	10.0	3.5	48.4	Compliance
0.503608	32.7	9.000	L1	9.9	13.3	46.0	Compliance
1.090848	38.3	9.000	L1	9.8	7.7	46.0	Compliance
1.117238	39.8	9.000	L1	9.8	6.2	46.0	Compliance
1.259081	40.8	9.000	L1	9.8	5.2	46.0	Compliance

AC120V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.153629	49.4	9.000	N	11.1	16.4	65.8	Compliance
0.163741	41.3	9.000	N	11.0	24.0	65.3	Compliance
0.193566	39.6	9.000	N	10.7	24.3	63.9	Compliance
0.372042	45.4	9.000	N	10.0	13.1	58.5	Compliance
1.209904	46.0	9.000	N	9.8	10.0	56.0	Compliance
1.259081	45.3	9.000	N	9.8	10.7	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.349066	38.2	9.000	N	10.0	10.8	49.0	Compliance
0.372042	43.7	9.000	N	10.0	4.8	48.5	Compliance
1.090848	37.9	9.000	N	9.8	8.1	46.0	Compliance
1.117238	39.6	9.000	N	9.8	6.4	46.0	Compliance
1.209904	39.3	9.000	N	9.8	6.7	46.0	Compliance
1.259081	39.6	9.000	N	9.8	6.4	46.0	Compliance


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission Below 1GHz tests were performed in the 3 meters chamber A, above 1GHz tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2017-12-11	2018-12-11
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
HP	Amplifier	8447D	2727A05902	2017-09-05	2018-09-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2018-01-04	2019-01-04
ETS-Lindgren	Horn Antenna	3115	000 527 35	2016-01-05	2019-01-04
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2017-09-05	2018-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2017-06-27	2018-06-27
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2017-06-16	2018-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2017-06-16	2018-06-16
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2017-06-27	2018-06-27
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Environmental Conditions


Temperature:	24.6~24.9 °C
Relative Humidity:	43~52 %
ATM Pressure:	100.8~101 kPa

* The testing was performed by Sunny Cen&Steven Zuo on 2018-05-02 and 2018-05-16.


Test Mode: Transmitting

1) 30MHz-1GHz(8DPSK High channel was the worst)

Horizontal:



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
119.2400	33.44	QP	-5.04	28.40	43.50	15.10
239.5200	42.30	QP	-6.10	36.20	46.00	9.80
270.5600	42.48	QP	-4.28	38.20	46.00	7.80
469.4100	31.89	QP	-0.49	31.40	46.00	14.60
540.2200	34.26	QP	0.24	34.50	46.00	11.50
807.9400	36.83	QP	4.87	41.70	46.00	4.30

Vertical:

Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
64.9200	49.03	QP	-11.83	37.20	40.00	2.80
139.6100	38.22	QP	-5.72	32.50	43.50	11.00
270.5600	43.68	QP	-4.28	39.40	46.00	6.60
455.8300	39.47	QP	-1.07	38.40	46.00	7.60
538.2800	40.54	QP	0.26	40.80	46.00	5.20
809.8800	35.39	QP	4.91	40.30	46.00	5.70

2)1GHz-25GHz:*BDR Mode (GFSK):*

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	69.35	PK	H	28.10	1.80	0.00	99.25	N/A	N/A
2402.00	67.94	AV	H	28.10	1.80	0.00	97.84	N/A	N/A
2402.00	77.26	PK	V	28.10	1.80	0.00	107.16	N/A	N/A
2402.00	75.34	AV	V	28.10	1.80	0.00	105.24	N/A	N/A
2390.00	26.46	PK	V	28.08	1.80	0.00	56.34	74.00	17.66
2390.00	14.67	AV	V	28.08	1.80	0.00	44.55	54.00	9.45
4804.00	47.62	PK	V	32.91	3.17	37.20	46.50	74.00	27.50
4804.00	36.15	AV	V	32.91	3.17	37.20	35.03	54.00	18.97
7206.00	46.54	PK	V	35.74	4.82	37.23	49.87	74.00	24.13
7206.00	35.27	AV	V	35.74	4.82	37.23	38.60	54.00	15.40
Middle Channel: 2441 MHz									
2441.00	68.32	PK	H	28.18	1.82	0.00	98.32	N/A	N/A
2441.00	66.56	AV	H	28.18	1.82	0.00	96.56	N/A	N/A
2441.00	76.11	PK	V	28.18	1.82	0.00	106.11	N/A	N/A
2441.00	74.38	AV	V	28.18	1.82	0.00	104.38	N/A	N/A
4882.00	46.69	PK	V	33.06	3.27	37.21	45.81	74.00	28.19
4882.00	35.57	AV	V	33.06	3.27	37.21	34.69	54.00	19.31
7323.00	45.62	PK	V	36.04	4.62	37.38	48.90	74.00	25.10
7323.00	34.29	AV	V	36.04	4.62	37.38	37.57	54.00	16.43
High Channel: 2480 MHz									
2480.00	67.84	PK	H	28.26	1.84	0.00	97.94	N/A	N/A
2480.00	65.63	AV	H	28.26	1.84	0.00	95.73	N/A	N/A
2480.00	76.03	PK	V	28.26	1.84	0.00	106.13	N/A	N/A
2480.00	74.26	AV	V	28.26	1.84	0.00	104.36	N/A	N/A
2483.50	26.37	PK	V	28.27	1.84	0.00	56.48	74.00	17.52
2483.50	15.12	AV	V	28.27	1.84	0.00	45.23	54.00	8.77
4960.00	46.84	PK	V	33.22	3.23	37.25	46.04	74.00	27.96
4960.00	35.52	AV	V	33.22	3.23	37.25	34.72	54.00	19.28
7440.00	45.56	PK	V	36.34	4.41	37.52	48.79	74.00	25.21
7440.00	34.35	AV	V	36.34	4.41	37.52	37.58	54.00	16.42

EDR Mode ($\pi/4$ -DQPSK):




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	70.15	PK	H	28.10	1.80	0.00	100.05	N/A	N/A
2402.00	67.49	AV	H	28.10	1.80	0.00	97.39	N/A	N/A
2402.00	77.89	PK	V	28.10	1.80	0.00	107.79	N/A	N/A
2402.00	74.52	AV	V	28.10	1.80	0.00	104.42	N/A	N/A
2390.00	25.93	PK	V	28.08	1.80	0.00	55.81	74.00	18.19
2390.00	12.68	AV	V	28.08	1.80	0.00	42.56	54.00	11.44
4804.00	46.99	PK	V	32.91	3.17	37.20	45.87	74.00	28.13
4804.00	35.43	AV	V	32.91	3.17	37.20	34.31	54.00	19.69
7206.00	45.56	PK	V	35.74	4.82	37.23	48.89	74.00	25.11
7206.00	34.35	AV	V	35.74	4.82	37.23	37.68	54.00	16.32
Middle Channel: 2441 MHz									
2441.00	69.75	PK	H	28.18	1.82	0.00	99.75	N/A	N/A
2441.00	66.53	AV	H	28.18	1.82	0.00	96.53	N/A	N/A
2441.00	77.38	PK	V	28.18	1.82	0.00	107.38	N/A	N/A
2441.00	74.24	AV	V	28.18	1.82	0.00	104.24	N/A	N/A
4882.00	47.07	PK	V	33.06	3.27	37.21	46.19	74.00	27.81
4882.00	35.58	AV	V	33.06	3.27	37.21	34.70	54.00	19.30
7323.00	45.76	PK	V	36.04	4.62	37.38	49.04	74.00	24.96
7323.00	34.15	AV	V	36.04	4.62	37.38	37.43	54.00	16.57
High Channel: 2480 MHz									
2480.00	68.75	PK	H	28.26	1.84	0.00	98.85	N/A	N/A
2480.00	65.48	AV	H	28.26	1.84	0.00	95.58	N/A	N/A
2480.00	76.85	PK	V	28.26	1.84	0.00	106.95	N/A	N/A
2480.00	73.59	AV	V	28.26	1.84	0.00	103.69	N/A	N/A
2483.50	27.12	PK	V	28.27	1.84	0.00	57.23	74.00	16.77
2483.50	15.27	AV	V	28.27	1.84	0.00	45.38	54.00	8.62
4960.00	46.92	PK	V	33.22	3.23	37.25	46.12	74.00	27.88
4960.00	35.53	AV	V	33.22	3.23	37.25	34.73	54.00	19.27
7440.00	45.89	PK	V	36.34	4.41	37.52	49.12	74.00	24.88
7440.00	34.15	AV	V	36.34	4.41	37.52	37.38	54.00	16.62

EDR Mode (8-DPSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	70.53	PK	H	28.10	1.80	0.00	100.43	N/A	N/A
2402.00	67.62	AV	H	28.10	1.80	0.00	97.52	N/A	N/A
2402.00	78.08	PK	V	28.10	1.80	0.00	107.98	N/A	N/A
2402.00	75.13	AV	V	28.10	1.80	0.00	105.03	N/A	N/A
2390.00	26.34	PK	V	28.08	1.80	0.00	56.22	74.00	17.78
2390.00	13.27	AV	V	28.08	1.80	0.00	43.15	54.00	10.85
4804.00	47.05	PK	V	32.91	3.17	37.20	45.93	74.00	28.07
4804.00	35.72	AV	V	32.91	3.17	37.20	34.60	54.00	19.40
7206.00	45.83	PK	V	35.74	4.82	37.23	49.16	74.00	24.84
7206.00	34.12	AV	V	35.74	4.82	37.23	37.45	54.00	16.55
Middle Channel: 2441 MHz									
2441.00	69.54	PK	H	28.18	1.82	0.00	99.54	N/A	N/A
2441.00	66.37	AV	H	28.18	1.82	0.00	96.37	N/A	N/A
2441.00	77.16	PK	V	28.18	1.82	0.00	107.16	N/A	N/A
2441.00	74.45	AV	V	28.18	1.82	0.00	104.45	N/A	N/A
4882.00	47.00	PK	V	33.06	3.27	37.21	46.12	74.00	27.88
4882.00	35.77	AV	V	33.06	3.27	37.21	34.89	54.00	19.11
7323.00	45.89	PK	V	36.04	4.62	37.38	49.17	74.00	24.83
7323.00	34.03	AV	V	36.04	4.62	37.38	37.31	54.00	16.69
High Channel: 2480 MHz									
2480.00	68.82	PK	H	28.26	1.84	0.00	98.92	N/A	N/A
2480.00	65.37	AV	H	28.26	1.84	0.00	95.47	N/A	N/A
2480.00	77.91	PK	V	28.26	1.84	0.00	108.01	N/A	N/A
2480.00	74.62	AV	V	28.26	1.84	0.00	104.72	N/A	N/A
2483.50	26.64	PK	V	28.27	1.84	0.00	56.75	74.00	17.25
2483.50	15.22	AV	V	28.27	1.84	0.00	45.33	54.00	8.67
4960.00	47.17	PK	V	33.22	3.23	37.25	46.37	74.00	27.63
4960.00	35.83	AV	V	33.22	3.23	37.25	35.03	54.00	18.97
7440.00	45.80	PK	V	36.34	4.41	37.52	49.03	74.00	24.97
7440.00	36.09	AV	V	36.34	4.41	37.52	39.32	54.00	14.68




Worst plots(8DPSK, High channel) **Horizontal**

Fundamental
Test with Band
Rejection Filter



Vertical

Fundamental
Test with Band
Rejection Filter



FCC §15.247(a) (1) - CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2018-01-04	2019-01-04
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data**Environmental Conditions**

Temperature:	26.1~26.9 °C
Relative Humidity:	51~57 %
ATM Pressure:	100.6~100.9 kPa

* The testing was performed by Andy Huang on 2018-04-27 and 2018-04-28.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
<i>BDR</i> (<i>GFSK</i>)	Low	2402	1.00	0.69
	Middle	2441	1.00	0.69
	High	2480	1.00	0.69
EDR ($\pi/4$ -DQPSK)	Low	2402	1.00	0.89
	Middle	2441	1.00	0.89
	High	2480	1.00	0.89
<i>EDR</i> (8-DPSK)	Low	2402	1.00	0.91
	Middle	2441	1.00	0.91
	High	2480	1.00	0.91

Note: Limit= $(2/3) \times 20\text{dB bandwidth}$

BDR Mode (GFSK):


Date: 27.APR.2018 23:53:13

Middle Channel



Date: 27.APR.2018 23:54:00


High Channel



Date: 27.APR.2018 23:55:06


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 27.APR.2018 23:55:56

Middle Channel



Date: 27.APR.2018 23:56:49


High Channel



Date: 27.APR.2018 23:59:40


EDR Mode (8-DPSK):

Low Channel




Date: 28.APR.2018 00:00:32

Middle Channel



Date: 28.APR.2018 00:02:29

High Channel



Date: 28.APR.2018 00:03:49

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2018-01-04	2019-01-04
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.1 °C
Relative Humidity:	57 %
ATM Pressure:	100.6 kPa

* The testing was performed by Andy Huang on 2018-04-27.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	1.04
	Middle	2441	1.04
	High	2480	1.04
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	1.34
	Middle	2441	1.34
	High	2480	1.34
EDR Mode (8-DPSK)	Low	2402	1.36
	Middle	2441	1.36
	High	2480	1.36


BDR Mode (GFSK):

Low Channel




Date: 27.APR.2018 23:36:28

Middle Channel




Date: 27.APR.2018 23:38:07


High Channel




Date: 27.APR.2018 23:39:05

*EDR Mode ($\pi/4$ -DQPSK):***Low Channel**


Date: 27.APR.2018 23:40:55

Middle Channel

Date: 27.APR.2018 23:43:40


High Channel

Date: 27.APR.2018 23:44:45

*EDR Mode (8-DPSK):***Low Channel**


Date: 27.APR.2018 23:46:11

Middle Channel



Date: 27.APR.2018 23:48:13

High Channel



Date: 27.APR.2018 23:50:33

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2018-01-04	2019-01-04
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.9 °C
Relative Humidity:	51 %
ATM Pressure:	100.9 kPa

* The testing was performed by Andy Huang on 2018-04-28.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15



Date: 28.APR.2018 00:08:52

EDR Mode ($\pi/4$ -DQPSK):


Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



Date: 28.APR.2018 00:13:07

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15



Date: 28.APR.2018 00:19:31

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2018-01-04	2019-01-04
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.9 °C
Relative Humidity:	51 %
ATM Pressure:	100.9 kPa

* The testing was performed by Andy Huang on 2018-04-28.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.415	0.133	0.4	Compliance
	Middle	0.413	0.132	0.4	Compliance
	High	0.413	0.132	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.683	0.269	0.4	Compliance
	Middle	1.683	0.269	0.4	Compliance
	High	1.683	0.269	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.946	0.314	0.4	Compliance
	Middle	2.946	0.314	0.4	Compliance
	High	2.946	0.314	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

DH1: Low Channel




Date: 28.APR.2018 18:12:46

DH1: Middle Channel




Date: 28.APR.2018 18:12:59

DH1: High Channel




Date: 28.APR.2018 18:13:19

DH3: Low Channel




Date: 28.APR.2018 18:14:07

DH3: Middle Channel




Date: 28.APR.2018 18:14:20

DH3: High Channel




Date: 28.APR.2018 18:14:34

DH5: Low Channel




Date: 28.APR.2018 18:15:27

DH5: Middle Channel



Date: 28.APR.2018 18:15:37

DH5: High Channel




Date: 28.APR.2018 18:15:46

EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
2DH1	Low	0.423	0.135	0.4	Compliance
	Middle	0.423	0.135	0.4	Compliance
	High	0.423	0.135	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
2DH3	Low	1.689	0.270	0.4	Compliance
	Middle	1.689	0.270	0.4	Compliance
	High	1.689	0.270	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
2DH5	Low	2.946	0.314	0.4	Compliance
	Middle	2.946	0.314	0.4	Compliance
	High	2.956	0.315	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

2DH1: Low Channel




Date: 28.APR.2018 18:16:22

2DH1: Middle Channel




Date: 28.APR.2018 18:16:31

2DH1: High Channel




Date: 28.APR.2018 18:16:40

2DH3: Low Channel




Date: 28.APR.2018 18:17:03

2DH3: Middle Channel




Date: 28.APR.2018 18:17:11

2DH3: High Channel




Date: 28.APR.2018 18:17:21


2DH5: Low Channel



Date: 28.APR.2018 18:17:47

2DH5: Middle Channel


Date: 28.APR.2018 18:17:56

2DH5: High Channel

Date: 28.APR.2018 18:18:04


EDR Mode (8-DPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
3DH1	Low	0.425	0.136	0.4	Compliance
	Middle	0.425	0.136	0.4	Compliance
	High	0.423	0.135	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
3DH3	Low	1.698	0.272	0.4	Compliance
	Middle	1.689	0.270	0.4	Compliance
	High	1.689	0.270	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
3DH5	Low	2.956	0.315	0.4	Compliance
	Middle	2.946	0.314	0.4	Compliance
	High	2.946	0.314	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

3DH1: Low Channel


Date: 28.APR.2018 18:18:34

3DH1: Middle Channel




Date: 28.APR.2018 18:19:04

3DH1: High Channel




Date: 28.APR.2018 18:22:26

3DH3: Low Channel




Date: 28.APR.2018 18:24:48


3DH3: Middle Channel




Date: 28.APR.2018 18:25:11

3DH3: High Channel


Date: 28.APR.2018 18:25:26

3DH5: Low Channel

Date: 28.APR.2018 18:26:02

3DH5: Middle Channel

Date: 28.APR.2018 18:26:38

3DH5: High Channel

Date: 28.APR.2018 18:26:49

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2017-12-11	2018-12-11
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.9 °C
Relative Humidity:	51 %
ATM Pressure:	100.9 kPa

* The testing was performed by Andy Huang on 2018-04-28.

Test Result: Compliance.

Test Mode: Transmitting

Mode	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	2402	8.10	21
	2441	7.68	21
	2480	6.90	21
EDR Mode ($\pi/4$ -DQPSK)	2402	9.03	21
	2441	8.60	21
	2480	7.90	21
EDR Mode (8-DPSK)	2402	9.13	21
	2441	8.71	21
	2480	9.14	21

Note: The data above was tested in conducted mode.

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2018-01-04	2019-01-04
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data**Environmental Conditions**

Temperature:	26.1~26.9 °C
Relative Humidity:	51~57 %
ATM Pressure:	100.6~100.9 kPa

* The testing was performed by Andy Huang on 2018-04-27 and 2018-04-28.


Test Result: Compliance

Single Channel Mode,
BDR Mode (GFSK):

Band Edge, Left Side

Date: 27.APR.2018 23:37:17


Band Edge, Right Side




Date: 27.APR.2018 23:39:49

EDR Mode ($\pi/4$ -DQPSK):


Band Edge, Left Side




Date: 27.APR.2018 23:41:38

Band Edge, Right Side

Date: 27.APR.2018 23:45:34


*EDR Mode (8-DPSK):***Band Edge, Left Side**

Date: 27.APR.2018 23:47:00




Date: 27.APR.2018 23:51:16


Hopping Mode,
BDR Mode (GFSK):




Date: 28.APR.2018 18:36:40

Band Edge, Right Side


Date: 28.APR.2018 18:39:15

*EDR Mode ($\pi/4$ -DQPSK):***Band Edge, Left Side**

Date: 28.APR.2018 18:42:33


Band Edge, Right Side

Date: 28.APR.2018 18:45:47

EDR Mode (8-DPSK)**Band Edge, Left Side**

Date: 28.APR.2018 18:51:47

Band Edge, Right Side



Date: 28.APR.2018 18:49:05

***** END OF REPORT *****