

# TEST REPORT

## Client Information:

Applicant: Shenzhen Zidoo Technology Co., Ltd  
Applicant add.: Room 1301,1302,1303,1307, Chentian R&D Building, No. 50 Baotian First Road, Chentian Community, Xixiang Street, Baoan District, Shenzhen  
Manufacturer: Shenzhen Zidoo Technology Co., Ltd  
Manufacturer add.: Room 1301,1302,1303,1307, Chentian R&D Building, No. 50 Baotian First Road, Chentian Community, Xixiang Street, Baoan District, Shenzhen

## Product Information:

Product Name: 8K UHD MEDIA PLAYER  
Model No.: ZD24S  
Serial Model: Z9X ULTRA, Z30 PRO,Z9X 8K,Z9G ULTRA  
Brand Name: ZIDOO  
Test samples.: AITSZ24052402-1  
FCC ID: 2AGN7-ZD24S

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

## Prepared By:

### Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Tel.: +86 0755-230967639 Fax.: +86 0755-230967639

Date of Receipt: May 24, 2024

Date of Test: May 24, 2024 ~ Jun. 28, 2024

Date of Issue: Jun. 28, 2024

Test Result: Pass

This device described above has been tested by Guangdong Asia Hongke Test Technology Limited and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Note: This report shall not be reproduced except in full, without the written approval of Guangdong Asia Hongke Test Technology Limited, this document may be altered or revised by Guangdong Asia Hongke Test Technology Limited, personal only, and shall be noted in the revision of the document. This test report must not be used by the client to claim product endorsement.

Reviewed by:

Leon Yi

Leon.yi

Approved by:

Sean She

Sean She



Guangdong Asia Hongke Test Technology Limited  
B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.

# 1 Contents

|   | Page      |
|---|-----------|
| COVER PAGE  |           |
| <b>1 CONTENTS</b>                                   | <b>2</b>  |
| <b>2 TEST SUMMARY</b>                               | <b>5</b>  |
| 2.1 Statement of the Measurement Uncertainty        | 5         |
| 2.2 Measurement Uncertainty                         | 5         |
| <b>3 TEST FACILITY</b>                              | <b>6</b>  |
| 3.1 Deviation from standard                         | 6         |
| 3.2 Abnormalities from standard conditions          | 6         |
| 3.3 Test Location                                   | 6         |
| <b>4 GENERAL INFORMATION</b>                        | <b>7</b>  |
| 4.1 Test frequencies                                | 8         |
| 4.2 EUT Peripheral List                             | 9         |
| 4.3 Test Peripheral List                            | 9         |
| 4.4 TEST METHODOLOGY                                | 10        |
| 4.5 Description of Test Modes                       | 11        |
| <b>5 EQUIPMENT USED DURING TEST</b>                 | <b>12</b> |
| <b>6 TEST RESULTS AND MEASUREMENT DATA</b>          | <b>13</b> |
| 6.1 Antenna requirement                             | 13        |
| 6.1.1 Standard requirement:                         | 13        |
| 6.1.2 EUT Antenna:                                  | 13        |
| 6.2 On Time and Duty Cycle                          | 14        |
| 6.2.1 Standard requirement:                         | 14        |
| 6.2.2 Measuring Instruments and Setting:            | 14        |
| 6.2.3 Test Procedures                               | 14        |
| 6.2.4 Test Setup Layout                             | 14        |
| 6.2.5 EUT Operation during Test                     | 14        |
| 6.2.6 Test result                                   | 14        |
| 6.3 Maximum Conducted Output Peak Power Measurement | 15        |
| 6.3.1 Standard requirement:                         | 15        |
| 6.3.2 Measuring Instruments:                        | 15        |
| 6.3.3 Test Procedures:                              | 15        |
| 6.3.4 Test Setup Layout                             | 15        |
| 6.3.5 EUT Operation during Test                     | 15        |
| 6.3.6 Test result                                   | 16        |
| 6.4 6 dB Spectrum Bandwidth Measurement             | 17        |
| 6.4.1 Standard requirement:                         | 17        |
| 6.4.2 Measuring Instruments:                        | 17        |
| 6.4.3 Test Procedures                               | 17        |

|       |  |    |
|-------|--|----|
| 6.4.4 | Test Setup Layout .....  | 17 |
| 6.4.5 | EUT Operation during Test.....                                     | 17 |
| 6.4.6 | Test result .....  | 17 |
| 6.5   | Power Spectral Density .....                                       | 18 |
| 6.5.1 | Standard requirement:.....   | 18 |
| 6.5.2 | Measuring Instruments and Setting: .....                           | 18 |
| 6.5.3 | Test Procedures .....  | 18 |
| 6.5.4 | Test Setup Layout .....  | 18 |
| 6.5.5 | EUT Operation during Test.....                                     | 18 |
| 6.5.6 | Test result .....  | 19 |
| 6.6   | Conducted Spurious Emissions and Band Edges Test.....              | 20 |
| 6.6.1 | Standard requirement:.....   | 20 |
| 6.6.2 | Measuring Instruments and Setting: .....                           | 20 |
| 6.6.3 | Test Procedures .....  | 20 |
| 6.6.4 | Test Setup Layout .....  | 20 |
| 6.6.5 | EUT Operation during Test.....                                     | 20 |
| 6.6.6 | Test result .....  | 21 |
| 6.7   | Radiated Emissions and Radiation Restricted band Measurement ..... | 22 |
| 6.7.1 | Standard requirement:.....   | 22 |
| 6.7.2 | Measuring Instruments and Setting: .....                           | 23 |
| 6.7.3 | Test Procedures .....  | 23 |
| 6.7.4 | Test Setup Layout .....  | 26 |
| 6.7.5 | EUT Operation during Test.....                                     | 27 |
| 6.7.6 | Test result .....  | 27 |
| 6.8   | Conducted Emissions.....   | 34 |
| 6.8.1 | Standard requirement:.....   | 34 |
| 6.8.2 | Test Setup Layout .....  | 34 |
| 6.8.3 | Test Procedures .....  | 34 |
| 6.8.4 | EUT Operation during Test.....                                     | 34 |
| 6.8.5 | Test result .....  | 34 |
| 7     | TEST SETUP PHOTOGRAPHS OF EUT.....                                 | 37 |
| 8     | EXTERNAL PHOTOGRAPHS OF EUT .....                                  | 37 |
| 9     | INTERNAL PHOTOGRAPHS OF EUT .....                                  | 37 |



**REPORT REVISE RECORD**

| Report Version | Revise Time | Issued Date   | Valid Version | Notes           |
|----------------|-------------|---------------|---------------|-----------------|
| V1.0           | /           | Jun. 28, 2024 | Valid         | Initial release |

## 2 Test Summary

| Test Item                                 | Section in CFR 47 | Result |
|---|-------------------|--------|
| Antenna requirement                       | §15.203           | Pass   |
| On Time and Duty Cycle                    | /                 | /      |
| Maximum Conducted Peak Output Power       | §15.247 (b)(3)    | Pass   |
| Power Spectral Density                    | §15.247 (e)       | Pass   |
| 6dB Bandwidth                             | §15.247 (a)(2)    | Pass   |
| Radiated and Conducted Spurious Emissions | §15.205/15.209    | PASS   |
| Emissions at Restricted Band              | §15.205/15.209    | Pass   |
| Conducted Emissions                       | §15.207(a)        | Pass   |
| RF Exposure                               | §15.247(i)§2.1091 | Pass   |

### Note

1. Test according to ANSI C63.10:2013.
2. The measurement uncertainty is not included in the test result.
3. Test results in other test report (RF Exposure Evaluation Report)

### 2.1 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the AiT quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

### 2.2 Measurement Uncertainty

| Test Item                        | Frequency Range | Measurement Uncertainty | Notes |
|----------------------------------|-----------------|-------------------------|-------|
| Radiated Emission                | 0.009MHz-30MHz  | 3.10dB                  | (1)   |
| Radiated Emission                | 30MHz-1GHz      | 3.75dB                  | (1)   |
| Radiated Emission                | 1GHz-18GHz      | 3.88dB                  | (1)   |
| Radiated Emission                | 18GHz-40GHz     | 3.88dB                  | (1)   |
| AC Power Line Conducted Emission | 0.15MHz ~ 30MHz | 1.20dB                  | (1)   |

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

### 3 Test Facility

**The test facility is recognized, certified or accredited by the following organizations:**

**FCC-Registration No.: 251906 Designation Number: CN1376**

Guangdong Asia Hongke Test Technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

**IC —Registration No.: 31737 CAB identifier: CN0165**

The 3m Semi-anechoic chamber of Guangdong Asia Hongke Test Technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 31737

**A2LA-Lab Cert. No.: 7133.01**

Guangdong Asia Hongke Test Technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### 3.1 Deviation from standard

None

#### 3.2 Abnormalities from standard conditions

None

#### 3.3 Test Location

**Guangdong Asia Hongke Test Technology Limited**

Address: B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Tel.: +86 0755-230967639 Fax.: +86 0755-230967639

## 4 General Information

|                        |   |
|------------------------|---|
| EUT Name:              | 8K UHD MEDIA PLAYER   |
| Model No:              | ZD24S   |
| Brand Name:            | ZIDOO   |
| Serial Model:          | Z9X ULTRA,Z30 PRO,Z9X 8K,Z9G ULTRA  |
| Sample(s) Status:      | Engineer sample   |
| Operation frequency:   | 802.11b/802.11g /802.11n(HT20) /802.11ax(HE20): 2412MHz~2462MHz<br>802.11n(HT40)/ 802.11ax(HE40): 2422MHz~2452MHz   |
| Channel Number:        | 802.11b/802.11g /802.11n(HT20) /802.11ax(HE20): 11<br>802.11n(HT40) /802.11ax(HE40): 7  |
| Channel separation:    | 5MHz  |
| Modulation Technology: | 802.11b(DSSS):CCK,DQPSK,DBPSK<br>802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM<br>802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM<br>802.11ax(OFDM):BPSK,QPSK,16-QAM,64-QAM |
| Antenna Type:          | Stick Antenna   |
| Antenna gain:          | Ant1&Ant2: 2.88dBi  |
| H/W No.:               | N/A   |
| S/W No.:               | N/A   |
| Adapter:               | Input: 100-240V 50/60Hz 0.8A<br>Output: 12V=2A 24W  |
| Model different:       | Different model names   |

Note:

For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

#### 4.1 Test frequencies

EUT channels and frequencies list:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 1       | 2412MHz         | 5       | 2432MHz         | 9       | 2452MHz         |
| 2       | 2417MHz         | 6       | 2437MHz         | 10      | 2457MHz         |
| 3       | 2422MHz         | 7       | 2442MHz         | 11      | 2462MHz         |
| 4       | 2427MHz         | 8       | 2447MHz         | -       | -               |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

|                        |   |          |          |
|------------------------|---|----------|----------|
| Transmitting mode      | Keep the EUT in continuously transmitting mode. |          |          |
| Test software:         | *##9646633##*                                   |          |          |
| Frequency              | 2412 MHz  | 2437 MHz | 2462 MHz |
| Parameters(802.11b)    | Default   | Default  | Default  |
| Parameters(802.11g)    | Default   | Default  | Default  |
| Parameters(802.11n20)  | Default   | Default  | Default  |
| Parameters(802.11ax20) | Default   | Default  | Default  |
| Frequency              | 2422MHz   | 2437MHz  | 2452MHz  |
| Parameters(802.11n40)  | Default   | Default  | Default  |
| Parameters(802.11ax40) | Default   | Default  | Default  |



#### 4.2 EUT Peripheral List

| No. | Equipment | Manufacturer | EMC Compliance | Model No. | Serial No. | Power cord | Remark |
|-----|-----------|--------------|----------------|-----------|------------|------------|--------|
| 1   | N/A       | N/A          | N/A            | N/A       | N/A        | N/A        | N/A    |

#### 4.3 Test Peripheral List

| No. | Equipment | Manufacturer | EMC Compliance | Model No. | Serial No. | Power cord | Signal cord |
|-----|-----------|--------------|----------------|-----------|------------|------------|-------------|
| 1   | Notebook  | DELL         | VOSTRO.3800    | DELL      | N/A        | N/A        | N/A         |
| 2   | USB Cable | N/A          | N/A            | 100cm     | N/A        | N/A        | N/A         |

## 4.4 TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Guangdong Asia Hongke Test Technology Limited

### 4.4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 4.4.2 EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209, 15.247 under the FCC Rules Part 15 Subpart C, ANSI C63.10-2013.

### 4.4.3 General Test Procedures

#### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.

## 4.5 Description of Test Modes

The EUT has been tested under operating condition.

AC main conducted emission pre-test voltage at both AC 120V/60Hz and AC 240V/50Hz, recorded worst case;

AC main conducted emission pre-test at charge from power adapter modes, recorded worst case;

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be IEEE 802.11b mode (LCH).

Verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

| Mode      | IEEE 802.11b        | IEEE 802.11g        | IEEE 802.11n(HT20) | IEEE 802.11n(HT40) |
|-----------|---------------------|---------------------|--------------------|--------------------|
| Data rate | 1Mbps               | 6Mbps               | MCS0               | MCS0               |
| Mode      | IEEE 802.11ax(HE20) | IEEE 802.11ax(HE40) |                    |                    |
| Data rate | MCS0                | MCS0                |                    |                    |

### Antenna & Bandwidth

| Antenna        | Chain 1 (ANT1)                      |                                     | Chain 2 (ANT2)                      |                                     | Simultaneously                      |
|----------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Bandwidth Mode | 20MHz                               | 40MHz                               | 20MHz                               | 40MHz                               | /                                   |
| IEEE 802.11b   | <input checked="" type="checkbox"/> | <input type="checkbox"/>            | <input checked="" type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/>            |
| IEEE 802.11g   | <input checked="" type="checkbox"/> | <input type="checkbox"/>            | <input checked="" type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/>            |
| IEEE 802.11n   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| IEEE 802.11ax  | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |

## 5 Equipment Used during Test

| No | Test Equipment                      | Manufacturer | Model No        | Serial No    | Cal. Date  | Cal. Due Date |
|----|-------------------------------------|--------------|-----------------|--------------|------------|---------------|
| 1  | Spectrum Analyzer                   | R&S          | FSV40           | 101470       | 2023.09.08 | 2024.09.07    |
| 2  | Spectrum Analyzer                   | Keysight     | N9020A          | MY51280643   | 2023.09.08 | 2024.09.07    |
| 3  | EMI Measuring Receiver              | R&S          | ESR             | 101660       | 2023.09.08 | 2024.09.07    |
| 4  | Low Noise Pre-Amplifier             | HP           | HP8447E         | 1937A01855   | 2023.09.08 | 2024.09.07    |
| 5  | Low Noise Pre-Amplifier             | Tsj          | MLA-0120-A02-34 | 2648A04738   | 2023.09.08 | 2024.09.07    |
| 6  | Passive Loop                        | ETS          | 6512            | 00165355     | 2022.09.04 | 2024.09.03    |
| 7  | TRILOG Super Broadband test Antenna | SCHWARZBECK  | VULB9160        | 9160-3206    | 2021.08.29 | 2024.08.28    |
| 8  | Broadband Horn Antenna              | SCHWARZBECK  | BBHA9120D       | 452          | 2021.08.29 | 2024.08.28    |
| 9  | SHF-EHF Horn Antenna 15-40GHz       | SCHWARZBECK  | BBHA9170        | BBHA9170367d | 2021.08.29 | 2024.08.28    |
| 10 | EMI Measuring Receiver              | R&S          | ESR             | 101160       | 2023.09.13 | 2024.09.12    |
| 11 | LISN                                | SCHWARZBECK  | NNLK 8129       | 8130179      | 2023.10.29 | 2024.10.28    |
| 12 | Pulse Limiter                       | R&S          | ESH3-Z2         | 102789       | 2023.09.13 | 2024.09.12    |
| 13 | Pro.Temp&Humi.chamber               | MENTEK       | MHP-150-1C      | MAA08112501  | 2023.09.08 | 2024.09.07    |
| 14 | RF Automatic Test system            | MW           | MW100-RFCB      | 21033016     | 2023.09.08 | 2024.09.07    |
| 15 | Signal Generator                    | Agilent      | N5182A          | MY50143009   | 2023.09.08 | 2024.09.07    |
| 16 | Wideband Radio communication tester | R&S          | CMW500          | 1201.0002K50 | 2023.09.08 | 2024.09.07    |
| 17 | RF Automatic Test system            | MW           | MW100-RFCB      | 21033016     | 2023.09.08 | 2024.09.07    |
| 18 | DC power supply                     | ZHAOXIN      | RXN-305D-2      | 28070002559  | N/A        | N/A           |
| 19 | RE Software                         | EZ           | EZ-EMC_RE       | Ver.AIT-03A  | N/A        | N/A           |
| 20 | CE Software                         | EZ           | EZ-EMC_CE       | Ver.AIT-03A  | N/A        | N/A           |
| 21 | RF Software                         | MW           | MTS 8310        | 2.0.0.0      | N/A        | N/A           |
| 22 | temporary antenna connector(Note)   | NTS          | R001            | N/A          | N/A        | N/A           |

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

## 6 Test results and Measurement Data

### 6.1 Antenna requirement

#### 6.1.1 Standard requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

#### 6.1.2 EUT Antenna:

*The antenna is Stick Antenna, the best case gain of the antenna is Ant1: 2.88dBi, Ant2: 2.88dBi reference to the Internal photos for details*

## 6.2 On Time and Duty Cycle

### 6.2.1 Standard requirement:

None; for reporting purpose only


### 6.2.2 Measuring Instruments and Setting:

Please refer to equipments list in this report. The following table is the setting of the spectrum analyser.

### 6.2.3 Test Procedures

1. Set the centre frequency of the spectrum analyser to the transmitting frequency;
2. Set the span=0MHz, RBW=8MHz, VBW=50MHz, Sweep time=20.27ms;
3. Detector = peak;
4. Trace mode = Single hold

### 6.2.4 Test Setup Layout



### 6.2.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 6.2.6 Test result

*For reporting purpose only.*

***Please refer to Appendix C***

## 6.3 Maximum Conducted Output Peak Power Measurement

### 6.3.1 Standard requirement:

According to §15.247(b): For systems using digital modulation in the 2400-2483.5 MHz and 5725-5850 MHz band, the limit for maximum peak conducted output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter peak output power. RSS-247 section 5.4 d): For DTSS employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.


### 6.3.2 Measuring Instruments:

Please refer to equipment's list in this report.

### 6.3.3 Test Procedures:

According to KDB558074 D01 15.247 Meas Guidance v05r02 Section 9.1 Maximum peak conducted output power, 9.1.2 The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

### 6.3.4 Test Setup Layout



### 6.3.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

**6.3.6 Test result**

PASS

**Please refer to Appendix C**

Remark:

1). Measured output power at difference data rate for each mode and recorded worst case for each mode.

2). Test results including cable loss;

3). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; MCS0 at IEEE 802.11n HT20; MCS0 at IEEE 802.11n HT40; MCS0 at IEEE 802.11ax HT20; MCS0 at IEEE 802.11ax HT40.



## 6.4 6 dB Spectrum Bandwidth Measurement

### 6.4.1 Standard requirement:

According to §15.247(a) (2): For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.4.2 Measuring Instruments:

Please refer to equipment's list in this report.


Please refer to equipment list in this report. The following table is the setting of the Spectrum Analyzer.

| Spectrum Parameter | Setting |
|--------------------|---------|
| Attenuation        | Auto    |
| RBW                | 100KHz  |
| VBW                | 300KHz  |
| Span Frequency     | 30MHz   |
| Detector           | Peak    |

### 6.4.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth and the video bandwidth were set according to KDB558074.
3. Measured the spectrum width with power higher than 6dB below carrier.

### 6.4.4 Test Setup Layout



### 6.4.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 6.4.6 Test result

PASS

**Please refer to Appendix C**

Remark:

- 1). Measured 6dB Bandwidth at difference data rate for each mode and recorded worst case for each mode.
- 2). Test results including cable loss;
- 3). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; MCS0 at IEEE 802.11n HT20; MCS0 at IEEE 802.11n HT40; MCS0 at IEEE 802.11ax HT20; MCS0 at IEEE 802.11ax HT40.

## 6.5 Power Spectral Density

### 6.5.1 Standard requirement:

According to §15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


### 6.5.2 Measuring Instruments and Setting:

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

### 6.5.3 Test Procedures

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
3. Set the RBW = 3 kHz.
4. Set the VBW  $\geq 3 \times \text{RBW}$
5. Set the span to 1.5 times the DTS channel bandwidth.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum power level.
11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
12. The resulting peak PSD level must shall not be greater than 8dBm in any 3 kHz..

### 6.5.4 Test Setup Layout



### 6.5.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 6.5.6 Test result

PASS

**Please refer to Appendix C**

Remark:

- 1). Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode;
- 2). Test results including cable loss;
- 3). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; MCS0 at IEEE 802.11n HT20; MCS0 at IEEE 802.11n HT40; MCS0 at IEEE 802.11ax HT20; MCS0 at IEEE 802.11ax HT40.

## 6.6 Conducted Spurious Emissions and Band Edges Test

### 6.6.1 Standard requirement:

According to §15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 6.6.2 Measuring Instruments and Setting:

Please refer to equipment list in this report. The following table is the setting of the spectrum analyzer.


| Spectrum Parameter                        | Setting       |
|---|---------------|
| Detector                                  | Peak          |
| Attenuation                               | Auto          |
| RB / VB (Emission in restricted band)     | 100KHz/300KHz |
| RB / VB (Emission in non-restricted band) | 100KHz/300KHz |

### 6.6.3 Test Procedures

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz

The spectrum from 9 kHz to 26.5GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

### 6.6.4 Test Setup Layout



### 6.6.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 6.6.6 Test result

PASS

***Please refer to Appendix C for conducted band edge emission.***

***Please refer to Appendix C for conducted spurious emissions;***

#### Remark:

- 1). Measured at difference data rate for each mode and recorded worst case for each mode.
- 2). Test results including cable loss;
- 3). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; MCS0 at IEEE 802.11n HT20; MCS0 at IEEE 802.11n HT40; MCS0 at IEEE 802.11ax HT20; MCS0 at IEEE 802.11ax HT40.
- 4). Not recorded test plots from 9 KHz to 30 MHz as emission levels 20dB lower than emission limit.

## 6.7 Radiated Emissions and Radiation Restricted band Measurement

### 6.7.1 Standard requirement:

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz               | MHz                 | MHz           | GHz         |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110       | 16.42-16.423        | 399.9-410     | 4.5-5.15    |
| \1\ 0.495-0.505   | 16.69475-16.69525   | 608-614       | 5.35-5.46   |
| 2.1735-2.1905     | 16.80425-16.80475   | 960-1240      | 7.25-7.75   |
| 4.125-4.128       | 25.5-25.67          | 1300-1427     | 8.025-8.5   |
| 4.17725-4.17775   | 37.5-38.25          | 1435-1626.5   | 9.0-9.2     |
| 4.20725-4.20775   | 73-74.6             | 1645.5-1646.5 | 9.3-9.5     |
| 6.215-6.218       | 74.8-75.2           | 1660-1710     | 10.6-12.7   |
| 6.26775-6.26825   | 108-121.94          | 1718.8-1722.2 | 13.25-13.4  |
| 6.31175-6.31225   | 123-138             | 2200-2300     | 14.47-14.5  |
| 8.291-8.294       | 149.9-150.05        | 2310-2390     | 15.35-16.2  |
| 8.362-8.366       | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4   |
| 8.37625-8.38675   | 156.7-156.9         | 2690-2900     | 22.01-23.12 |
| 8.41425-8.41475   | 162.0125-167.17     | 3260-3267     | 23.6-24.0   |
| 12.29-12.293.     | 167.72-173.2        | 3332-3339     | 31.2-31.8   |
| 12.51975-12.52025 | 240-285             | 3345.8-3358   | 36.43-36.5  |
| 12.57675-12.57725 | 322-335.4           | 3600-4400     | (\2\)       |
| 13.36-13.41       |                     |               |             |

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490       | 2400/F(KHz)                       | 300                           |
| 0.490~1.705       | 24000/F(KHz)                      | 30                            |
| 1.705~30.0        | 30                                | 30                            |
| 30~88             | 100                               | 3                             |
| 88~216            | 150                               | 3                             |
| 216~960           | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

### 6.7.2 Measuring Instruments and Setting:

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter                        | Setting   |
|---|---|
| Attenuation                               | Auto  |
| Start Frequency                           | 1000 MHz  |
| Stop Frequency                            | 10 <sup>th</sup> carrier harmonic                 |
| RB / VB (Emission in restricted band)     | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |

| Receiver Parameter     | Setting                                    |
|------------------------|--|
| Attenuation            | Auto                                       |
| Start ~ Stop Frequency | 9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG  |
| Start ~ Stop Frequency | 150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB/VB 120kHz/1MHz for QP   |

### 6.7.3 Test Procedures

#### 1) Sequence of testing 9 kHz to 30 MHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

##### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

##### Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor,

margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.



### 3) Sequence of testing 1 GHz to 18 GHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

#### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

#### 4) Sequence of testing above 18 GHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.


##### Premeasurement:


- The antenna is moved spherical over the EUT in different polarisations of the antenna.

##### Final measurement:


- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

#### 6.7.4 Test Setup Layout





Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

### 6.7.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 6.7.6 Test result

|                |                  |          |     |
|----------------|------------------|----------|-----|
| Temperature    | 26°C             | Humidity | 54% |
| Configurations | IEEE 802.11b/g/n |          |     |

Remarks:

1. Only the worst case Main Antenna test data.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

**■ Results of Radiated Emissions (9 KHz~30MHz)**

| Freq.<br>(MHz) | Level<br>(dBuV) | Over Limit<br>(dB) | Over Limit<br>(dBuV) | Remark   |
|----------------|-----------------|--------------------|----------------------|----------|
| -              | -               | -                  | -                    | See Note |

**Note:**

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

## Results of Radiated Emissions (30MHz~1GHz)

Pre-scan all test modes, found worst case at IEEE 802.11ax20 (middle Channel), recorded the worst case results in this report (IEEE 802.11ax20 (middle Channel)).

|                |          |              |  |
|----------------|----------|--------------|--|
| Model name:    | ZD24S    | Test Date :  | 2024-05-27   |
| Polarization : | Vertical | Test Result: | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail |



Remark:


Emission Level = Reading + Factor;

Factor = Antenna Factor + Cable Loss – Pre-amplifier;

Margin= Emission Level - Limit.

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|
| 1   | 33.1530         | 43.12          | -17.35        | 25.77          | 40.00          | -14.23      | QP   |
| 2 * | 58.7773         | 53.60          | -17.19        | 36.41          | 40.00          | -3.59       | QP   |
| 3   | 71.9075         | 52.91          | -19.29        | 33.62          | 40.00          | -6.38       | QP   |
| 4   | 117.2369        | 42.37          | -18.69        | 23.68          | 43.50          | -19.82      | QP   |
| 5   | 234.4970        | 48.14          | -19.42        | 28.72          | 46.00          | -17.28      | QP   |
| 6   | 827.2033        | 41.07          | -5.67         | 35.40          | 46.00          | -10.60      | QP   |

|                |            |              |  |
|----------------|------------|--------------|--|
| Model name:    | ZD24S      | Test Date :  | 2024-05-27   |
| Polarization : | Horizontal | Test Result: | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail |



Remark:

Emission Level = Reading + Factor;

Factor = Antenna Factor + Cable Loss – Pre-amplifier;

Margin= Emission Level - Limit.

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|
| 1   | 59.2532         | 41.10          | -17.21        | 23.89          | 40.00          | -16.11      | QP   |
| 2   | 71.5053         | 40.42          | -19.21        | 21.21          | 40.00          | -18.79      | QP   |
| 3   | 160.7961        | 35.85          | -16.56        | 19.29          | 43.50          | -24.21      | QP   |
| 4   | 242.6954        | 51.10          | -18.78        | 32.32          | 46.00          | -13.68      | QP   |
| 5   | 338.2814        | 45.28          | -15.98        | 29.30          | 46.00          | -16.70      | QP   |
| 6 * | 774.9733        | 40.05          | -6.43         | 33.62          | 46.00          | -12.38      | QP   |

## Results for Radiated Emissions (1- 26 GHz)

Note: All modes have been tested, the worst mode is 802.11ax20, and this report only shows the worst case.

802.11ax20\_2412M

H

| Frequency | Meter Reading | Factor | Emission Level | Limits   | Margin | Detector Type |
|-----------|---------------|--------|----------------|----------|--------|---------------|
| (MHz)     | (dBμV)        | (dB/m) | (dBμV/m)       | (dBμV/m) | (dB)   |               |
| 4824      | 47.36         | 5.08   | 52.44          | 74       | -21.56 | PEAK          |
| 4824      | 36.21         | 5.08   | 41.29          | 54       | -12.71 | AVG           |
| 7236      | 45.22         | 7.55   | 52.77          | 74       | -21.23 | PEAK          |
| 7236      | 29.67         | 7.55   | 37.22          | 54       | -16.78 | AVG           |

V

| Frequency | Meter Reading | Factor | Emission Level | Limits   | Margin | Detector Type |
|-----------|---------------|--------|----------------|----------|--------|---------------|
| (MHz)     | (dBμV)        | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   |               |
| 4824      | 47.01         | 5.08   | 52.09          | 74       | -21.91 | PEAK          |
| 4824      | 37.06         | 5.08   | 42.14          | 54       | -11.86 | AVG           |
| 7236      | 43.53         | 7.55   | 51.08          | 74       | -22.92 | PEAK          |
| 7236      | 31.16         | 7.55   | 38.71          | 54       | -15.29 | AVG           |

802.11ax20\_2437M

H

| Frequency | Meter Reading | Factor | Emission Level | Limits   | Margin | Detector Type |
|-----------|---------------|--------|----------------|----------|--------|---------------|
| (MHz)     | (dBμV)        | (dB/m) | (dBμV/m)       | (dBμV/m) | (dB)   |               |
| 4874      | 46.35         | 5.13   | 51.48          | 74       | -22.52 | PEAK          |
| 4874      | 37.11         | 5.13   | 42.24          | 54       | -11.76 | AVG           |
| 7311      | 46.27         | 7.49   | 53.76          | 74       | -20.24 | PEAK          |
| 7311      | 30.53         | 7.49   | 38.02          | 54       | -15.98 | AVG           |

V

| Frequency | Meter Reading | Factor | Emission Level | Limits   | Margin | Detector Type |
|-----------|---------------|--------|----------------|----------|--------|---------------|
| (MHz)     | (dBμV)        | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   |               |
| 4874      | 46.78         | 5.13   | 51.91          | 74       | -22.09 | PEAK          |
| 4874      | 34.87         | 5.13   | 40.00          | 54       | -14.00 | AVG           |
| 7311      | 46.32         | 7.49   | 53.81          | 74       | -20.19 | PEAK          |
| 7311      | 29.94         | 7.49   | 37.43          | 54       | -16.57 | AVG           |

802.11ax20\_2462M

H

| Frequency | Meter Reading | Factor | Emission Level | Limits   | Margin | Detector Type |
|-----------|---------------|--------|----------------|----------|--------|---------------|
| (MHz)     | (dBμV)        | (dB/m) | (dBμV/m)       | (dBμV/m) | (dB)   |               |
| 4924      | 45.21         | 5.18   | 50.39          | 74       | -23.61 | PEAK          |
| 4924      | 35.93         | 5.18   | 41.11          | 54       | -12.89 | AVG           |
| 7386      | 44.21         | 7.82   | 52.03          | 74       | -21.97 | PEAK          |
| 7386      | 32.10         | 7.82   | 39.92          | 54       | -14.08 | AVG           |

V

| Frequency | Meter Reading | Factor | Emission Level | Limits   | Margin | Detector Type |
|-----------|---------------|--------|----------------|----------|--------|---------------|
| (MHz)     | (dBμV)        | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   |               |
| 4924      | 46.62         | 5.18   | 51.80          | 74       | -22.20 | PEAK          |
| 4924      | 35.22         | 5.18   | 40.40          | 54       | -13.60 | AVG           |
| 7386      | 43.66         | 7.82   | 51.48          | 74       | -22.52 | PEAK          |
| 7386      | 30.52         | 7.82   | 38.34          | 54       | -15.66 | AVG           |

#### Notes:

- 1). Measuring frequencies from 9 KHz - 10<sup>th</sup> harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.
- 2). Radiated emissions measured in frequency range from 9 KHz~10th harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.
- 3). Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; MCS0 at IEEE 802.11n HT20; MCS0 at IEEE 802.11n HT40; MCS0 at IEEE 802.11ax HT20; MCS0 at IEEE 802.11ax HT40.
- 5). Margin= Emission Level – Limit
- 6). Emission Level = Reading + Factor
- 7). Factor = Antenna Factor + Cable Loss – Pre-amplifier



**Radiation Restricted band**
**Horizontal-L**

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|
| 1   | 2386.27         | 41.64          | -5.77         | 35.87          | 74             | -38.13      | peak |
| 2   | 2390            | 41.38          | -5.72         | 35.66          | 74             | -38.34      | peak |
| 3   | 2400            | 40.26          | -5.61         | 34.65          | 74             | -39.35      | peak |

**Vertical-L**

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|
| 1   | 2385.25         | 41.01          | -5.8          | 35.21          | 74             | -38.79      | peak |
| 2   | 2390            | 40.3           | -5.94         | 34.36          | 74             | -39.64      | peak |
| 3   | 2400            | 41.97          | -5.65         | 36.32          | 74             | -37.68      | peak |

**Horizontal-H**

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|
| 1   | 2483.5          | 37.02          | -5.29         | 31.73          | 74             | -42.27      | peak |
| 2   | 2485.13         | 36.36          | -5.44         | 30.92          | 74             | -43.08      | peak |

**Vertical-H**

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|
| 1   | 2483.5          | 36.98          | -5.29         | 31.69          | 74             | -42.31      | peak |
| 2   | 2484.77         | 37.52          | -5.03         | 32.49          | 74             | -41.51      | peak |

**Remarks:**

- 1).  $\text{Margin} = \text{Emission Level} - \text{Limit}$
- 2).  $\text{Emission Level} = \text{Reading} + \text{Factor}$
- 3).  $\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Pre-amplifier}$
- 4). All the modes have been tested and the only shows the worst case 802.11ax(HT20) mode.
- 5). The PEAK value is less than the AVG limit, the AVG result no need be show in this report.

## 6.8 Conducted Emissions


### 6.8.1 Standard requirement:

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

| Frequency Range (MHz) | Limits (dBμV) |          |
|-----------------------|---------------|----------|
|                       | Quasi-peak    | Average  |
| 0.15 to 0.50          | 66 to 56      | 56 to 46 |
| 0.50 to 5             | 56            | 46       |
| 5 to 30               | 60            | 50       |

\* Decreasing linearly with the logarithm of the frequency

### 6.8.2 Test Setup Layout



### 6.8.3 Test Procedures

The transmitter output is connected to EMI receiver. The resolution bandwidth is set to 9 kHz. The video bandwidth is set to 30 kHz, Sweep time=Auto

The spectrum from 150 kHz to 30MHz is investigated with the transmitter set to the lowest, middle, and highest channels.

### 6.8.4 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 6.8.5 Test result

PASS


The test data please refer to following page.

|                |                  |          |     |
|----------------|------------------|----------|-----|
| Temperature    | 26°C             | Humidity | 54% |
| Configurations | IEEE 802.11b/g/n |          |     |

**Measurement data:**

**AC Conducted Emission of charge from Adapter mode @ AC 120V/60Hz @ IEEE 802.11ax(HT20)  
(worst case)**


|               |         |              |  |
|---------------|---------|--------------|--|
| Model name:   | ZD24S   | Test Date :  | 2024-05-27   |
| ATM Pressure: | 101 kPa | Test Result: | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail |
| Phase :       | Line    |              |  |



Remark: Correct Factor = Insertion loss of LISN + Cable loss + Insertion loss of Pulse Limiter;  
Measurement Result = Reading Level +Correct Factor;  
Margin = Measurement Result- Limit;

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-----------------|------------------|-----------------|----------------|--------|
| 1   | 0.1500             | 34.82             | 11.84           | 46.66            | 66.00           | -19.34         | QP     |
| 2   | 0.2040             | 20.07             | 10.69           | 30.76            | 53.45           | -22.69         | AVG    |
| 3   | 0.2893             | 30.37             | 10.69           | 41.06            | 60.54           | -19.48         | QP     |
| 4   | 0.3704             | 15.99             | 10.69           | 26.68            | 48.49           | -21.81         | AVG    |
| 5   | 0.5141             | 17.22             | 10.69           | 27.91            | 46.00           | -18.09         | AVG    |
| 6   | 0.6000             | 32.29             | 10.68           | 42.97            | 56.00           | -13.03         | QP     |
| 7   | 0.7752             | 19.81             | 10.66           | 30.47            | 46.00           | -15.53         | AVG    |
| 8   | 1.0230             | 17.29             | 10.64           | 27.93            | 46.00           | -18.07         | AVG    |
| 9   | 1.0275             | 34.76             | 10.64           | 45.40            | 56.00           | -10.60         | QP     |
| 10  | 1.2975             | 16.55             | 10.68           | 27.23            | 46.00           | -18.77         | AVG    |
| 11  | 1.5360             | 34.62             | 10.71           | 45.33            | 56.00           | -10.67         | QP     |
| 12  | 2.6295             | 27.63             | 10.79           | 38.42            | 56.00           | -17.58         | QP     |

|               |         |              |  |
|---------------|---------|--------------|--|
| Model name:   | ZD24S   | Test Date :  | 2024-05-27   |
| ATM Pressure: | 101 kPa | Test Result: | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail |
| Phase :       | Neutral |              |  |



Remark: Correct Factor = Insertion loss of LISN + Cable loss + Insertion loss of Pulse Limiter;  
Measurement Result = Reading Level +Correct Factor;  
Margin = Measurement Result- Limit;

| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-----------------|------------------|-----------------|----------------|--------|
| 1   | 0.2040             | 18.17             | 10.70           | 28.87            | 53.45           | -24.58         | AVG    |
| 2   | 0.2174             | 35.34             | 10.70           | 46.04            | 62.92           | -16.88         | QP     |
| 3   | 0.3975             | 14.94             | 10.69           | 25.63            | 47.91           | -22.28         | AVG    |
| 4   | 0.4020             | 30.37             | 10.69           | 41.06            | 57.81           | -16.75         | QP     |
| 5   | 1.3785             | 14.69             | 10.70           | 25.39            | 46.00           | -20.61         | AVG    |
| 6   | 1.4144             | 29.95             | 10.70           | 40.65            | 56.00           | -15.35         | QP     |
| 7   | 2.1255             | 16.20             | 10.78           | 26.98            | 46.00           | -19.02         | AVG    |
| 8   | 2.1705             | 28.66             | 10.79           | 39.45            | 56.00           | -16.55         | QP     |
| 9   | 2.4450             | 27.76             | 10.79           | 38.55            | 56.00           | -17.45         | QP     |
| 10  | 3.3043             | 11.20             | 10.89           | 22.09            | 46.00           | -23.91         | AVG    |
| 11  | 4.5914             | 20.04             | 11.01           | 31.05            | 56.00           | -24.95         | QP     |
| 12  | 7.6333             | 8.83              | 11.05           | 19.88            | 50.00           | -30.12         | AVG    |

#### Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

## **7 Test Setup Photographs of EUT**

Please refer to separated files for Test Setup Photos of the EUT.

## **8 External Photographs of EUT**

Please refer to separated files for External Photos of the EUT.

## **9 Internal Photographs of EUT**

Please refer to separated files for Internal Photos of the EUT.

-----End-----