

FCC Test Report

Report No.: RWAZ202300119A
Applicant: Shenzhen Youmi Intelligent Technology Co., Ltd.
Address: 406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China
Product Name: Smart Tablet
Product Model: TG2404GBA
Multiple Models: N/A
Trade Mark: UMIDIGI
FCC ID: 2ATZ4-G6TAB
Standards: FCC CFR Title 47 Part 15C (§15.247)
Test Date: 2023/12/23-2024/01/23
Test Result: Complied
Report Date: 2024/2/2

Reviewed by:

Abel chen

Abel Chen
Project Engineer

Approved by:

Jacob Kong

Jacob Kong
Manager

Prepared by:

World Alliance Testing and Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen,
Guangdong, People's Republic of China



This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★"

Announcement

1. This test report shall not be reproduced in full or partial, without the written approval of World Alliance Testing and Certification (Shenzhen) Co., Ltd
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.
5. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

Revision History

Version No.	Issued Date	Description
00	2024-02-02	Original

Contents

1	General Information	4
1.1	Client Information	4
1.2	Product Description of EUT	4
1.3	Antenna information	4
1.4	Related Submittal(s)/Grant(s).....	5
1.5	Measurement Uncertainty	5
1.6	Laboratory Location.....	5
1.7	Test Methodology	5
2	Description of Measurement.....	6
2.1	Test Configuration.....	6
2.2	Test Auxiliary Equipment	6
2.3	Test Setup.....	7
2.4	Test Procedure	9
2.5	Measurement Method.....	10
2.6	Measurement Equipment	10
3	Test Results	12
3.1	Test Summary.....	12
3.2	Limit	13
3.3	AC Line Conducted Emissions Test Data.....	14
3.4	Radiated emission Test Data.....	17
3.5	RF Conducted Test Data	25
3.5.1	20 dB Emission Bandwidth and 99% Occupied Bandwidth.....	25
3.5.2	Maximum Conducted Peak Output Power.....	25
3.5.3	Channel separation	26
3.5.4	Number of hopping Frequency	26
3.5.5	Time of occupancy (dwell time).....	26
3.5.6	100 kHz Bandwidth of Frequency Band Edge	27
4	Test Setup Photo.....	39
5	E.U.T Photo	40

1 General Information

1.1 Client Information

Applicant:	Shenzhen Youmi Intelligent Technology Co., Ltd.
Address:	406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China
Manufacturer:	Shenzhen Youmi Intelligent Technology Co., Ltd.
Address:	406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China

1.2 Product Description of EUT

The EUT is Smart Tablet that contains Classic Bluetooth (BDR/EDR), BLE, 2.4G/5G WLAN, GSM/GPRS/EGPRS/WCDMA/LTE radios, this report covers the full testing of the Classic Bluetooth (BDR/EDR) radio.

Sample Serial Number	30-2 for CE&RE test, 30-1 for RF test conducted test (assigned by WATC)
Sample Received Date	2023/12/12
Sample Status	Good Condition
Frequency Range	2402MHz - 2480MHz
Maximum Conducted Peak Output Power	1.69dBm
Modulation Technology	GFSK, $\pi/4$ DQPSK, 8DPSK
Spatial Streams	SISO (1TX, 1RX)
Antenna Gain [#]	0.97dBi
Power Supply	DC5V from adapter or DC3.8 V from battery
Adapter 1 Information	Model: HF-0502000U Input: AC100-240V~ 50/60Hz 0.3A Output: DC 5.0V 2A
Adapter 2 Information	Model: HJ-0502000W2-US Input: AC100-240V~ 50/60Hz 0.3A Output: DC 5V 2A
Modification	Sample No Modification by the test lab

1.3 Antenna information

15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
Device Antenna information:	
The BLE antenna is an internal antenna which cannot replace by end-user, please see product internal photos for details.	

1.4 Related Submittal(s)/Grant(s)

FCC Part 15, Subpart C, Equipment Class: DTS, FCC ID: 2ATZ4-G6TAB
 FCC Part 15, Subpart E, Equipment Class: NII, FCC ID: 2ATZ4-G6TAB
 FCC Part 22, Subpart H/Part 24, Subpart E/Part 27, Equipment Class: PCB,
 FCC ID: 2ATZ4-G6TAB

1.5 Measurement Uncertainty

Parameter		Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
AC Power Lines Conducted Emissions		±3.14dB
Emissions, Radiated	Below 30MHz	±2.78dB
	Below 1GHz	±4.84dB
	Above 1GHz	±5.44dB
Emissions, Conducted		1.75dB
Conducted Power		0.74dB
Frequency Error		150Hz
Bandwidth		0.34%
Power Spectral Density		0.74dB
Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.		

1.6 Laboratory Location

World Alliance Testing and Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China

Tel: +86-755-29691511, Email: qa@watc.com.cn

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 463912, the FCC Designation No. : CN5040.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0160.

1.7 Test Methodology

FCC CFR 47 Part 2

FCC CFR 47 Part 15

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2020

2 Description of Measurement

2.1 Test Configuration

Operating channels:					
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	39	2441	76	2478
1	2403	40	2442	77	2479
...	...	...	...	78	2480
38	2440	...	...	/	/
According to ANSI C63.10-2020 chapter 5.6.1 Table 11 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:					
Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	39	2441	78	2480

Test Mode:				
Transmitting mode:		Keep the EUT in continuous transmitting with modulation		
Exercise software [#] :		Engineering mode		
Mode	Data rate	Power Level Setting [#]		
		Low Channel	Middle Channel	High Channel
GFSK	1Mbps	7	7	7
$\pi/4$ DQPSK	2Mbps	7	7	7
8DPSK	3Mbps	7	7	7
The exercise software and the maximum power setting that provided by manufacturer.				


Worst-Case Configuration:
For radiated emissions, EUT was investigated in three orthogonal orientation, the worst-case orientation was recorded in report
For AC power line conducted emission and radiated emission 9kHz-1GHz and above 18GHz were performed with the EUT transmits at the channel with highest output power as worst-case scenario.

2.2 Test Auxiliary Equipment

Manufacturer	Description	Model	Serial Number
/	/	/	/

2.3 Test Setup


1) Conducted emission measurement:




Note: The 0.8 m distance specified between EUT/AE/PSU and AMN/AAN, is applicable only to the EUT being measured. If the device is AE then it shall be >0.8 m.

2) Radiated emission measurement:


Below 30MHz (3m SAC)




30MHz-1GHz (3m SAC)




1GHz-18GHz(3m FAC)



Above 18GHz (3m FAC)



3) RF Conducted Test



2.4 Test Procedure

Conducted emission:

1. The E.U.T is placed on a non-conducting table 40cm from the vertical ground plane and 80cm above the horizontal ground plane (Please refer to the block diagram of the test setup and photographs).
2. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
3. Line conducted data is recorded for both Line and Neutral

Radiated Emission Procedure:

a) For below 30MHz

1. All measurements were made at a test distance of 3 m. The measured data was extrapolated from the test distance (3m) to the specification distance (300 m from 9-490 kHz and 30 m from 490 kHz- 30 MHz) to clearly show the relative levels of fundamental and spurious emissions and demonstrate compliance with the requirement that the level of any spurious emissions be below the level of the intentionally transmitted signal. The extrapolation factor for the limits were $40 \cdot \log(\text{test distance} / \text{specification distance})$.
2. Loop antenna use, investigation was done on the three antenna orientations (parallel, perpendicular, ground-parallel)

b) For 30MHz-1GHz:

1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.
2. EUT works in each mode of operation that needs to be tested. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.

c) For above 1GHz:

1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m (1-18GHz) and 1.5 m (above 18GHz).
2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.
3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
4. Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

RF Conducted Test:

1. The antenna port of EUT was connected to the RF port of the test equipment (Power Meter or

- Spectrum analyzer) through Attenuator and RF cable.
- The cable assembly insertion loss of 11dB (including 10dB Attenuator and 1.0 dB cable) was entered as an offset in the power meter. Note: Actual cable loss was unavailable at the time of testing, therefore a loss of 1.0dB was assumed as worst case. This was later verified to be true by laboratory. (if the RF cable provided by client, the cable loss declared by client)
 - The EUT is keeping in continuous transmission mode and tested in all modulation modes.

2.5 Measurement Method

Description of Test	Measurement Method
AC Line Conducted Emissions	ANSI C63.10-2020 Section 6.2
Maximum Conducted Output Power	ANSI C63.10-2020 Section 7.8.5
20 dB Emission Bandwidth	ANSI C63.10-2020 Section 6.9.2
99% Occupied Bandwidth	ANSI C63.10-2020 Section 6.9.3
Channel separation	ANSI C63.10-2020 Section 7.8.2
Number of hopping Frequency	ANSI C63.10-2020 Section 7.8.3
Time of occupancy (dwell time)	ANSI C63.10-2020 Section 7.8.4
100kHz Bandwidth of Frequency Band Edge	ANSI C63.10-2020 Section 7.8.7.2&6.10
Radiated emission	ANSI C63.10-2020 Section 7.8&6.3&6.4&6.5&6.6

2.6 Measurement Equipment

Manufacturer	Description	Model	Management No.	Calibration Date	Calibration Due Date
AC Line Conducted Emission Test					
ROHDE& SCHWARZ	EMI TEST RECEIVER	ESR	101817	2023/7/3	2024/7/2
R&S	LISN	ENV216	101748	2023/8/1	2024/7/30
N/A	Coaxial Cable	NO.12	N/A	2023/7/3	2024/7/2
Farad	Test Software	EZ-EMC	Ver. EMEC-3A1	/	/
Radiated Emission Test					
R&S	EMI test receiver	ESR3	102758	2023/7/3	2024/7/2
ROHDE& SCHWARZ	SPECTRUM ANALYZER	FSV40-N	101608	2023/7/3	2024/7/2
SONOMA INSTRUMENT	Low frequency amplifier	310	186014	2023/7/12	2024/7/11

COM-POWER	preamplifier	PAM-118A	18040152	2023/8/21	2024/8/20
COM-POWER	Amplifier	PAM-840A	461306	2023/8/8	2024/8/7
ETS	Passive Loop Antenna	6512	29604	2023/7/7	2024/7/6
SCHWARZBECK	Log - periodic wideband antenna	VULB 9163	9163-872	2023/7/7	2024/7/6
Astro Antenna Ltd	Horn antenna	AHA-118S	3015	2023/7/6	2024/7/5
Ducommun technologies	Horn Antenna	ARH-4223-02	1007726-03	2023/7/10	2024/7/9
Ducommun technologies	Horn Antenna	ARH-2823-02	1007726-03	2023/7/10	2024/7/9
Oulitong	Band Reject Filter	OBSF-2400-248 3.5-50N	OE02103119	2023/9/15	2024/9/14
N/A	Coaxial Cable	N/A	NO.9	2023/8/8	2024/8/7
N/A	Coaxial Cable	N/A	NO.10	2023/8/8	2024/8/7
N/A	Coaxial Cable	N/A	NO.11	2023/8/8	2024/8/7
Audix	Test Software	E3	191218 V9	/	/
RF Conducted Test					
R&S	Spectrum Analyzer	FSV40	101590	2023/11/16	2024/11/15
MARCONI	10dB Attenuator	1692595	2942	2023/10/25	2024/10/24
ANRITSU	USB Power Sensor	MA24418A	12620	2023/7/12	2024/7/11

Note: All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or International standards.

3 Test Results

3.1 Test Summary

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247 (a)(1)	20dB Emission Bandwidth	Compliance
-	99% Occupied Bandwidth	Report only
§15.247 (a)(1)	Channel separation	Compliance
§15.247 (a)(1)(iii)	Number of hopping Frequency	Compliance
§15.247 (a)(1)(iii)	Time of occupancy (dwell time)	Compliance
§15.247(b)(1)	Maximum Conducted Output Power	Compliance
§15.247(d)	100kHz Bandwidth of Frequency Band Edge	Compliance
§15.205, §15.209, §15.247(d)	Radiated emission	Compliance

3.2 Limit

Test items	Limit
AC Line Conducted Emissions	See details §15.207 (a)
Conducted Output Power	For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.
Channel separation	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
Number of hopping Frequency	Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.
Time of occupancy (dwell time)	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.
Spurious Emissions, 100kHz Bandwidth of Frequency Band Edge	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.3 AC Line Conducted Emissions Test Data

Test Date:	2024-1-23	Test By:	Lirou Li
Environment condition:	Temperature: 21.8°C; Relative Humidity:37%; ATM Pressure: 101.3kPa		


Conducted Emission Measurement

File :RWAZ202300119

Data :#6

Date: 2024/1/23

Time: 11:08:59



Limit: QP

Mode:transmitting

Note: BT

Phase:

L1

Temperature: 21.8

Power: AC 120V/60Hz

Humidity: 37 %

Air Pressure: 1013 hpa

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over Limit		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	36.84	10.81	47.65	66.00	-18.35	QP	
2		0.1500	21.85	10.81	32.66	56.00	-23.34	AVG	
3		0.1780	34.79	10.70	45.49	64.58	-19.09	QP	
4		0.1780	20.76	10.70	31.46	54.58	-23.12	AVG	
5		0.5299	32.95	10.82	43.77	56.00	-12.23	QP	
6		0.5299	21.43	10.82	32.25	46.00	-13.75	AVG	
7	*	0.6020	34.82	10.84	45.66	56.00	-10.34	QP	
8		0.6020	24.33	10.84	35.17	46.00	-10.83	AVG	
9		0.6300	33.59	10.84	44.43	56.00	-11.57	QP	
10		0.6300	19.95	10.84	30.79	46.00	-15.21	AVG	
11		1.3140	30.34	10.88	41.22	56.00	-14.78	QP	
12		1.3140	19.10	10.88	29.98	46.00	-16.02	AVG	

*:Maximum data x:Over limit !:over margin

Engineer Signature: Lirou


Conducted Emission Measurement

File :RWAZ202300119

Data :#5

Date: 2024/1/23

Time: 11:05:22



Limit: QP
Mode:transmitting
Note: BT

Phase: **N**
Power: AC 120V/60Hz

Temperature: 21.8
Humidity: 37 %
Air Pressure: 1013 hpa

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over Limit	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1780	36.77	10.50	47.27	64.58	-17.31	QP
2		0.1780	19.58	10.50	30.08	54.58	-24.50	AVG
3		0.1980	31.07	10.42	41.49	63.69	-22.20	QP
4		0.1980	13.30	10.42	23.72	53.69	-29.97	AVG
5		0.2260	28.54	10.45	38.99	62.60	-23.61	QP
6		0.2260	9.92	10.45	20.37	52.60	-32.23	AVG
7		0.3180	26.68	10.56	37.24	59.76	-22.52	QP
8		0.3180	11.19	10.56	21.75	49.76	-28.01	AVG
9		0.5500	28.13	10.68	38.81	56.00	-17.19	QP
10		0.5500	13.90	10.68	24.58	46.00	-21.42	AVG
11	*	0.6340	28.88	10.62	39.50	56.00	-16.50	QP
12		0.6340	15.15	10.62	25.77	46.00	-20.23	AVG

*:Maximum data x:Over limit !:over margin

Engineer Signature: Lirou

Remark:

Measurement (dBuV)= Reading Level (dBuV) + Correct Factor(dB)

Correct Factor(dB)= LISN Voltage Division Factor (dB)+ Cable loss(dB)

Over Limit = Measurement – Limit

3.4 Radiated emission Test Data


9 kHz-30MHz:

Test Date:	2024-01-19	Test By:	Bard Huang
Environment condition:	Temperature: <u>24.1</u> °C; Relative Humidity: <u>60</u> %; ATM Pressure: <u>100.9</u> kPa		

For radiated emissions below 30MHz, there were no emissions found within 20dB of limit.

30MHz-1GHz:

Test Date:	2024-01-19	Test By:	Bard Huang
Environment condition:	Temperature: <u>24.1</u> °C; Relative Humidity: <u>60</u> %; ATM Pressure: <u>100.9</u> kPa		




Project No. : RWAZ202300119-RF
 Test Mode : Transmitting
 Test Voltage : AC120V 60Hz
 Environment : 24.1°C/60%R.H./100.9kPa
 Tested by : Bard Huang
 Polarization : horizontal
 Remark : BT

--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector

1	88.808	34.15	-16.06	18.09	43.50	-25.41	Peak
2	157.076	39.13	-17.01	22.12	43.50	-21.38	Peak
3	179.229	45.54	-15.71	29.83	43.50	-13.67	Peak
4	223.635	42.69	-13.42	29.27	46.00	-16.73	Peak
5	256.072	38.63	-12.31	26.32	46.00	-19.68	Peak
6	363.144	35.08	-9.47	25.61	46.00	-20.39	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain



Project No. : RWAZ202300119-RF
Test Mode : Transmitting
Test Voltage : AC120V 60Hz
Environment : 24.1°C/60%R.H./100.9kPa
Tested by : Bard Huang
Polarization : vertical
Remark : BT

--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector

1	31.180	51.20	-15.32	35.88	40.00	-4.12	QP
2	59.025	42.03	-13.56	28.47	40.00	-11.53	Peak
3	88.187	36.74	-16.24	20.50	43.50	-23.00	Peak
4	100.934	34.53	-14.19	20.34	43.50	-23.16	Peak
5	154.821	38.95	-17.23	21.72	43.50	-21.78	Peak
6	176.655	40.88	-15.96	24.92	43.50	-18.58	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain

Remark:

Level = Reading + Factor

Factor = Antenna factor + Cable loss – Amplifier gain

Over Limit = Level – Limit

Above 1GHz:

Test Date:	2024-01-22	Test By:	Bard Huang
Environment condition:	Temperature: 23.9°C; Relative Humidity:48%; ATM Pressure: 101.6kPa		

Frequency (MHz)	Reading level (dBμV)	Polar (H/V)	Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
GFSK							
Low Channel							
2390	49.36	horizontal	8.25	57.61	74	-16.39	Peak
2390	36.88	horizontal	8.25	45.13	54	-8.87	Average
2390	49.17	vertical	8.25	57.42	74	-16.58	Peak
2390	37.74	vertical	8.25	45.99	54	-8.01	Average
4804	50.03	horizontal	0.21	50.24	74	-23.76	Peak
4804	37.26	horizontal	0.21	37.47	54	-16.53	Average
4804	49.77	vertical	0.21	49.98	74	-24.02	Peak
4804	36.08	vertical	0.21	36.29	54	-17.71	Average
Middle Channel							
4882	49.73	horizontal	0.45	50.18	74	-23.82	Peak
4882	36.91	horizontal	0.45	37.36	54	-16.64	Average
4882	49.52	vertical	0.45	49.97	74	-24.03	Peak
4882	36.75	vertical	0.45	37.2	54	-16.8	Average
High Channel							
2483.5	49.32	horizontal	8.25	57.57	74	-16.43	Peak
2483.5	37.94	horizontal	8.25	46.19	54	-7.81	Average
2483.5	49.18	vertical	8.25	57.43	74	-16.57	Peak
2483.5	37.83	vertical	8.25	46.08	54	-7.92	Average
4960	52.08	horizontal	0.93	53.01	74	-20.99	Peak
4960	37.29	horizontal	0.93	38.22	54	-15.78	Average
4960	52.36	vertical	0.93	53.29	74	-20.71	Peak
4960	37.47	vertical	0.93	38.4	54	-15.6	Average
π/4-DQPSK							
Low Channel							
2390	49.45	horizontal	8.25	57.7	74	-16.3	Peak
2390	38.8	horizontal	8.25	47.05	54	-6.95	Average
2390	49.29	vertical	8.25	57.54	74	-16.46	Peak
2390	39.67	vertical	8.25	47.92	54	-6.08	Average
4804	50.07	horizontal	0.21	50.28	74	-23.72	Peak
4804	37.1	horizontal	0.21	37.31	54	-16.69	Average
4804	50.92	vertical	0.21	51.13	74	-22.87	Peak
4804	36.99	vertical	0.21	37.2	54	-16.8	Average
Middle Channel							
4882	49.79	horizontal	0.45	50.24	74	-23.76	Peak
4882	36.88	horizontal	0.45	37.33	54	-16.67	Average
4882	51.61	vertical	0.45	52.06	74	-21.94	Peak
4882	36.73	vertical	0.45	37.18	54	-16.82	Average

High Channel							
2483.5	49.67	horizontal	8.25	57.92	74	-16.08	Peak
2483.5	37.01	horizontal	8.25	45.26	54	-8.74	Average
2483.5	49.54	vertical	8.25	57.79	74	-16.21	Peak
2483.5	36.89	vertical	8.25	45.14	54	-8.86	Average
4960	50.22	horizontal	0.93	51.15	74	-22.85	Peak
4960	36.15	horizontal	0.93	37.08	54	-16.92	Average
4960	51.41	vertical	0.93	52.34	74	-21.66	Peak
4960	36.27	vertical	0.93	37.2	54	-16.8	Average
8DPSK							
Low Channel							
2390	49.54	horizontal	8.25	57.79	74	-16.21	Peak
2390	37.69	horizontal	8.25	45.94	54	-8.06	Average
2390	49.42	vertical	8.25	57.67	74	-16.33	Peak
2390	37.55	vertical	8.25	45.8	54	-8.2	Average
4804	50.47	horizontal	0.21	50.68	74	-23.32	Peak
4804	37.05	horizontal	0.21	37.26	54	-16.74	Average
4804	50.26	vertical	0.21	50.47	74	-23.53	Peak
4804	36.92	vertical	0.21	37.13	54	-16.87	Average
Middle Channel							
4882	49.88	horizontal	0.45	50.33	74	-23.67	Peak
4882	36.8	horizontal	0.45	37.25	54	-16.75	Average
4882	49.75	vertical	0.45	50.20	74	-23.8	Peak
4882	36.69	vertical	0.45	37.14	54	-16.86	Average
High Channel							
2483.5	48.94	horizontal	8.25	57.19	74	-16.81	Peak
2483.5	37.07	horizontal	8.25	45.32	54	-8.68	Average
2483.5	48.8	vertical	8.25	57.05	74	-16.95	Peak
2483.5	36.93	vertical	8.25	45.18	54	-8.82	Average
4960	49.1	horizontal	0.93	50.03	74	-23.97	Peak
4960	36.16	horizontal	0.93	37.09	54	-16.91	Average
4960	50.27	vertical	0.93	51.2	74	-22.8	Peak
4960	36.35	vertical	0.93	37.28	54	-16.72	Average

Remark:

Corrected Amplitude= Reading level + corrected Factor


Corrected Factor = Antenna factor + Cable loss – Amplifier gain


Margin = Corrected Amplitude – Limit

The emission levels of other frequencies that were lower than the limit 20dB, not show in test report.

For emissions in 18GHz-25GHz range, all emissions were investigated and in the noise floor level.

Test plot for example as below:





3.5 RF Conducted Test Data

Test Date:	2023/12/23	Test By:	Ryan Zhang
Environment condition:	Temperature: 25°C; Relative Humidity:46%; ATM Pressure: 101.54kPa		

3.5.1 20 dB Emission Bandwidth and 99% Occupied Bandwidth

Test Mode	Channel	20dB BW [MHz]	99% OBW[MHz]
GFSK	2402	0.964	0.878
	2441	0.964	0.874
	2480	0.960	0.870
$\pi/4$ DQPSK	2402	1.284	1.174
	2441	1.288	1.174
	2480	1.288	1.178
8DPSK	2402	1.296	1.174
	2441	1.296	1.178
	2480	1.296	1.178

3.5.2 Maximum Conducted Peak Output Power

Test Mode	Channel[MHz]	Result[dBm]	Limit[dBm]	Verdict
GFSK	2402	0.03	21	Pass
	2441	1.61	21	Pass
	2480	0.15	21	Pass
$\pi/4$ DQPSK	2402	-0.24	21	Pass
	2441	1.41	21	Pass
	2480	0.48	21	Pass
8DPSK	2402	0.02	21	Pass
	2441	1.69	21	Pass
	2480	0.73	21	Pass

3.5.3 Channel separation

Test Mode	Channel[MHz]	Result[MHz]	Limit[MHz]	Verdict
GFSK	2402	1.000	0.643	Pass
	2441	1.000	0.643	Pass
	2480	1.000	0.640	Pass
$\pi/4$ DQPSK	2402	1.000	0.856	Pass
	2441	1.000	0.859	Pass
	2480	1.000	0.859	Pass
8DPSK	2402	1.000	0.864	Pass
	2441	1.000	0.864	Pass
	2480	1.000	0.864	Pass

Note: Limit $\leq 2/3 \times 20\text{dB BW}$

3.5.4 Number of hopping Frequency

Test Mode	Frequency Range [MHz]	Number of hopping Frequency	Limit	Verdict
GFSK	2400-2483.5	79	≥ 15	Pass
$\pi/4$ DQPSK	2400-2483.5	79	≥ 15	Pass
8DPSK	2400-2483.5	79	≥ 15	Pass

3.5.5 Time of occupancy (dwell time)

Test Mode	Packet Type	Channel[MHz]	Pulse Time [ms]	Result[s]	Limit[s]	Verdict
GFSK	DH1	2402	0.408	0.131	0.400	Pass
	DH3	2441	1.662	0.266	0.400	Pass
	DH5	2480	2.910	0.310	0.400	Pass
$\pi/4$ DQPSK	2DH1	2402	0.400	0.128	0.400	Pass
	2DH3	2441	1.650	0.264	0.400	Pass
	2DH5	2480	2.910	0.310	0.400	Pass
8DPSK	3DH1	2402	0.398	0.127	0.400	Pass
	3DH3	2441	1.650	0.264	0.400	Pass
	3DH5	2480	2.900	0.309	0.400	Pass

Note:

DH1: Dwell time=Pulse time (ms) $\times (1600/2/79) \times 31.6\text{s}$

DH3: Dwell time=Pulse time (ms) $\times (1600/4/79) \times 31.6\text{s}$


DH5: Dwell time=Pulse time (ms) $\times (1600/6/79) \times 31.6\text{s}$




3.5.6 100 kHz Bandwidth of Frequency Band Edge

Test Mode	Channel	Result	Limit	Verdict
GFSK	2402	Refer test plot	Refer test plot	Pass
	2480	Refer test plot	Refer test plot	Pass
$\pi/4$ DQPSK	2402	Refer test plot	Refer test plot	Pass
	2480	Refer test plot	Refer test plot	Pass
8DPSK	2402	Refer test plot	Refer test plot	Pass
	2480	Refer test plot	Refer test plot	Pass


Test Plots:



20 dB Emission Bandwidth:




8DPSK	/
Lowest channel	/
 Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT 1PK Max M1[1] -29.55 dBm 2.40135200 GHz -0.74 dB 1.29600 MHz CF 2.402 GHz 501 pts Span 2.0 MHz Date: 23, DEC, 2023 15:13:13	/
Middle channel	/
 Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT 1PK Max M1[1] -22.79 dBm 2.44034800 GHz 0.59 dB 1.29600 MHz CF 2.441 GHz 501 pts Span 2.0 MHz Date: 23, DEC, 2023 15:14:49	/
High channel	/
 Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT 1PK Max M1[1] -23.48 dBm 2.47934800 GHz 0.20 dB 1.29600 MHz CF 2.48 GHz 501 pts Span 2.0 MHz Date: 23, DEC, 2023 15:16:11	/




99% Occupied Bandwidth:




8DPSK	/
Lowest channel	/
 1PK Max Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT M1[1] -4.05 dBm 2.40202400 GHz 1.173652695 MHz CF 2.402 GHz 501 pts Span 2.0 MHz Date: 23, DEC, 2023 15:13:23	/
Middle channel	/
 1PK Max Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT M1[1] -2.39 dBm 2.44102400 GHz 1.177644711 MHz CF 2.441 GHz 501 pts Span 2.0 MHz Date: 23, DEC, 2023 15:14:55	/
High channel	/
 1PK Max Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT M1[1] -3.39 dBm 2.48002400 GHz 1.177644711 MHz CF 2.48 GHz 501 pts Span 2.0 MHz Date: 23, DEC, 2023 15:16:26	/

Channel separation:







8DPSK	/
Lowest channel	/
 Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.3 μs VBW 100 kHz Mode Auto FFT 1Pk Max M1[1] -2.77 dBm D1[1] 0.30 dBm CF 2.4025 GHz 501 pts Span 3.0 MHz Data: 23, DEC, 2023 15:21:56	/
Middle channel	/
 Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.3 μs VBW 100 kHz Mode Auto FFT 1Pk Max M1[1] -0.83 dBm D1[1] 0.44 dBm CF 2.4415 GHz 501 pts Span 3.0 MHz Data: 23, DEC, 2023 15:21:59	/
High channel	/
 Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.3 μs VBW 100 kHz Mode Auto FFT 1Pk Max M1[1] -3.23 dBm D1[1] -0.14 dBm CF 2.4795 GHz 501 pts Span 3.0 MHz Data: 23, DEC, 2023 15:19:58	/

Number of hopping Frequency




Time of occupancy (dwell time)



8DPSK	/
Lowest channel	/
Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 1 ms VBW 3 MHz SQL TRG:VID IPK Cirw  CF 2.411 GHz 501 pts 100.0 μs/ Date: 22 DEC 2022 15:52:04	/
Middle channel	/
Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 3 ms VBW 3 MHz SQL TRG:VID IPK Cirw  CF 2.411 GHz 501 pts 300.0 μs/ Date: 22 DEC 2022 15:52:45	/
High channel	/
Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 5 ms VBW 3 MHz SQL TRG:VID IPK Cirw  CF 2.411 GHz 501 pts 500.0 μs/ Date: 22 DEC 2022 15:59:21	/


100kHz Bandwidth of Frequency Band Edge:




Hopping enabled

GFSK

Lowest channel



High channel




$\pi/4$ DQPSK

Lowest channel



High channel




8DPSK

Lowest channel



High channel



4 Test Setup Photo

Please refer to the attachment RWAZ202300119 Test Setup photo.

5 E.U.T Photo

Please refer to the attachment RWAZ202300119 External photo and RWAZ202300119 Internal photo.

---End of Report---