FCC RADIO TEST REPORT FCC ID:2AFA3RLTP4028

Product: smartphone Trade Name: N/A Model Number: RLTP4028-BLACK Serial Model: V41 Report No.: ISOT15070054R1

Prepared for

Shenzhen Vastking Electronic Co.,LTD. 2/F, Building 6, ZhengZhong Industrial Park, Qiaotou Community, Fuyong, Baoan, Shenzhen, China

Prepared by

Shenzhen ISOTek Standards Technical Services Co.,Ltd. 13/F, HuaFengRui Building, XinHu Rd., XiXiang, Bao'an District,Shenzhen,China Tel.: +86-755- 23087378 Fax.: +86-755-23087278 Http://www.ISOTek.com.cn

TEST RESULT CERTIFICATION

Applicant's name	Shenzhen Vastking Electronic Co., LTD.
Address	2/F, Building 6, ZhengZhong Industrial Park, Qiaotou Community, Fuyong, Baoan, Shenzhen, China
Manufacture's Name	Shenzhen Vastking Electronic Co., LTD.
Address:	2/F, Building 6, ZhengZhong Industrial Park, Qiaotou Community, Fuyong, Baoan, Shenzhen, China
Product name:	smartphone
Model and/or type reference:	RLTP4028-BLACK
Serial Model :	V41
Standards	FCC Part 22H and 24E and FCC Part 27: 01 Oct. 2014
Test procedure:	TIA/EIA 603D

This device described above has been tested by ISOTek, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ISOTek, this document may be altered or revised by ISOTek, personnel only, and shall be noted in the revision of the document.

Date of Test.....

Date of Issue 22 July. 2015

Test Result Pass

Compiled by:

lisa hung

Lisa Huang/ Project Engineer

Approved by:

2: chard cham

Richard Chen/ Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION	5
1.2 RELATED SUBMITTAL(S) / GRANT (S)	7
1.3 TEST METHODOLOGY	7
1.4 TEST FACILITY	7
1.5 MEASUREMENT INSTRUMENTS	7
1.6 SPECIAL ACCESSORIES	7
1.7 EQUIPMENT MODIFICATIONS	7
2. SYSTEM TEST CONFIGURATION	9
2.1 EUT CONFIGURATION	9
2.2 EUT EXERCISE	9
2.3 GENERAL TECHNICAL REQUIREMENTS	9
2.4 CONFIGURATION OF EUT SYSTEM	
3. SUMMARY OF TEST RESULTS	11
4. DESCRIPTION OF TEST MODES	11
5. OUTPUT POWER	12
5.1 Conducted Output Power	
5.2 Radiated Output Power	
6. SPURIOUS EMISSION	23
6.1 CONDUCTED SPURIOUS EMISSION	
7. FREQUENCY STABILITY	32
7.1 MEASUREMENT METHOD	

7.2 PROVISIONS APPLICABLE	32
7.3 MEASUREMENT RESULT	33
8. BANDWIDTH	36
8.1APPLICABLE STANDARD	36
8.2 Test Procedure	36
8.3 MEASUREMENT RESULT	36
9. BAND EDGE	39
9.1 Applicable Standard	39
9.2 Test Procedure	39
9.3 MEASUREMENT RESULT	39
10. PEAK-TO-AVERAGE RATIO	40
DESCRIPTION OF THE PAR MEASUREMENT	40
10.1 MEASURING INSTRUMENTS	40
10.2 TEST PROCEDURES	40
10.3 TEST SETUP	40
10.4 TEST RESULT OF PEAK-TO-AVERAGE RATIO	41
TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION	42
TEST PLOTS FOR OCCUPIED BANDWIDTH (99%)	58
EMISSION BANDWIDTH (-26DBC)	58
	67
TEST PLOTS FOR BAND EDGES	67
	73
PHOTOGRAPHS OF TEST SETUP	73

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

A major technical description of EUT is described as following:

Product Designation:	smartphone		
Model Name	RLTP4028-BLACK		
Serial Model	V41		
Model Difference	All the model are the same circuit and RF module, except the model name and colour.		
Hardware version:	MB0MBA4C1-1(WUZHU)		
Software version:	HQD_D133_271_0000_4.4.2_1.1_07	721_T05	
Frequency Bands:	 WCDMA : ◯HSDPA ◯HSUPA □ Band 1:1920 - 1980 MHz ○ Band 2:1850 - 1910 MHz ○ Band 4:1710 - 1755 MHz ○ Band 5:824 - 849 MHz □ Band 8:880 - 915 MHz 	 	
Emission Designator	824.2-848.8MHz:249KGXW; 1850.2-1909.8MHz:248KGXW 826.4-846.6MHz:4M15F9W; 1852.4-1907.6MHz:4M16F9W 1712.6-1752.4 MHz:4M18F9W		
GPRS/EDGE Class	Multi-Class12; Only 4 timeslots are used for GPRS		
Modulation Technique:	GSM/GPRS: GMSK; EDGE:8PSK;RMC/AMR: QPSK; WCDMA:QPSK & 16QAM		
Supported mode:	2G:GSM Voice for GSM850,EGSM90 Level: class 12; support EDGE; WCDMA:RMC/AMR 12.2Kbps Rel 99 Release 6 Cat 6	00,DCS1800 and PCS1900,GPRS 9, HSDPA Release 7 Cat 16, HSUPA	
Antenna:	FPCB Antenna		
Antenna gain:	1.0 dBi		
Battery parameter:	DC 3.7V,1500mAh		
Adapter Input:	100-240V~,50/60 Hz		
Adapter Output:	5.0V,500mA		
SIM CARD	The Phone Two SIM Card sockets		
Extreme Vol. Limits:	DC3.6 V to 4.2 V (Nominal DC3.7V)		

Extreme Temp. Tolerance	-10℃ to +50℃
** Note: The High Vo	Liphtage 4.2V and Low Voltage 3.6V was declared by manufacturer, The EUT
couldn't be operate	normally with higher or lower voltage.
· · ·	· • • •

1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: 2AFA3RLTP4028 filing to comply with the FCC Part 22H&24E&27.

1.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of TIA/EIA 603D and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

1.4 TEST FACILITY

The test site used to collect the radiated data is located at:

Shenzhen ISOTek Standards Technical Services Co., Ltd.

13/F, HuaFengRui Building, XinHu Rd., XiXiang, Bao'an District, Shenzhen, China.

The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2009.

FCC Registration No.: 918037

1.5 MEASUREMENT INSTRUMENTS

Term	Kind of	Manufaatuura	Type No. Serial No.		Last	Calibrated	Calibration
nem	Equipment	Manufacturer	Type No.	be no. Senai no.		until	period
1	Spectrum Analyzer	Aglient	E4446A	US44300451	2015.07.06	2016.07.05	1 year
2	EMI Test Receiver	R&S	ESCI	101165	2015.07.06	2016.07.05	1 year
3	Communication Tester	r&s	CMU200	A0304247	2015.05.04	2016.05.03	1 year
4	Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2015.07.06	2016.07.05	1 year
5	Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-439	2015.07.06	2016.07.05	1 year
6	Horn Antenna	Schwarzbeck	BBHA 9170	9170-182	2015.07.06	2016.07.05	1 year
7	Horn Antenna	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	SIGNAL GENERATOR	AGILENT	E4438C	878743	2015.05.04	2016.05.03	1 year
9	Amplifier	Schwarzbeck	BBV9743	9743-019	2015.07.06	2016.07.05	1 year
10	Test Cable Below 1GHz	ATM	R-01	3564	2015.07.06	2016.07.05	1 year
11	Test Cable Above 1GHz	ATM	R-02	3565	2015.07.06	2016.07.05	1 year
12	Horn Antenna	Sunol Sciences	DRH-118	A052604	2015.07.06	2016.07.05	1 year
13	Horn Antenna	Sunol Sciences	DRH-118	A052605	2015.07.06	2016.07.05	1 year

1.6 SPECIAL ACCESSORIES

The battery and the charger, earphone supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

1.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

Item Number	Item Description		FCC Rules
1	Output	Conducted output power	22.913(a) / 24.232 (b), §2.1046
1	Power	Radiated output power	§ 27.50(c.10); § 27.50(d.4)
2	Spurious Emission	Conducted spurious emission Radiated spurious emission	2.1051 / 22.917 / 24.238, § 2.1051, § 2.1053,§ 27.53(h)
3	Frequency Stability		2.1055 /24.235/§ 27.5(h);§ 27.54
4	Occupied I	Bandwidth	2.1049 (h)(i) /§ 27.53(a.5)
5	Emission Bandwidth		22.917(b) / 24.238 (b)/§ 27.53(a.5)
6	Band Edge		22.917(b) / 24.238 (b)/ § 27.53(h)
7	Peak-to-Average Ratio		24.232(d)

2.3 GENERAL TECHNICAL REQUIREMENTS

2.4 CONFIGURATION OF EUT SYSTEM

Fig. 2-1 Configuration of EUT System

EUT

Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	ID or Specification	Note
1	smartphone	RLTP4028-BLACK	FCC ID: 2AFA3RLTP4028	EUT

Note: All the accessories have been used during the test.

the following "EUT" in setup diagram means EUT system.

ltem Number	Item Description		FCC Rules	Result
1	Output Power	Conducted Output Power Radiated Output Power	22.913(a) / 24.232 (b), §2.1046 § 27.50(c.10); § 27.50(d.4)	Pass
2	Conducted Spurious Spurious Emission Emission Radiated Spurious Emission		2.1051 / 22.917 / 24.238, § 2.1051, § 2.1053,§ 27.53(h)	Pass
3	Frequency	Stability	2.1055 /24.235/§ 27.5(h); § 27.54	Pass
4	Occupied Bandwidth		2.1049 (h)(i) /§ 27.53(a.5)	Pass
5	Emission Bandwidth		22.917(b) / 24.238 (b)/§ 27.53(a.5)	Pass
6	Band Edge		22.917(b) / 24.238 (b)/ § 27.53(h)	Pass
7	Peak-to-Average Ratio		24.232(d)	Pass

3. SUMMARY OF TEST RESULTS

4. DESCRIPTION OF TEST MODES

During the testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GPRS850 and GPRS1900 frequency band.

Note: GSM/GPRS/EDGE 850, GSM/GPRS/EDGE 1900, HSDPA band II, HSUPA band II, HSDPA band V, HSUPA band V, HSDPA band IV, HSUPA band IV modes have been tested during the test. the worst condition (GSM850, GSM1900, RMC 12.2k) be recorded in the test report if no other modes test data. The phone has dual SIM Card sockets but can not transmit simultaneously. Pre-test dual SIM Card sockets, only the worst case SIM 1 Card sockets is recorded in the report.

5. OUTPUT POWER

5.1 Conducted Output Power

5.1.1 MEASUREMENT METHOD

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all modes (GSM/GPRS/EDGE 850, GSM/GPRS/EDGE 1900, HSDPA band II, HSUPA band II, HSDPA band V, HSUPA band V HSDPA band IV, HSUPA band IV) at 3 typical channels (the Top Channel, the Middle Channel and the Bottom Channel) for each band.

5.1.2 TEST SETUP



Note: Measurement setup for testing on Antenna connector

5.1.3 MEASUREMENT RESULT

Mode	Frequency (MHz)	Maximum Burst-Average Output Power
	824.2	32.85
GSM850	836.6	32.92
	848.8	32.89
000000	824.2	32.91
GPRS850	836.6	32.69
(1 5101)	848.8	32.65
000000	824.2	32.12
GPRS850	836.6	31.91
(2 5101)	848.8	31.84
	824.2	30.44
GPR5850	836.6	30.16
(3 5101)	848.8	30.04
	824.2	29.34
GPRS850	836.6	29.01
(4 3101)	848.8	28.79
	824.2	26.91
EGPR3600	836.6	26.89
	848.8	26.85
	824.2	26.56
(2 Slot)	836.6	26.61
(2 3101)	848.8	26.58
	824.2	25.96
(3 Slot)	836.6	25.88
	848.8	25.91
	824.2	25.44
(1 Slot)	836.6	25.39
(4 5101)	848.8	25.37

	Mode	Frequency (MHz)	Maximum Burst-Average Output Power
		1850.2	29.69
	GSM1900	1880	29.45
		1909.8	29.35
		1850.2	29.68
	GPRS1900	1880	29.49
	(1 Slot)	1909.8	29.48
		1850.2	28.95
	GPRS1900	1880	28.82
	(2 Slot)	1909.8	28.75
		1850.2	27.24
	GPRS1900	1880	27.22
	(3 Slot)	1909.8	27.28
		1850.2	26.16
	GPRS1900	1880	26.16
	(4 Slot)	1909.8	26.38
		1850.2	25.82
	EGPRS1900	1880	25.78
	(1 Slot)	1909.8	25.74
		1850.2	25.45
	EGPRS1900	1880	25.51
	(2 Slot)	1909.8	25.47
		1850.2	24.85
	EGPRS1900	1880	24.77
	(3 3101)	1909.8	24.83
		1850.2	24.33
		1880	24.28
	(4 SIOT)	1909.8	24.26
L			

UMTS BAND	
-----------	--

Mada	Frequency	Maximum Burst-Average
wode	(MHz)	Output Power
	1852.4	22.08
	1880.0	22.02
RIVIC	1907.6	22.06
	1852.4	21.74
	1880.0	21.65
AIVIN	1907.6	21.72
	1852.4	21.99
NODEA Subtoct 1	1880	21.89
Sublest 1	1907.6	21.62
Церри	1852.4	21.89
Subtest 2	1880	21.70
Sublest 2	1907.6	21.70
Церри	1852.4	21.56
NODEA Subtest 3	1880	21.67
Sublest 5	1907.6	21.59
Церри	1852.4	21.61
NJDFA Subtest /	1880	21.68
Sublest 4	1907.6	21.89
	1852.4	21.65
Subtest 1	1880.0	21.68
Sublest	1907.6	21.97
	1852.4	21.50
Subtest 2	1880.0	21.86
Sublest 2	1907.6	21.58
	1852.4	21.87
Subtoct 3	1880.0	21.77
Sublest 5	1907.6	21.67
	1852.4	21.56
Subtect 1	1880.0	21.86
	1907.6	21.58
	1852.4	21.46
Subtect 5	1880.0	21.58
	1907.6	21.79

|--|

Mada	Frequency	Maximum Burst-Average
Mode	(MHz)	Output Power
	1712.6	22.02
VVCDIMA 1700	1732.6	22.02
RMC	1752.4	22.02
	1712.6	21.53
	1732.6	21.35
AMR	1752.4	21.63
	1712.6	21.26
	1732.6	21.53
Subtest 1	1752.4	21.32
	1712.6	21.22
HSDPA	1732.6	21.76
Subtest 2	1752.4	21.62
	1712.6	21.42
HSDPA -	1732.6	21.34
Subtest 3	1752.4	21.13
	1712.6	21.26
HSDPA	1732.6	21.53
Subtest 4	1752.4	21.32
	1712.6	21.22
HSUPA	1732.6	21.76
Subtest 1	1752.4	21.62
	1712.6	21.42
HSUPA	1732.6	21.34
Subtest 2	1752.4	21.13
	1712.6	21.26
HSUPA	1732.6	21.53
Subtest 3	1752.4	21.32
	1712.6	21.22
HSUPA	1732.6	21.76
Subtest 4	1752.4	21.62
	1712.6	21.42
HSUPA	1732.6	21.34
Subtest 5	1752.4	21.13

UMTS BAND V

Mede	Frequency	Maximum Burst-Average
Mode	(MHz)	Output Power
	826.4	22.97
	835.0	22.74
RIVIC	846.6	22.95
	826.4	22.71
	835.0	22.73
AIVIR	846.6	22.63
	826.4	21.79
HSDFA Subtest 1	835.0	21.81
Sublest 1	846.6	22.11
	826.4	21.81
HSDPA Subtest 2	835.0	21.97
Sublest 2	846.6	21.86
	826.4	21.93
HSDPA Subtest 2	835.0	21.99
Sublest 3	846.6	21.75
	826.4	21.8
HSDPA Subtest 4	835.0	22.03
Sublest 4	846.6	22.09
	826.4	21.93
HSUPA Subtest 1	835.0	21.91
Sublest 1	846.6	21.49
	826.4	21.84
HSUPA Subtest 2	835.0	22.06
Sublest 2	846.6	20.81
	826.4	21.73
HSUPA Subtest 2	835.0	22.11
Sublest 3	846.6	21.94
	826.4	22.05
HSUPA Subtest 4	835.0	21.81
Subtest 4	846.6	22.17
	826.4	22.13
	835.0	22.25
Sublesi 5	846.6	21.94

5.2 Radiated Output Power

5.2.1 MEASUREMENT METHOD

- 1. The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.
- 2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
- 3. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. Sample Calculation:

EUT Field Strength (dBm) = Reading (Signal generator) + Antenna Gain (substitution antenna) - Cable loss (From Signal Generator to substitution antenna)

Test setup

Below 1GHz





Test Result: Pass

5.2.2 MEASUREMENT RESULT

Radiated Power (ERP) for GSM 850 MHZ					
		Result			
Mode	Frequency	Max. Peak ERP	Polarization	Conclusion	
		(dBm)	Of Max. ERP		
GSM850	824.2	29.98	Horizontal	Pass	
	824.2	28.86	Vertical	Pass	
	836.6	30.75	Horizontal	Pass	
	836.6	27.93	Vertical	Pass	
	848.8	30.73	Horizontal	Pass	
	848.8	29.98	Vertical	Pass	

Radiated Power (ERP) for GPRS 850 MHZ					
		Re	Result		
Mode	Frequency	Max. Peak ERP	Polarization	Conclusion	
		(dBm)	Of Max. ERP		
GPRS850	824.2	28.47	Horizontal	Pass	
	824.2	29.42	Vertical	Pass	
	836.6	29.59	Horizontal	Pass	
	836.6	29.03	Vertical	Pass	
	848.8	29.56	Horizontal	Pass	
	848.8	28.69	Vertical	Pass	

Radiated Power (ERP) for EDGE 850 MHZ					
	Result		sult		
Mode	Frequency	Max. Peak ERP	Polarization	Conclusion	
		(dBm)	Of Max. ERP		
EDGE850	824.2	24.12	Horizontal	Pass	
	824.2	24.22	Vertical	Pass	
	836.6	24.30	Horizontal	Pass	
	836.6	24.36	Vertical	Pass	
	848.8	24.87	Horizontal	Pass	
	848.8	24.31	Vertical	Pass	

Radiated Power (E.I.R.P) for PCS 1900 MHZ					
		Res	sult		
Mode	Frequency	Max. Peak	Polarization	Conclusion	
		E.I.R.P.(dBm)	Of Max. E.I.R.P.		
	1850.2	28.63	Horizontal	Pass	
	1850.2	27.47	Vertical	Pass	
PCS 1900	1880.0	29.52	Horizontal	Pass	
	1880.0	27.32	Vertical	Pass	
	1909.8	29.42	Horizontal	Pass	
	1909.8	28.29	Vertical	Pass	

Radiated Power (E.I.R.P) for GPRS 1900 MHZ					
	Result		sult		
Mode	Frequency	Max. Peak	Polarization	Conclusion	
		E.I.R.P.(dBm)	Of Max. E.I.R.P.		
	1850.2	27.38	Horizontal	Pass	
	1850.2	27.78	Vertical	Pass	
GPRS	1880.0	27.77	Horizontal	Pass	
1900	1880.0	27.36	Vertical	Pass	
	1909.8	27.54	Horizontal	Pass	
	1909.8	27.45	Vertical	Pass	

		Re	sult	
Mode	Frequency	Max. Peak	Polarization	Conclusion
		E.I.R.P.(dBm)	Of Max. E.I.R.P.	
EDGE 1900	1850.2	23.50	Horizontal	Pass
	1850.2	23.10	Vertical	Pass
	1880.0	23.90	Horizontal	Pass
	1880.0	23.96	Vertical	Pass
	1909.8	23.71	Horizontal	Pass
	1909.8	23.99	Vertical	Pass

	Radiated Power (E.I.R.P) for UMTS band II					
			Result			
Mode	Frequency	Max. Peak	Polarization	Conclusion		
		E.I.R.P.(dBm)	Of Max. E.I.R.P.			
	1852.4	22.89	Horizontal	Pass		
	1852.4	22.47	Vertical	Pass		
RMC	1880.0	21.82	Horizontal	Pass		
12.2kbps	1880.0	22.87	Vertical	Pass		
	1907.6	22.67	Horizontal	Pass		
	1907.6	22.35	Vertical	Pass		

Radiated Power (E.I.R.P) for UMTS band IV					
		Result			
Mode	Frequency	Max. Peak	Polarization	Conclusion	
		E.I.R.P.(dBm)	Of Max. E.I.R.P.		
	1712.6	22.56	Horizontal	Pass	
	1732.6	22.63	Vertical	Pass	
RMC	1752.4	21.68	Horizontal	Pass	
12.2kbps	1712.6	22.34	Vertical	Pass	
	1732.6	22.47	Horizontal	Pass	
	1752.4	22.73	Vertical	Pass	

Radiated Power (E.I.R.P) for UMTS band V						
			Result			
Mode	Frequency	Max. Peak	Polarization	Conclusion		
		E.I.R.P.(dBm)	Of Max. E.I.R.P.			
	826.4	21.27	Horizontal	Pass		
	826.4	22.37	Vertical	Pass		
RMC	836.6	22.77	Horizontal	Pass		
12.2kbps	836.6	21.46	Vertical	Pass		
	846.6	21.11	Horizontal	Pass		
	846.6	22.68	Vertical	Pass		

NOTE 1: in the part, result the worst case GPRS 1slot for GSM 850 and PCS1900, and RMC 12.2kbps for band II and band IV and band V.

6. SPURIOUS EMISSION

6.1 CONDUCTED SPURIOUS EMISSION

6.1.1 MEASUREMENT METHOD

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1, Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 9 GHz.

2, Determine EUT transmit frequencies: the following typical channels were chosen to conducted emissions testing.

Typical Channels for testing of GSM 850 MHz					
Channel	Frequency (MHz)				
128	824.2				
190	836.6				
251	848.8				

Typical Channels for testing of PCS 1900 MHz					
Channel	Frequency (MHz)				
512	1850.2				
661	1880.0				
810	1909.8				

Typical Channels for testing of UMTS band II						
Channel	Frequency (MHz)					
9262	1852.4					
9400	1880.0					
9538	1907.6					

Typical Channels for testing of UMTS band IV						
Channel	Frequency (MHz)					
1313	1712.6					
1413	1732.6					
1512	1752.4					

Typical Channels for testing of UMTS band V						
Channel	Frequency (MHz)					
4132	826.4					
4183	836.6					
4233	846.6					

6.1.2 PROVISIONS APPLICABLE

On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

6.1.3 MEASUREMENT RESULT

PLEASE REFER TO : APPENDIX I TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION

Note: 1. Below 30MHZ no Spurious found and The GSM modes is the worst condition.

2. As no emission found in standby or receive mode, no recording in this report.

6.2 Radiated Spurious Emission

6.2.1 MEASUREMENT METHOD

The measurements procedures specified in TIA-603D-2004 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GPRS850, GPRS1900, HSDPA band II/IV/V) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for each band.Only shown the worst data.

The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, RSE=Rx (dBuV) +CL (dB) +SA (dB) +Gain (dBi) -107 (dBuV to dBm) The SA is calibrated using following setup.



b) EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS 1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz) ,GSM850 band (824.2MHz, 836.6MHz, 848.8MHz), UMTS band II(1852.4MHz, 1880MHz, 1907.6MHz), UMTS band IV(1712.6MHz, 1732.6MHz, 1752.4MHz),UMTS band V(826.4MHz, 835.0MHz, 846.6MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of any band into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below: Power=PMea+A_{Rpl}

6.2.2 PROVISIONS APPLICABLE

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Note: only result the worst condition of each test mode:

6.2.3 MEASUREMENT RESULT

GSM 850:

Test Results for Channel 128/824.2 MHz						
Frequency(MHz)	Power(dBm)	A _{Rpl} (dBm)	Р _{меа} (dBm)	Limit (dBm)	Polarity	
1648.4	-32.26	7.8	-24.46	-13	Vertical	
1648.4	-32.79	7.8	-24.99	-13	Horizontal	
2472.6	-36.29	11	-25.29	-13	Vertical	
2472.6	-32.5	11	-21.5	-13	Horizontal	
3296.8	-33.23	12.3	-20.93	-13	Horizontal	
3296.8	-34.6	12.3	-22.3	-13	Vertical	
	Test Re	sults for Cha	innel 190/836.	6 MHz		
1673.2	-33.4	8	-25.4	-13	Vertical	
1673.2	-34.82	8	-26.82	-13	Horizontal	
2509.8	-32.71	11.2	-21.51	-13	Vertical	
2509.8	-32.04	11.2	-20.84	-13	Horizontal	
3346.4	-35.8	12.6	-23.2	-13	Horizontal	
3346.4	-33.51	12.6	-20.91	-13	Vertical	
	Test Re	sults for Cha	nnel 251/848.	8 MHz		
1697.6	-30.14	8.1	-22.04	-13	Vertical	
1697.6	-29.27	8.1	-21.17	-13	Horizontal	
2546.4	-31.22	11.69	-19.53	-13	Vertical	
2546.4	-31.56	11.69	-19.87	-13	Horizontal	
3395.2	-32.47	12.92	-19.55	-13	Horizontal	
3395.2	-34.37	12.92	-21.45	-13	Vertical	

PCS 19	00:
--------	-----

Test Results for Channel 512/1850.2MHz						
Frequency(MHz)	Power(dBm)	A _{Rpl} (dBm)	Р _{меа} (dBm)	Limit (dBm)	Polarity	
3700.4	-37.08	13.42	-23.66	-13	Horizontal	
3700.4	-36.01	13.42	-22.59	-13	Vertical	
5550.6	-37.86	17.12	-20.74	-13	Vertical	
5550.6	-36.41	17.12	-19.29	-13	Horizontal	
7400.8	-38.75	19.26	-19.49	-13	Horizontal	
7400.8	-41.2	19.26	-21.94	-13	Vertical	
	Test Res	sults for Cha	nnel 661/1880).0MHz		
3760	-36.08	13.76	-22.32	-13	Horizontal	
3760	-35.27	13.76	-21.51	-13	Vertical	
5640	-40.06	17.56	-22.5	-13	Vertical	
5640	-42.08	17.56	-24.52	-13	Horizontal	
7520	-41.82	19.6	-22.22	-13	Horizontal	
7520	-42.37	19.6	-22.77	-13	Vertical	
	Test Res	sults for Cha	nnel 810/1909	9.8MHz		
3819.6	-37.91	13.87	-24.04	-13	Horizontal	
3819.6	-34.88	13.87	-21.01	-13	Vertical	
5729.4	-38.26	17.66	-20.6	-13	Vertical	
5729.4	-39.43	17.66	-21.77	-13	Horizontal	
7639.2	-39.56	19.75	-19.81	-13	Horizontal	
7639.2	-42.2	19.75	-22.45	-13	Vertical	

UMTS band II:

Test Results for Channel 9262/1852.4MHz						
Frequency(MHz)	Power(dBm)	A _{Rpl} (dBm)	Р _{меа} (dBm)	Limit (dBm)	Polarity	
3700.8	-32.28	13.42	-18.86	-13	Horizontal	
3700.8	-33.49	13.42	-20.07	-13	Vertical	
5551.2	-37.28	17.12	-20.16	-13	Vertical	
5551.2	-36.97	17.12	-19.85	-13	Horizontal	
	Test Res	ults for Cha	nnel 9400/1880	MHz		
3760	-33.9	13.76	-20.14	-13	Horizontal	
3760	-33.52	13.76	-19.76	-13	Vertical	
5640	-40.02	17.56	-22.46	-13	Vertical	
5640	-39.2	17.56	-21.64	-13	Horizontal	
	Test Resu	ults for Chan	nel 9538/1907.	6MHz		
3819.2	-34.02	13.87	-20.15	-13	Horizontal	
3819.2	-35.91	13.87	-22.04	-13	Vertical	
5728.8	-39.02	17.66	-21.36	-13	Vertical	
5728.8	-38.02	17.66	-20.36	-13	Horizontal	

UMTS band IV:

Test Results for Channel 1313/ 1712.6MHz						
Frequency(MHz)	Power(dBm)	A _{Rpl} (dBm)	Р _{меа} (dBm)	Limit (dBm)	Polarity	
3425.2	-32.54	13.02	-19.52	-13	Horizontal	
3425.2	-33.90	13.02	-20.88	-13	Vertical	
5137.8	-37.46	16.88	-20.58	-13	Vertical	
5137.8	-37.19	16.88	-20.31	-13	Horizontal	
	Test Resu	Its for Chan	nel 1413/ 1732	.6MHz		
3465.2	-34.16	13.16	-21.00	-13	Horizontal	
3465.2	-33.62	13.16	-20.46	-13	Vertical	
5197.8	-40.82	17.02	-23.80	-13	Vertical	
5197.8	-39.85	17.02	-22.83	-13	Horizontal	
	Test Resu	Its for Chan	nel 1512/ 1752	.4MHz		
3504.8	-34.60	13.08	-21.52	-13	Horizontal	
3504.8	-36.62	13.07	-23.55	-13	Vertical	
5257.2	-39.57	17.15	-22.42	-13	Vertical	
5257.2	-38.74	17.15	-21.59	-13	Horizontal	

Test Results for Channel 4233/846.6MHz						
Frequency(MHz)	Power(dBm)	A _{Rpl} (dBm)	Р _{меа} (dBm)	Limit (dBm)	Polarity	
1673.2	-31.65	8.1	-23.55	-13	Vertical	
1673.2	-29.2	8.1	-21.1	-13	Horizontal	
2509.8	-37.12	11.69	-25.43	-13	Horizontal	
2509.8	-37.33	11.69	-25.64	-13	Vertical	
3346.4	-36.21	12.92	-23.29	-13	Horizontal	
3346.4	-42.23	12.92	-29.31	-13	Vertical	
	Test R	esults for Chan	nel 4182/836.4MH	łz		
1672.8	-33.24	8	-25.24	-13	Vertical	
1672.8	-28.94	8	-20.94	-13	Horizontal	
2509.2	-31.24	11.2	-20.04	-13	Horizontal	
2509.2	-32.13	11.2	-20.93	-13	Vertical	
3345.6	-35.94	12.6	-23.34	-13	Horizontal	
3345.6	-32.89	12.6	-20.29	-13	Vertical	
	Test Res	ults for Char	nel 4132/826.4	4MHz		
1652.8	-30.4	8	-22.4	-13	Vertical	
1652.8	-30.6	8	-22.6	-13	Horizontal	
2479.2	-31.24	11.2	-20.04	-13	Horizontal	
2479.2	-31.23	11.2	-20.03	-13	Vertical	
3305.6	-32.55	12.6	-19.95	-13	Horizontal	
3305.6	-39.12	12.6	-26.52	-13	Vertical	

UMTS band V:

Note: Below 30MHZ no Spurious found.

7. FREQUENCY STABILITY

7.1 MEASUREMENT METHOD

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1 , Measure the carrier frequency at room temperature.

2 , Subject the EUT to overnight soak at -10 $^{\circ}$ C.

3 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 band , channel 190 for GSM 850 band, channel 9400 for UMTS band II and channel 4175 for UMTS band V and channel 1413 for UMTS band IV measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.

4 , Repeat the above measurements at 10 $^\circ\!C$ increments from -10 $^\circ\!C$ to +50 $^\circ\!C$. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.

5 , Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.

6 , Subject the EUT to overnight soak at +50 $^{\circ}$ C.

7 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.

8 , Repeat the above measurements at 10 $^\circ\!C$ increments from +50 $^\circ\!C$ to -10 $^\circ\!C$. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.

9 , At all temperature levels hold the temperature to +/- 0.5° C during the measurement procedure.

7.2 PROVISIONS APPLICABLE

7.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.6VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

7.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment, the normal environment temperature is 20°C.

7.3 MEASUREMENT RESULT

Frequency Error Against Voltage for GSM 850 band		
Voltage (V) Frequency Error (Hz) Frequency Error (ppm)		
3.6	19	0.023
3.7	20	0.024
4.2	21	0.025

Frequency Error Against Temperature for GSM 850 band		
Temperature (℃)	Frequency Error (Hz)	Frequency Error (ppm)
Voltage : DC3.7V		
-10	45	0.054
0	48	0.057
10	32	0.038
20	26	0.031
30	28	0.033
40	37	0.044
50	40	0.048

Note: The EUT doesn't work below -10 $^\circ\!\mathrm{C}$

Frequency Error Against Voltage for PCS 1900 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.6	27	0.014
3.7	35	0.019
4.2	31	0.016

Frequency Error Against Temperature for PCS 1900 band			
Temperature (℃)	Frequency Error (Hz)	Frequency Error (ppm)	
Nominal Voltage : DC3.7V			
-10	39	0.021	
0	25	0.013	
10	24	0.013	
20	32	0.017	
30	36	0.019	
40	44	0.023	
50	48	0.026	

Note: The EUT doesn't work below -10 $^\circ\!\mathrm{C}$

Frequency Error Against Voltage for UMTS band II		
Voltage (V) Frequency Error (Hz) Frequency Error (ppm)		Frequency Error (ppm)
3.6	30	0.016
3.7	28	0.015
4.2	32	0.017

Frequency Error Against Temperature for UMTS band II		
Temperature (℃)	Frequency Error (Hz)	Frequency Error (ppm)
Nominal Voltage : DC3.7V		
-10	43	0.023
0	35	0.019
10	28	0.015
20	25	0.013
30	30	0.016
40	37	0.020
50	42	0.022

Note: The EUT doesn't work below -10 $^\circ\!\mathrm{C}$

Frequency Error Against Voltage for UMTS band IV		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.6	25	0.014
3.7	33	0.019
4.2	37	0.021

Frequency Error Against Temperature for UMTS band IV			
Temperature (℃)	Frequency Error (Hz)	Frequency Error (ppm)	
	Nominal Voltage : DC3.7V		
-10	46	0.027	
0	37	0.021	
10	32	0.018	
20	27	0.016	
30	47	0.027	
40	52	0.030	
50	36	0.021	

Note: The EUT doesn't work below -10 $^\circ\!\mathrm{C}$

Frequency Error Against Voltage for UMTS band V		
Voltage (V) Frequency Error (Hz) Frequency Error (ppm)		
3.6	24	0.029
3.7	22	0.026
4.2	25	0.030

Frequency Error Against Temperature for UMTS band V		
Temperature (℃)	Frequency Error (Hz)	Frequency Error (ppm)
Nominal Voltage : DC3.7V		
-10	36	0.043
0	32	0.038
10	28	0.033
20	35	0.042
30	28	0.033
40	36	0.043
50	42	0.050

Note: The EUT doesn't work below -10°C

8. BANDWIDTH

8.1APPLICABLE STANDARD

FCC §2.1049, §22.917, §22.905 and §24.238 and §27.53(a.5)

8.2 Test Procedure

- 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- 2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.
- 3. Details according with KDB 971168 section 4.1 & 4.2.



Test Equipment List and Details

Refer a test equipment and calibration data table in this test report.

8.3 MEASUREMENT RESULT

Occupied Bandwidth (99%) for GSM 850 band		
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
Low Channel	824.2	248.9033
Middle Channel	836.6	248.4883
High Channel	848.8	244.9317

Occupied Bandwidth (99%) for PCS 1900 band				
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)		
Low Channel	1850.2	242.7375		
Middle Channel	1880.0	248.4596		
High Channel	1909.8	248.3604		
Occupied Bandwidth (99%) for UMTS band II				
---	----------------	-------------------------------	--	--
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(MHz)		
Low Channel	1852.4	4.1610		
Middle Channel	1880.0	4.1551		
High Channel	1907.6	4.1513		

Occupied Bandwidth (99%) for UMTS band IV						
Mode Frequency(MHz) Occupied Bandwidth (99%)(MH						
Low Channel	hannel 1712.6	4.1808				
Middle Channel	1732.6	4.1680				
High Channel	1752.4	4.1585				

Occupied Bandwidth (99%) for UMTS band V						
Mode Frequency(MHz) Occupied Bandwidth (99%)(MH						
Low Channel	826.4	4.1423				
Middle Channel	Middle Channel 836.4					
High Channel 846.6 4.1527						

Emission Bandwidth (-26dBc) for GSM 850 band						
Mode Frequency(MHz) Emission Bandwidth (-26dBc)(
Low Channel	824.2	319.160				
Middle Channel	le Channel 836.6 3					
High Channel	314.065					

Emission Bandwidth (-26dBc) for PCS 1900 band						
Mode Frequency(MHz) Emission Bandwidth (-26dBc)(kł						
Low Channel	1850.2	319.950				
Middle Channel	1880.0	319.707				
High Channel	1909.8	317.344				

Emission Bandwidth (-26dBc) for UMTS band II						
Mode	Frequency(MHz) Emission Bandwidth (-26dBc)(
Low Channel	1852.4	4.686				
Middle Channel	1880.0	4.668				
High Channel	1907.6	4.716				

Emission Bandwidth (-26dBc) for UMTS band IV						
Mode Frequency(MHz) Emission Bandwidth (-26dBc)(MHz						
Low Channel	annel 1712.6 4.795					
Middle Channel	1732.6	4.687				
High Channel	1752.4	4.699				

Emission Bandwidth (-26dBc) for UMTS band V						
Mode Frequency(MHz) Emission Bandwidth (-26dBc)(MH						
Low Channel	826.4	4.619				
Middle Channel	836.4	4.623				
High Channel	4.639					

9. BAND EDGE

9.1 Applicable Standard

According to 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$.

According to \$24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$.

According to 27.53(h), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$.

9.2 Test Procedure

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.

2. The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.

3. Details according with KDB 971168 section 6.0.



Test Equipment List and Details

Refer a test equipment and calibration data table in this test report.

9.3 MEASUREMENT RESULT

Please refers to Appendix III for compliance test plots for band edges

10. Peak-to-Average Ratio DESCRIPTION OF THE PAR MEASUREMENT The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB. **10.1 MEASURING INSTRUMENTS** See list of measuring instruments of this test report. **10.2 TEST PROCEDURES** 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. For GSM/EGPRS operating modes: a. Set the RBW = 1MHz, VBW = 1MHz, Peak detector in spectrum analyzer. b. Set EUT in maximum power output, and triggered the burst signal. c. Measured respectively the Peak level and Mean level, and the deviation was recorded as Peak to Average Ratio. 4. For UMTS operating modes: a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer. b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %. **TEST SETUP** 10.3



Cellular Band						
Modes	GSM850		GSM1900			
Channal	128	190	251	512	661	810
Channel	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency(MHz)	824.2	836.6	848.8	1850.2	1880	1909.8
Peak-to-Average Ratio (dB)	0.07	-0.03	0.02	0.05	0.00	-0.01
	•	Cellular	Band		•	•
	WCDMA Band II		WCDMA Band V			
wodes	(R	MC 12.2K	bps)	(R	MC 12.2K	bps)
Channel	9262	9400	9538	4132	4175	4233
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency(MHz)	1852.4	1880	1907.6	826.4	836.6	846.6
Peak-to-Average Ratio (dB)	-0.357	-0.299	-0.182	-0.373	-0.481	-0.116
		Cellular	Band			
Modes	WCDMA Band IV		WCDMA Band -			
	(R	MC 12.2K	bps)			
Channel	1313	1413	1512	(Low)	(Mid)	(High)
Gildiniei	(Low)	(Mid)	(High)	(2011)	(ivita)	(ingri)
Frequency(MHz)	1712.6	1732.6	1752.4			
Peak-to-Average Ratio (dB)	0.542	0.245	0.464			





Conducted Emission Transmitting Mode CH 128 5GHz - 10GHz











Conducted Emission Transmitting Mode CH 251 30MHz – 5GHz

Conducted Emission Transmitting Mode CH 251 5GHz - 10GHz





Conducted Emission Transmitting Mode CH 512 10GHz - 20GHz





Conducted Emission Transmitting Mode CH 661 10GHz - 20GHz





Conducted Emission Transmitting Mode CH 810 10GHz - 20GHz





Conducted Emission Transmitting Mode CH 9262 10GHz – 20GHz





Conducted Emission Transmitting Mode CH 9400 10GHz - 20GHz





Conducted Emission Transmitting Mode CH 9538 30MHz - 10GHz

Conducted Emission Transmitting Mode CH 9538 10GHz - 20GHz





Conducted Emission Transmitting Mode CH 1313 10GHz - 20GHz





Conducted Emission Transmitting Mode CH 1413 10GHz - 20GHz





Conducted Emission Transmitting Mode CH 1512 30MHz - 10GHz

Conducted Emission Transmitting Mode CH 1512 10GHz - 20GHz





Conducted Emission Transmitting Mode CH 4132 5GHz - 10GHz





Conducted Emission Transmitting Mode CH 4183 30MHz -5GHz

Conducted Emission Transmitting Mode CH 4183 5GHz - 10GHz





Conducted Emission Transmitting Mode CH 4233 30MHz – 5GHz

Conducted Emission Transmitting Mode CH 4233 5GHz - 10GHz



APPENDIX II TEST PLOTS FOR OCCUPIED BANDWIDTH (99%) EMISSION BANDWIDTH (-26dBC)



Occupied Bandwidth (99%) GSM 850 BAND CH 128

Occupied Bandwidth (99%) GSM 850 BAND CH 190





Occupied Bandwidth (99%) GSM 850 BAND CH 251

Occupied Bandwidth (99%) PCS 1900 BAND CH 512





Occupied Bandwidth (99%) PCS 1900 BAND CH 661

Occupied Bandwidth (99%) PCS 1900 BAND CH 810





Occupied Bandwidth (99%) UMTS band II CH 9262

Occupied Bandwidth (99%) UMTS band II CH 9400



Occupied Bandwidth (99%) UMTS band II CH 9538



Occupied Bandwidth (99%) UMTS band IV CH 1313







Occupied Bandwidth (99%) UMTS band V CH 4132

Occupied Bandwidth (99%) UMTS band V CH 4183



Agilent R Т Trace/View Ch Freq 846.6 MHz Trig Free Trace Occupied Bandwidth 2 3 1 Clear Write Ref 25 dBm Atten 35 dB Ext PG -4 dB #Peak Max Hold Log 0 Ó 10 dB/ ÷ m Min Hold View Center 846.6 MHz Span 6 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 62.16 ms (401 pts) Occupied Bandwidth Occ BW % Pwr 99.00 % Blank -26.00 dB 4.1527 MHz x dB More Transmit Freq Error 22.060 kHz 1 of 2 x dB Bandwidth 4.639 MHz No Peak Found

Occupied Bandwidth (99%) UMTS band V CH 4233





High Band Edge GSM 850 BAND CH 251





High Band Edge PCS 1900 BAND CH 810





High Band Edge UMTS BAND II CH 9538





High Band Edge UMTS BAND IV CH 1512





High Band Edge UMTS BAND V CH 4233


