

ALLEGRO Wall Mount

March 25, 2014

RF Exposure calculation

Based on FCC 1.1307 & 2.1091, FCC OET Bulletin 65

1. Categorically Exclusion from exposure Evaluation:

According to FCC regulation, RF exposure evaluation is Categorically Excluded if transmitter's operation frequency is less than 1.5GHz and ERP is less than 1.5W.

- 2. Absolute maximum specification of ALLEGRO WALL MOUNT transmitter
 - Operational frequency band **450MHz to 470MHz**
 - The ALLEGRO WALL MOUNT transmitter is measured for MAX RF Power 2.7 W
 - Absolute Maximum transmission time(duration) for any ALLEGRO WALL MOUNTtransmitters does not exceed 0.32 s
 - Transmission period-absolute maximum is **3 transmission** perhour
 - ALL ALLEGRO WALL MOUNT transmitters utilize 4GFSK modulation
- 3. Average RF Power Calculation

FCC regulation on permissible RF exposure are not based on the peak envelope power, but on average power (P_ave) over a 30-minute time period for uncontrolled environments.

As mentioned in (2), during any 30 minutes ALLEGRO WALL MOUNT can transmit 1.5 times. Duration is 0.32 second.

With maximum RF radiation equal to 2.7 W, the average RF Power over 30 minutes is:

P_ave(worst case) at 30 minute=2.7×1.5×0.32/30×60=0.72 mW

4. Maximum radiated Power Density prediction (S):

The predict power density (**S**) at distance **R=20 cm** from transmitter with **P_ave**=0.72 mW, next formula is used:

S=P_ave/($4 \times \pi \times R^2$)

For the worst case prediction of power density at or near a transmitter surface let's use:

S=P_ave/($4 \times \pi \times R^2$)=

=0.72mW/(4×3.14×20cm×20cm)=0.00014 mW/cm²

This is the worst case of the near field power density of ALLEGRO WALL MOUNTtransmitter.

5. Maximum Permissible Exposure (MPE) from ALLEGRO WALL MOUNT

As FCC require, the maximum permissible exposure for general public in "uncontrolled situation" at 20 cm is:

MPE=frequency[MHz]/1500=460MHz/1500=0.307mW/ cm^2

Compare results in (4) and (5),

S=0.00014 mW/ cm^2 <MPE=0.307 mW/ cm^2

We see that ALLEGRO WALL MOUNTfully complies with RF safety at a distance 20cm.

Dr. SlavaSnitkovsky

Telematics-Wireless