



TEST REPORT Report No.: CHTEW20060006 **Report Verification:** SHT2005070601EW Project No..... FCC ID.....: : 2AVTH-LO14WA Applicant's name : Hyundai Technology Group, Inc. Address.....: 2601 Walnut Ave. Tustin, CA, USA Manufacturer..... Hyundai Technology Group, Inc. 2601 Walnut Ave. Tustin, CA, USA Address.....: Test item description: Notebook Trade Mark HYUNDAI Model/Type reference.....: Hyundai Onnyx III Listed Model(s) LO14WA1BK,LO14WA1B,LO14WB1B,LO14WA1S,LO14WA1R G,LO14WB1S,Hyundai Onnyx III Plus Standard:: FCC CFR Title 47 Part 15 Subpart C Section 15.247 Date of receipt of test sample......: May 18, 2020 Date of testing..... May 19, 2020-Jun.01, 2020 Date of issue..... Jun.01, 2020 PASS Result.....: Jang hui Zhu Compiled by (Position+Printed name+Signature): File administrator Fanghui Zhu Supervised by (Position+Printed name+Signature): Project Engineer Kiki Kong Approved by (Position+Printed name+Signature): **RF Manager Hans Hu** Testing Laboratory Name: : Shenzhen Huatongwei International Inspection Co., Ltd. 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Address..... Tianliao, Gongming, Shenzhen, China Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. The test report merely correspond to the test sample.

Contents

<u>1.</u>	TEST STANDARDS AND REPORT VERSION	3
1.1. 1.2.	Test Standards Report version	3 3
<u>2.</u>	TEST DESCRIPTION	4
<u>3.</u>	SUMMARY	5
3.1. 3.2. 3.3. 3.4.	Client Information Product Description Radio Specification Description Testing Laboratory Information	5 5 5 6
<u>4.</u>	TEST CONFIGURATION	7
4.1. 4.2. 4.3. 4.4. 4.5. 4.6.	Test frequency list Test mode Support unit used in test configuration and system Testing environmental condition Measurement uncertainty Equipment Used during the Test	7 7 7 8 8 9
<u>5.</u>	TEST CONDITIONS AND RESULTS	11
5.1. 5.2. 5.3. 5.4. 5.5. 5.6. 5.7. 5.8. 5.9. 5.10.	Antenna Requirement AC Conducted Emission Peak Output Power Power Spectral Density 6dB bandwidth 99% Occupied Bandwidth Duty Cycle Conducted Band edge and Spurious Emission Radiated Band edge Emission Radiated Spurious Emission	11 12 15 16 17 18 19 20 22 22
<u>6.</u>	TEST SETUP PHOTOS	29
<u>7.</u>	EXTERANAL AND INTERNAL PHOTOS	31
8.	APPENDIX REPORT	39

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- <u>FCC Rules Part 15.247</u>: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- ANSI C63.10:2013: American National Standard for Testing Unlicensed Wireless Devices
- KDB 558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2020-06-01	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result	
5.1	Antenna Requirement	15.203/15.247(c)	PASS	
5.2	AC Conducted Emission	15.207	PASS	
5.3	Peak Output Power	15.247(b)(3)	PASS	
5.4	Power Spectral Density	15.247(e)	PASS	
5.5	6dB Bandwidth	15.247(a)(2)	PASS	
5.6	99% Occupied Bandwidth	-	PASS ^{*1}	
5.7	Duty cycle	-	PASS ^{*1}	
5.8	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS	
5.9	Radiated Band Edge Emission	15.205/15.209	PASS	
5.10	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS	

Note:

- The measurement uncertainty is not included in the test result.
- *1: No requirement on standard, only report these test data.

3. SUMMARY

3.1. Client Information

Applicant:	Hyundai Technology Group, Inc.
Address:	2601 Walnut Ave. Tustin, CA, USA
Manufacturer:	Hyundai Technology Group, Inc.
Address:	2601 Walnut Ave. Tustin, CA, USA

3.2. Product Description

Name of EUT:	Notebook		
Trade Mark:	HYUNDAI		
Model No.:	Hyundai Onnyx III		
Listed Model(s):	LO14WA1BK,LO14WA1B,LO14WB1B,LO14WA1S,LO14WA1RG,LO14W B1S,Hyundai Onnyx III Plus		
Power supply:	DC 7.6V		
Hardware version:	IP3_AN10F MB_V30		
Software version:	1909		
Adapter Information:	Model: RY-24A120200VU Input: AC 100-240V~ 50/60Hz 0.8A Output: DC 12V 2.0A		
Battery Information:	Model: NV-3285128-2S NOM 7.6V 5000mAh 38Wh Max Voltage: 8.7V		

3.3. Radio Specification Description

Bluetooth version:	V4.0
Support function ^{*2} :	BLE
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	FPC Antenna
Antenna gain:	1.28 dBi

Note:

*2: only show the RF function associated with this report.

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.			
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China			
	Туре	Accreditation Number		
	CNAS	L1225		
Qualifications	A2LA	3902.01		
	FCC	762235		
	Canada	5377A		

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

Channel	Frequency (MHz)
00	2402
01	2404
:	÷
19	2440
:	÷
38	2478
39	2480

4.2. Test mode

For RF test items

The engineering test program was provided and enabled to make EUT continuous transmit.

For Radiated spurious emissions test item:

The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

4.3. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whet	Whether support unit is used?							
~	✓ No							
Item	Equipement Trade Name Model No. FCC ID Power cord							
1								
2								

4.4. Testing environmental condition

Туре	Requirement	Actual	
Temperature:	15~35°C	25°C	
Relative Humidity:	25~75%	50%	
Air Pressure:	860~1060mbar	1000mbar	

4.5. Measurement uncertainty

Test Item	Measurement Uncertainty
AC Conducted Emission (150kHz~30MHz)	3.02 dB
Radiated Emission (30MHz~1000MHz	4.90 dB
Radiated Emissions (1GHz~25GHz)	4.96 dB
Peak Output Power	0.51 dB
Power Spectral Density	0.51 dB
Conducted Spurious Emission	0.51 dB
6dB Bandwidth	70 Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.6. Equipment Used during the Test

•	Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
•	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27	
•	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2019/10/26	2020/10/25	
•	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2019/10/23	2020/10/22	
٠	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2019/10/23	2020/10/22	
•	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLE X_142	EF-NM- BNCM-2M	2019/10/23	2020/10/22	
•	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A	

•	Radiated emission-6th test site										
Used	Test Equipment	Manufacturer	Equipment Model No.		Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)				
•	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2021/09/29				
•	EMI Test Receiver	est Receiver R&S		ESCI	100900	2019/10/26	2020/10/25				
•	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2018/04/02	2021/04/01				
•	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	538	2018/04/04	2021/04/03				
•	Pre-Amplifer	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2019/11/14	2020/11/13				
•	RF Connection Cable	HUBER+SUHNER	HTWE0062- 01	N/A	N/A	2019/08/21	2020/08/20				
•	RF Connection Cable			SUCOFLEX 104	501184/4 2020/05/27		2021/05/26				
•	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A				

•	Radiated emis	sion-7th test site					
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
•	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2021/09/26
•	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2019/10/26	2020/10/25
•	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2017/04/01	2020/03/31
•	Horn Antenna SCHWARZBECK		HTWE0103	BBHA9170	25841	2018/10/11	2021/10/10
•	Broadband Horn Antenna SCHWARZE		HTWE0103	BBHA9170	BBHA9170472	2018/10/11	2021/10/11
•	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2019/11/14	2020/11/13
•	Broadband Pre- amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2020/05/23	2021/05/22
•	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2020/05/10	2021/05/09
•	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2020/05/10	2021/05/09
•	RF Connection Cable	HUBER+SUHNER	HTWE0120-03	6m 3GHz RG Serisa	N/A	2020/05/10	2021/05/09
•	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2020/05/10	2021/05/09
•	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	6m 18GHz S Serisa	N/A	2020/05/10	2021/05/09
•	Test Software	Audix	N/A	E3	N/A	N/A	N/A

•	RF Conducted Method										
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)					
•	Signal and spectrum Analyzer	R&S	FSV40	100048	2019/10/26	2020/10/25					
•	Spectrum Analyzer	Agilent	N9020A	MY50510187	2019/10/26	2020/10/25					
•	Power Meter	Anritsu	ML249A	N/A	2019/10/26	2020/10/25					
0	Radio communication tester	R&S	CMW500	137688-Lv	2019/10/26	2020/10/25					

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

<u>Requirement</u>

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responseble party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULT

☑ Passed □ Not Applicable

The antenna type is a FPC antenna, the directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)				
	Quasi-peak	Average			
0.15-0.5	66 to 56*	56 to 46*			
0.5-5	56	46			
5-30	60	50			

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE


- 1. The EUT was setup according to ANSI C63.10 requirements.
- The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
- The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
- 4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
- 5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
- 6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
- 7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
- 8. During the above scans, the emissions were maximized by cable manipulation.


TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☑ Passed □ Not Applicable






5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

TEST CONFIGURATION



TEST PROCEDURE

- 1. The EUT was tested according to ANSI C63.10 and KDB 558074 D01 requirements.
- 2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
- 3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
- 4. Record the measurement data.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☑ Passed □ Not Applicable

TEST Data

Please refer to appendix A on the appendix report


5.4. Power Spectral Density

<u>LIMIT</u>

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

- 1. Connect the antenna port(s) to the spectrum analyzer input,
- Configure the spectrum analyzer as shown below: Center frequency=DTS channel center frequency Span =1.5 times the DTS bandwidth RBW = 3 kHz ≤ RBW ≤ 100 kHz, VBW ≥ 3 × RBW Sweep time = auto couple Detector = peak Trace mode = max hold
- 3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
- 4. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☑ Passed □ Not Applicable

TEST Data

Please refer to appendix B on the appendix report


5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



➡ Ground Reference Plane ◄

TEST PROCEDURE

- 1. Connect the antenna port(s) to the spectrum analyzer input.
- 2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).

Center Frequency =DTS channel center frequency

Span=2 x DTS bandwidth

RBW = 100 kHz, VBW \ge 3 × RBW

Sweep time= auto couple

Detector = Peak

Trace mode = max hold

- 3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

🛛 Passed 🛛 🗌

Not Applicable

TEST Data


Please refer to appendix C on the appendix report

5.6. 99% Occupied Bandwidth

<u>LIMIT</u>

N/A

TEST CONFIGURATION



TEST PROCEDURE

- 1. Connect the antenna port(s) to the spectrum analyzer input.
- 2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).

Center Frequency =channel center frequency Span≥1.5 x OBW RBW = 1%~5%OBW VBW ≥ 3 × RBW Sweep time= auto couple Detector = Peak Trace mode = max hold

3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☑ Passed □ Not Applicable


TEST Data

Please refer to appendix D on the appendix report

5.7. Duty Cycle

N/A

TEST CONFIGURATION



TEST PROCEDURE

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- Use the following spectrum analyzer settings: Span=zero span, Frequency=centered channel, RBW= 1 MHz, VBW ≥ RBW Sweep=as necessary to capture the entire dwell time, Detector function = peak, Trigger mode
- 4. Measure and record the duty cycle data

TEST MODE:

Please refer to the clause 4.2

TEST Data


Please refer to appendix E on the appendix report

5.8. Conducted Band edge and Spurious Emission

<u>LIMIT</u>

FCC CFR Title 47 Part 15 Subpart C Section15.247 (d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

- 1. Connect the antenna port(s) to the spectrum analyzer input.
- Establish a reference level by using the following procedure Center frequency=DTS channel center frequency The span = 1.5 times the DTS bandwidth. RBW = 100 kHz, VBW ≥ 3 x RBW

Detector = peak, Sweep time = auto couple, Trace mode = max hold

Allow trace to fully stabilize

Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

3. Emission level measurement

Set the center frequency and span to encompass frequency range to be measured

RBW = 100 kHz, VBW \ge 3 x RBW

Detector = peak, Sweep time = auto couple, Trace mode = max hold

Allow trace to fully stabilize

Use the peak marker function to determine the maximum amplitude level.

- 4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
- Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☑ Passed □ Not Applicable

TEST Data

Please refer to appendix F on the appendix report


5.9. Radiated Band edge Emission

<u>LIMIT</u>

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

- 1. The EUT was setup and tested according to ANSI C63.10.
- 2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3. The EUT waspositioned such that the distance from antenna to the EUT was 3 meters.
- 4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find themaximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
- 5. Use the following spectrum analyzer settings:
 - a) Span shall wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

- VBW=10Hz, When duty cycle is no less than 98 percent
- VBW≥1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clasue 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☑ Passed □ Not Applicable

Note:

- 1) Level= Reading + Factor; Factor = Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

Test channe	el				CH00						
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value		
2310.00	35.40	27.96	7.73	38.17	32.92	74.00	-41.08	Vertical	Peak		
2390.03	34.75	27.72	7.84	37.97	32.34	74.00	-41.66	Vertical	Peak		
2310.00	36.38	27.96	7.73	38.17	33.90	74.00	-40.10	Horizontal	Peak		
2390.03	35.57	27.72	7.84	37.97	33.16	74.00	-40.84	Horizontal	Peak		
2310.00	31.89	27.96	7.73	38.17	29.41	54.00	-24.59	Vertical	Average		
2390.03	30.07	27.72	7.84	37.97	27.66	54.00	-26.34	Vertical	Average		
2310.00	28.21	27.96	7.73	38.17	25.73	54.00	-28.27	Horizontal	Average		
2390.03	28.65	27.72	7.84	37.97	26.24	54.00	-27.76	Horizontal	Average		

Test channe	el				CH39				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.50	35.49	27.43	8.04	37.59	33.37	74.00	-40.63	Vertical	Peak
2500.00	33.76	27.40	8.08	37.38	31.86	74.00	-42.14	Vertical	Peak
2483.50	34.32	27.43	8.04	37.59	32.20	74.00	-41.80	Horizontal	Peak
2500.00	34.10	27.40	8.08	37.38	32.20	74.00	-41.80	Horizontal	Peak
2483.50	26.63	27.43	8.04	37.59	24.51	54.00	-29.49	Vertical	Average
2500.00	26.58	27.40	8.08	37.38	24.68	54.00	-29.32	Vertical	Average
2483.50	27.14	27.43	8.04	37.59	25.02	54.00	-28.98	Horizontal	Average
2500.00	25.72	27.40	8.08	37.38	23.82	54.00	-30.18	Horizontal	Average

5.10. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value		
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak		
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak		
1.705 MHz ~30 MHz	30 @30m	Quasi-peak		


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION

➢ 9 kHz ~ 30 MHz




> 30 MHz ~ 1 GHz



> Above 1 GHz

Page: 25 of 39

Issued: 2



TEST PROCEDURE

- 1. The EUT was setup and tested according to ANSI C63.10 .
- 2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
- 4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
- 5. Set to the maximum power setting and enable the EUT transmit continuously.
- 6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

- VBW=10Hz, When duty cycle is no less than 98 percent
- − VBW≥1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clasue 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☑ Passed □ Not Applicable

Note:


- 1) Above 1GHz Final Level = Read level + Antenna Factor + Cable Loss Preamplifier Factor
- 2) Over Limit = Level Limit
- Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

<u> TEST DATA FOR 9 kHz ~ 30 MHz</u>

The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

TEST DATA FOR 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH39 which it was worst case, so only show the worst case's data on this report.



<u> TEST DATA FOR 1 GHz ~ 25 GHz</u>

Test channe	el				CH00							
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value			
1173.94	37.48	25.50	5.45	37.65	30.78	74.00	-43.22	Vertical	Peak			
3151.99	35.02	29.00	9.30	37.71	35.61	74.00	-38.39	Vertical	Peak			
5125.52	32.04	32.10	12.04	35.02	41.16	74.00	-32.84	Vertical	Peak			
8022.46	31.79	37.14	15.60	34.40	50.13	74.00	-23.87	Vertical	Peak			
1225.86	36.24	25.76	5.59	37.65	29.94	74.00	-44.06	Horizontal	Peak			
3208.66	34.30	28.87	9.46	37.34	35.29	74.00	-38.71	Horizontal	Peak			
5125.52	32.49	32.10	12.04	35.02	41.61	74.00	-32.39	Horizontal	Peak			
9157.86	32.52	38.63	15.97	35.71	51.41	74.00	-22.59	Horizontal	Peak			

Test channe	el				CH19				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1357.25	36.05	26.27	5.93	37.35	30.90	74.00	-43.10	Vertical	Peak
3516.59	34.52	29.17	9.92	37.81	35.80	74.00	-38.20	Vertical	Peak
5164.81	31.63	31.91	12.05	34.79	40.80	74.00	-33.20	Vertical	Peak
8615.13	31.72	37.43	15.93	34.48	50.60	74.00	-23.40	Vertical	Peak
1263.88	36.78	25.93	5.69	37.65	30.75	74.00	-43.25	Horizontal	Peak
2875.99	35.04	28.60	8.88	36.54	35.98	74.00	-38.02	Horizontal	Peak
4444.56	32.34	30.78	11.16	36.65	37.63	74.00	-36.37	Horizontal	Peak
8042.90	31.31	37.19	15.67	34.37	49.80	74.00	-24.20	Horizontal	Peak


Test channe	el				CH39				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1353.80	35.38	26.28	5.92	37.33	30.25	74.00	-43.75	Vertical	Peak
3176.16	35.30	28.95	9.37	37.56	36.06	74.00	-37.94	Vertical	Peak
5047.83	32.06	32.19	12.02	35.35	40.92	74.00	-33.08	Vertical	Peak
8681.17	32.03	37.62	15.95	34.60	51.00	74.00	-23.00	Vertical	Peak
1706.70	36.82	25.11	6.57	37.87	30.63	74.00	-43.37	Horizontal	Peak
2252.46	35.20	28.10	7.69	38.07	32.92	74.00	-41.08	Horizontal	Peak
5271.06	33.39	31.40	12.25	35.00	42.04	74.00	-31.96	Horizontal	Peak
8571.38	31.98	37.23	15.92	34.40	50.73	74.00	-23.27	Horizontal	Peak

6. TEST SETUP PHOTOS

Radiated Emission










AC Conducted Emission





7. EXTERANAL AND INTERNAL PHOTOS

External Photos












Shenzhen Huatongwei International Inspection Co., Ltd.










Shenzhen Huatongwei International Inspection Co., Ltd.


Internal Photos















Shenzhen Huatongwei International Inspection Co., Ltd.









Shenzhen Huatongwei International Inspection Co., Ltd.








Shenzhen Huatongwei International Inspection Co., Ltd.

Report Template Version: V02 (2019-10)








Shenzhen Huatongwei International Inspection Co., Ltd.

Issued:



8. APPENDIX REPORT

Shenzhen Huatongwei International Inspection Co., Ltd.

APPENDIX REPORT

Project No.	SHT2005070601EW	Radio Specification	Bluetooth BLE
Test sample No.	YPHT20050706001	Model No.	Hyundai Onnyx III
Start test date	2020/5/25	Finish date	2020/5/25
Temperature	25°C	Humidity	50%
Test Engineer	Jiongsheng.Feng	Auditor	William . wang


Appendix clause	Test item	Result
А	Peak Output Power	PASS
В	Power Spectral Density	PASS
С	6 dB Bandwidth	PASS
D	99% Occupied Bandwidth	PASS
E	Duty cycle	PASS
F	Band edge and Spurious Emissions (conducted)	PASS

Appendix A:	Peak Output Power
-------------	-------------------

Туре	Channel	Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
	00	-1.85	-1.86		
BT-BLE	19	-2.03	-2.04	≤30.00	Pass
	39	-2.59	-2.61		

Appendix B: Power Spectral Density

Туре	Channel	Power Spectral Density(dBm/3KHz)	Limit (dBm/3KHz)	Result
	00	-20.15		
BT-BLE	19	-20.20	≤8.00	Pass
	39	-20.86		




Appendix C: 6dB bandwidth

Туре	Channel	6dB Bandwidth(kHz)	Limit (kHz)	Result
	00	640.00		
BT-BLE	19	664.00	≥500	Pass
	39	682.00		




Appendix D: 99% Occupied Bandwidth

Туре	Channel	99% Occupied Bandwidth(MHz)	Limit (kHz)	Result
	00	1.03		
BT-BLE	19	1.03	-	Pass
	39	1.03		





Appendix E: Duty cycle


Test Frequency (MHz)	T _{on time} for single burst (ms)	T _{period} (ms)	Duty cycle	1/T _{on time} (kHz)
2440	0.10	0.62	16.1%	10
	Ref Level 30.00 dim • Att model • Rt model	All of the second sec	SGL	



Appendix F: Band edge and Spurious Emissions (conducted)







-----End of Report------