

**TEST REPORT**

<b>Applicant:</b>	ARTIKA FOR LIVING INC.
<b>Address of Applicant:</b>	1756 50th avenue, Lachine, QC, Canada H8T 2V5
<b>Manufacturer:</b>	FOSHAN ECCO LIGHTING CO.,LTD
<b>Address of Manufacturer:</b>	No.70, East Development Zone, Donglian Shichen Village , Danzao Town, Nanhai District, Foshan City, Guangdong Province, P.R.China
<b>Product name:</b>	LED mirror light
<b>Model:</b>	WMIRH-ROCH-D28-XXXXXXXX("XXXXXXXX" can be A to Z and/or 0 to 9 and/or blank, means commercial code), WMIRH-ROCH-D28-DXXXXXXXX("XXXXXXXX" can be A to Z and/or 0 to 9 and/or blank, means commercial code), M211D71XXXXXXXX("XXXXXXXX" can be A to Z and/or 0 to 9 and/or blank, means commercial code), ZSJ-M211D71XXXXXXXX("XXXXXXXX" can be A to Z and/or 0 to 9 and/or blank, means commercial code).
<b>Rating(s):</b>	AC120V, 60Hz, 45W
<b>Trademark:</b>	ARTIKA
<b>Standards:</b>	FCC Part15 subpart B
<b>FCC ID:</b>	2AUHG-WMIRH-ROCH
<b>Date of Receipt:</b>	2024-03-20
<b>Date of Test:</b>	2024-03-20~2024-04-06
<b>Date of Issue:</b>	2024-04-06
<b>Test Result</b>	<b>Pass*</b>

\* In the configuration tested, the test item complied with the standards specified above.

**Authorized for issue by:****Test by:**

Apr.06, 2024 Chivas Tsang

Project Engineer

Date

Name/Position

Signature

**Reviewed by:**


Apr.06, 2024 Victor Meng

Project Manager

Date

Name/Position

Signature



This report is for the exclusive use of ITL's client and is provided pursuant to the agreement between ITL assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the ITL name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by ITL. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an ITL certification program. The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

**Testing Laboratory information:**

Testing Laboratory Name .....: ITL Co., LTD  
Address .....: No.8, Jinqianling Street 5, Huangjiang, Dongguan, Guangdong, China.  
Testing location .....: Same as above  
Tel.....: 0086-769-39001678  
Fax .....: 0086-20-62824387  
E-mail .....: itl@i-testlab.com

**Possible test case verdicts:**

- test case does not apply to the test object..: N/A
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.: F (Fail)

**General remarks:**

**The test results presented in this report relate only to the object tested.**

**The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.**

This report would be invalid test report without all the signatures of testing technician and approver.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

**General product information:**

All modes are identical to each other except for the model name.

All tests were performed on the model WMIRH-ROCH-D28-BL as representatives.

**Test Summary:**

The following standards have been applied to ensure the product conforms with the protection requirements of the council directive FCC part 15B.

Electromagnetic Emissions				
Test Item	Test Standard	Test Method	Class/Severity	Result
Conducted Emission(0.15-30MHz)	FCC part 15.107	ANSI C63.4:2014	Class B	PASS
Radiated Emission(30-1000MHz)	FCC part 15.109	ANSI C63.4:2014	Class B	PASS

**Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS Lab code:L9342**
- **FCC Designation No.:CN5035**
- **IC Registration NO.: 12593A**
- **NVLAP LAB CODE: 600199-0**

**Test Location:**

All the tests were performed in ITL Co., LTD. Where is located at at No.8, Jinqianling Street 5, Huangjiang, Dongguan, Guangdong, China.

Tel: 0086-769-39001678, Fax: 0086-20-62824387

No test is subcontracted

## TABLE OF CONTENTS

<b>TEST REPORT</b>	1
<b>Test Summary:</b>	3
Test Facility	3
<b>Test Location:</b>	3
<b>Section 1 General Information and Equipment Used</b>	5
1.1 Client Information	5
1.2 EUT General and Technical Descriptions	5
1.3 Support Equipment(s) and Test Configuration	5
1.3.1 Details of Support Equipment(s)	5
1.3.2 Working State of EUT	5
1.3.3 Block Diagram of Test Configuration	5
1.4 Equipment Used during Test	6
<b>Section 2 Emission Test Results</b>	7
2.1 Conducted Emission at Mains Terminals, 150 kHz to 30MHz	7
2.1.1 E.U.T. Operation	7
2.1.2 Test Setup and Procedure	8
2.1.3 Measurement Data	8
2.2 Radiated Emissions, 30MHz to 1GHz	11
2.2.1 E.U.T. Operation	11
2.2.2 Test Setup and Procedure	12
2.2.3 Measurement Data	13
<b>Section 3 Photographs</b>	15
3.1 Conducted Emissions Mains Terminals Test Setup	15
3.2 Radiated Emissions, 30MHz to 1GHz Test Setup	15
3.3 EUT Constructional Details	16

## Section 1 General Information and Equipment Used

### 1.1 Client Information

Applicant: ARTIKA FOR LIVING INC.  
Address of Applicant: 1756 50th avenue, Lachine, QC, Canada H8T 2V5

### 1.2 EUT General and Technical Descriptions

EUT Name: LED mirror light  
EUT Model: WMIRH-ROCH-D28-BL  
EUT Trademark: ARTIKA  
Input Voltage: 120V~  
Frequency: 60Hz  
Input Power/Current: 45W.  
Output rated: /  
Power Cable Description: /  
Other Cables Description: /  
I/O Ports: /  
Function(s) Description: /  
Accessories information: /

### 1.3 Support Equipment(s) and Test Configuration

#### 1.3.1 Details of Support Equipment(s)

Description	Manufacturer	Model No.	Connection	Working state
/	/	/	/	/

#### 1.3.2 Working State of EUT

Power Supply of EUT: 120V~ 60Hz  
EUT Status: Pre-test the EUT in On Mode with each mode to find the worst case, Compliance test the EUT in On Mode with brightest white light and the fog removal function is enabled as the worst case was found.

#### 1.3.3 Block Diagram of Test Configuration

/

---

**1.4 Equipment Used during Test**

---

Conducted Emission						
No.	Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
DGITL-303a	EMI Test receiver	R&S	ESCI	100910	2023.04.07	2024.04.07
DGITL-304	L.I.S.N.#1	R&S	ESH3-Z5	100272	2023.04.07	2024.04.07
DGITL-302	Shielded Room	ETS•Lindgren	8*4*3	CT09010	2020.08.03	2023.08.03
DGITL-316	Pulse Limiter	R&S	ESH3-Z2	100327	2023.04.07	2024.04.07

Radiated Emission						
No.	Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
DGITL- 301	Semi-Anechoic chamber	ETS•Lindgren	9*6*6	CT000874-1181	2020.08.03	2023.08.03
DGITL- 307	EMI test receiver	R&S	ESVS10	833616/003	2023.04.07	2024.04.07
DGITL- 306	Spectrum Analyzer	Agilent Technologies	N9010A	MY54200334	2023.04.07	2024.04.07
DGITL- 308	Bilog Antenna	ETS•Lindgren	3142E	156975	2023.05.14	2025.05.14
DGITL- 352	Pre Amplifier	MInI-Circuits	ZFC-1000 HX	SN292801110	2023.04.07	2024.04.07

## Section 2 Emission Test Results

### 2.1 Conducted Emission at Mains Terminals, 150 kHz to 30MHz

Test Requirement:	FCC part 15.107
Test Method:	ANSI C63.4:2014
Test Voltage:	120V AC, 60Hz
Frequency Range:	150 kHz to 30MHz
Detector:	Peak for pre-scan Quasi-Peak and Average at frequency with maximum peak (9 kHz resolution bandwidth)
Uncertainty:	2Uc (V) = 2.3dB
Class / Limit:	Class B

Frequency range MHz	Class B Limits dB (μV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
NOTE 1 :The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		
NOTE 2: The lower limit is applicable at the transition frequency.		

#### 2.1.1 E.U.T. Operation

Operating Environment:


Temperature: 23.0 °C

Humidity: 49 % RH

Atmospheric Pressure: 101 kPa

EUT Operation: Pre-test the EUT in On Mode with each mode to find the worst case, Compliance test the EUT in On Mode with brightest white light and the fog removal function is enabled as the worst case was found.

## 2.1.2 Test Setup and Procedure



1. The mains terminal disturbance voltage test was conducted in a shielded room.
2. The EUT was connected to nominal power supply through a LISN 1 (Line Impedance Stabilization Network) which provides a  $50\Omega/50\mu\text{H}+5\Omega$  linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

## 2.1.3 Measurement Data


Pre-scan was performed with peak detected on both live and neutral cable. Quasi-peak & average measurements were performed at the frequencies which maximum peak emission level was detected. Please see the attached Quasi-peak and Average test results.



Live Line:

Peak Scan:

Level (dBuV)



Quasi-peak and Average measurement


NO.	Freq MHz	Level dBuV	Remark	LISN Factor dB	Cable Loss dB	Limit Line dBuV	Margin dB
1	0.190	57.05	QP	9.68	0.21	64.04	-6.99
2	0.190	44.75	Average	9.68	0.21	54.02	-9.27
3	0.778	40.94	QP	9.70	0.29	56.00	-15.06
4	0.778	36.06	Average	9.70	0.29	46.00	-9.94
5	1.176	41.88	QP	9.67	0.32	56.00	-14.12
6	1.176	35.22	Average	9.67	0.32	46.00	-10.78
7	2.354	42.06	QP	9.64	0.36	56.00	-13.94
8	2.354	34.51	Average	9.64	0.36	46.00	-11.49
9	7.708	43.93	QP	9.69	0.42	60.00	-16.07
10	7.708	36.46	Average	9.69	0.42	50.00	-13.54
11	27.933	36.29	QP	9.66	0.50	60.00	-23.71
12	27.933	30.47	Average	9.66	0.50	50.00	-19.53

Level=Read Level + LISN Factor + Cable Loss

## Neutral Line:

Peak Scan:

Level (dB  $\mu$  V)



Quasi-peak and Average measurement

NO.	Freq MHz	Level dBuV	Remark	LISN Factor dB	Cable Loss dB	Limit Line dBuV	Margin dB
1	0.194	54.70	QP	9.64	0.21	63.86	-9.16
2	0.194	40.39	Average	9.64	0.21	53.84	-13.45
3	0.696	44.56	QP	9.62	0.29	56.00	-11.44
4	0.696	37.39	Average	9.62	0.29	46.00	-8.61
5	2.000	43.51	QP	9.62	0.35	56.00	-12.49
6	2.000	33.94	Average	9.62	0.35	46.00	-12.06
7	2.429	44.47	QP	9.62	0.36	56.00	-11.53
8	2.429	35.50	Average	9.62	0.36	46.00	-10.50
9	5.000	39.21	QP	9.62	0.40	56.00	-16.79
10	5.000	31.42	Average	9.62	0.40	46.00	-14.58
11	27.933	35.16	QP	9.62	0.50	60.00	-24.84
12	27.933	30.85	Average	9.62	0.50	50.00	-19.15

Level=Read Level + LISN Factor + Cable Loss

## 2.2 Radiated Emissions, 30MHz to 1GHz

Test Requirement:	FCC part 15.109
Test Method:	ANSI C63.4:2014
Test Voltage:	120V AC, 60Hz
Frequency Range:	30MHz to 1GHz
Measurement Distance	3m
Detector:	Peak for pre-scan Quasi-Peak if maximised peak within 6dB of limit (120 kHz resolution bandwidth)
Uncertainty:	$2U_c(V) = 3.35\text{dB}$
Class / Limit:	Class B

Frequency range MHz	Quasi-peak limits dB ( $\mu\text{V/m}$ )
30 to 88	40
88 to 216	43.5
216 to 960	46
960 to 1000	54
At transitional frequencies the lower limit applies	


### 2.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C      Humidity: 49 % RH      Atmospheric Pressure: 101 kPa

EUT Operation: Pre-test the EUT in On Mode with each mode to find the worst case, Compliance test the EUT in On Mode with brightest white light and the fog removal function is enabled as the worst case was found.

## 2.2.2 Test Setup and Procedure




1. The radiated emissions test was conducted in a semi-anechoic chamber.
2. Biconical and log periodic antenna was used for the frequency range from 30MHz to 1GHz
3. The EUT was connected to nominal power supply through a mains power outlet which was bonded to the ground reference plane; The mains cables were draped to the ground reference plane. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. Before final measurements of radiated emissions, a pre-scan was performed in the spectrum mode with the peak detector to find out the maximum emissions spectrum plots of the EUT.
5. The frequencies of maximum emission were determined in the final radiated emissions measurement. At each frequency, the EUT was rotated 360° , and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum disturbance. Measurements were performed for both horizontal and vertical antenna polarization.

### 2.2.3 Measurement Data

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement


No.	Freq MHz	Read Level dBμV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBμV/m	Limit Line dBμV/m	Over Limit dB	Pol/Phase	Remark
1	35.875	29.64	18.43	0.68	28.51	20.24	40.00	-19.76	HORIZONTAL	QP
2	51.301	42.25	6.95	0.82	28.54	21.48	40.00	-18.52	HORIZONTAL	QP
3	67.913	42.68	6.50	0.96	28.28	21.86	40.00	-18.14	HORIZONTAL	QP
4	131.758	41.62	8.89	1.37	28.36	23.52	43.50	-19.98	HORIZONTAL	QP
5	180.649	36.55	9.55	1.61	27.79	19.92	43.50	-23.58	HORIZONTAL	QP
6	272.278	26.73	12.89	2.02	27.32	14.32	46.00	-31.68	HORIZONTAL	QP

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**



**Vertical:**

Peak scan

Level (dB $\mu$ V/m)

Quasi-peak measurement


No.	Freq MHz	Read Level dB $\mu$ V	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dB $\mu$ V/m	Limit Line dB $\mu$ V/m	Over Limit dB	Pol/Phase	Remark
1	35.375	42.81	18.78	0.68	28.56	33.71	40.00	-6.29	VERTICAL	QP
2	59.649	55.03	4.69	0.89	28.21	32.40	40.00	-7.60	VERTICAL	QP
3	67.438	55.80	6.39	0.96	28.28	34.87	40.00	-5.13	VERTICAL	QP
4	75.182	51.02	7.21	1.01	28.19	31.05	40.00	-8.95	VERTICAL	QP
5	139.361	47.09	8.44	1.41	28.21	28.73	43.50	-14.77	VERTICAL	QP
6	180.017	31.06	9.50	1.61	27.80	14.37	43.50	-29.13	VERTICAL	QP

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**

---

## Section 3 Photographs

### 3.1 Conducted Emissions Mains Terminals Test Setup



### 3.2 Radiated Emissions, 30MHz to 1GHz Test Setup





---

This report is for the exclusive use of ITL's client and is provided pursuant to the agreement between ITL assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the ITL name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by ITL. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an ITL certification program. The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

---


### 3.3 EUT Constructional Details





---

This report is for the exclusive use of ITL's client and is provided pursuant to the agreement between ITL assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the ITL name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by ITL. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an ITL certification program. The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.


















END OF THE TEST REPORT