

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-212-RWD-083

Reception No. : 2101000293

Applicant : LG Electronics USA

Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, 07632, United States

Manufacturer : LG Electronics Inc.

Address : 222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

Type of Equipment : DISPLAY ASM-VIDEO

FCC ID. : BEJIR12PT-TS

Model Name : IR12PT-TS

Serial number : N/A

Total page of Report : 137 pages (including this page)

Date of Incoming : January 11, 2021

Date of issue : February 19, 2021

SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.


It is not a generally valid assessment of the features of the respective products of the mass-production.



Tested by
Hyung-Kwon, Oh / Manager
ONETECH Corp.



Reviewed by
Tae-Ho, Kim / Senior Manager
ONETECH Corp.



Approved by
Ki-Hong, Nam / General Manager
ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	7
2. TEST SUMMARY.....	8
2.1 TEST ITEMS AND RESULTS	8
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	8
2.3 RELATED SUBMITTAL(S) / GRANT(S)	8
2.4 PURPOSE OF THE TEST	8
2.5 TEST METHODOLOGY.....	8
2.6 TEST FACILITY.....	8
3. GENERAL INFORMATION.....	9
3.1 PRODUCT DESCRIPTION.....	9
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	9
4. EUT MODIFICATIONS.....	9
5. SYSTEM TEST CONFIGURATION	10
5.1 JUSTIFICATION.....	10
5.2 PERIPHERAL EQUIPMENT	10
5.3 MODE OF OPERATION DURING THE TEST	10
5.4 CONFIGURATION OF TEST SYSTEM.....	16
5.5 ANTENNA REQUIREMENT	16
6. PRELIMINARY TEST	16
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	16
6.2 GENERAL RADIATED EMISSIONS TESTS	16
7. MINIMUM 20 DB BANDWIDTH.....	17
7.1 OPERATING ENVIRONMENT	17
7.2 TEST SET-UP	17
7.3 TEST DATE	17
7.4 TEST DATA FOR 1 MBPS.....	18
7.4.1 Test data for Antenna 0	18
7.4.2 Test data for Antenna 1	20
7.5 TEST DATA FOR 2 MBPS.....	22
7.5.1 Test data for Antenna 0	22
7.5.2 Test data for Antenna 1	24
7.6 TEST DATA FOR 3 MBPS.....	26
7.6.1 Test data for Antenna 0	26

7.6.2 Test data for Antenna 1	28
8. HOPPING FREQUENCY SEPARATION.....	30
8.1 OPERATING ENVIRONMENT	30
8.2 TEST SET-UP	30
8.3 TEST DATE	30
8.4 TEST DATA FOR 1 MBPS	31
8.4.1 Test data for Antenna 0	31
8.4.2 Test data for Antenna 1	32
8.5 TEST DATA FOR 2 MBPS	33
8.5.1 Test data for Antenna 0	33
8.5.2 Test data for Antenna 1	34
8.6 TEST DATA FOR 3 MBPS	35
8.6.1 Test data for Antenna 0	35
8.6.2 Test data for Antenna 1	36
9. NUMBER OF HOPPING CHANNELS	37
9.1 OPERATING ENVIRONMENT	37
9.2 TEST SET-UP	37
9.3 TEST DATE	37
9.4 TEST DATA FOR 1 MBPS	38
9.4.1 Test data for Antenna 0	38
9.4.2 Test data for Antenna 1	41
9.5 TEST DATA FOR 2 MBPS	44
9.5.1 Test data for Antenna 0	44
9.5.2 Test data for Antenna 1	47
9.6 TEST DATA FOR 3 MBPS	50
9.6.1 Test data for Antenna 0	50
9.6.2 Test data for Antenna 1	53
10. TIME OF OCCUPANCY	56
10.1 OPERATING ENVIRONMENT	56
10.2 TEST SET-UP	56
10.3 TEST DATE	56
10.4 TEST DATA FOR 1 MBPS	57
10.4.1 Test data for Antenna 0	57
10.4.2 Test data for Antenna 1	59
10.5 TEST DATA FOR 2 MBPS	61
10.5.1 Test data for Antenna 0	61

10.5.2 Test data for Antenna 1	63
10.6 TEST DATA FOR 3 MBPS	65
10.6.1 Test data for Antenna 0	65
10.6.2 Test data for Antenna 1	67
11. MAXIMUM PEAK OUTPUT POWER	69
11.1 OPERATING ENVIRONMENT	69
11.2 TEST SET-UP	69
11.3 TEST DATE	69
11.4 TEST DATA FOR 1 MBPS	70
11.4.1 Test data for Antenna 0	70
11.4.2 Test data for Antenna 1	72
11.5 TEST DATA FOR 2 MBPS	74
11.5.1 Test data for Antenna 0	74
11.5.2 Test data for Antenna 1	76
11.6 TEST DATA FOR 3 MBPS	78
11.6.1 Test data for Antenna 0	78
11.6.2 Test data for Antenna 1	80
12. 100 KHZ BANDWIDTH OUTSIDE THE FREQUENCY BAND	82
12.1 OPERATING ENVIRONMENT	82
12.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	82
12.3 TEST SET-UP FOR RADIATED MEASUREMENT	82
12.4 TEST DATE	82
12.5 TEST DATA FOR CONDUCTED EMISSION	83
12.5.1 Test data for 1 Mbps	83
12.5.2 Test data for 2 Mbps	95
12.5.3 Test data for 3 Mbps	107
12.6 TEST DATA FOR TRANSMITTING MODE RADIATED EMISSION	119
12.6.1 Radiated Emission which fall in the Restricted Band	119
12.6.2 Spurious & Harmonic Radiated Emission above 1 GHz	125
13. RADIATED EMISSION TEST	131
13.1 OPERATING ENVIRONMENT	131
13.2 TEST SET-UP	131
13.3 TEST DATE	132
13.4 TEST DATA FOR 30 MHZ ~ 1 000 MHZ	133
13.4.1 Test data for Bluetooth 1	133
13.4.2 Test data for Bluetooth 2	134

13.4.3 Test data for Bluetooth 1/2	135
13.5 Test data for Below 30 MHz	136
13.6 TEST DATA FOR ABOVE 1 GHz	136
14. LIST OF TEST EQUIPMENT	137

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-212-RWD-083	February 19, 2021	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : LG Electronics USA

Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, 07632, United States

Contact Person : Dae Woong, Kim / Director, Regulatory and Environmental Affairs

Telephone No. : +201-266-2215

FCC ID : BEJIR12PT-TS

Model Name : IR12PT-TS

Brand Name : -

Serial Number : N/A

Date : February 19, 2021

EQUIPMENT CLASS	DSS – PART 15 SPREAD SPECTRUM TRANSMITTER
E.U.T. DESCRIPTION	DISPLAY ASM-VIDEO
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247 (a) (1)	Carrier Frequency Separation	Met the Limit / PASS
15.247 (a) (1) (iii)	Minimum Number of Hopping Channels	Met the Limit / PASS
15.247 (a) (1) (iii)	Average Time of Occupancy	Met the Limit / PASS
15.247 (b) (1)	Maximum Peak Conducted Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.209	Radiated Emission Limits, General Requirement	Met the Limit / PASS
15.207	Conducted Limits	N/A (See Note)
15.203	Antenna Requirement	Met requirement / PASS

Note: This test is not performed because the EUT is operated by DC Power.

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247.

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-20122/ C-14617/ G-10666/ T-11842

ISED (Innovation, Science and Economic Development Canada) – Registration No. Site# 3736A-3

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The LG Electronics USA, Model IR12PT-TS (referred to as the EUT in this report) is a DISPLAY ASM-VIDEO. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	DISPLAY ASM-VIDEO		
Temperature Range	-40 °C ~ 85 °C		
OPERATING FREQUENCY	2 402 MHz ~ 2 480 MHz		
MODULATION TYPE	GFSK for 1 Mbps, π/4-DQPSK for 2 Mbps, 8-DPSK for 3 Mbps		
RF OUTPUT POWER	Antenna 0	1 Mbps	0.74 dBm
		2 Mbps	3.10 dBm
		3 Mbps	3.57 dBm
	Antenna 1	1 Mbps	1.97 dBm
		2 Mbps	4.29 dBm
		3 Mbps	4.75 dBm
ANTENNA TYPE	Metal Antenna		
ANTENNA GAIN	Antenna 0	5.21 dBi	
	Antenna 1	3.33 dBi	
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	20 MHz, 24 MHz, 25 MHz		

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	LG Electronics Inc.	N/A	N/A
Sub Board	LG Electronics Inc.	N/A	N/A
LCD	INNOLUX Corp.	DD126EA-01A	N/A

5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
IR12PT-TS	LG Electronics Inc.	DISPLAY ASM-VIDEO (EUT)	
CMW500	ROHDE & SCHWARZ	WLAN / Bluetooth Signalling	EUT

5.3 Mode of operation during the test

For the testing, software used to control the EUT for staying in continuous transmitting is programmed.

For final testing, the EUT was set at 2 402 MHz, 2 441MHz, and 2 480 MHz to get a maximum emission levels from the EUT. The EUT was moved throughout the XY, XZ, and YZ planes and the worst case is “XY” axis, but the worst data was recorded in this report.

-. Channel List (Bluetooth)

Channel	Frequency[MHz]	Channel	Frequency[MHz]	Channel	Frequency[MHz]
0	2 402.00	27	2 429.00	54	2 456.00
1	2 403.00	28	2 430.00	55	2 457.00
2	2 404.00	29	2 431.00	56	2 458.00
3	2 405.00	30	2 432.00	57	2 459.00
4	2 406.00	31	2 433.00	58	2 460.00
5	2 407.00	32	2 434.00	59	2 461.00
6	2 408.00	33	2 435.00	60	2 462.00
7	2 409.00	34	2 436.00	61	2 463.00
8	2 410.00	35	2 437.00	62	2 464.00
9	2 411.00	36	2 438.00	63	2 465.00
10	2 412.00	37	2 439.00	64	2 466.00
11	2 413.00	38	2 440.00	65	2 467.00
12	2 414.00	39	2 441.00	66	2 468.00
13	2 415.00	40	2 442.00	67	2 469.00
14	2 416.00	41	2 443.00	68	2 470.00
15	2 417.00	42	2 444.00	69	2 471.00
16	2 418.00	43	2 445.00	70	2 472.00
17	2 419.00	44	2 446.00	71	2 473.00
18	2 420.00	45	2 447.00	72	2 474.00
19	2 421.00	46	2 448.00	73	2 475.00
20	2 422.00	47	2 449.00	74	2 476.00
21	2 423.00	48	2 450.00	75	2 477.00
22	2 424.00	49	2 451.00	76	2 478.00
23	2 425.00	50	2 452.00	77	2 479.00
24	2 426.00	51	2 453.00	78	2 480.00
25	2 427.00	52	2 454.00		
26	2 428.00	53	2 455.00		


-. Duty Cycle


Mode	Tx On Time [ms]	Tx Off Time [ms]	Duty Cycle [%]	Correction Factor [dB]
Bluetooth [1 Mbps]_Antenna 0	2.90	3.76	77.13	1.13
Bluetooth [2 Mbps]_Antenna 0	2.90	3.76	77.13	1.13
Bluetooth [3 Mbps]_Antenna 0	2.88	3.74	77.01	1.13
Bluetooth [1 Mbps]_Antenna 1	2.88	3.74	77.01	1.13
Bluetooth [2 Mbps]_Antenna 1	2.88	3.74	77.01	1.13
Bluetooth [3 Mbps]_Antenna 1	2.88	3.74	77.01	1.13

Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) * 100


Correction Factor : 10 * Log(1 / (Duty Cycle / 100))

-. Test Plot_Antenna 0






Bluetooth_2 Mbps




Bluetooth_3 Mbps


-. Test Plot_Antenna 1



Bluetooth_1 Mbps



Bluetooth_2 Mbps



Bluetooth_3 Mbps

5.4 Configuration of Test System

Line Conducted Test: It is not need to test this requirement, because the EUT shall be operated by DC Power.

Radiated Emission Test: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The antenna of the EUT is a Metal Antenna on the main board in the EUT, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
It is not need to test this requirement, because the power of the EUT is supplied by DC Power.	

6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X


7. MINIMUM 20 dB BANDWIDTH

7.1 Operating environment

Temperature : 23 °C
Relative humidity : 45 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 1 % to 5 % of the OBW, and peak detection was used. The 20 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 20 dB.




7.3 Test Date

January 11, 2021 ~ January 14, 2021


7.4 Test data for 1 Mbps

7.4.1 Test data for Antenna 0


CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	764.20
Middle	2 441.00	764.20
High	2 480.00	764.20



Low Channel




Middle Channel




High Channel


7.4.2 Test data for Antenna 1

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	764.20
Middle	2 441.00	764.20
High	2 480.00	764.20





Middle Channel





High Channel

7.5 Test data for 2 Mbps


7.5.1 Test data for Antenna 0

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	1 353.60
Middle	2 441.00	1 348.70
High	2 480.00	1 353.60






Middle Channel




High Channel


7.5.2 Test data for Antenna 1

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	1 348.70
Middle	2 441.00	1 348.70
High	2 480.00	1 348.70





Middle Channel





High Channel

7.6 Test data for 3 Mbps


7.6.1 Test data for Antenna 0

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	1 308.70
Middle	2 441.00	1 343.70
High	2 480.00	1 338.70






Middle Channel




High Channel


7.6.2 Test data for Antenna 1

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	1 343.70
Middle	2 441.00	1 343.70
High	2 480.00	1 338.70





Middle Channel



High Channel


8. HOPPING FREQUENCY SEPARATION

8.1 Operating environment

Temperature : 23 °C
Relative humidity : 45 % R.H.

8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to 5 MHz. The analyzer is set to peak hold then a pseudo-random hopping sequence of the transmitter is captured. The mark delta function was used to measure the frequency separation between two adjacent hopping channels.



8.3 Test Date


January 11, 2021 ~ January 14, 2021

8.4 Test data for 1 Mbps

8.4.1 Test data for Antenna 0

-. Test Result : Pass


MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
999.00	509.47	Separated by a minimum of 509.47 kHz



8.4.2 Test data for Antenna 1

-. Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
999.00	509.47	Separated by a minimum of 509.47 kHz




8.5 Test data for 2 Mbps

8.5.1 Test data for Antenna 0

-. Test Result : Pass


MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
999.00	899.13	Separated by a minimum of 899.13 kHz



8.5.2 Test data for Antenna 1

-. Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
999.00	899.13	Separated by a minimum of 899.13 kHz




8.6 Test data for 3 Mbps

8.6.1 Test data for Antenna 0

-. Test Result : Pass


MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
999.00	895.80	Separated by a minimum of 895.8 kHz



8.6.2 Test data for Antenna 1

-. Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
999.00	895.80	Separated by a minimum of 895.80 kHz




9. NUMBER OF HOPPING CHANNELS

9.1 Operating environment

Temperature : 23 °C
Relative humidity : 45 % R.H.

9.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to 100 MHz and the resolution bandwidth is set to 100 kHz. The analyzer is set to peak hold and then complete pseudo-random hopping sequence of the transmitter is captured.



9.3 Test Date


January 11, 2021 ~ January 14, 2021


9.4 Test data for 1 Mbps

9.4.1 Test data for Antenna 0


-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
1 Mbps	79	Minimum of 15	64






Number of hopping channel: 28




Number of hopping channel: 30




9.4.2 Test data for Antenna 1


-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
1 Mbps	79	Minimum of 15	64






Number of hopping channel: 28



Number of hopping channel: 30





9.5 Test data for 2 Mbps

9.5.1 Test data for Antenna 0


-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
2 Mbps	79	Minimum of 15	64






Number of hopping channel: 28




Number of hopping channel: 30




9.5.2 Test data for Antenna 1


-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
2 Mbps	79	Minimum of 15	64






Number of hopping channel: 28



Number of hopping channel: 30





9.6 Test data for 3 Mbps

9.6.1 Test data for Antenna 0


-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
3 Mbps	79	Minimum of 15	64






Number of hopping channel: 28




Number of hopping channel: 30




9.6.2 Test data for Antenna 1


-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
3 Mbps	79	Minimum of 15	64






Number of hopping channel: 28



Number of hopping channel: 30



10. TIME OF OCCUPANCY

10.1 Operating environment

Temperature : 23 °C
Relative humidity : 45 % R.H.

10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The transmitter is set to operate in its normal frequency hopping mode. The center frequency of the spectrum analyzer is set to one of hopping channels near the center of the operating band and span is set to zero Hz. The sweep time is set to display one complete pulse. The mark delta function is used to measure the duration of the pulses.



10.3 Test Date

January 11, 2021 ~ January 14, 2021

10.4 Test data for 1 Mbps

10.4.1 Test data for Antenna 0

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μ s with 79 channels.


For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second ($= 1\,600/2/79$) for DH1, and 5.06 times ($= 1\,600/4/79$) for DH3, and 3.38 times ($= 1\,600/6/79$) for DH5.


Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.380	10.13	31.60	121.64	400.00	PASS
DH3	1.640	5.06	31.60	262.23	400.00	
DH5	2.880	3.38	31.60	307.61	400.00	

Total dwell time is calculated as following.


Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.





DH3



DH5

10.4.2 Test data for Antenna 1

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μ s with 79 channels.


For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second ($= 1\,600/2/79$) for DH1, and 5.06 times ($= 1\,600/4/79$) for DH3, and 3.38 times ($= 1\,600/6/79$) for DH5.


Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.380	10.13	31.60	121.64	400.00	PASS
DH3	1.640	5.06	31.60	262.23	400.00	
DH5	2.900	3.38	31.60	309.74	400.00	

Total dwell time is calculated as following.


Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.





DH3



DH5

10.5 Test data for 2 Mbps

10.5.1 Test data for Antenna 0

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μ s with 79 channels.


For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second ($= 1\,600/2/79$) for DH1, and 5.06 times ($= 1\,600/4/79$) for DH3, and 3.38 times ($= 1\,600/6/79$) for DH5.


Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.385	10.13	31.60	123.24	400.00	PASS
DH3	1.640	5.06	31.60	262.23	400.00	
DH5	2.900	3.38	31.60	309.74	400.00	

Total dwell time is calculated as following.


Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.





DH3



DH5

10.5.2 Test data for Antenna 1

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μ s with 79 channels.


For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second ($= 1\,600/2/79$) for DH1, and 5.06 times ($= 1\,600/4/79$) for DH3, and 3.38 times ($= 1\,600/6/79$) for DH5.


Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.385	10.13	31.60	123.24	400.00	PASS
DH3	1.640	5.06	31.60	262.23	400.00	
DH5	2.900	3.38	31.60	309.74	400.00	

Total dwell time is calculated as following.


Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.





DH3



DH5

10.6 Test data for 3 Mbps

10.6.1 Test data for Antenna 0

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μ s with 79 channels.


For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second ($= 1\,600/2/79$) for DH1, and 5.06 times ($= 1\,600/4/79$) for DH3, and 3.38 times ($= 1\,600/6/79$) for DH5.


Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.385	10.13	31.60	123.24	400.00	PASS
DH3	1.640	5.06	31.60	262.23	400.00	
DH5	2.900	3.38	31.60	309.74	400.00	

Total dwell time is calculated as following.


Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.





DH3



DH5

10.6.2 Test data for Antenna 1

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μ s with 79 channels.


For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second ($= 1\,600/2/79$) for DH1, and 5.06 times ($= 1\,600/4/79$) for DH3, and 3.38 times ($= 1\,600/6/79$) for DH5.


Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.385	10.13	31.60	123.24	400.00	PASS
DH3	1.630	5.06	31.60	260.63	400.00	
DH5	2.900	3.38	31.60	309.74	400.00	

Total dwell time is calculated as following.


Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.





DH3



DH5

11. MAXIMUM PEAK OUTPUT POWER


11.1 Operating environment

Temperature : 23 °C
Relative humidity : 45 % R.H.

11.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer.

The resolution bandwidth is set to $\geq$ DTS Bandwidth, the video bandwidth is set to 3 times the resolution bandwidth.



11.3 Test Date

January 11, 2021 ~ January 14, 2021


11.4 Test data for 1 Mbps


11.4.1 Test data for Antenna 0

-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	MEASURED VLAUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402.00	0.74	30.00	29.26
MIDDLE	2 441.00	-0.47	30.00	30.47
HIGH	2 480.00	-2.25	30.00	32.25

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)





Middle Channel




High Channel


11.4.2 Test data for Antenna 1

-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	MEASURED VLAUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402.00	1.97	30.00	28.03
MIDDLE	2 441.00	1.05	30.00	28.95
HIGH	2 480.00	0.25	30.00	29.75

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)





Middle Channel



High Channel


11.5 Test data for 2 Mbps


11.5.1 Test data for Antenna 0

-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	MEASURED VLAUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402.00	3.10	21.00	17.90
MIDDLE	2 441.00	2.22	21.00	18.78
HIGH	2 480.00	0.60	21.00	20.40

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)





Middle Channel




High Channel

11.5.2 Test data for Antenna 1

-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	MEASURED VLAUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402.00	4.29	21.00	16.71
MIDDLE	2 441.00	3.68	21.00	17.32
HIGH	2 480.00	2.70	21.00	18.30

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)



Low Channel