

label 料号: label Part NO.:

Q40G007N23627B

客户  
Customer

充电桩

型 号  
Model

指示灯和外机标签

销 向  
Sales Area

EU

安规签核Safety parts:

YesNo

内销中文字体要求高度1.8mm以上

YesNo

针对带有UL logo的标签,其厂家须在最小包装上标示UL Recognized Component Mark  公司名称,型号及 UL file no.

条码印刷:  
barcode print:

1.所有条码读码等级: C级及以上,客户有特殊要求除外;

REVISION

VERSION

版本变更说明:  
Version Changed Description:

FCC ID号码变更: 2BG8P变更成2BBXG

备注Remark:

Jilly.chen  
2024-09-25

捷联电子(福建)有限公司  
TPV Electronics (Fujian) Co., Ltd.  
地址(Add): 中国福建省福清市元洪路上郑Shangzheng,Yuanhong Road, Fuqing City, Fujian Province, China  
电话(Tel): +86-591-85285555 85285559  
传真(Fax): +86-591-85285447  
邮编(Postcode): 350301

R=1

宽度: 35mm

长度: 130mm

CHARGING STATUS INDICATOR:

|                |            |          |                   |       |
|----------------|------------|----------|-------------------|-------|
| PLEASE PLUG IN | PLUGGED IN | CHARGING | CHARGING FINISHED | FAULT |
|                |            |          |                   |       |

SIGNAL STATUS INDICATOR:

|           |                    |                            |               |
|-----------|--------------------|----------------------------|---------------|
| CONNECTED | CONFIGURATION MODE | CONNECTING TO THE INTERNET | NO CONNECTION |
|           |                    |                            |               |

EVIQO

ELECTRIC VEHICLE AC SMART CHARGING STATION

MODEL: EVIPOWER248N

Power Frequency: 50-60Hz  
Rated Current: 48A  
Protection Level: Type4  
Conforms to: UL Std.2594  
For use with Electric Vehicles  
Operating temperature:  
-22°F(-30 °C) to 131°F(55 °C)

Rated Power: 11.5kW  
Rated Voltage: 200-240 VAC  
Production Date: 24-09  
Conforms to: CSA Std.C22.2#280  
Ventilation Not Required  
SN:

iOS APP

Android APP

APP Guide

Intertek  
EVIQO  
TECHNOLOGIES  
LIMITED

技术要求

|          |                                                                                    |        |            |
|----------|------------------------------------------------------------------------------------|--------|------------|
| 材质       | 销银龙                                                                                | 印刷颜色   | 1C         |
| 规格(厚度)   | 75*40*5C                                                                           | 胶型要求   | 永久胶粘剂      |
| 使用膜类     | 覆光膜                                                                                | 认证要求   | ROSH/REACH |
| 不干胶长期耐温性 | 零下40~高温80 摄氏度                                                                      | 产品特征要求 | 防水防晒,耐高低温  |
| 被贴物      | PC材料带皮纹+喷漆+平贴                                                                      |        |            |
| 标准要求     | 符合GB/T22771-2008的标准 和 GB/18724-2008的标准。                                            |        |            |
| 印刷要求     | 印刷清晰,表面干净整洁,无变形,无划伤,扫码等级达到B级以上                                                     |        |            |
| 备注:      | 1. GB/T22771-2008的标准,耐光等级需达到7级以上(不含7级)<br>2. GB/18724-2008的标准, (印刷品与印刷油墨耐各种试剂性的测定) |        |            |



1) 根据 TPV 推行 RoHS 的有关规定,所有的原材料及辅助材料必须符合 RoHS 的有关规定

2) 所有原材料的规定物质:如镉 (Cd) 汞 (Hg) 铅 (Pb) 六价铬 PBB's PBDE's 及镉 (Cd)+汞 (Hg)+铅 (Pb)+六价铬 (针对随机出货的包装材料)的具体含量依据最新版 RD EMS-01<<供应商环境管理物质管控标准>>的具体限值要求执行

1)According to the rule about RoHS of TPV,All raw material and assistant material should accord with the rule of RoHS

2)All the stated substance of raw material: the actual content of Cd/Hg/Pb/Cr/PBB's/PBDE's and Cd+Hg+Pb+Cr(aim at the packing material with the product), should accord with the latest version of RD EMS-01<<The controlled standard aboutenvironment substance for supplier>>.