

RF Exposure Evaluation Declaration

Product Name : GPS Locator

Model No. : GV500

FCC ID: YQD-GV500

Applicant : Queclink Wireless Solutions Co.,Ltd.

Address : Room 501, Building 9, No.99,
Tianzhou Road, Shanghai, China

Date of Receipt : 07/28/2014

Issued Date : 08/05/2014

Report No. : UL12620140728FCC016-3

Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of Unilab Corporation.

RF Exposure Evaluation Declaration

Issued Date : 08/05/2014

Report No. : UL12620140728FCC016-3



Product Name : GPS Locator

Applicant : Queclink Wireless Solutions Co.,Ltd

Address : Room 501, Building 9, No 99, TianZhou Road, Shanghai, China

Manufacturer : Queclink Wireless Solutions Co.,Ltd.

Address : Room 501, Building 9, No 99, TianZhou Road, Shanghai, China

Model No. : GV500

EUT Voltage : Extreme Low:8,Nominal:12,Extreme High:32

Brand Name : Queclink

Applicable Standard : FCC OET Bulletin 65 Supplement C (Edition 01-01)

Test Result : Complied

Performed Location : Unilab (Shanghai) Co.,Ltd.

FCC 2.948 register number is 714465

No.1350, Lianxi Road, Pudong New District, Shangha, China

TEL:+86-21-5027-5125/FAX:+86-21-5027-5126-876

Documented By :

A handwritten signature in black ink that reads "Andy Wei".

(Technical Engineer: Andy Wei)

Reviewed By :

A handwritten signature in black ink that reads "Forest Cao".

(Senior Engineer: Forest Cao)

Approved By :

A handwritten signature in black ink that reads "Eva Wang".

(Supervisor: Eva Wang)

1. EUT Description

Product Name:	GPS Locator
Model Name:	GV500
Hardware Version:	V1.04
Software Version:	A04V14
RF Exposure Environment:	Uncontrolled
GSM/GPRS	
Support Band:	GSM850/ PCS 1900
Tx Frequency Range:	GSM 850: 824.2MHz to 848.8MHz PCS 1900: 1850.2MHz to 1909.8MHz
Rx Frequency Range:	GSM 850: 869.2MHz to 893.8MHz PCS 1900: 1930.2MHz to 1989.8MHz
Type of modulation:	GMSK
Antenna Type:	Connector
Antenna Peak Gain:	GSM 850: 0dBi PCS 1900: 0.5dBi

2. RF Exposure Evaluation

2.1 Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range(MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A)Limits for Occupation/Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B)Limits for General Occupation/UnControlled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 22°C and 45% RH.

2.3.Test Result of RF Exposure Evaluation

This device is evaluated by mobile device with general population/uncontrolled exposure condition
For this device, the calculation is using the most conservative values, and the results are as follows:

Test Mode	ERP (dBm)	EIRP (dBm)	Peak EIRP (mW)	Average EIRP (mW)	Calculated RF Exposure at d = 20cm (mW/cm2)	MPE Limit (mW/cm2)
GSM850	29.51	31.69	1475.71	185.78	0.04	0.55
GSM1900	/	26.71	468.81	59.02	0.01	1.00
GPRS850	28.96	31.11	1291.22	162.55	0.03	0.55
GPRS1900	/	26.28	424.62	53.46	0.01	1.00

Test Mode	Antenna Gain (dBi)	Maximum Output Power (dBm)	Maximum Output Power (mW)	Average EIRP (mW)	Calculated RF Exposure at d = 20cm (mW/cm2)	MPE Limit (mW/cm2)
GSM 850	0	35	3162.28	398.11	0.08	0.55
GSM 1900	0.5	32	1584.89	223.87	0.05	1.00
GPRS 850	0	35	3162.28	398.11	0.08	0.55
GPRS 1900	0.5	32	1584.89	223.87	0.05	1.00

This device can pass RF exposure limit.