

RF EXPOSURE EVALUATION REPORT

APPLICANT	: Rhino Mobility LLC
PRODUCT NAME	: Module
MODEL NAME	: M3501
BRAND NAME	: RHINO
FCC ID	: 2AUOUM3501
STANDARD(S)	: FCC 47CFR Part 2(2.1091)
RECEIPT DATE	: 2024-10-28
TEST DATE	: 2024-12-19 to 2024-12-20
ISSUE DATE	: 2025-01-10

Edited by:

Pang Siyu

Pang Siyu (Rapporteur)

Approved by:

Yueming

Gan Yueming (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.



Shenzhen Morlab Communications Technology Co., Ltd. FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555 Fax: 86-755-36698525 Http://www.morlab.cn



DIRECTORY

1.	Technical Information	3
1.1	Applicant and Manufacturer Information	3
1.2	2 Equipment under Test (EUT) Description	3
1.3	Applied Reference Documents	· 6
2.	Device Category and RF Exposure Limit	7
3.	RF Output Power	8
4.	RF Exposure Assessment	10
An	nex A General Information	12

Change History				
Version	Date	Reason for Change		
1.0 2025-01-10		First edition		





1. Technical Information

Note: Provide by applicant.

1.1 Applicant and Manufacturer Information

Applicant:	Rhino Mobility LLC
Applicant Address: 8 The Green, Suite A, Dover, Delaware, 19901, USA	
Manufacturer: Rhino Mobility LLC	
Manufacturer Address:	8 The Green, Suite A, Dover, Delaware,19901, USA

1.2 Equipment under Test (EUT) Description

Product Name: Module		
Hardware Version: SM3501_V1.0		
Software Version:	M3501(001)_20250109	
Software Version: Frequency Bands:	M3501(001)_20250109 LTE Band 2: 1850 MHz ~1910 MHz LTE Band 4: 1710 MHz ~1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~787 MHz LTE Band 14: 788 MHz ~ 798 MHz LTE Band 25: 1850 MHz ~ 1915 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 30: 2305 MHz ~ 2315 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 43: 3550 MHz ~ 3700 MHz LTE Band 66:1710 MHz ~1780 MHz LTE Band 71: 663 MHz ~ 698 MHz SG NR n2: 1850 MHz ~ 1910 MHz 5G NR n7: 2500 MHz ~ 2570 MHz SG NR n7: 2500 MHz ~ 2570 MHz SG NR n7: 824 MHz ~ 849 MHz 5G NR n7: 2500 MHz ~ 2570 MHz SG NR n7: 2500 MHz ~ 1910 MHz 5G NR n7: 2500 MHz ~ 2570 MHz 5G NR n7: 2500 MHz ~ 2570 MHz 5G NR n7: 2500 MHz ~ 1910 MHz 5G NR n7: 2500 MHz ~ 1910 MHz 5G NR n7: 2500 MHz ~ 1915 MHz 5G NR n25: 1850 MHz ~ 1915 MHz 5G NR n25: 1850 MHz ~ 1915 MHz 5G NR n26: 814 MHz ~ 849 MHz 5G NR n26: 814 MHz ~ 849 MHz 5G NR n26: 814 MHz ~ 8	
	5G NR n41: 2496 MHz ~ 2690 MHz	



Shenzhen Morlab Communications Technology Co., Ltd. FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555 Http://www.morlab.cn

Fax: 86-755-36698525



	5G NR n48: 3550 MHz ~ 3700 M	Hz			
	5G NR n66: 1710 MHz ~ 1780 MHz				
	5G NR n71: 663 MHz ~ 698 MHz				
	5G NR n77: 3300 MHz ~ 4200 MHz				
	5G NR n78: 3300 MHz ~ 3800 M	Hz			
	LTE: QPSK,16QAM,64QAM, 256	QAM			
Modulation Mode:	5G NR: DFT-s-OFDM/CP-OFDM	PI/2 BPSK			
	QPSK, 16QAM, 64QAM,	256QAM			
Antenna Type:	LTE ANT: PIFA Antenna 5G NR ANT: PIFA Antenna				
	Frequency Bands	Antenna Gain (dBi)			
	LTE Band 2				
		0.24			
		-0.24			
		1.71			
	LIE Band 7	-0.18			
	LTE Band 12	1.88			
	LTE Band 13	1.69			
	LTE Band 14	1.65			
	LTE Band 25	1.14			
	LTE Band 26	1.71			
	LTE Band 30	-1.66			
	LTE Band 41	0.06			
	LTE Band 48	-0.42			
Automa Osia	LTE Band 66	-0.24			
Antenna Gain:	LTE Band 71	-1.26			
	5G NR n2	1.14			
	5G NR n5	1.71			
	5G NR n7	-0.18			
	5G NR n12	1.88			
	5G NR n14	1.65			
	5G NR n25	1 14			
	5G NB n26	1 71			
	5G NR p30	-1 66			
	5G NR n41	0.06			
	5G NR p48	-0.42			
	5G NP 266	-0.34			
		-0.24			
		-1.20			
	5G NR n77	1.01			



Shenzhen Morlab Communications Technology Co., Ltd. FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Fax: 86-755-36698525

Http://www.morlab.cn



REPORT No.: SZ24100188S01

		5G NR n78	1.01
--	--	-----------	------

Note:

When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% Confidence intervals.



Shenzhen Morlab Communications Technology Co., Ltd. FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555

Fax: 86-755-36698525

Http://www.morlab.cn



1.3 Applied Reference Documents

Leading reference documents for testing:

Identity	Document Title	Method Determination /Remark		
ECC 47 CEB Bort 2(2 1001)	Radio Frequency Radiation Exposure	No doviation		
FCC 47 CFR Fait 2(2.1091)	Assessment: mobile devices	NO GENALION		
KDB 447498 D01v06General RF Exposure GuidanceNo deviation				
Note 1: Additions to, deviation, or exclusions from the method shall be judged in the "method				
determination" column of add, deviate or exclude from the specific method shall be explained in				
the "Remark" of the above table.				



Shenzhen Morlab Communications Technology Co., Ltd. FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555

Fax: 86-755-36698525

Http://www.morlab.cn



2. RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)	
(B) Limits for Gene	ral Population/Unc	ontrolled Exposur	e	
0.3-1.34	614	1.63	*(100)	30	
1.34-30	824/f	2.19/f	*(180/f ²)	30	
30-300	27.5	0.073	0.2	30	
300-1500	-	- f/1500		30	
1500-100,000 -		-	1.0	30	

Table 1—Limits for Maximum Permissible Exposure (MPE)

f = frequency in MHz* = Plane-wave equivalent power density



Shenzhen Morlab Communications Technology Co., Ltd. FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555

Fax: 86-755-36698525 E-mail: service@morlab.cn

Http://www.morlab.cn

Page 7 of 12



> WWAN Maximum Average Power

Wireless Mode	Frequency (MHz)	Max Tune-up Limit (dBm)		
LTE Band 2	1880	24.00		
LTE Band 4	1732.5	24.00		
LTE Band 5	836.5	24.00		
LTE Band 7	2535	24.00		
LTE Band 12	707.5	24.00		
LTE Band 13	782	24.00		
LTE Band 14	793	24.00		
LTE Band 25	1882.5	24.00		
LTE Band 26	831.5	24.00		
LTE Band 30	2310	24.00		
LTE Band 41	2593	24.00		
LTE Band 48	3625	24.00		
LTE Band 66	1745	24.00		
LTE Band 71	683	24.00		
5G NR n2	1880	24.50		
5G NR n5	836.5	24.00		
5G NR n7	2535	24.00		
5G NR n12	707.5	24.00		
5G NR n14	793	24.00		
5G NR n25	1882.5	24.50		
5G NR n26 (814-824MHz)	819	24.00		
5G NR n26 (824-849MHz)	836.5	24.00		
5G NR n30	2310	24.00		
5G NR n41	2592.99	23.50		
5G NR n48	3624.99	23.50		
5G NR n66	1745	24.00		
5G NR n71	680.5	24.00		
5G NR n77 (3450-3550MHz)	3500.01	24.00		



Shenzhen Morlab Communications Technology Co., Ltd. FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555

Fax: 86-755-36698525

Http://www.morlab.cn



REPORT No.: SZ24100188S01

5G NR n77 (3700-3980MHz)	3840	24.00	
5G NR n78 (3450-3550MHz)	3500.01	24.00	
5G NR n78 (3700-3980MHz)	3750	24.00	

Note :

According to KDB 447498 Section 4.3, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.



Shenzhen Morlab Communications Technology Co., Ltd. FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555

Fax: 86-755-36698525

Http://www.morlab.cn



4. RF Exposure Assessment

> Standalone Transmission Assessment:

Bands	Frequency (MHz)	Tune-up Power (dBm)	Maximum Antenna Gain (dBi)	EIRP (mW)	PD (mW/cm²)	Limit Value (mW/cm²)
LTE Band 2	1880	24.00	1.14	326.59	0.065	1.0
LTE Band 4	1732.5	24.00	-0.24	237.68	0.047	1.0
LTE Band 5	836.5	24.00	1.71	372.39	0.074	0.558
LTE Band 7	2535	24.00	-0.18	240.99	0.048	1.0
LTE Band 12	707.5	24.00	1.88	387.26	0.077	0.472
LTE Band 13	782	24.00	1.69	370.68	0.074	0.521
LTE Band 14	793	24.00	1.65	367.28	0.073	0.529
LTE Band 25	1882.5	24.00	1.14	326.59	0.065	1.0
LTE Band 26	831.5	24.00	1.71	372.39	0.074	0.554
LTE Band 30	2310	24.00	-1.66	171.40	0.034	1.0
LTE Band 41	2593	24.00	0.06	254.68	0.051	1.0
LTE Band 48	3625	24.00	-0.42	228.03	0.045	1.0
LTE Band 66	1745	24.00	-0.24	237.68	0.047	1.0
LTE Band 71	683	24.00	-1.26	187.93	0.037	0.455
5G NR n2	1880	24.50	1.14	366.44	0.073	1.253
5G NR n5	836.5	24.00	1.71	372.39	0.074	0.558
5G NR n7	2535	24.00	-0.18	240.99	0.048	1.0
5G NR n12	707.5	24.00	1.88	387.26	0.077	0.472
5G NR n14	793	24.00	1.65	367.28	0.073	0.529
5G NR n25	1882.5	24.50	1.14	366.44	0.073	1.0
5G NR n26 (814-824MHz)	819	24.00	1.71	372.39	0.074	0.546
5G NR n26 (824-849MHz)	836.5	24.00	1.71	372.39	0.074	0.558
5G NR n30	2310	24.00	-1.66	171.40	0.034	1.0
5G NR n41	2592.99	23.50	0.06	226.99	0.045	1.0
5G NR n48	3624.99	23.50	-0.42	203.24	0.040	1.0
5G NR n66	1745	24.00	-0.24	237.68	0.047	1.0
5G NR n71	680.5	24.00	-1.26	187.93	0.037	0.454
5G NR n77 (3450-3550MHz)	3500.01	24.00	1.01	316.96	0.063	1.0
5G NR n77 (3700-3980MHz)	3840	24.00	1.01	316.96	0.063	1.0



Shenzhen Morlab Communications Technology Co., Ltd. FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555

Fax: 86-755-36698525

Http://www.morlab.cn



5G NR n78 (3450-3550MHz)	3500.01	24.00	1.01	316.96	0.063	1.0
5G NR n78 (3700-3980MHz)	3750	24.00	1.01	316.96	0.063	1.0

Note:

1. According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

2. MPE calculate method

Power Density = EIRP/ $4\pi R^2$

Where: EIRP = P+G

- P = Output Power (dBm)
- G = Antenna Gain (dBi)
- R = Separation Distance (20cm)

> Simultaneous Transmission Assessment

This device contains transmitters that don't operate simultaneously, therefore simultaneous transmission analysis is not required.

> Conclusion:

According to FCC 47 CFR Part 2 (2.1091), this device complies with human exposure basic restrictions.



Shenzhen Morlab Communications Technology Co., Ltd. FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555

Fax: 86-755-36698525



Annex A General Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.		
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8		
	LongChang Road, Block 67, BaoAn District, ShenZhen,		
	GuangDong Province, P. R. China		
Telephone:	+86 755 36698555		
Facsimile:	+86 755 36698525		

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.	
Address:	FL.1-3, Building A, FeiYang Science Park, No.8	
	LongChang Road, Block 67, BaoAn District, ShenZhen,	
	GuangDong Province, P. R. China	

3. Facilities and Accreditations

The FCC designation number is CN1192, the test firm registration number is 226174.

END OF REPORT



Shenzhen Morlab Communications Technology Co., Ltd. FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555

Fax: 86-755-36698525

Http://www.morlab.cn