

FCC ID:2A5GJ-TD01-EM-A1

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	7.044	5.06	7±1	8.00	6.31	<5	1.95576	3.00	YES
	2.441	7.227	5.28	7±1	8.00	6.31	<5	1.97158	3.00	YES
	2.480	6.816	4.80	6±1	7.00	5.01	<5	1.57854	3.00	YES
π /4DQPSK	2.402	7.955	6.24	7±1	8.00	6.31	<5	1.95576	3.00	YES
	2.441	7.971	6.27	7±1	8.00	6.31	<5	1.97158	3.00	YES
	2.480	7.874	6.13	7±1	8.00	6.31	<5	1.98727	3.00	YES
8DQPSK	2.402	8.38	6.89	8±1	9.00	7.94	<5	2.46216	3.00	YES
	2.441	8.527	7.12	8±1	9.00	7.94	<5	2.48207	3.00	YES
	2.480	7.956	6.25	7±1	8.00	6.31	<5	1.98727	3.00	YES

Conclusion:

For the max result : $2.48207 \leq$ FCC Limit 3.0 for 1g SAR.