

FCC Part 15C

Measurement and Test Report

For



Shenzhen AngSi Technology Co., Ltd.

901B, Ling Yun Building, Hong Lang North No.2 Road , Bao An District,

ShenZhen PRC

FCC ID: 2AGA6-OONTZA3PRO

FCC Rule(s):	<u>FCC Part 15.247</u>
Product Description:	<u>Bluetooth Speaker</u>
Tested Model:	<u>OontZ Angle 3 PRO</u>
Report No.:	<u>WTX19X03014435W-1</u>
Sample Receipt Date:	<u>2019-03-15</u>
Tested Date:	<u>2019-03-15 to 2019-04-01</u>
Issued Date:	<u>2019-04-02</u>
Tested By:	<u>Ray Yang / Engineer</u>
Reviewed By:	<u>Silin Chen / EMC Manager</u>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u>
Prepared By:	



Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,

Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 MEASUREMENT UNCERTAINTY.....	7
1.7 TEST EQUIPMENT LIST AND DETAILS.....	8
2. SUMMARY OF TEST RESULTS.....	9
3. RF EXPOSURE.....	10
3.1 STANDARD APPLICABLE.....	10
3.2 TEST RESULT.....	10
4. ANTENNA REQUIREMENT.....	11
4.1 STANDARD APPLICABLE.....	11
4.2 EVALUATION INFORMATION.....	11
5. FREQUENCY HOPPING SYSTEM REQUIREMENTS.....	12
5.1 STANDARD APPLICABLE.....	12
5.2 FREQUENCY HOPPING SYSTEM.....	12
5.3 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....	13
6. QUANTITY OF HOPPING CHANNELS AND CHANNEL SEPARATION.....	14
6.1 STANDARD APPLICABLE.....	14
6.2 TEST PROCEDURE.....	14
6.3 SUMMARY OF TEST RESULTS/PLOTS.....	14
7. DWELL TIME OF HOPPING CHANNEL.....	21
7.1 STANDARD APPLICABLE.....	21
7.2 TEST PROCEDURE.....	21
7.3 SUMMARY OF TEST RESULTS/PLOTS.....	22
8. 20DB BANDWIDTH.....	36
8.1 STANDARD APPLICABLE.....	36
8.2 TEST PROCEDURE.....	36
8.3 SUMMARY OF TEST RESULTS/PLOTS.....	37
9. RF OUTPUT POWER.....	42
9.1 STANDARD APPLICABLE.....	42
9.2 TEST PROCEDURE.....	42
9.3 SUMMARY OF TEST RESULTS/PLOTS.....	42
10. FIELD STRENGTH OF SPURIOUS EMISSIONS.....	49
10.1 STANDARD APPLICABLE.....	49
10.2 TEST PROCEDURE.....	49
10.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	50
10.4 SUMMARY OF TEST RESULTS/PLOTS.....	50
11. OUT OF BAND EMISSIONS.....	65
11.1 STANDARD APPLICABLE.....	65
11.2 TEST PROCEDURE.....	65
11.3 SUMMARY OF TEST RESULTS/PLOTS.....	66
12. CONDUCTED EMISSIONS.....	77
12.1 TEST PROCEDURE.....	77
12.2 BASIC TEST SETUP BLOCK DIAGRAM.....	77
12.3 TEST RECEIVER SETUP.....	77
12.4 SUMMARY OF TEST RESULTS/PLOTS.....	77

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen AngSi Technology Co., Ltd.
Address of applicant: 901B, Ling Yun Building, Hong Lang North No.2 Road , Bao An District, ShenZhen PRC

Manufacturer: Shenzhen AngSi Technology Co., Ltd.
Address of manufacturer: 901B, Ling Yun Building, Hong Lang North No.2 Road , Bao An District, ShenZhen PRC

General Description of EUT	
Product Name:	Bluetooth Speaker
Brand Name:	/
Model No.:	OontZ Angle 3 PRO
Adding Model(s):	/
Rated Voltage:	Battery:DC3.6V
Battery Capacity:	5000mAh
Power Adapter:	/
The product include two bluetooth modules(module-1:AC18APJ096-21A8; module-2:ATS2825)	
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Module-1	
Bluetooth Version:	V4.2 (BDR/EDR mode)
Frequency Range:	2402-2480MHz
RF Output Power:	4.787dBm (Conducted)
Data Rate:	1Mbps, 2Mbps
Modulation:	GFSK, Pi/4 QDPSK
Quantity of Channels:	79
Channel Separation:	1MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	0dBi

Technical Characteristics of EUT	
Module-2	
Bluetooth Version:	V4.2 (BDR/EDR mode)
Frequency Range:	2402-2480MHz
RF Output Power:	4.637dBm (Conducted)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, Pi/4 QDPSK, 8DPSK
Quantity of Channels:	79
Channel Separation:	1MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	0dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05r01: Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The Fcc Rules

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2402MHz
TM2	Middle Channel	2441MHz
TM3	High Channel	2480MHz
TM4	Hopping	2402-2480MHz

Modulation Configure			
Modulation	Packet	Packet Type	Packet Size
GFSK	DH1	4	27
	DH3	11	183
	DH5	15	339
Pi/4 DQPSK	2DH1	20	54
	2DH3	26	367
	2DH5	30	679
8DPSK	3DH1	24	83
	3DH3	27	552
	3DH5	31	1021

Note: the Bluetooth has been tested on the modulation of module 1 GFSK, (Pi/4)DQPSK ,8DPSK and module 2 GFSK, (Pi/4)DQPSK compliance test and record the worst case.

Test Conditions	
Temperature:	22~25 °C
Relative humidity	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2018-05-22	2019-05-21
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2018-05-22	2019-05-21
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2018-05-22	2019-05-21
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2018-05-22	2019-05-21
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2018-05-22	2019-05-21
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2018-05-22	2019-05-21
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2018-05-22	2019-05-21
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2018-05-22	2019-05-21
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2018-05-22	2019-05-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2019-03-18	2020-03-17
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2019-03-18	2020-03-17
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2019-03-18	2020-03-17
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2019-03-18	2020-03-17
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§ 15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.209(a)	Radiated Spurious Emissions	Compliant
§ 15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§ 15.247(a)(1)	Channel Separation	Compliant
§ 15.247(a)(1)(iii)	Time of Occupancy (Dwell time)	Compliant
§ 15.247(a)	20dB Bandwidth	Compliant
§ 15.247(b)(1)	RF Power Output	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant
§ 15.247(a)(1)	Frequency Hopping Sequence	Compliant
§ 15.247(g), (h)	Frequency Hopping System	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has an integral antenna, fulfill the requirement of this section.

5. Frequency Hopping System Requirements

5.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

5.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with a Bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for 558074 D01 15.247 Meas Guidance v05r01 and FCC Part 15.247 rule.

5.3 EUT Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

6. Quantity of Hopping Channels and Channel Separation

6.1 Standard Applicable

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

6.2 Test Procedure

According to KDB 558074 D01 v05r01 Subclause 9 and ANSI C63.10-2013 section 7.8.3, the number of hopping frequencies test method as follows.

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.


According to KDB 558074 D01 v05r01 Subclause 9 and ANSI C63.10-2013 section 7.8.2, the EUT shall have its hopping function enabled, the Carrier frequency separation test method as follows:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.


6.3 Summary of Test Results/Plots

Module-1:



Mode	Channel	Carrier Frequencies Separation (kHz)	Result
GFSK	Low	975.0	Pass
	Middle	1005	Pass
	High	1005	Pass
π /4DQPSK	Low	1005	Pass
	Middle	997.5	Pass
	High	1012.5	Pass

Module-2:




Mode	Channel	Carrier Frequencies Separation (kHz)	Result
GFSK	Low	997.5	Pass
	Middle	1005	Pass
	High	1005	Pass
8DPSK	Low	1005	Pass
	Middle	990.0	Pass
	High	990.0	Pass


Modeule-1:

Channel Separation-GFSK


Low Channel



Middle Channel




High Channel




Channel Separation- $\pi/4$ DQPSK


Low Channel



Middle Channel




High Channel




Modeule-2:

Channel Separation-GFSK


Low Channel



Middle Channel




High Channel




Channel Separation-8DPSK


Low Channel



Middle Channel



High Channel



7. Dwell Time of Hopping Channel

7.1 Standard Applicable

According to 15.247(a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

7.2 Test Procedure

According to KDB 558074 D01 v05r01 Subclause 9 and ANSI C63.10-2013 section 7.8.4, the dwell time of a hopping channel test method as follows.

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\begin{aligned} &(\text{Number of hops in the period specified in the requirements}) = \\ &(\text{number of hops on spectrum analyzer}) \times (\text{period specified in the requirements} / \text{analyzer sweep time}) \end{aligned}$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation. The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

7.3 Summary of Test Results/Plots

The dwell time within a period in data mode is independent from the packet type (packet length).

Test data is corrected with the worse case, which the packet length is DH1, DH3, and DH5.

The test period: $T = 0.4 \text{ Second} * 79 \text{ Channel} = 31.6 \text{ s}$

Dwell time = time slot length * (Hopping rate / Number of hopping channels) * Period

Module-1:




Modulation	Test Channel	Packet	Time Slot Length	Dwell Time	Limit
			ms	ms	ms
GFSK	Low	DH1	0.44	134.400	400
		DH3	1.70	268.800	400
		DH5	2.94	312.533	400
	Middle	DH1	0.42	134.400	400
		DH3	1.70	268.800	400
		DH5	2.95	311.467	400
	High	DH1	0.42	134.400	400
		DH3	1.70	268.800	400
		DH5	2.95	311.467	400
$\pi/4$ DQPSK	Low	2DH1	0.44	137.600	400
		2DH3	1.70	268.800	400
		2DH5	2.95	312.533	400
	Middle	2DH1	0.43	140.800	400
		2DH3	1.70	268.800	400
		2DH5	2.95	313.600	400
	High	2DH1	0.45	140.800	400
		2DH3	1.70	268.800	400
		2DH5	2.95	313.600	400

Module-2:

Modulation	Test Channel	Packet	Time Slot Length	Dwell Time	Limit
			ms	ms	ms
GFSK	Low	DH1	0.42	134.400	400
		DH3	1.68	268.800	400
		DH5	2.93	312.533	400
	Middle	DH1	0.42	134.400	400
		DH3	1.68	268.800	400
		DH5	2.93	311.467	400
	High	DH1	0.42	134.400	400
		DH3	1.68	268.800	400
		DH5	2.93	311.467	400
8DPSK	Low	3DH1	0.45	137.600	400
		3DH3	1.69	268.800	400
		3DH5	2.94	312.533	400
	Middle	3DH1	0.45	140.800	400
		3DH3	1.69	268.800	400
		3DH5	2.94	313.600	400
	High	3DH1	0.43	140.800	400
		3DH3	1.68	268.800	400
		3DH5	2.94	313.600	400


Please refer to the test plots as below:

Module-1:


DH1	
Low Channel	
Middle Channel	
High Channel	

DH3


Low Channel



Middle Channel




High Channel




DH5


Low Channel









Middle Channel



High Channel




2DH1 Low Channel	 Agilent R T Ref 20 dBm #Atten 30 dB Mkr1 Δ 440 μs -1.561 dB Peak Log 10 dB/Offset 1 dB W1 S2 S3 VS AA Center 2.40200000 GHz Center 2.402 GHz Res BW 1 MHz #VBW 3 MHz Span 0 Hz Sweep 4 ms (401 pts) No Peak Found Freq/Channel Center Freq 2.40200000 GHz Start Freq 2.40200000 GHz Stop Freq 2.40200000 GHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
Middle Channel	 Agilent R T Ref 20 dBm #Atten 30 dB Mkr1 Δ 430 μs 0.486 dB Peak Log 10 dB/Offset 1 dB W1 S2 S3 VS AA Center 2.44100000 GHz Center 2.441 GHz Res BW 1 MHz #VBW 3 MHz Span 0 Hz Sweep 4 ms (401 pts) No Peak Found Freq/Channel Center Freq 2.44100000 GHz Start Freq 2.44100000 GHz Stop Freq 2.44100000 GHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
High Channel	 Agilent R T Ref 20 dBm #Atten 30 dB Mkr1 Δ 450 μs -1.457 dB Peak Log 10 dB/Offset 1 dB W1 S2 S3 VS AA Marker Δ 450.000000 μs -1.457 dB Center 2.48 GHz Res BW 1 MHz #VBW 3 MHz Span 0 Hz Sweep 4 ms (401 pts) No Peak Found Marker Select Marker 1 2 3 4 Normal Delta Delta Pair (Tracking Ref) Ref Delta Span Pair Span Center Off More 1 of 2


2DH3	
Low Channel	
Middle Channel	
High Channel	

2DH5


Low Channel



Middle Channel




High Channel




Module-2:

DH1


Low Channel






Middle Channel




High Channel




DH3	
Low Channel	
Middle Channel	
High Channel	

DH5


Low Channel









Middle Channel



High Channel




3DH1	
Low Channel	
Middle Channel	
High Channel	


3DH3 Low Channel	
Middle Channel	
High Channel	

3DH5


Low Channel



Middle Channel



High Channel



8. 20dB Bandwidth

8.1 Standard Applicable

According to 15.247(a) and 15.215(c). 20dB bandwidth is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.2 Test Procedure

According to KDB 558074 D01 v05r01 Subclause 9 and ANSI C63.10-2013 section 6.9.2, the 20dB bandwidth test method as follows.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

8.3 Summary of Test Results/Plots




Module-1:

Test Mode	Test Channel MHz	20 dB Bandwidth MHz	Result
GFSK	2402	1.029	Pass
	2441	1.028	Pass
	2480	1.028	Pass
Pi/4 QDPSK	2402	1.309	Pass
	2441	1.306	Pass
	2480	1.308	Pass

Module-2:


Test Mode	Test Channel MHz	20 dB Bandwidth MHz	Result
GFSK	2402	1.027	Pass
	2441	1.027	Pass
	2480	1.028	Pass
8DPSK	2402	1.305	Pass
	2441	1.313	Pass
	2480	1.304	Pass

Module-1:


GFSK	
Low Channel	 Agilent R T Ch Freq 2.402 GHz Trig Free Occupied Bandwidth Center 2.40200000 GHz Ref 20 dBm #Atten 30 dB #Peak Log 10 dB/Offset 1 dB Center 2.402 GHz Span 3 MHz #Res BW 10 kHz #VBW 30 kHz Sweep 31.08 ms (401 pts) Occupied Bandwidth 918.9596 kHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error -27.613 kHz x dB Bandwidth 1.029 MHz Freq/Channel Center Freq 2.40200000 GHz Start Freq 2.40050000 GHz Stop Freq 2.40350000 GHz CF Step 300.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
Middle Channel	 Agilent R T Ch Freq 2.441 GHz Trig Free Occupied Bandwidth Center 2.44100000 GHz Ref 20 dBm #Atten 30 dB #Peak Log 10 dB/Offset 1 dB Center 2.441 GHz Span 3 MHz #Res BW 10 kHz #VBW 30 kHz Sweep 31.08 ms (401 pts) Occupied Bandwidth 920.7997 kHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error -26.110 kHz x dB Bandwidth 1.028 MHz Freq/Channel Center Freq 2.44100000 GHz Start Freq 2.43950000 GHz Stop Freq 2.44250000 GHz CF Step 300.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
High Channel	 Agilent R T Ch Freq 2.48 GHz Trig Free Occupied Bandwidth Center 2.48000000 GHz Ref 20 dBm #Atten 30 dB #Peak Log 10 dB/Offset 1 dB Center 2.48 GHz Span 3 MHz #Res BW 10 kHz #VBW 30 kHz Sweep 31.08 ms (401 pts) Occupied Bandwidth 922.1597 kHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error -26.124 kHz x dB Bandwidth 1.028 MHz Freq/Channel Center Freq 2.48000000 GHz Start Freq 2.47850000 GHz Stop Freq 2.48150000 GHz CF Step 300.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin

Pi/4 QDPSK


Low Channel



Middle Channel




High Channel




Module-2:

GFSK


Low Channel






Middle Channel



High Channel



8DPSK	
Low Channel	 Agilent R T Ch Freq 2.402 GHz Trig Free Occupied Bandwidth Ref 20 dBm #Atten 30 dB #Peak Log 10 dB/Offset 1 dB Center 2.402 GHz Span 3 MHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts) Occupied Bandwidth 1.1820 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error 15.111 kHz x dB Bandwidth 1.305 MHz Trace/View 1 Trace 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2
Middle Channel	 Agilent R T Ch Freq 2.441 GHz Trig Free Occupied Bandwidth Center 2.441000000 GHz Ref 20 dBm #Atten 30 dB #Peak Log 10 dB/Offset 1 dB Center 2.441 GHz Span 3 MHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts) Occupied Bandwidth 1.1812 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error 13.697 kHz x dB Bandwidth 1.313 MHz Freq/Channel Center Freq 2.44100000 GHz Start Freq 2.43950000 GHz Stop Freq 2.44250000 GHz CF Step 300.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
High Channel	 Agilent R T Ch Freq 2.48 GHz Trig Free Occupied Bandwidth Center 2.480000000 GHz Ref 20 dBm #Atten 30 dB #Peak Log 10 dB/Offset 1 dB Center 2.48 GHz Span 3 MHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts) Occupied Bandwidth 1.1805 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error 13.731 kHz x dB Bandwidth 1.304 MHz Freq/Channel Center Freq 2.48000000 GHz Start Freq 2.47850000 GHz Stop Freq 2.48150000 GHz CF Step 300.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin

9. RF Output Power

9.1 Standard Applicable

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

9.2 Test Procedure

According to KDB 558074 D01 v05r01 Subclause 9 and ANSI C63.10-2013 section 7.8.5, the output power test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

- a) Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e) A plot of the test results and setup description shall be included in the test report.

9.3 Summary of Test Results/Plots




Module-1:




Modulation type	Channel	Output power (dBm)	Output power (mW)	Limit (mW)	Result
GFSK	Low	3.724	2.357	1000	Pass
	Middle	2.750	1.884		
	High	0.246	1.058		
$\pi/4$ DQPSK	Low	4.787	3.011	1000	Pass
	Middle	3.958	2.488		
	High	1.472	1.403		

Module-2:




Modulation type	Channel	Output power (dBm)	Output power (mW)	Limit (mW)	Result
GFSK	Low	2.907	1.953	1000	Pass
	Middle	1.289	1.346		
	High	0.414	1.100		
$\pi/4$ DQPSK	Low	4.451	2.787	1000	Pass
	Middle	2.567	1.806		
	High	1.775	1.505		
8DPSK	Low	4.637	2.909	1000	Pass
	Middle	2.741	1.880		
	High	1.887	1.544		




Module-1:




GFSK	
Low Channel	
Middle Channel	
High Channel	

Pi/4 QDPSK	
Low Channel	 Agilent R T Ref 20 dBm #Atten 30 dB Mkr1 2.401975 GHz 4.787 dBm Peak Log 10 dB/Offset 1 dB M1 S2 S3 FC AA Marker 2.401975000 GHz 4.787 dBm Center 2.402 GHz Span 10 MHz #Res BW 3 MHz #VBW 3 MHz Sweep 4 ms (401 pts) Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
Middle Channel	 Agilent R T Ref 20 dBm #Atten 30 dB Mkr1 2.440975 GHz 3.958 dBm Peak Log 10 dB/Offset 1 dB M1 S2 S3 FC AA Marker 2.440975000 GHz 3.958 dBm Center 2.441 GHz Span 10 MHz #Res BW 3 MHz #VBW 3 MHz Sweep 4 ms (401 pts) Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
High Channel	 Agilent R T Ref 20 dBm #Atten 30 dB Mkr1 2.479700 GHz 1.472 dBm Peak Log 10 dB/Offset 1 dB M1 S2 S3 FC AA Marker 2.479700000 GHz 1.472 dBm Center 2.48 GHz Span 10 MHz #Res BW 3 MHz #VBW 3 MHz Sweep 4 ms (401 pts) Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2

Module-2:

GFSK	
Low Channel	
Middle Channel	
High Channel	

Pi/4 QDPSK	
Low Channel	 Agilent R T Ref 20 dBm #Atten 30 dB Mkr1 2.401775 GHz 4.451 dBm #Peak Log 10 dB/Offset 1 dB M1 S2 S3 FC AA Marker 2.401775000 GHz 4.451 dBm Center 2.402 GHz Span 10 MHz #Res BW 3 MHz #VBW 3 MHz Sweep 4 ms (401 pts) Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
Middle Channel	 Agilent R T Ref 20 dBm #Atten 30 dB Mkr1 2.440925 GHz 2.567 dBm #Peak Log 10 dB/Offset 1 dB M1 S2 S3 FC AA Marker 2.440925000 GHz 2.567 dBm Center 2.441 GHz Span 10 MHz #Res BW 3 MHz #VBW 3 MHz Sweep 4 ms (401 pts) Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
High Channel	 Agilent R T Ref 20 dBm #Atten 30 dB Mkr1 2.479900 GHz 1.775 dBm #Peak Log 10 dB/Offset 1 dB M1 S2 S3 FC AA Marker 2.479900000 GHz 1.775 dBm Center 2.48 GHz Span 10 MHz #Res BW 3 MHz #VBW 3 MHz Sweep 4 ms (401 pts) Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2

8DPSK	
Low Channel	
Middle Channel	
High Channel	

10. Field Strength of Spurious Emissions

10.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

10.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

10.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

10.4 Summary of Test Results/Plots


Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.

➤ Spurious Emissions Below 1GHz


➤ Module-1

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	42.4508	27.22	-12.21	15.01	40.00	-24.99	97	100	peak
2	105.6414	27.26	-13.44	13.82	43.50	-29.68	100	100	peak
3	293.0842	26.87	-8.30	18.57	46.00	-27.43	119	100	peak
4	451.1349	27.98	-6.20	21.78	46.00	-24.22	93	100	peak
5	640.6109	27.68	-2.68	25.00	46.00	-21.00	344	100	peak
6	866.0878	27.67	0.28	27.95	46.00	-18.05	155	100	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.5591	27.89	-12.56	15.33	40.00	-24.67	318	100	peak
2	90.5374	27.66	-13.51	14.15	43.50	-29.35	304	100	peak
3	324.4561	26.64	-7.94	18.70	46.00	-27.30	92	100	peak
4	422.0577	28.60	-6.27	22.33	46.00	-23.67	287	100	peak
5	566.6223	27.72	-4.33	23.39	46.00	-22.61	63	100	peak
6	813.1116	28.13	-0.45	27.68	46.00	-18.32	281	100	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.1616	27.16	-12.89	14.27	40.00	-25.73	224	100	peak
2	97.4560	27.86	-14.11	13.75	43.50	-29.75	90	100	peak
3	283.9791	26.48	-8.83	17.65	46.00	-28.35	92	100	peak
4	419.1081	27.03	-6.33	20.70	46.00	-25.30	112	100	peak
5	590.9737	27.72	-3.37	24.35	46.00	-21.65	230	100	peak
6	827.4934	27.41	-0.29	27.12	46.00	-18.88	215	100	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	42.7496	28.05	-12.18	15.87	40.00	-24.13	86	100	peak
2	90.5374	27.13	-13.51	13.62	43.50	-29.88	107	100	peak
3	302.4812	26.60	-8.19	18.41	46.00	-27.59	57	100	peak
4	422.0577	27.23	-6.27	20.96	46.00	-25.04	93	100	peak
5	597.2234	27.97	-3.35	24.62	46.00	-21.38	327	100	peak
6	796.1830	29.64	-1.61	28.03	46.00	-17.97	127	100	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.1616	26.18	-12.89	13.29	40.00	-26.71	179	100	peak
2	91.8163	27.62	-13.76	13.86	43.50	-29.64	307	100	peak
3	265.6757	28.26	-8.95	19.31	46.00	-26.69	85	100	peak
4	375.9385	27.45	-7.11	20.34	46.00	-25.66	223	100	peak
5	588.9051	27.65	-3.40	24.25	46.00	-21.75	278	100	peak
6	810.2654	28.62	-0.49	28.13	46.00	-17.87	192	100	peak


Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.2120	29.02	-13.14	15.88	40.00	-24.12	295	100	peak
2	90.5374	26.97	-13.51	13.46	43.50	-30.04	91	100	peak
3	282.9852	27.38	-8.84	18.54	46.00	-27.46	218	100	peak
4	426.5210	27.72	-6.14	21.58	46.00	-24.42	113	100	peak
5	593.0497	28.08	-3.35	24.73	46.00	-21.27	150	100	peak
6	863.0562	28.27	0.19	28.46	46.00	-17.54	123	100	peak


➤ Module-2

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	37.2855	26.58	-13.52	13.06	40.00	-26.94	74	100	peak
2	89.9047	26.45	-13.47	12.98	43.50	-30.52	178	100	peak
3	240.8304	27.16	-10.01	17.15	46.00	-28.85	61	100	peak
4	406.0880	26.74	-6.60	20.14	46.00	-25.86	140	100	peak
5	582.7425	27.24	-3.61	23.63	46.00	-22.37	126	100	peak
6	827.4934	31.69	-0.29	31.40	46.00	-14.60	97	100	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.3755	26.77	-11.88	14.89	40.00	-25.11	116	100	peak
2	90.5374	28.44	-13.51	14.93	43.50	-28.57	248	100	peak
3	259.2338	26.91	-9.38	17.53	46.00	-28.47	89	100	peak
4	408.9460	28.91	-6.51	22.40	46.00	-23.60	161	100	peak
5	550.9480	28.54	-4.79	23.75	46.00	-22.25	55	100	peak
6	755.3873	28.31	-1.75	26.56	46.00	-19.44	347	100	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.2120	28.30	-13.14	15.16	40.00	-24.84	360	100	peak
2	89.9047	28.45	-13.47	14.98	43.50	-28.52	91	100	peak
3	302.4812	26.20	-8.19	18.01	46.00	-27.99	300	100	peak
4	413.2706	28.14	-6.43	21.71	46.00	-24.29	96	100	peak
5	582.7425	27.18	-3.61	23.57	46.00	-22.43	138	100	peak
6	687.1507	27.85	-2.08	25.77	46.00	-20.23	246	100	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.0245	26.83	-12.92	13.91	40.00	-26.09	241	100	peak
2	83.5222	27.58	-17.45	10.13	40.00	-29.87	146	100	peak
3	298.2681	26.29	-8.16	18.13	46.00	-27.87	133	100	peak
4	392.0951	27.43	-7.09	20.34	46.00	-25.66	115	100	peak
5	545.1826	28.27	-4.88	23.39	46.00	-22.61	148	100	peak
6	706.6999	27.76	-1.81	25.95	46.00	-20.05	258	100	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.9658	27.01	-12.05	14.96	40.00	-25.04	341	100	peak
2	89.2764	26.58	-13.96	12.62	43.50	-30.88	241	100	peak
3	283.9792	27.41	-8.83	18.58	46.00	-27.42	62	100	peak
4	417.6411	27.91	-6.36	21.55	46.00	-24.45	224	100	peak
5	593.0497	28.18	-3.35	24.83	46.00	-21.17	301	100	peak
6	866.0879	27.10	0.28	27.38	46.00	-18.62	325	100	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	37.2855	28.44	-13.52	14.92	40.00	-25.08	257	100	peak
2	88.9639	27.72	-14.21	13.51	43.50	-29.99	97	100	peak
3	291.0360	26.97	-8.44	18.53	46.00	-27.47	220	100	peak
4	397.6334	27.63	-6.85	20.78	46.00	-25.22	92	100	peak
5	560.6928	28.74	-4.47	24.27	46.00	-21.73	285	100	peak
6	742.2587	28.70	-1.94	26.76	46.00	-19.24	274	100	peak

➤ Spurious Emissions Above 1GHz

Module-1:

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
4804.00	61.89	-3.87	58.02	74.00	-15.98	H	PK
4804.00	47.56	-3.87	43.69	54.00	-10.31	H	AV
7206.00	55.74	1.14	56.88	74.00	-17.12	H	PK
7206.00	41.46	1.19	42.65	54.00	-11.35	H	AV
4804.00	60.75	-3.86	56.89	74.00	-17.11	V	PK
4804.00	45.80	-3.86	41.94	54.00	-12.06	V	AV
7206.00	56.59	1.10	57.69	74.00	-16.31	V	PK
7206.00	42.70	1.10	43.80	54.00	-10.20	V	AV
Middle Channel-2441MHz							
4882.00	60.62	-3.74	56.88	74.00	-17.12	H	PK
4882.00	46.69	-3.74	42.95	54.00	-11.05	H	AV
7323.00	56.55	1.47	58.02	74.00	-15.98	H	PK
7323.00	42.19	1.47	43.66	54.00	-10.34	H	AV
4882.00	61.23	-3.74	57.49	74.00	-16.51	V	PK
4882.00	45.70	-3.74	41.96	54.00	-12.04	V	AV
7323.00	55.28	1.47	56.75	74.00	-17.25	V	PK
7323.00	41.21	1.47	42.68	54.00	-11.32	V	AV
High Channel-2480MHz							
4960.00	61.26	-3.59	57.67	74.00	-16.33	H	PK
4960.00	45.77	-3.59	42.18	54.00	-11.82	H	AV
7440.00	55.30	1.79	57.09	74.00	-16.91	H	PK
7440.00	41.46	1.79	43.25	54.00	-10.75	H	AV
4960.00	61.27	-3.59	57.68	74.00	-16.32	V	PK
4960.00	46.35	-3.59	42.76	54.00	-11.24	V	AV
7440.00	55.05	1.79	56.84	74.00	-17.16	V	PK
7440.00	41.86	1.79	43.65	54.00	-10.35	V	AV

Module-2:

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
4804.00	61.59	-3.87	57.72	74.00	-16.28	H	PK
4804.00	46.57	-3.87	42.70	54.00	-11.30	H	AV
7206.00	55.74	1.14	56.88	74.00	-17.12	H	PK
7206.00	42.48	1.19	43.67	54.00	-10.33	H	AV
4804.00	61.57	-3.86	57.71	74.00	-16.29	V	PK
4804.00	46.35	-3.86	42.49	54.00	-11.51	V	AV
7206.00	55.78	1.10	56.88	74.00	-17.12	V	PK
7206.00	42.24	1.10	43.34	54.00	-10.66	V	AV
Middle Channel-2441MHz							
4882.00	60.53	-3.74	56.79	74.00	-17.21	H	PK
4882.00	47.39	-3.74	43.65	54.00	-10.35	H	AV
7323.00	56.12	1.47	57.59	74.00	-16.41	H	PK
7323.00	42.21	1.47	43.68	54.00	-10.32	H	AV
4882.00	60.59	-3.74	56.85	74.00	-17.15	V	PK
4882.00	46.46	-3.74	42.72	54.00	-11.28	V	AV
7323.00	56.19	1.47	57.66	74.00	-16.34	V	PK
7323.00	41.71	1.47	43.18	54.00	-10.82	V	AV
High Channel-2480MHz							
4960.00	60.06	-3.59	56.47	74.00	-17.53	H	PK
4960.00	46.92	-3.59	43.33	54.00	-10.67	H	AV
7440.00	54.80	1.79	56.59	74.00	-17.41	H	PK
7440.00	40.96	1.79	42.75	54.00	-11.25	H	AV
4960.00	60.75	-3.59	57.16	74.00	-16.84	V	PK
4960.00	47.30	-3.59	43.71	54.00	-10.29	V	AV
7440.00	55.80	1.79	57.59	74.00	-16.41	V	PK
7440.00	41.32	1.79	43.11	54.00	-10.89	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

11. Out of Band Emissions

11.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

11.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.6, the Band-edge measurements for RF conducted emissions test method as follows.

- a) Connect the EMI receiver or spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described in step e) (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).
- b) Set the EUT to the lowest frequency channel (for the hopping on test, the hopping sequence shall include the lowest frequency channel).
- c) Set the EUT to operate at maximum output power and 100% duty cycle, or equivalent “normal mode of operation” as specified in 6.10.3.
- d) If using the radiated method, then use the applicable procedure(s) of 6.4, 6.5, or 6.6, and orient the EUT and measurement antenna positions to produce the highest emission level.
- e) Perform the test as follows:
 - 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
 - 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
 - 3) Attenuation: Auto (at least 10 dB preferred).
 - 4) Sweep time: Coupled.
 - 5) Resolution bandwidth: 100 kHz.
 - 6) Video bandwidth: 300 kHz.
 - 7) Detector: Peak.
 - 8) Trace: Max hold.
- f) Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several minutes to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.
- g) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak

function to move the marker to the peak of the in-band emission.

h) Repeat step c) through step e) for every applicable modulation.

i) Set the EUT to the highest frequency channel (for the hopping on test, the hopping sequence shall include the highest frequency channel) and repeat step c) through step d).

j) The band-edge measurement shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Restricted-band band-edge test method please refers to ANSI C63.10-2013 section 6.10.5. The emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated band-edge measurements.


According to ANSI C63.10-2013 section 7.8.8, Conducted spurious emissions shall be measured for the transmit frequency, per 5.5 and 5.6, and at the maximum transmit powers.

Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The instrument shall span 30 MHz to 10 times the operating frequency in GHz, with a resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector. The band 30 MHz to the highest frequency may be split into smaller spans, as long as the entire spectrum is covered.

11.3 Summary of Test Results/Plots


➤ Module-1

Test Channel	Low	Polarity:	Vertical(worst case)
--------------	-----	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	42.28	-7.78	34.50	54.00	-19.50	Average Detector
	2310.000	54.14	-7.78	46.36	74.00	-27.64	Peak Detector
2	2390.000	44.57	-7.32	37.25	54.00	-16.75	Average Detector
	2390.000	62.63	-7.32	55.31	74.00	-18.69	Peak Detector
3	2401.843	109.87	-7.25	102.62	/	/	Average Detector
	2401.741	111.71	-7.25	104.46	/	/	Peak Detector


Test Channel	High	Polarity:	Vertical(worst case)
--------------	------	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.955	97.93	-6.79	91.14	/	/	Average Detector
	2479.855	105.41	-6.79	98.62	/	/	Peak Detector
2	2483.500	56.00	-6.77	49.23	54.00	-4.77	Average Detector
	2483.500	66.52	-6.77	59.75	74.00	-14.25	Peak Detector
3	2500.000	41.40	-6.67	34.73	54.00	-19.27	Average Detector
	2500.000	54.73	-6.67	48.06	74.00	-25.94	Peak Detector


➤ Module-2

Test Channel	Low	Polarity:	Vertical(worst case)
--------------	-----	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	42.21	-7.78	34.43	54.00	-19.57	Average Detector
	2310.000	55.33	-7.78	47.55	74.00	-26.45	Peak Detector
2	2390.000	44.51	-7.32	37.19	54.00	-16.81	Average Detector
	2390.000	61.93	-7.32	54.61	74.00	-19.39	Peak Detector
3	2401.843	109.75	-7.25	102.50	/	/	Average Detector
	2402.047	111.66	-7.25	104.41	/	/	Peak Detector

Test Channel	High	Polarity:	Vertical(worst case)
--------------	------	-----------	----------------------






No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.955	100.20	-6.79	93.41	/	/	Average Detector
	2479.756	104.88	-6.79	98.09	/	/	Peak Detector
2	2483.500	58.23	-6.77	51.46	54.00	-2.54	Average Detector
	2483.500	66.10	-6.77	59.33	74.00	-14.67	Peak Detector
3	2500.000	41.40	-6.67	34.73	54.00	-19.27	Average Detector
	2500.000	52.84	-6.67	46.17	74.00	-27.83	Peak Detector

Module-1:



Worst mode DH1

Low channel




Worst mode DH1



Middle channel



Worst mode DH1




High channel





Module-2:

Worst mode DH1





Low channel




Worst mode DH1



Middle channel



Worst mode DH1



High channel




12. Conducted Emissions

12.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

12.2 Basic Test Setup Block Diagram



12.3 Test Receiver Setup


During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal

12.4 Summary of Test Results/Plots


Modoule-1:

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1540	50.10	10.10	60.20	65.78	-5.58	QP
2	0.1820	28.99	10.11	39.10	54.39	-15.29	AVG
3	0.1900	47.78	10.12	57.90	64.04	-6.14	QP
4	0.3060	27.78	10.19	37.97	50.08	-12.11	AVG
5	0.6140	28.46	10.35	38.81	46.00	-7.19	AVG
6	0.6180	39.53	10.35	49.88	56.00	-6.12	QP


Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1819	50.87	10.11	60.98	64.39	-3.41	QP
2	0.1860	29.17	10.11	39.28	54.21	-14.93	AVG
3	0.3700	38.05	10.24	48.29	58.50	-10.21	QP
4	0.3700	22.42	10.24	32.66	48.50	-15.84	AVG
5	1.9100	32.29	10.60	42.89	56.00	-13.11	QP
6	2.0340	17.31	10.61	27.92	46.00	-18.08	AVG


Module-2:

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1540	51.55	10.10	61.65	65.78	-4.13	QP
2	0.1700	50.10	10.11	60.21	64.96	-4.75	QP
3	0.1860	28.43	10.11	38.54	54.21	-15.67	AVG
4	0.4260	27.72	10.26	37.98	47.33	-9.35	AVG
5	0.6180	39.94	10.35	50.29	56.00	-5.71	QP
6	0.6180	28.11	10.35	38.46	46.00	-7.54	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.2460	44.57	10.15	54.72	61.89	-7.17	QP
2	0.2460	24.88	10.15	35.03	51.89	-16.86	AVG
3	0.6220	33.27	10.35	43.62	56.00	-12.38	QP
4	0.6220	21.98	10.35	32.33	46.00	-13.67	AVG
5	4.0420	30.58	10.72	41.30	56.00	-14.70	QP
6	4.0939	14.11	10.72	24.83	46.00	-21.17	AVG

***** END OF REPORT *****