

# Certificate of Test

September 2006

## Sunrex Technology Corp.

Product Type : Power Presenter

Model Number : ML521A, A400, A500

Test Report Number : 0608049 Rev. 1

Date of Test : August 08, 2006- August 23, 2006

This Product was tested to the following standards at the laboratory of Global EMC Standard Tech. Corp., and found Compliance.

**Standards:**

FCC Part 15 Subpart C Paragraph 15.249

ANSI C63.4: 2003

[http : //www.gestek.com.tw](http://www.gestek.com.tw)



Sharon Chang, President

## GesTek EMC Lab

N0. 3, Pau-Tou-Tsuo Valley, Chia-Pau Tsuen,  
Lin Kou Hsiang, Taipei County, Taiwan, R.O.C.  
TEL:886-2-2603-5321  
FAX:886-2-2603-5325

Date: September 05, 2006



200085-0





**Test Report  
Application for  
Certification  
On Behalf Of**

**Sunrex Technology Corp.**

**EUT:  
Power Presenter**

**Model Number:  
ML521A, A400, A500**

**FCC ID:  
J75521A**

**Prepared for:  
Sunrex Technology Corp.  
No. 188-1, Chung Cheng Rd., Ta Ya Shiang, Taichung Hsien,  
Taiwan, R.O.C.**

**Report By :Global EMC Standard Tech. Corp.  
No.3 Pau-Tou-Tsuo Valley, Chia-Pau  
Tsuen, Lin Kou Hsiang, Taipei County,  
Taiwan, R.O.C.  
Tel : 886-2- 2603-5321  
Fax : 886-2- 2603-5325**

1. Test results given in this report only relate to the specimen(s) tested, measured.
2. This report is the property of GesTek, and shall not be reproduced, other than in full, without the written consent of GesTek.
3. The report must not be used by the client to claim product certification, approval, or endorsement by any agency of the federal government.
4. All data in this report are traceable to national standard or international standard.

# TABLE OF CONTENTS

DESCRIPTION	PAGE
<b>1. CERTIFICATION.....</b>	<b>3</b>
<b>2. GENERAL INFORMATION.....</b>	<b>4</b>
2.1 PRODUCTION DESCRIPTION.....	4
2.2 OPERATIONAL DESCRIPTION .....	5
2.3 TEST MODES & EUT COMPONENTS DESCRIPTION .....	5
2.4 SUMMARY OF TEST PROCEDURE AND TEST RESULTS.....	5
2.5 CONFIGURATION OF THE TESTED SYSTEM .....	6
2.6 TEST FACILITY.....	7
2.7 TEST SETUP .....	8
2.8 EUT OPERATING CONDITIONS.....	8
<b>3. RADIATION EMISSION DATA .....</b>	<b>9</b>
3.1 TEST EQUIPMENT .....	9
3.2 OPEN TEST SITE SETUP DIAGRAM .....	9
3.3 RADIATED EMISSION LIMIT .....	10
3.4 EUT CONFIGURATION .....	11
3.5 OPERATING CONDITION OF EUT .....	11
3.6 RADIATED EMISSION DATA .....	11
3.7 RADIATED EMISSIONS MEASUREMENT RESULTS .....	12
<b>4. BAND EDGE .....</b>	<b>17</b>
4.1 TEST EQUIPMENT .....	17
4.2 BLOCK DIAGRAM OF TEST SETUP .....	17
4.3 BAND EDGE LIMIT .....	18
4.4 EUT CONFIGURATION .....	18
4.5 OPERATING CONDITION OF EUT .....	18
4.6 TEST RELULT.....	19
<b>5. DUTY CYCLE.....</b>	<b>25</b>
5.1 TEST EQUIPMENT .....	25
5.2 BLOCK DIAGRAM OF TEST SETUP .....	25
5.3 TEST RESULT .....	25
<b>6. PHOTOGRAPHS FOR TEST.....</b>	<b>27</b>
6.1 TEST PHOTOGRAPHS FOR RADIATION .....	27
<b>7. PHOTOGRAPHS FOR PRODUCT .....</b>	<b>29</b>
<b>8. EMI REDUCTION METHOD DURING COMPLIANCE TESTING .....</b>	<b>34</b>

## 1. CERTIFICATION

**Applicant : Sunrex Technology Corp.**

Applicant Address : No. 188-1, Chung Cheng Rd., Ta Ya Shiang, Taichung Hsien,  
Taiwan, R.O.C.

EUT Description : Power Presenter

Model Number : ML521A, A400, A500

Serial Number : N/A

Brand Name : Sunrex

FCC ID : J75521A

Tested Power Supply : Battery DC 3.0V

Manufacturer : Sunrex Technology Corp.

Manufacturer Address : No. 188-1, Chung Cheng Rd., Ta Ya Shiang, Taichung Hsien,  
Taiwan, R.O.C.

**MEASUREMENT PROCEDURES USED:**


- ☒ **CFR 47, Part 15** Radio Frequency Device Subpart C Intentional Radiators :2005
- ☒ **ANSI C63.4** Methods of Measurements of Radio-Noise Emissions from Low- Voltage  
Electrical and Electronic Equipment in the range of 9kHz To 40GHz.  
2003

THE MEASUREMENT SHOWN IN THE ATTACHMENT WAS MADE IN ACCORDANCE WITH  
THE PROCEDURES INDICATED, AND THE MAXIMUM ENERGY EMITTED BY THE  
EQUIPMENT WAS FOUND TO BE WITHIN THE ABOVE LIMITS APPLICABLE.

Sample Received Date : **August 08, 2006**

Final Test Date : **August 23, 2006**

In order to ensure the quality and accuracy of this document, the contents have been thoroughly reviewed  
by the following qualified personnel from GesTek Lab.

**Documented By :**


Rini Chen / adm. Dept. Supervisor

**Tested By :**

Perry Lin / eng. Dept. Engineer

**Technical Reviewed By :**

Shine Chang / eng. Dept. Supervisor

**Approved By :**

Tonny Lin / General Manager

This test data shown below is traceable to National or international standard such as NIST/USA,  
etc. The laboratory's NVLAP accreditation in no way constitutes or implies product certification,  
approval, or endorsement by NVLAP or the United States government.

## 2. GENERAL INFORMATION

### 2.1 PRODUCTION DESCRIPTION

**Product Name** : Power Presenter  
**Model Number** : ML521A, A400, A500  
**Serial Number** : N/A  
**Brand Name** : Sunrex  
**FCC ID** : J75521A  
**Modulation Type** : GFSK  
**Antenna Type** : Printed on PCB  
**Frequency Range** : 2.420GHz  
**Channel Number** : 1 Channel  
**Channel Control** : N/A  
**Working Voltage** : Battery DC 3.0V

#### Frequency of Each Channel:

Channel	Frequency (GHz)
1	2.420

#### Note:

1. This device is a 2.4GHz Power Presenter included wireless transmission of presenter and receiver. The test report is for transmitter.
2. This device is one channel and perform the test, then record on this report.
3. The antenna of EUT is printer on PCB and conform to FCC 15.203.
4. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.249.
5. A400 and A500 are multiple listing model number.
6. The device of receiver to accordance with Part 15 regulations and under Declaration of Conformity and record of measurment in test report that the report number is 0608049FCC DOC.

## 2.2 OPERATIONAL DESCRIPTION

This device is a 2.4GHz Power Presenter included wireless transmitter of keyboard and receiver. It is powered by Battery DC 3.0V.

This device is only one channel and it is operated in 2.420GHz with GFSK modulation.

The Receiver is usb interface and it is capable to receive signal from transmitter to control PC or notebook.

Another information please refer to users manual.

## 2.3 TEST MODES & EUT COMPONENTS DESCRIPTION

EUT: Power Presenter, M/N: ML521A, A400, A500	
Test Mode	Mode 1-Continue Transmit
Frequency	2.420 GHz

## 2.4 SUMMARY OF TEST PROCEDURE AND TEST RESULTS

Test Item	Applied Standard Section	Test Result
Radistion Emission	15.209, ANSI C63.4 Section 8	Pass (refer to section 3.7)
Peak Power Output	15.249(a), ANSI C63.4 Section 13 & Annex I	Pass (refer to section 3.7)
Band Edge	15.249(d) , ANSI C63.4 Section 13 & Annex I	Pass (refer to section 4.6)

## 2.5 CONFIGURATION OF THE TESTED SYSTEM

The FCC IDs/Types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards, which have grants) are:

Device	No.	Configuration
<b>NOTEBOOK</b>	<b>DELL NB 2</b>	Model Number : Latitude D600 PPO5L BSMI ID : R33002 Serial Number : 11444680576 C.P.U : Intel Pentium M 1.4G HZ DDR : PC2100 256MB F.D.D : N/A H.D.D. : Manufacturer : HITACHI 20.G M/N: IC25N020ATMR04-0, S/N:MRG157K1GJP9JH BSMI ID:D33082 CD-ROM : Manufacturer :DELL M/N:6T980-A01 BATTERY : Manufacturer :DELL Li-ion MODULE : M/N:6Y270 RATING:14.8V 220mAh AC ADAPTOR : Manufacturer :DELL M/N: PA-1650-05D S/N:CN-05U092-71615-41K-58C3 INPUT:AC 100-240 V~1.5A 50-60HZ Shielded, Undetachable, 2.5m
<b>Power Presenter (RX)</b>	-----	Manufacturer : Sunrex Model Number : RX505A

## 2.6 TEST FACILITY

Ambient conditions in the laboratory:


ITEMS	REQUIRED
TEMPERATURE (°C)	15-35
HUMIDITY (%RH)	30-60
BAROMETRIC PRESSURE (mbar)	860-1060
FCC SITE DESCRIPTION	Aug. 10, 1995 /Aug. 25, 1998 File on FCC Engineering Laboratory Federal Communication Commission 7435 Oakland Mills Road Columbia, MD 21046 Reference 31040/SIT1300F2
NVLAP LAB. CODE	200085-0 United States Department of commerce National Institute of Standards and Technology National Voluntary Laboratory Accreditation Program Accreditation on NVLAP effective through Sep. 30, 2006 For CISPR 22, FCC Method and AS/NZS CISPR 22 Measurement.
Chinese National Laboratory Accreditation Certificate R.O.C.	Recognized by the Council of Chinese National Laboratory Accreditation and confirmed to meet the requirements of ISO/IEC 17025 also has been registered for fifteen items, and meet the requirements of the Article 4 of Measures Governing the Recognition both Approval of Designated Laboratory for Commodities Inspection and has been registered for four items within the field of Electrical Testing. Registration No.: 1082 Registration on CNLA effective through April 30, 2006.



## 2.7 TEST SETUP



EUT: Power Presenter



## 2.8 EUT OPERATING CONDITIONS

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to a typical use. The exercise sequence is listed as below:

1. Setup the EUT and simulators as shown on 2.7.
2. Turn on the power of all equipments.
3. The transmitter will transmit the signal continue.
4. Confirm the receiver is receive signal and start test.
5. Repeat the above steps.

### 3. RADIATION EMISSION DATA

#### 3.1 TEST EQUIPMENT


The following test equipments are used during the radiated emission tests:

Radiated test was performed on: ☐ Site #1 ☒ Site #2 ☐ Site #3 ☐ Site #4

Item	Instrument	Manufacturer	Model	Serial No.	Last Cal.
1	Test Receiver	R & S	ESCS30	825022/003	06/08/06
2	Spectrum Analyzer	Rohde & Schwarz	FSP40	100061	04/03/06
	Spectrum Analyzer	HP	E4407B	39240339	07/26/06
3	Power Meter	Rohde & Schwarz	NRVS	100666	04/07/06
4	Peak Power Sensor	Rohde & Schwarz	NRV-Z32	8360191058	04/07/06
5	Pre-Amplifier	HP	8447D	2944A08610	09/13/05
6	Pre-Amplifier	HP	8449B	3008A01263	04/06/06
7	BILOG ANTENNA	SCHAFFNER	CBL6112B	2833	11/26/05
8	Horn Antenna	Schwarzbeck	BBHA 9120	D243	04/06/06
9	RF Cable	GesTek	N/A	GTK-E-A152-01	12/20/05
10	Open Site	GesTek	N/A	B1	11/22/05
11	Test Program Software	GesTek	N/A	GTK-E-S001-01	N/A

Note: All measurement critical items of test instrumentation were within their calibration period of 1 year.

#### 3.2 OPEN TEST SITE SETUP DIAGRAM



### 3.3 RADIATED EMISSION LIMIT

#### ☒ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

Frequency	Distance	Field Strength	
MHz	Meter	$\mu\text{V/M}$	$\text{dB}\mu\text{V/M}$
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0

#### Remarks :

1. RF Voltage ( $\text{dB}\mu\text{V/m}$ ) =  $20 \log \text{RF Voltage } (\mu\text{V/m})$
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

#### ☒ Fundamental and Harmonics Emission Limits

Frequency	Distance	Field Strength of Fundamental		Field Strength of Harmonics	
MHz	Meter	$\mu\text{V/M}$	$\text{dB}\mu\text{V/M}$	$\mu\text{V/M}$	$\text{dB}\mu\text{V/M}$
902-928	3	50	94	500	54
2400-2483.5	3	50	94	500	54
5725-5875	3	50	94	500	54

#### Remarks :

1. RF Voltage ( $\text{dB}\mu\text{V/m}$ ) =  $20 \log \text{RF Voltage } (\mu\text{V/m})$
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

### 3.4 EUT CONFIGURATION

The equipment which is listed 2.6 are installed on Radiated Emission Test to meet the Commission requirement and operating in a manner which tends to maximize its emission characteristics in a normal application.

The device under test, installed in a representative system as described in section 3.2, was placed on a non-conductive table whose total height equaled 80 cm. This table can be rotated 360 degree. The measurement antenna was mounted to a non-conductive mast capable of moving the antenna vertically. Antenna height was varied from 1 meter to 4 meters and the system under test was rotated from 0 degree through 360 degrees relative to the antenna position and polarization (Horizontal and Vertical). Also the I/O cable position was investigated to find the maximum emission condition.

### 3.5 OPERATING CONDITION OF EUT

Same as section 2.7.

### 3.6 RADIATED EMISSION DATA

The measurement range of radiated emission, which is from [30 MHz to 10 Harminics](#), was investigated. All readings below 1GHz are quasi-peak values with a resolution bandwidth of 120 KHz. Above 1GHz are peak and avg. values with a resolution bandwidth of 1MHz. The initial step in collecting radiated emission data is a spectrum analyzer peak scans of the measurement range for all the test modes and then use test receiver for final measurement. Then the worst modes were reported the following data pages.

### 3.7 RADIATED EMISSIONS MEASUREMENT RESULTS

#### 3.7.1 HARMONIC RADIATED EMISSIONS


Date of Test	August 15, 2006	Temperature	26 deg/C
EUT	Power Presenter	Humidity	55 %RH
Working Cond.	TX Mode		
Antenna distance	3m at Horizontal	Frequency Range	30-1000MHz

No.	Frequency MHz	Reading Level dBuV	Factor dB	Measurement dBuV/m	Limit dBuV/m	Over Limit dB	Detector
1	305.4900	30.20	-7.73	22.47	46.00	-23.53	QP
2	384.1100	36.40	-6.53	29.87	46.00	-16.13	QP
3	472.7600	28.91	-4.72	24.19	46.00	-21.81	QP
4	572.7100	29.68	-2.81	26.87	46.00	-19.13	QP
5	615.2400	29.40	-2.16	27.24	46.00	-18.76	QP
6	724.9900	27.38	-0.92	26.46	46.00	-19.54	QP

#### Remarks:

1. All Readings below 1GHz are Quasi-Peak.
2. Measurement = Reading + Factor (Could have  $\pm 0.01$  tolerance due to computer automatically round off calculation).
3. Over Limit (Margin Value)=Measurement level-Limit value.
4. The " " means this data is worst-case Measurement level.

80.0 dBuV/m




Date of Test	August 15, 2006	Temperature	26 deg/C
EUT	Power Presenter	Humidity	55 %RH
Working Cond.	TX Mode		
Antenna distance	3m at Vertical	Frequency Range	30-1000MHz

No.	Frequency MHz	Reading Level dBuV	Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over Limit dB	Detector
1	315.0500	28.80	-7.58	21.22	46.00	-24.78	QP
2	331.8300	36.20	-7.32	28.88	46.00	-17.12	QP
3	352.8300	30.60	-7.00	23.60	46.00	-22.40	QP
4	425.6800	30.40	-5.73	24.67	46.00	-21.33	QP
5	453.3000	29.90	-5.14	24.76	46.00	-21.24	QP
6	625.1300	28.80	-2.07	26.73	46.00	-19.27	QP

**Remarks:**

1. All Readings below 1GHz are Quasi-Peak.
2. Measurement = Reading + Factor (Could have  $\pm 0.01$  tolerance due to computer automatically round off calculation).
3. Over Limit (Margin Value)=Measurement level-Limit value.
4. The " " means this data is worst-case Measurement level.

80.0 dBuV/m



Date of Test	August 08, 2006	Temperature	25.6 deg/C
EUT	Power Presenter	Humidity	63 %RH
Working Cond.	TX Mode		
Antenna distance	3m at Horizontal	Frequency Range	Above 1GHz

### Peak

No.	Frequency MHz	Reading Level dB $\mu$ V	Factor dB	Measurement dB $\mu$ V/m	Limit dB $\mu$ V/m	Over Limit dB	Detector
1	4839.9300	56.35	1.45	57.80	74.00	-16.20	peak
2	7260.4800	60.18	9.50	69.68	74.00	-4.32	peak
3	9679.3000	45.20	6.82	52.02	74.00	-21.98	peak
4	12099.2500	42.65	13.34	55.99	74.00	-18.01	peak
5	14519.2500	41.11	8.63	< 49.74	74.00	-24.26	peak
6	16940.2500	41.73	6.34	< 48.07	74.00	-25.93	peak

### Average

No.	Frequency [MHz]	Peak Emission Level [dB(uV/m)]	Duty Cycle [dB]	Emission Level [dB(uV/m)]	Limit [dB(uV/m)]	Margin [dB]
1	4839.93	57.80	-20	37.80	54.00	16.20
2	7260.48	69.68	-20	49.68	54.00	4.32
3	12099.25	55.99	-20	35.99	54.00	18.01

### Remark

1. All Readings below 1GHz are Quasi-Peak and above 1GHz are peak or average.
2. Spectrum Analyzer Setting(Peak Detector): RBW=1MHz, VBW=1MHZ, Span=100MHz.
3. AVG Emission=Peak Emission + Duty Cycle(Log Scale).
4. Emission Level= Reading + Correction Factor (Could have  $\pm 0.01$  tolerance due to computer automatically round off calculation).
5. Correction Factor= Antenna Factor + Cable Loss – Amplifier Factor
6. Margin Value=Emission level-Limit value.
7. The average measurement was not performed when the peak measured data under the limit of average detection. If the average value is measured, peak measurement should also be supplied.
8. The Duty Cycle is refer to section 5.
9. If Duty Cycle is smaller than -20dB, based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.

Date of Test	August 08, 2006	Temperature	25.6 deg/C
EUT	Power Presenter	Humidity	63 %RH
Working Cond.	TX Mode		
Antenna distance	3m at Vertical	Frequency Range	Above 1GHz

### Peak

No.	Frequency MHz	Reading Level dB $\mu$ V	Factor dB	Measurement dB $\mu$ V/m	Limit dB $\mu$ V/m	Over Limit dB	Detector
1	4839.7000	57.92	1.74	59.66	74.00	-14.34	peak
2	7259.7500	52.45	8.68	61.13	74.00	-12.87	peak
3	9679.7500	42.21	9.95	52.16	74.00	-21.84	peak
4	12099.7500	41.72	15.78	57.50	74.00	-16.50	peak
5	14520.6200	41.64	6.93	< 48.57	74.00	-25.43	peak
6	16940.3500	40.14	5.91	< 46.05	74.00	-27.95	peak

### Average

No.	Frequency [MHz]	Peak Emission Level [dB(uV/m)]	Duty Cycle [dB]	Emission Level [dB(uV/m)]	Limit [dB(uV/m)]	Margin [dB]
1	4839.70	59.66	-20	39.66	54.00	14.34
2	7259.75	61.13	-20	41.13	54.00	12.87
3	12099.75	57.50	-20	37.50	54.00	16.50

### Remark

1. All Readings below 1GHz are Quasi-Peak and above 1GHz are peak or average.
2. Spectrum Analyzer Setting(Peak Detector): RBW=1MHz, VBW=1MHz, Span=100MHz.
3. AVG Emission=Peak Emission + Duty Cycle(Log Scale).
4. Emission Level= Reading + Correction Factor (Could have  $\pm 0.01$  tolerance due to computer automatically round off calculation).
5. Correction Factor= Antenna Factor + Cable Loss – Amplifier Factor
6. Margin Value=Emission level-Limit value.
7. The average measurement was not performed when the peak measured data under the limit of average detection. If the average value is measured, peak measurement should also be supplied.
8. The Duty Cycle is refer to section 5.
9. If Duty Cycle is smaller than -20dB, based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.



## 3.7.2 FUNDAMENTAL RADIATED EMISSIONS

Date of Test	August 10, 2006	Temperature	25.6 deg/C
EUT	Power Presenter	Humidity	63 %RH
Working Cond.	TX Mode: 2420MHz		
Antenna distance	3m		

## Horizontal

No.	Frequency MHz	Reading Level dBuV	Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over Limit dB	Detector
1	2420.000	57.52	31.45	88.97	114	-25.03	peak

## Vertical

No.	Frequency MHz	Reading Level dBuV	Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over Limit dB	Detector
1	2420.2000	51.42	24.30	75.72	114	-38.28	peak

## Remark

1. All Readings below 1GHz are Quasi-Peak and above 1GHz are peak or average.
2. Spectrum Analyzer Setting(Peak Detector): RBW=1MHz, VBW=1MHz, Span=100MHz.
3. AVG Emission=Peak Emission + Duty Cycle(Log Scale).
4. Measurement = Reading + Correction Factor (Could have  $\pm 0.01$  tolerance due to computer automatically round off calculation).
5. Correction Factor= Antenna Factor + Cable Loss – Amplifier Factor
6. Margin Value=Emission level-Limit value.
7. The average measurement was not performed when the peak measured data under the limit of average detection. If the average value is measured, peak measurement should also be supplied.
8. The Duty Cycle is refer to section 5.
9. If Duty Cycle is smaller than -20dB, based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.

## 4. BAND EDGE


### 4.1 TEST EQUIPMENT

Item	Instrument	Manufacturer	Model	Serial No.	Last Cal.
1	Test Receiver	Rohde & Schwarz	ESVS30	829007/014	01/19/06
2	Spectrum Analyzer	Rohde & Schwarz	FSP40	100061	04/03/06
3	Spectrum Analyzer	HP	E4407B	39240339	07/26/06
4	Power Meter	Rohde & Schwarz	NRVS	100666	04/07/06
5	Peak Power Sensor	Rohde & Schwarz	NRV-Z32	8360191058	04/07/06
6	Pre-Amplifier	HP	8449B	3008A01263	04/06/06
7	BILOG ANTENNA	SCHAFFNER	CBL6112B	2620	11/26/05
8	Horn Antenna	Schwarzbeck	BBHA 9120	D243	12/21/05
9	RF Cable	GesTek	N/A	GTK-E-A152-01	12/20/05
10	Open Site	GesTek	N/A	B1	11/22/05
11	Test Program Software	GesTek	N/A	GTK-E-S001-01	N/A

Note: All measurement critical items of test instrumentation were within their calibration period of 1 year.

### 4.2 BLOCK DIAGRAM OF TEST SETUP

#### ◎ RF Radiated Measurement: ◎



#### **4.3 BAND EDGE LIMIT**

In any 100KHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 50dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209 (a) (see Section 15.205(c)).

#### **4.4 EUT CONFIGURATION**

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4:2000 on radiated measurement.

The bandwidth below 1GHz setting on the field strength meter is 120KHz, above 1GHz are 1MHz.

#### **4.5 OPERATING CONDITION OF EUT**

Same as section 2.7.

#### 4.6 TEST RELULT

Date of Test	Augsut 22, 2006	Temperature	25 deg/C
EUT	Power Presenter	Humidity	40 %RH
Working Cond.	Tx Mode		
Antenna distance	3m at Horizontal	Test Band	Lower

### Radiation Emission of Fundamental Peak

Frequency [MHz]	Reading Level [dB(uV)]	Correction Factor [dB/m]	Emission Level [dB(uV/m)]
2420.2	57.52	31.45	88.79

#### Remark:

1. All Readings below 1GHz are Quasi-Peak and above 1GHz are peak or average.
2. Spectrum Analyzer Setting(Peak Detector): RBW=1MHz, VBW=1MHZ.
3. Emission Level= Reading + Correction Factor (Could have  $\pm 0.01$  tolerance due to computer automatically round off calculation).
4. Correction Factor= Antenna Factor + Cable Loss – Amplifier Factor

#### TEST Result

The band edge emission plot on next page are Peak and Average. The polt for peak is appear (45.05)dB delta between carry power and maximum emission in restrict band 2347 MHz.

The above tables are list of fundamental emission test result.

Therefore, peak field strength of 2347 MHz is 88.79 dBuV/m – 40.05 dB = 48.74 dBuV/m which is under 74dBuV/m.

Average filed strength = Peak filed strength x Duty Cycle

(20logAVG = 20logPeak + 20logDuty Cycle)

20logDuty Cycle = (-38.41)dB

Average field strength of (2347)MHz is

(48.74) dBuV/m + (-20)dB = (28.74)dBuV/m which is under 54dBuV/m.

#### Remark:

If Duty Cycle is smaller than -20dB, based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.

Date of Test	August 22, 2006	Temperature	25 deg/C
EUT	Power Presenter	Humidity	40 %RH
Working Cond.	Tx Mode		
Antenna distance	3m at Vertical	Test Band	Lower

## Radiation Emission of Fundamental Peak

Frequency [MHz]	Reading Level [dB(uV)]	Correction Factor [dB/m]	Emission Level [dB(uV/m)]
2402.2	51.42	24.3	75.72

### Remark:

1. All Readings below 1GHz are Quasi-Peak and above 1GHz are peak or average.
2. Spectrum Analyzer Setting(Peak Detector): RBW=1MHz, VBW=1MHZ.
3. Emission Level= Reading + Correction Factor (Could have  $\pm 0.01$  tolerance due to computer automatically round off calculation).
4. Correction Factor= Antenna Factor + Cable Loss – Amplifier Factor

## TEST Result

The band edge emission plot on next page are Peak and Average. The polt for peak is appear (45.05)dB delta between carry power and maximum emission in restrict band 2347 MHz.

The above tables are list of fundamental emission test result.

Therefore, peak field strength of 2347 MHz is 75.72 dBuV/m – 45.05 dB = 30.67 dBuV/m which is under 74dBuV/m.

Average filed strength = Peak filed strength × Duty Cycle

(20logAVG = 20logPeak + 20logDuty Cycle)


20logDuty Cycle = (-38.41)dB

Average field strength of (2347)MHz is

(30.67) dBuV/m + (-20)dB = (10.67)dBuV/m which is under 54dBuV/m.

### Remark:

If Duty Cycle is smaller than -20dB, based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.



Date: 22.AUG.2006 15:27:03

Date of Test	August 22, 2006	Temperature	25 deg/C
EUT	Power Presenter	Humidity	40 %RH
Working Cond.	Tx Mode		
Antenna distance	3m at Horizontal	Test Band	Higher

## Radiation Emission of Fundamental Peak

Frequency [MHz]	Reading Level [dB(uV)]	Correction Factor [dB/m]	Emission Level [dB(uV/m)]
2420	57.42	31.45	88.79

### Remark:

1. All Readings below 1GHz are Quasi-Peak and above 1GHz are peak or average.
2. Spectrum Analyzer Setting(Peak Detector): RBW=1MHz, VBW=1MHZ.
3. Emission Level= Reading + Correction Factor (Could have  $\pm 0.01$  tolerance due to computer automatically round off calculation).
4. Correction Factor= Antenna Factor + Cable Loss – Amplifier Factor

## TEST Result

The band edge emission plot on next page are Peak and Average. The polt for peak is appear (67.81)dB delta between carry power and maximum emission in restrict band 2483.5 MHz.

The above tables are list of fundamental emission test result.

Therefore, peak field strength of 2483.5 MHz is 88.79 dBuV/m – 67.81 dB = 20.98 dBuV/m which is under 74dBuV/m.

Average filed strength = Peak filed strength x Duty Cycle

(20logAVG = 20logPeak + 20logDuty Cycle)

20logDuty Cycle = (-38.41)dB

Average field strength of (2483.5)MHz is

( 20.98) dBuV/m + (-20)dB = (0.98)dBuV/m which is under 54dBuV/m.

### Remark:

If Duty Cycle is smaller than -20dB, based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.

Date of Test	August 22, 2006	Temperature	25 deg/C
EUT	Power Presenter	Humidity	40 %RH
Working Cond.	Tx Mode		
Antenna distance	3m at Vertical	Test Band	Higher

## Radiation Emission of Fundamental Peak

Frequency [MHz]	Reading Level [dB(uV)]	Correction Factor [dB/m]	Emission Level [dB(uV/m)]
2420.2	51.42	24.3	75.72

### Remark:

1. All Readings below 1GHz are Quasi-Peak and above 1GHz are peak or average.
2. Spectrum Analyzer Setting(Peak Detector): RBW=1MHz, VBW=1MHz.
3. Emission Level= Reading + Correction Factor (Could have  $\pm 0.01$  tolerance due to computer automatically round off calculation).
4. Correction Factor= Antenna Factor + Cable Loss – Amplifier Factor

## TEST Result

The band edge emission plot on next page are Peak and Average. The polt for peak is appear (67.81)dB delta between carry power and maximum emission in restrict band 2483.5 MHz.

The above tables are list of fundamental emission test result.


Therefore, peak field strength of 2483.5 MHz is 75.72 dBuV/m – 67.81 dB = 7.91 dBuV/m which is under 74dBuV/m.

### Remark:

If Duty Cycle is smaller than -20dB, based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.

The average measurement was not performed when the peak measured data under the limit of average detection. If the average value is measured, peak measurement should also be supplied.





Date: 22.AUG.2006 15:36:40

## 5. DUTY CYCLE


### 5.1 TEST EQUIPMENT

The following test equipments are used during the radiated emission tests:

Item	Instrument	Manufacturer	Model	Serial No.	Last Cal.
1	Spectrum Analyzer	Rohde & Schwarz	FSP40	100061	04/03/06
2	Spectrum Analyzer	HP	E4407B	39240339	07/26/06

Note: All measurement critical items of test instrumentation were within their calibration period of 1 year.

### 5.2 BLOCK DIAGRAM OF TEST SETUP



### 5.3 TEST RESULT

Date of Test	August 23, 2006	Temperature	25 deg/C
EUT	Power Presenter	Humidity	40 %RH
Working Cond.	Channel 1		

Duty Cycle = Time on of 100ms / 100ms

Frequency 2420 MHz

Time on of one slot length = 600 (μs) = 0.6 (msec)

Totally time of one period = 57.2 (msec)


Time on of of 100ms = 1.2 (msec)

Duty Cycle = 1.2 / 100 = 0.012


20 log 0.012 = -38.41 dB

Remark:

If Duty Cycle is smaller than -20dB, based on FCC part15 the duty cycle correction factor is -20dB for calculating average emission.



Date: 23.AUG.2006 10:03:03




Date: 22.AUG.2006 13:46:47

## 6. PHOTOGRAPHS FOR TEST

### 6.1 TEST PHOTOGRAPHS FOR RADIATION

30-1000MHz



**Above 1GHz**





## 7. PHOTOGRAPHS FOR PRODUCT

- 1.
- 2.







- 3.
- 4.







5.

6. MB





7.  
8.



## 9. Label Here



## 8. EMI REDUCTION METHOD DURING COMPLIANCE TESTING

No modification was made during testing.

## **Appendix A**

### **Circuit (Block) Diagram**

(Shall be added by Applicant)

## **Appendix B**

## **User Manual**

(Shall be added by Applicant)