

ANWEI commnuication Equipment Co.,Ltd





APPROVAL SHEET

Customer	Tai Yi	Specs	FP001
Part Number		Frequency Band	2G:GSM850/900/1800/1900 3G:WCDMA-B2/4/5 4G:LTE-B2/4/5/12/13/25/26/41/66/71
Color	Black	Edition	REV:A0
Salesperson	Mr.Xie	Design	Zong Zhi Hui
Structure	QIN YUN LIN	Confirm	
Date	2024/07/01	Signing Date	

Customer confirmation:

ANT Manufacturers: ANWEI commnuication Equipment Co.,Ltd
Address:2nd Floor, East Block, Building 5, Yifenghua Innovation Industrial Park, Huaning Road, Dalang Street, Longhua District, Shenzhen City, Guangdong Province

Project development environment




天线增益(Antenna gain)


Standard	Band	Frequency	Gain(dBi)
FDD_LTE	FDD_B2	1860	2.52
FDD_LTE	FDD_B4	1760	2.19
FDD_LTE	FDD_B5	840	-0.74
FDD_LTE	FDD_B12	700	0.19
FDD_LTE	FDD_B13	780	-0.71
FDD_LTE	FDD_B25	1860	2.52
FDD_LTE	FDD_B26	840	-0.74
TDD_LTE	FDD_B41	2580	-1.00
FDD_LTE	FDD_B66	1760	2.19
FDD_LTE	FDD_B71	670	-0.08
WCDMA	WCDMA_B2	1860	2.52
WCDMA	WCDMA_B4	1760	2.19
WCDMA	WCDMA_B5	840	-0.74
GSM	GSM850	840	-0.74
GSM	GSM900	900	-4.03
GSM	DCS1800	1760	2.19
GSM	PCS1900	1860	2.52
2.4GWIFI	2.4G	2450	1.63
GPS	L1	1575	1.49
BT	2.4G	2450	1.63

Main antenna apple map


MAX:-0.08dBi
MIN:-17.47dBi




MAX:0.19dBi
MIN:-22.94dBi




MAX:-0.71dBi
MIN:-22.59dBi




MAX:-0.74dBi
MIN:-23.37dBi




MAX:-4.03dBi
MIN:-32.03dBi




MAX:2.19dBi
MIN:-18.49dBi



MAX:2.52dBi
MIN:-19.34dBi



MAX:-1dBi
MIN:-19.35dBi



(Main antenna) PolarGraphs/EtotalGraphs

